

# Package ‘matter’

April 15, 2020

**Type** Package

**Title** A framework for rapid prototyping with file-based data structures

**Version** 1.12.0

**Date** 2016-10-11

**Author** Kylie A. Bemis <k.bemis@northeastern.edu>

**Maintainer** Kylie A. Bemis <k.bemis@northeastern.edu>

**Description** Memory-efficient reading, writing, and manipulation of structured binary data as file-based vectors, matrices, arrays, lists, and data frames.

**License** Artistic-2.0

**Depends** R (>= 3.5), BiocParallel, methods, stats, biglm

**Imports** BiocGenerics, ProtGenerics, digest, irlba, utils

**Suggests** BiocStyle, testthat

**Collate** matterGenerics.R utils.R drle.R atoms.R matter.R matter\_vec.R matter\_mat.R matter\_arr.R matter\_list.R matter\_str.R matter\_fc.R matter\_vt.R rep\_vt.R sparse\_mat.R virtual\_mat.R virtual\_tbl.R virtual\_df.R coerce.R stats.R stream\_stat.R apply.R scale.R biglm.R prcomp.R altrep.R

**biocViews** Infrastructure, DataRepresentation

**URL** <https://github.com/kuwisdelu/matter>

**git\_url** <https://git.bioconductor.org/packages/matter>

**git\_branch** RELEASE\_3\_10

**git\_last\_commit** dc00133

**git\_last\_commit\_date** 2019-10-29

**Date/Publication** 2020-04-14

## R topics documented:

apply	2
biglm	3
binvec	5
bsearch	6

checksum . . . . .	7
chunk_apply . . . . .	8
colStats . . . . .	9
combine . . . . .	11
combiner . . . . .	11
delayed-ops . . . . .	12
drle-class . . . . .	13
keys . . . . .	14
lapply . . . . .	15
locmax . . . . .	16
matter-class . . . . .	17
matter-datypes . . . . .	19
matter-options . . . . .	20
matter_arr-class . . . . .	20
matter_df-class . . . . .	22
matter_fc-class . . . . .	24
matter_list-class . . . . .	26
matter_mat-class . . . . .	28
matter_str-class . . . . .	30
matter_vec-class . . . . .	32
prcomp . . . . .	34
profmem . . . . .	35
rep_vt-class . . . . .	36
scale . . . . .	37
sparse_mat-class . . . . .	38
stream-stats . . . . .	41
struct . . . . .	44
summary-stats . . . . .	45
tolerance . . . . .	47
uuid . . . . .	47
virtual_mat-class . . . . .	48

**Index** **51**

---

apply *Apply Functions Over “matter” Matrices*

---

**Description**

An implementation of `apply` for `matter_mat`, `sparse_mat` and `virtual_mat` matrices.

**Usage**

```
## S4 method for signature 'matter_mat'
apply(X, MARGIN, FUN, ..., BPPARAM = bpparam())
```

```
## S4 method for signature 'sparse_mat'
apply(X, MARGIN, FUN, ..., BPPARAM = bpparam())
```

```
## S4 method for signature 'virtual_mat'
apply(X, MARGIN, FUN, ..., BPPARAM = bpparam())
```

## Arguments

X	A <a href="#">matter</a> matrix-like object.
MARGIN	Must be 1 or 2 for <a href="#">matter_mat</a> matrices, where ‘1’ indicates rows and ‘2’ indicates columns. The dimension names can also be used if X has <code>dimnames</code> set.
FUN	The function to be applied.
...	Additional arguments to be passed to FUN.
BPPARAM	An optional instance of <code>BiocParallelParam</code> . See documentation for <a href="#">bplapply</a> .

## Details

Because FUN must be executed by the interpreter in the appropriate R environment, the full row or column will be loaded into memory. The `chunksize` of X is ignored. For summary statistics, functions like [colMeans](#) and [rowMeans](#) offer greater control over memory pressure. When performed in parallel, the `matter` metadata is serialized to each R session, so all workers must be able to access the data via the same `paths()`.

## Value

See [apply](#) for details.

## Warning

Applying a function over the rows of a column-major matrix (e.g., [matter\\_matc](#)) or over the columns of a row-major matrix (e.g., [matter\\_matr](#)) may be very slow.

## Author(s)

Kylie A. Bemis

## See Also

[apply](#)

## Examples

```
register(SerialParam())  
  
x <- matter(1:100, nrow=10, ncol=10)  
  
apply(x, 2, summary)
```

---

biglm

*Using “biglm” with “matter”*

---

## Description

This method allows [matter\\_mat](#) matrices and [matter\\_df](#) data frames to be used with the [biglm](#) and [bigglm](#) functions from the “biglm” package.

**Usage**

```
## S4 method for signature 'formula,virtual_df'
biglm(formula, data, weights = NULL, sandwich = FALSE)

## S4 method for signature 'formula,virtual_df'
bigglm(formula, data, ..., chunksize = NULL)

## S4 method for signature 'formula,matrix'
bigglm(formula, data, ..., chunksize = NULL, fc = NULL)

## S4 method for signature 'formula,sparse_mat'
bigglm(formula, data, ..., chunksize = NULL, fc = NULL)

## S4 method for signature 'formula,virtual_mat'
bigglm(formula, data, ..., chunksize = NULL, fc = NULL)
```

**Arguments**

formula	A model formula.
data	A <code>matrix</code> matrix with column names.
weights	A one-sided, single-term formula specifying weights.
sandwich	If TRUE, compute the Huber/White sandwich covariance matrix (uses $p^4$ memory rather than $p^2$ ).
chunksize	An integer giving the maximum number of rows to process at a time. If left NULL, this will be calculated by dividing the chunksize of data by the number of variables in the formula.
fc	Either column indices or names of variables which are factors.
...	Additional options passed to <code>bigglm</code> .

**Value**

An object of class `bigglm`.

**Author(s)**

Kylie A. Bemis

**See Also**

`bigglm`

**Examples**

```
set.seed(1)

x <- matrix(rnorm(1000), nrow=100, ncol=10)

colnames(x) <- c(paste0("x", 1:9), "y")

fm <- paste0("y ~ ", paste0(paste0("x", 1:9), collapse=" + "))
fm <- as.formula(fm)
```

```
fit <- bigglm(fm, data=x, chunksize=50)
coef(fit)
```

---

binvec *Bin a vector*

---

## Description

Bin a vector based on intervals or groups.

## Usage

```
binvec(x, u, v, method = "sum")
```

## Arguments

x	A numeric vector.
u, v	The (inclusive) lower and upper indices of the bins, or a factor providing the groupings.
method	The method used to bin the values. This is efficiently implemented for "sum", "mean", "min" or "max". Providing a function will use a less-efficient fallback.

## Value

An vector of the summarized (binned) values.

## Author(s)

Kylie A. Bemis

## Examples

```
set.seed(1)
x <- runif(20)
binvec(x, c(1,6,11,16), c(5,10,15,20), method="mean")
binvec(x, seq(from=1, to=21, by=5), method="mean")
g <- rep(c("a", "b", "c", "d"), each=5)
binvec(x, g, method="mean")
```

---

bsearch

*Binary Search with Approximate Matching*


---

### Description

Given a set of keys and a sorted (non-decreasing) vector of values, use a binary search to find the indexes in values that match the values of key. This implementation allows for returning the index of the nearest match if there are no exact matches. It also allows specifying a tolerance for comparison of doubles.

### Usage

```
bsearch(key, values, tol = 0, tol.ref = "none",
nomatch = NA_integer_, nearest = FALSE)
```

### Arguments

key	A vector of keys to match.
values	A sorted (non-decreasing) vector of values to be matched.
tol	The tolerance for matching doubles. Must be $\geq 0$ .
tol.ref	One of 'none', 'key', or 'values'. If 'none', then comparison of doubles is done by taking the absolute difference. If either 'key' or 'values', then relative differences are used, and this specifies which to use as the reference (target) value.
nomatch	The value to be returned in the case when no match is found, coerced to an integer. (Ignored if nearest = TRUE.)
nearest	Should the index of the closest match be returned if no exact matches are found?

### Details

The algorithm is implemented in C and currently only works for 'integer', 'numeric', and 'character' vectors. If there are multiple matches, then the first match that is found will be returned, with no guarantees. If a nonzero tolerance is provided, the closest match will be returned.

The "nearest" match for strings when there are no exact matches is decided by the match with the most initial matching characters. Tolerance is ignored for strings and integers. Behavior is undefined and results may be unexpected if values includes NAs.

### Value

A vector of the same length as key, giving the indexes of the matches in values.

### Author(s)

Kylie A. Bemis

### See Also

[match](#), [pmatch](#), [findInterval](#)

**Examples**

```
x <- c(1.11, 2.22, 3.33, 5.0, 5.1)

bsearch(2.22, x) # 2
bsearch(3.0, x) # NA
bsearch(3.0, x, nearest=TRUE) # 3
bsearch(3.0, x, tol=0.1, tol.ref="values") # 3

y <- c("hello", "world!")
bsearch("world!", y) # 2
bsearch("worl", y) # NA
bsearch("worl", y, nearest=TRUE) # 2
```

---

`checksum`*Calculate Checksums and Cryptographic Hashes*

---

**Description**

This is a generic function for applying cryptographic hash functions and calculating checksums for arbitrary R objects.

**Usage**

```
checksum(x, ...)

## S4 method for signature 'matter'
checksum(x, algo = c("sha1", "md5"), ...)
```

**Arguments**

<code>x</code>	An object to be hashed.
<code>algo</code>	The hash function to use.
<code>...</code>	Additional arguments to be passed to the hash function.

**Details**

The method for `matter` objects calculates checksums of each of the files in the object's paths.

**Value**

A character vector giving the hash or hashes of the object.

**Author(s)**

Kylie A. Bemis

**See Also**

[digest](#)

**Examples**

```
x <- matter(1:10)
y <- matter(1:10)

checksum(x)
checksum(y) # should be the same
```

---

 chunk\_apply

*Apply Functions Over Chunks of a Vector or Matrix*


---

**Description**

Perform equivalents of `lapply` and `apply`, but over parallelized chunks of the data. This is most useful if accessing the data is potentially time-consuming, such as for file-based `matter` objects. Operating on chunks reduces the number of IO operations.

**Usage**

```
chunk_apply(X, FUN, MARGIN, ..., simplify = FALSE,
            chunks = NA, view = c("element", "chunk"),
            attr = list(), alist = list(), outfile = NULL,
            verbose = FALSE, BPRED0 = list(), BPPARAM = bpparam())
```

**Arguments**

<code>X</code>	A list, vector, or matrix. These may be any class that implements suitable methods for <code>[</code> , <code>[[</code> , <code>dim</code> , and <code>length()</code> .
<code>FUN</code>	The function to be applied.
<code>MARGIN</code>	If the object is matrix-like, which dimension to iterate over. Must be 1 or 2, where 1 indicates rows and 2 indicates columns. The dimension names can also be used if <code>X</code> has <code>dimnames</code> set.
<code>...</code>	Additional arguments to be passed to <code>FUN</code> .
<code>simplify</code>	Should the result be simplified into a vector, matrix, or higher dimensional array?
<code>chunks</code>	The number of chunks to use. If <code>NA</code> (the default), this is inferred from <code>chunksize(X)</code> for <code>matter</code> objects, or from <code>getOption("matter.default.chunksize")</code> for non- <code>matter</code> classes. For IO-bound operations, using fewer chunks will often be faster, but use more memory.
<code>view</code>	What should be passed as the argument to <code>FUN</code> : "element" means the vector element, row, or column are passed (same as the behavior of <code>lapply</code> and <code>apply</code> ), and "chunk" means to pass the entire chunk.
<code>attr</code>	A list of attributes that will be attached to the argument passed to <code>FUN</code> as-is.
<code>alist</code>	A list of vector-like attributes that will be attached to the argument passed to <code>FUN</code> , subsetted to the current elements.
<code>outfile</code>	If non- <code>NULL</code> , a file path where the results should be written as they are processed. Not implemented yet.
<code>verbose</code>	Should user messages be printed with the current chunk being processed?
<code>BPRED0</code>	See documentation for <a href="#">bplapply</a> .
<code>BPPARAM</code>	An optional instance of <code>BiocParallelParam</code> . See documentation for <a href="#">bplapply</a> .



**Value**

Typically, a list if `simplify=FALSE`. Otherwise, the results may be coerced to a vector or array.

**Author(s)**

Kylie A. Bemis

**See Also**

[lapply](#), [apply](#)

**Examples**

```
register(SerialParam())

set.seed(1)
x <- matrix(rnorm(1000^2), nrow=1000, ncol=1000)

out <- chunk_apply(x, mean, 1, chunks=20, verbose=TRUE)
```

---

colStats

*Row and Column Summary Statistics*

---

**Description**

These functions perform calculation of summary statistics over matrix rows and columns, for each level of a grouping variable (optionally), and with implicit row/column scaling and centering if desired.

**Usage**

```
## S4 method for signature 'ANY'
colStats(x, stat, groups,
         na.rm = FALSE, tform = identity,
         col.center = NULL, col.scale = NULL,
         row.center = NULL, row.scale = NULL,
         drop = TRUE, BPPARAM = bpparam(), ...)
```

```
## S4 method for signature 'ANY'
rowStats(x, stat, groups,
         na.rm = FALSE, tform = identity,
         col.center = NULL, col.scale = NULL,
         row.center = NULL, row.scale = NULL,
         drop = TRUE, BPPARAM = bpparam(), ...)
```

**Arguments**

x	A matrix on which to calculate summary statistics.
stat	The name of summary statistics to compute over the rows or columns of a matrix. Allowable values include: "min", "max", "prod", "sum", "mean", "var", "sd", "any", and "all".

groups	A factor or vector giving the grouping. If not provided, no grouping will be used.
na.rm	If TRUE, remove NA values before summarizing.
tform	A dimensionality-preserving transformation to be applied to the matrix (e.g., <code>log()</code> or <code>sqrt()</code> ).
col.center	A vector of column centers to subtract from each row. (Or a matrix with a column for each level of groups.)
col.scale	A vector of column scaling factors to divide from each row. (Or a matrix with a column for each level of groups.)
row.center	A vector of row centers to subtract from each column. (Or a matrix with a column for each level of groups.)
row.scale	A vector of row centers to scaling factors to divide from each column. (Or a matrix with a column for each level of groups.)
drop	If only a single summary statistic is calculated, return the results as a vector (or matrix) rather than a list.
BPPARAM	An optional instance of <code>BiocParallelParam</code> . See documentation for <a href="#">bplapply</a> .
...	Additional arguments.

### Details

The summary statistics methods are calculated over chunks of the matrix using [colstreamStats](#) and [rowstreamStats](#). For `matrix` objects, the iteration is performed over the major dimension for IO efficiency.

### Value

A list for each `stat` requested, where each element is either a vector (if no grouping variable is provided) or a matrix where each column corresponds to a different level of groups.

If `drop=TRUE`, and only a single statistic is requested, then the result will be unlisted and returned as a vector or matrix.

### Author(s)

Kylie A. Bemis

### See Also

[colSums](#)

### Examples

```
register(SerialParam())

set.seed(1)

x <- matrix(runif(100^2), nrow=100, ncol=100)

groups <- as.factor(rep(letters[1:5], each=20))

colStats(x, "mean", groups=groups)
```

---

combine	<i>Combine Out-of-Memory Objects</i>
---------	--------------------------------------

---

**Description**

This is a generic function for combining matter objects. A default fallback method to `c()` is provided as well.

This generic is internally used to implement `c()`, `cbind()`, and `rbind()` for matter objects.

**Usage**

```
combine(x, y, ...)
```

**Arguments**

x	One of the objects.
y	A second object.
...	Any other objects of the same class as x and y.

**Author(s)**

Kylie A. Bemis

**Examples**

```
x <- 1:5  
y <- 6:10  
  
combine(x, y)
```

---

combiner	<i>Get or Set combiner for an Object</i>
----------	--

---

**Description**

This is a generic function for getting or setting the 'combiner' for an object with values to combine.

**Usage**

```
combiner(object)  
  
combiner(object) <- value
```

**Arguments**

object	An object with a combiner.
value	The value to set the combiner.

**Author(s)**

Kylie A. Bemis

**See Also**

[sparse\\_mat](#)

**Examples**

```
x <- sparse_mat(diag(10))
combiner(x)
combiner(x) <- "sum"
x[]
```

---

delayed-ops

*Delayed Operations on “matter” Objects*

---

**Description**

Some arithmetic, comparison, and logical operations are available as delayed operations on [matter](#) objects. With these operations, no out-of-memory data is changed, and the operation is only executed when elements of the object are actually accessed.

**Details**

Currently the following delayed operations are supported:

‘Arith’: ‘+’, ‘-’, ‘\*’, ‘/’, ‘^’, ‘

‘Compare’: ‘==’, ‘>’, ‘<’, ‘!=’, ‘<=’, ‘>=’

‘Logic’: ‘&’, ‘|’

‘Ops’: ‘Arith’, ‘Compare’, ‘Logic’

‘Math’: ‘exp’, ‘log’, ‘log2’, ‘log10’

Delayed operations are applied at the C++ layer immediately after the elements are read from virtual memory. This means that operations that are implemented in C and/or C++ for efficiency (such as summary statistics) will also reflect the execution of the delayed operations.

**Value**

A new [matter](#) object with the registered delayed operation. Data in storage is not modified; only object metadata is changed.

**Author(s)**

Kylie A. Bemis

**See Also**

[Arith](#), [Compare](#), [Logic](#), [Ops](#), [Math](#)

**Examples**

```
x <- matter(1:100)
y <- 2 * x + 1

x[1:10]
y[1:10]

mean(x)
mean(y)
```

---

drle-class

*Delta Run Length Encoding*


---

**Description**

The `drle` class stores delta-run-length-encoded vectors. These differ from other run-length-encoded vectors provided by other packages in that they allow for runs of values that each differ by a common difference (`delta`).

**Usage**

```
## Instance creation
drle(x, cr_threshold = 0, delta = TRUE)

is.drle(x)
## Additional methods documented below
```

**Arguments**

<code>x</code>	An integer or numeric vector to convert to delta run length encoding for <code>drle()</code> ; an object to test if it is of class <code>drle</code> for <code>is.drle()</code> .
<code>cr_threshold</code>	The compression ratio threshold to use when converting a vector to delta run length encoding. The default (0) always converts the object to <code>drle</code> . Values of <code>cr_threshold &lt; 1</code> correspond to compressing even when the output will be larger than the input (by a certain ratio). For values <code>&gt; 1</code> , compression will only take place when the output is (approximately) at least <code>cr_threshold</code> times smaller.
<code>delta</code>	Should non-zero deltas be considered by the encoding? (Default TRUE.) If FALSE, then ordinary run-length-encoding is used.

**Value**

An object of class `drle`.

**Slots**

**values:** The values that begin each run.  
**lengths:** The length of each run.  
**deltas:** The difference between the values of each run.

## Creating Objects

`drle` instances can be created through `drle()`.

## Methods

Standard generic methods:

`x[i]`: Get the elements of the uncompressed vector.

`length(x)`: Get the length of the uncompressed vector.

`c(x, ...)`: Combine vectors.

## Author(s)

Kylie A. Bemis

## See Also

[rle](#)

## Examples

```
## Create a drle vector
x <- c(1,1,1,1,1,6,7,8,9,10,21,32,33,34,15)
y <- drle(x)

# Check that their elements are equal
x == y[]
```

---

keys

*Get or Set Keys for an Object*

---

## Description

This is a generic function for getting or setting 'keys' for an object with key-value pairs such as a map data structure.

## Usage

```
keys(object)
```

```
keys(object) <- value
```

## Arguments

`object` An object with keys.

`value` The value to set the keys.

## Author(s)

Kylie A. Bemis

**See Also**[sparse\\_mat](#)**Examples**

```
x <- sparse_mat(diag(10))
keys(x)
keys(x) <- 1:10
x[]
```

lapply

*Apply Functions Over “matter” Lists***Description**

An implementation of [lapply](#) and [sapply](#) for [matter\\_list](#) objects.

**Usage**

```
## S4 method for signature 'matter_list'
lapply(X, FUN, ..., BPPARAM = bpparam())

## S4 method for signature 'matter_list'
sapply(X, FUN, ..., BPPARAM = bpparam(),
simplify = TRUE, USE.NAMES = TRUE)
```

**Arguments**

X	A <a href="#">matter</a> list-like object.
FUN	The function to be applied.
...	Additional arguments to be passed to FUN.
simplify	Should the result be simplified into a vector, matrix, or higher dimensional array?
USE.NAMES	Use names(X) for the names of the answer. If X is a character, use X as names unless it has names already.
BPPARAM	An optional instance of <a href="#">BiocParallelParam</a> . See documentation for <a href="#">bplapply</a> .

**Details**

Because FUN must be executed by the interpreter in the appropriate R environment, the full list element will be loaded into memory. The chunksize of X is ignored. When performed in parallel, the matter metadata is serialized to each R session, so all workers must be able to access the data via the same paths().

**Value**

See [lapply](#) for details.

**Author(s)**

Kylie A. Bemis

**See Also**[lapply](#)**Examples**

```
register(SerialParam())  
  
x <- matter_list(list(1:10, b=11:20, 21:30), names=c("a", "b", "c"))  
  
lapply(x, sum)  
  
sapply(x, sum)
```

---

`locmax`*Local Maxima*

---

**Description**

Find the indices of the local maxima of a vector.

**Usage**

```
locmax(x, halfWindow = 2, findLimits = FALSE)
```

**Arguments**

<code>x</code>	A numeric vector.
<code>halfWindow</code>	The number of vector elements to look on either side of an element before considering it a local maximum.
<code>findLimits</code>	If TRUE, then also return the approximate boundaries of the peak.

**Details**

For this function, a local maximum is defined as an element greater than all of the elements within `halfWindow` elements to the left of it, and greater than or equal to all of the elements within `halfWindow` elements to the right of it.

The boundaries are found by descending the local maxima until the elements are no longer non-increasing. Small increases within `halfWindow` of the local maxima are ignored.

**Value**

An integer vector giving the indices of the local maxima, potentially with attributes 'lower' and 'upper' if `findLimits=TRUE`.

**Author(s)**

Kylie A. Bemis

**Examples**

```
x <- c(0, 1, 1, 2, 3, 2, 1, 4, 5, 1, 1, 0)  
  
locmax(x, findLimits=TRUE)
```



**Description**

The matter class and its subclasses are designed for easy on-demand read/write access to binary virtual memory data structures, and working with them as vectors, matrices, arrays, lists, and data frames.

**Usage**

```
## Instance creation
matter(...)

# Check if an object is a matter object
is.matter(x)

# Coerce an object to a matter object
as.matter(x, ...)

## Additional methods documented below
```

**Arguments**

```
...      Arguments passed to subclasses.
x        An object to check if it is a matter object or coerce to a matter object.
```

**Value**

An object of class `matter`.

**Slots**

**data:** This slot stores the information about locations of the data in virtual memory and within files.

**datamode:** The storage mode of the *accessed* data when read into R. This is a 'character' vector of with possible values 'raw', 'logical', 'integer', 'numeric', or 'virtual'.

**paths:** A 'character' vector of the paths to the files where the data are stored.

**filemode:** The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.

**chunksize:** The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.

**length:** The length of the data.

**dim:** Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.

**names:** The names of the data elements for vectors.

**dimnames:** Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.

**ops:** Delayed operations to be applied on atoms.

## Creating Objects

`matter` is a virtual class and cannot be instantiated directly, but instances of its subclasses can be created through `matter()`.

## Methods

Class-specific methods:

`atomdata(x)`: Access the 'data' slot.

`adata(x)`: An alias for `atomdata(x)`.

`datamode(x)`, `datamode(x) <- value`: Get or set 'datamode'.

`paths(x)`, `paths(x) <- value`: Get or set 'paths'.

`filemode(x)`, `filemode(x) <- value`: Get or set 'filemode'.

`readonly(x)`, `readonly(x) <- value`: A shortcut for getting or setting 'filemode'.

`chunksize(x)`, `chunksize(x) <- value`: Get or set 'filemode'.

Standard generic methods:

`length(x)`, `length(x) <- value`: Get or set 'length'.

`dim(x)`, `dim(x) <- value`: Get or set 'dim'.

`names(x)`, `names(x) <- value`: Get or set 'names'.

`dimnames(x)`, `dimnames(x) <- value`: Get or set 'dimnames'.

## Author(s)

Kylie A. Bemis

## See Also

[matter\\_vec](#), [matter\\_mat](#), [matter\\_arr](#), [matter\\_list](#), [matter\\_fc](#), [matter\\_str](#), [matter\\_df](#)

## Examples

```
## Create a matter_vec vector
x <- matter(1:100, length=100)
x

## Create a matter_mat matrix
x <- matter(1:100, nrow=10, ncol=10)
x
```

## Description

The matter package defines a number of data types for translating between data elements stored in virtual memory and data elements loaded into R. These are typically set and stored via the `datamode` argument and slot.

At the R level, matter objects may be any of the following data modes:

- `raw`:matter objects of this mode are typically vectors of raw bytes.
- `logical`:Any matter object that represents a logical vector or has had any Compare or Logic delayed operations applied to it will be of this type.
- `integer`:matter objects represented as integers in R.
- `numeric`:matter objects represented as doubles in R.
- `character`:matter objects represented as character vectors in R.
- `virtual`:A number of matter objects do not necessarily represent out-of-memory data, or may include a number of components mixed between virtual memory and real memory; these will use this data mode.

In virtual memory, matter objects may be composed of atomic units of the following data types:

- `char`:8-bit signed integer; defined as `char`.
- `uchar`:8-bit unsigned integer; used for ‘Rbyte’ or ‘raw’; defined as unsigned `char`.
- `short`:16-bit signed integer; defined as `int16_t`.
- `ushort`:16-bit unsigned integer; defined as `uint16_t`.
- `int`:32-bit signed integer; defined as `int32_t`.
- `uint`:32-bit unsigned integer; defined as `uint32_t`.
- `long`:64-bit signed integer; defined as `int64_t`.
- `ulong`:64-bit unsigned integer; defined as `uint64_t`.
- `float`:Platform dependent, but usually a 32-bit float; defined as `float`.
- `double`:Platform dependent, but usually a 64-bit float; defined as `double`.

While a substantial effort is made to coerce data elements properly between data types, sometimes this cannot be done losslessly. This will generate a warning (typically *many* such warnings) that can be silenced by setting `options(matter.cast.warning=FALSE)`.

Note that the unsigned data types do not support NA; coercion to signed `short` and `long` attempts to preserve missingness. The special values NaN, Inf, and -Inf are only supported by the floating-point types, and will be set to NA for signed integral types, and to 0 for unsigned integral types.

---

 matter-options

 Options for “matter” Objects
 

---

### Description

The matter package provides the following options:

- `options(matter.cast.warning=TRUE)`: Should a warning be emitted when casting between data types results in a loss of precision?
- `options(matter.default.chunksize=1000000L)`: The default chunksize for new matter objects. This is the (suggested) maximum number of elements which should be accessed at once by summary functions and linear algebra. Ignored when explicitly subsetting the dataset. Must be an integer.
- `options(matter.show.head=TRUE)`: Should a preview of the beginning of the data be displayed when the object is printed?
- `options(matter.show.head.n=6)`: The number of elements, rows, and/or columns to be displayed by the object preview.
- `options(matter.coerce.altrep=FALSE)`: When coercing matter objects to native R objects (such as `matrix`), should a matter-backed ALTREP object be returned instead? The initial coercion will be cheap, and the result will look like a native R object. This does not guarantee that the full data is never read into memory. Not all functions are ALTREP-aware at the C-level, so some operations may still trigger the full data to be read into memory. This should only ever happen once, as long as the object is not duplicated, though.
- `options(matter.coerce.altrep.list=FALSE)`: Should a matter-backed ALTREP list be returned when coercing `matter_list` lists to native R lists? Lists are treated differently, because the coercion is more costly, as the metadata for each list element must be uncompressed and converted to separate ALTREP representations. (Note that this does not affect `matter_df` data frames, which do not compress metadata about the columns, because the columns are regular matter vectors.)
- `options(matter.wrap.altrep=FALSE)`: When coercing to a matter-backed ALTREP object, should the object be wrapped in an ALTREP wrapper? (This is always done in cases where the coercion preserves existing attributes.) This allows setting of attributes without triggering a (potentially expensive) duplication of the object when safe to do so.
- `options(matter.dump.dir=tempdir())`: Temporary directory where matter object files should be dumped when created without user-specified file paths.

---

 matter\_arr-class

 Out-of-Memory Arrays
 

---

### Description

The `matter_arr` class implements out-of-memory arrays.

**Usage**

```
## Instance creation
matter_arr(data, datamode = "double", paths = NULL,
           filemode = ifelse(all(file.exists(paths)), "r", "rw"),
           offset = 0, extent = prod(dim), dim = 0, dimnames = NULL,
           chunksize = getOption("matter.default.chunksize"), ...)

## Additional methods documented below
```

**Arguments**

data	An optional data vector which will be initially written to virtual memory if provided.
datamode	A 'character' vector giving the storage mode of the data in virtual memory. Allowable values are the C types ('char', 'uchar', 'short', 'ushort', 'int', 'uint', 'long', 'ulong', 'float') and their R equivalents ('raw', 'logical', 'integer', 'numeric'). See ?datatypes for details.
paths	A 'character' vector of the paths to the files where the data are stored. If 'NULL', then a temporary file is created using <a href="#">tempfile</a> .
filemode	The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
offset	A vector giving the offsets in number of bytes from the beginning of each file in 'paths', specifying the start of the data to be accessed for each file.
extent	A vector giving the length of the data for each file in 'paths', specifying the number of elements of size 'datamode' to be accessed from each file.
dim	A vector giving the dimensions of the array.
dimnames	The names of the matrix dimensions.
chunksize	The (suggested) maximum number of elements which should be accessed at once by summary functions and linear algebra. Ignored when explicitly subsetting the dataset.
...	Additional arguments to be passed to constructor.

**Value**

An object of class [matter\\_arr](#).

**Slots**

**data:** This slot stores the information about locations of the data in virtual memory and within the files.

**datamode:** The storage mode of the *accessed* data when read into R. This is a 'character' vector of with possible values 'raw', 'logical', 'integer', 'numeric', or 'virtual'.

**paths:** A 'character' vector of the paths to the files where the data are stored.

**filemode:** The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.

**chunksize:** The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.

length: The length of the data.

dim: Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.

names: The names of the data elements for vectors.

dimnames: Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.

ops: Delayed operations to be applied on atoms.

## Extends

[matter](#)

## Creating Objects

matter\_arr instances can be created through matter\_arr() or matter().

## Methods

Standard generic methods:

x[...], x[...] <- value: Get or set the elements of the array.

## Author(s)

Kylie A. Bemis

## See Also

[matter](#)

## Examples

```
x <- matter_arr(1:1000, dim=c(10,10,10))
x
```

---

matter\_df-class

*Out-of-Memory Data Frames*

---

## Description

The virtual\_df class implements lightweight data frames that may be a mixture of atomic vectors and matter vectors, simulating the behavior of data.frame.

The matter\_df class extends virtual\_df to implement fully out-of-memory data frames where all columns are matter objects.

Calling as.matter() on an ordinary R data.frame will coerce all columns to matter objects to create a matter\_df data frame.

**Usage**

```
## Instance creation
virtual_df(..., row.names = NULL, stringsAsFactors = default.stringsAsFactors())

matter_df(..., row.names = NULL, stringsAsFactors = default.stringsAsFactors())

## Additional methods documented below
```

**Arguments**

`...` These arguments become the data columns or data frame variables. They should be named.

`row.names` A character vector giving the row names.

`stringsAsFactors` Should character vectors be converted to factors? This is recommended for `matter_df`, as accessing the underlying out-of-memory integer vectors (for a factor) is typically much faster than accessing a vector of out-of-memory strings.

**Value**

An object of class `virtual_df` or `matter_df`.

**Slots**

`data`: This slot stores the information about locations of the data in virtual memory and within the files.

`datamode`: The storage mode of the *accessed* data when read into R. This is a 'character' vector of with possible values 'raw', 'logical', 'integer', 'numeric', or 'virtual'.

`paths`: A 'character' vector of the paths to the files where the data are stored.

`filemode`: The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.

`chunksize`: The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.

`length`: The length of the data.

`dim`: Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.

`names`: The names of the data elements for vectors.

`dimnames`: Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.

`ops`: Delayed operations to be applied on atoms.

**Extends**

`matter`

**Creating Objects**

`virtual_df` instances can be created through `virtual_df()`.

`matter_df` instances can be created through `matter_df()`.

**Methods**

Standard generic methods:

`x$name`, `x$name <- value`: Get or set a single column.

`x[[i]]`, `x[[i]] <- value`: Get or set a single column.

`x[i]`, `x[i] <- value`: Get or set multiple columns.

`x[i, j, ..., drop]`, `x[i, j] <- value`: Get or set the elements of the data frame.

**Author(s)**

Kylie A. Bemis

**See Also**

[matter](#)

**Examples**

```
x <- matter_df(a=as.matter(1:10), b=11:20, c=as.matter(letters[1:10]))
x
x[1:2]
x[[2]]
x[["c"]]
x[, "c"]
x[1:5, c("a", "c")]
x$c
x$c[1:5]
```

---

matter\_fc-class

*Out-of-Memory Factors*

---

**Description**

The `matter_fc` class implements out-of-memory factors.

**Usage**

```
## Instance creation
matter_fc(data, datamode = "int", paths = NULL,
          filemode = ifelse(all(file.exists(paths)), "r", "rw"),
          offset = 0, extent = length, length = 0L, names = NULL,
          levels = base::levels(as.factor(data)),
          chunksize = getOption("matter.default.chunksize"), ...)

## Additional methods documented below
```



**Arguments**

data	An optional data vector which will be initially written to the data in virtual memory if provided.
datamode	Must be an integral type for factors.
paths	A 'character' vector of the paths to the files where the data are stored. If 'NULL', then a temporary file is created using <a href="#">tempfile</a> .
filemode	The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
offset	A vector giving the offsets in number of bytes from the beginning of each file in 'paths', specifying the start of the data to be accessed for each file.
extent	A vector giving the length of the data for each file in 'paths', specifying the number of elements of size 'datamode' to be accessed from each file.
length	An optional number giving the total length of the data across all files, equal to the sum of 'extent'. This is ignored and calculated automatically if 'extent' is specified.
names	The names of the data elements.
levels	The levels of the factor.
chunksize	The (suggested) maximum number of elements which should be accessed at once by summary functions and linear algebra. Ignored when explicitly subsetting the dataset.
...	Additional arguments to be passed to constructor.

**Value**

An object of class [matter\\_fc](#).

**Slots**

data:	This slot stores the information about locations of the data in virtual memory and within the files.
datamode:	The storage mode of the <i>accessed</i> data when read into R. This is a 'character' vector of with possible values 'raw', 'logical', 'integer', 'numeric', or 'virtual'.
paths:	A 'character' vector of the paths to the files where the data are stored.
filemode:	The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
chunksize:	The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.
length:	The length of the data.
dim:	Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.
names:	The names of the data elements for vectors.
dimnames:	Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.
ops:	Delayed operations to be applied on atoms.
levels:	The levels of the factor.

**Extends**

[matter](#), [matter\\_vec](#)

**Creating Objects**

matter\_fc instances can be created through `matter_fc()` or `matter()`.

**Methods**

Standard generic methods:

`x[i]`, `x[i] <- value`: Get or set the elements of the factor.

`levels(x)`, `levels(x) <- value`: Get or set the levels of the factor.

**Author(s)**

Kylie A. Bemis

**See Also**

[matter](#), [matter\\_vec](#)

**Examples**

```
x <- matter_fc(rep(c("a", "a", "b"), 5), levels=c("a", "b", "c"))
x
```

---

matter\_list-class      *Out-of-Memory Lists of Vectors*

---

**Description**

The `matter_list` class implements out-of-memory lists.

**Usage**

```
## Instance creation
matter_list(data, datamode = "double", paths = NULL,
            filemode = ifelse(all(file.exists(paths)), "r", "rw"),
            offset = c(0, cumsum(sizeof(datamode) * extent)[-length(extent)]),
            extent = lengths, lengths = 0, names = NULL, dimnames = NULL,
            chunksize = getOption("matter.default.chunksize"), ...)

## Additional methods documented below
```

**Arguments**

data	An optional data list which will be initially written to the data in virtual memory if provided.
datamode	A 'character' vector giving the storage mode of the data in virtual memory. Allowable values are the C types ('char', 'uchar', 'short', 'ushort', 'int', 'uint', 'long', 'ulong', 'float') and their R equivalents ('raw', 'logical', 'integer', 'numeric'). See ?datatypes for details.
paths	A 'character' vector of the paths to the files where the data are stored. If 'NULL', then a temporary file is created using <a href="#">tempfile</a> .
filemode	The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
offset	A vector giving the offsets in number of bytes from the beginning of each file in 'paths', specifying the start of the data to be accessed for each file.
extent	A vector giving the length of the data for each file in 'paths', specifying the number of elements of size 'datamode' to be accessed from each file.
lengths	A vector giving the length of each element of the list.
names	The names of the data elements.
dimnames	The names of the data elements' data elements.
chunksize	The (suggested) maximum number of elements which should be accessed at once by summary functions and linear algebra. Ignored when explicitly subsetting the dataset.
...	Additional arguments to be passed to constructor.

**Value**

An object of class [matter\\_list](#).

**Slots**

- data:** This slot stores the information about locations of the data in virtual memory and within the files.
- datamode:** The storage mode of the *accessed* data when read into R. This is a 'character' vector of with possible values 'raw', 'logical', 'integer', 'numeric', or 'virtual'.
- paths:** A 'character' vector of the paths to the files where the data are stored.
- filemode:** The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
- chunksize:** The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.
- length:** The length of the data.
- dim:** Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.
- names:** The names of the data elements for vectors.
- dimnames:** Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.
- ops:** Delayed operations to be applied on atoms.

**Extends**[matter](#)**Creating Objects**

matter\_list instances can be created through matter\_list() or matter().

**Methods**

Standard generic methods:

x[[i]], x[[i]] <- value: Get or set a single element of the list.

x[[i, j]]: Get the jth sub-elements of the ith element of the list.

x[i], x[i] <- value: Get or set the ith elements of the list.

lengths(x): Get the lengths of all elements in the list.

**Author(s)**

Kylie A. Bemis

**See Also**[matter](#)**Examples**

```
x <- matter_list(list(c(TRUE,FALSE), 1:5, c(1.11, 2.22, 3.33)), lengths=c(2,5,3))
x[]
x[1]
x[[1]]

x[[3,1]]
x[[2,1:3]]
```

---

matter\_mat-class      *Out-of-Memory Matrices*

---

**Description**

The matter\_mat class implements out-of-memory matrices.

**Usage**

```
## Instance creation
matter_mat(data, datamode = "double", paths = NULL,
           filemode = ifelse(all(file.exists(paths)), "r", "rw"),
           offset = c(0, cumsum(sizeof(datamode) * extent)[-length(extent)]),
           extent = if (rowMaj) rep(ncol, nrow) else rep(nrow, ncol),
           nrow = 0, ncol = 0, rowMaj = FALSE, dimnames = NULL,
           chunksize = getOption("matter.default.chunksize"), ...)

## Additional methods documented below
```

**Arguments**

data	An optional data matrix which will be initially written to the data in virtual memory if provided.
datamode	A 'character' vector giving the storage mode of the data in virtual memory. Allowable values are the C types ('char', 'uchar', 'short', 'ushort', 'int', 'uint', 'long', 'ulong', 'float') and their R equivalents ('raw', 'logical', 'integer', 'numeric'). See ?datatypes for details.
paths	A 'character' vector of the paths to the files where the data are stored. If 'NULL', then a temporary file is created using <a href="#">tempfile</a> .
filemode	The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
offset	A vector giving the offsets in number of bytes from the beginning of each file in 'paths', specifying the start of the data to be accessed for each file.
extent	A vector giving the length of the data for each file in 'paths', specifying the number of elements of size 'datamode' to be accessed from each file.
nrow	An optional number giving the total number of rows.
ncol	An optional number giving the total number of columns.
rowMaj	Whether the data should be stored in row-major order (as opposed to column-major order) in virtual memory. Defaults to 'FALSE', for efficient access to columns. Set to 'TRUE' for more efficient access to rows instead.
dimnames	The names of the matrix dimensions.
chunksize	The (suggested) maximum number of elements which should be accessed at once by summary functions and linear algebra. Ignored when explicitly subsetting the dataset.
...	Additional arguments to be passed to constructor.

**Value**

An object of class [matter\\_mat](#).

**Slots**

- data:** This slot stores the information about locations of the data in virtual memory and within the files.
- datamode:** The storage mode of the *accessed* data when read into R. This is a 'character' vector of with possible values 'raw', 'logical', 'integer', 'numeric', or 'virtual'.
- paths:** A 'character' vector of the paths to the files where the data are stored.
- filemode:** The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
- chunksize:** The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.
- length:** The length of the data.
- dim:** Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.
- names:** The names of the data elements for vectors.

**dimnames:** Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.

**ops:** Delayed operations to be applied on atoms.

## Extends

[matter](#)

## Creating Objects

matter\_mat instances can be created through matter\_mat() or matter().

## Methods

Standard generic methods:

`x[i, j, ..., drop], x[i, j] <- value`: Get or set the elements of the matrix. Use `drop = NULL` to return a subset of the same class as the object.

`x %*% y`: Matrix multiplication. At least one matrix must be an in-memory R matrix (or vector).

`crossprod(x, y)`: Alias for `t(x) %*% y`.

`tcrossprod(x, y)`: Alias for `x %*% t(y)`.

`cbind(x, ...), rbind(x, ...)`: Combine matrices by row or column.

`t(x)`: Transpose a matrix. This is a quick operation which only changes metadata and does not touch the out-of-memory data.

## Author(s)

Kylie A. Bemis

## See Also

[matter](#)

## Examples

```
x <- matter_mat(1:100, nrow=10, ncol=10)
x
```

---

matter\_str-class

*Out-of-Memory Strings*

---

## Description

The matter\_str class implements out-of-memory strings.

**Usage**

```
## Instance creation
matter_str(data, datamode = "uchar", paths = NULL,
           filemode = ifelse(all(file.exists(paths)), "r", "rw"),
           offset = c(0, cumsum(sizeof("uchar") * extent)[-length(extent)]),
           extent = nchar, nchar = 0, names = NULL, encoding = "unknown",
           chunksize = getOption("matter.default.chunksize"), ...)

## Additional methods documented below
```

**Arguments**

data	An optional character vector which will be initially written to the data in virtual memory if provided.
datamode	Must be "uchar" (or "raw") for strings.
paths	A 'character' vector of the paths to the files where the data are stored. If 'NULL', then a temporary file is created using <code>tempfile</code> .
filemode	The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
offset	A vector giving the offsets in number of bytes from the beginning of each file in 'paths', specifying the start of the data to be accessed for each file.
extent	A vector giving the length of the data for each file in 'paths', specifying the number of elements of size 'datamode' to be accessed from each file.
nchar	A vector giving the length of each element of the character vector.
names	The names of the data elements.
encoding	The character encoding to use (if known).
chunksize	The (suggested) maximum number of elements which should be accessed at once by summary functions and linear algebra. Ignored when explicitly subsetting the dataset.
...	Additional arguments to be passed to constructor.

**Value**

An object of class `matter_str`.

**Slots**

**data:** This slot stores the information about locations of the data in virtual memory and within the files.

**datamode:** The storage mode of the *accessed* data when read into R. This is a 'character' vector of with possible values 'raw', 'logical', 'integer', 'numeric', or 'virtual'.

**paths:** A 'character' vector of the paths to the files where the data are stored.

**filemode:** The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.

**chunksize:** The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.

**length:** The length of the data.

**dim:** Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.

**names:** The names of the data elements for vectors.

**dimnames:** Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.

**ops:** Delayed operations to be applied on atoms.

**encoding:** The character encoding of the strings.

## Extends

[matter](#)

## Creating Objects

matter\_str instances can be created through matter\_str() or matter().

## Methods

Standard generic methods:

x[i], x[i] <- value: Get or set the string elements of the vector.

lengths(x): Get the number of characters (in bytes) of all string elements in the vector.

## Author(s)

Kylie A. Bemis

## See Also

[matter](#)

## Examples

```
x <- matter_str(rep(c("hello", "world!"), 50))
x
```

---

matter\_vec-class      *Out-of-Memory Vectors*

---

## Description

The matter\_vec class implements out-of-memory vectors.

## Usage

```
## Instance creation
matter_vec(data, datamode = "double", paths = NULL,
           filemode = ifelse(all(file.exists(paths)), "r", "rw"),
           offset = 0, extent = length, length = 0L, names = NULL,
           chunksize = getOption("matter.default.chunksize"), ...)

## Additional methods documented below
```



**Arguments**

data	An optional data vector which will be initially written to the data in virtual memory if provided.
datamode	A 'character' vector giving the storage mode of the data in virtual memory. Allowable values are the C types ('char', 'uchar', 'short', 'ushort', 'int', 'uint', 'long', 'ulong', 'float') and their R equivalents ('raw', 'logical', 'integer', 'numeric'). See ?datatypes for details.
paths	A 'character' vector of the paths to the files where the data are stored. If 'NULL', then a temporary file is created using <a href="#">tempfile</a> .
filemode	The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
offset	A vector giving the offsets in number of bytes from the beginning of each file in 'paths', specifying the start of the data to be accessed for each file.
extent	A vector giving the length of the data for each file in 'paths', specifying the number of elements of size 'datamode' to be accessed from each file.
length	An optional number giving the total length of the data across all files, equal to the sum of 'extent'. This is ignored and calculated automatically if 'extent' is specified.
names	The names of the data elements.
chunksize	The (suggested) maximum number of elements which should be accessed at once by summary functions and linear algebra. Ignored when explicitly subsetting the dataset.
...	Additional arguments to be passed to constructor.

**Value**

An object of class [matter\\_vec](#).

**Slots**

- data:** This slot stores the information about locations of the data in virtual memory and within the files.
- datamode:** The storage mode of the *accessed* data when read into R. This is a 'character' vector of with possible values 'raw', 'logical', 'integer', 'numeric', or 'virtual'.
- paths:** A 'character' vector of the paths to the files where the data are stored.
- filemode:** The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.
- chunksize:** The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.
- length:** The length of the data.
- dim:** Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.
- names:** The names of the data elements for vectors.
- dimnames:** Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.
- ops:** Delayed operations to be applied on atoms.

**Extends**[matter](#)**Creating Objects**

`matter_vec` instances can be created through `matter_vec()` or `matter()`.

**Methods**

Standard generic methods:

`x[i]`, `x[i] <- value`: Get or set the elements of the vector.

`c(x, ...)`: Combine vectors.

`t(x)`: Transpose a vector (to a row matrix). This is a quick operation which only changes metadata and does not touch the out-of-memory data.

**Author(s)**

Kylie A. Bemis

**See Also**[matter](#)**Examples**

```
x <- matter_vec(1:100)
x
```

---

prcomp

*Principal Components Analysis for “matter” Matrices*


---

**Description**

This method allows computation of a truncated principal components analysis of a `matter_mat` matrix using the implicitly restarted Lanczos method [irlba](#).

**Usage**

```
## S4 method for signature 'matter_mat'
prcomp(x, n = 3, retx = TRUE, center = TRUE, scale. = FALSE, ...)
```

**Arguments**

<code>x</code>	A <a href="#">matter</a> matrix.
<code>n</code>	The number of principal componenets to return, must be less than <code>min(dim(x))</code> .
<code>retx</code>	A logical value indicating whether the rotated variables should be returned.
<code>center</code>	A logical value indicating whether the variables should be shifted to be zero-centered, or a centering vector of length equal to the number of columns of <code>x</code> . The centering is performed implicitly and does not change the out-of-memory data in <code>x</code> .

scale. A logical value indicating whether the variables should be scaled to have unit variance, or a scaling vector of length equal to the number of columns of `x`. The scaling is performed implicitly and does not change the out-of-memory data in `x`.

... Additional options passed to [irlba](#).

**Value**

An object of class 'prcomp'. See [?prcomp](#) for details.

**Note**

The 'tol' truncation argument found in the default [prcomp](#) method is not supported. In place of the truncation tolerance in the original function, the argument `n` explicitly gives the number of principal components to return. A warning is generated if the argument 'tol' is used.

**Author(s)**

Kylie A. Bemis

**See Also**

[bigglm](#)

**Examples**

```
set.seed(1)

x <- matter_mat(rnorm(1000), nrow=100, ncol=10)

prcomp(x)
```

---

profmem

*Profile Memory Use*

---

**Description**

These are utility functions for profiling memory used by objects and by R during the execution of an expression.

**Usage**

```
profmem(expr)

mem(x, reset = FALSE)
```

**Arguments**

`expr` An expression to be evaluated.

`x` An object, to identify how much memory it is using.

`reset` Should the maximum memory used by R be reset?

**Details**

These are wrappers around the built-in `gc` function. Note that they only count memory managed by R.

**Value**

For `profmem`, a vector giving [1] the amount of memory used at the start of execution, [2] the amount of memory used at the end of execution, [3] the maximum amount of memory used during execution, [4] the memory overhead as defined by the maximum memory used minus the starting memory use, and [5] the execution time in seconds.

For `mem`, either a single numeric value giving the memory used by an object, or a vector providing a more readable version of the information returned by `gc` (see its help page for details).

**Author(s)**

Kylie A. Bemis

**See Also**

`gc`,

**Examples**

```
x <- 1:100
mem(x)
profmem(mean(x + 1))
```

---

rep\_vt-class

*Virtual Replication of Vectors*

---

**Description**

The `rep_vt` class simulates the behavior of the base function `rep` without actually allocating memory for the duplication. Only the original vector and the expected length of the result are stored. All attributes of the original vector (including names) are dropped.

**Usage**

```
## Instance creation
rep_vt(x, times, length.out = length(x) * times)

## Additional methods documented below
```

**Arguments**

<code>x</code>	A vector (of any mode).
<code>times</code>	The number of times to repeat the whole vector.
<code>length.out</code>	The desired length of the result.

**Value**

An object of class `rep_vt`.

**Slots**

`data`: The original vector.

`length`: The expected length of the repeated virtual vector.

**Creating Objects**

`rep_vt` instances can be created through `rep_vt()`.

**Methods**

Standard generic methods:

`x[i]`: Get the elements of the uncompressed vector.

`x[[i]]`: Get a single element of the uncompressed vector.

`length(x)`: Get the length of the uncompressed vector.

**Author(s)**

Kylie A. Bemis

**See Also**

`[base]{rep}`

**Examples**

```
## Create a rep_vt vector
init <- 1:3
x <- rep(init, length.out=100)
y <- rep_vt(init, length.out=100)

# Check that their elements are equal
x == y[]
```

---

scale

*Scaling and Centering of “matter” Matrices*

---

**Description**

An implementation of `scale` for `matter_mat` matrices.

**Usage**

```
## S4 method for signature 'matter_mat'
scale(x, center = TRUE, scale = TRUE)
```

**Arguments**

x	A <code>matter_mat</code> object.
center	Either a logical value or a numeric vector of length equal to the number of columns of 'x'.
scale	Either a logical value or a numeric vector of length equal to the number of columns of 'x'.

**Details**

See `scale` for details.

**Value**

A `matter_mat` object with the appropriate 'scaled:center' and 'scaled:scale' attributes set. No data in virtual memory is changed, but the scaling will be applied any time the data is read. This includes but is not limited to loading data elements via subsetting, summary statistics methods, and matrix multiplication.

**Author(s)**

Kylie A. Bemis

**See Also**

`scale`

**Examples**

```
x <- matter(1:100, nrow=10, ncol=10)

scale(x)
```

---

sparse\_mat-class

*Sparse Matrices*

---

**Description**

The `sparse_mat` class implements sparse matrices, potentially stored out-of-memory. Both compressed-sparse-column (CSC) and compressed-sparse-row (CSR) formats are supported. Non-zero elements are internally represented as key-value pairs.

**Usage**

```
## Instance creation
sparse_mat(data, datamode = "double", nrow = 0, ncol = 0,
           rowMaj = FALSE, dimnames = NULL, keys = NULL,
           tolerance = c(abs=0), combiner = "identity",
           chunksize = getOption("matter.default.chunksize"), ...)

# Check if an object is a sparse matrix
is.sparse(x)
```

```
# Coerce an object to a sparse matrix
as.sparse(x, ...)
```

```
## Additional methods documented below
```

### Arguments

data	Either a length-2 'list' with elements 'keys' and 'values' which provide the halves of the key-value pairs of the non-zero elements, or a data matrix that will be used to initialize the sparse matrix. If a list is given, all 'keys' elements must be <i>sorted</i> in increasing order.
datamode	A 'character' vector giving the storage mode of the data in virtual memory. Allowable values are R numeric and logical types ('logical', 'integer', 'numeric') and their C equivalents.
nrow	An optional number giving the total number of rows.
ncol	An optional number giving the total number of columns.
keys	Either NULL or a vector with length equal to the number of rows (for CSC matrices) or the number of columns (for CSR matrices). If NULL, then the 'key' portion of the key-value pairs that make up the non-zero elements are assumed to be row or column indices. If a vector, then they define how the non-zero elements are matched to rows or columns. The 'key' portion of each non-zero element is matched against this canonical set of keys using binary search. Allowed types for keys are 'integer', 'numeric', and 'character'.
rowMaj	Whether the data should be stored using compressed-sparse-row (CSR) representation (as opposed to compressed-sparse-column (CSC) representation). Defaults to 'FALSE', for efficient access to columns. Set to 'TRUE' for more efficient access to rows instead.
dimnames	The names of the sparse matrix dimensions.
tolerance	For 'numeric' keys, the tolerance used for floating-point equality when determining key matches. The vector should be named. Use 'absolute' to use absolute differences, and 'relative' to use relative differences.
combiner	In the case of collisions when matching keys, how the row- or column-vectors should be combined. Acceptable values are "identity", "min", "max", "sum", and "mean". A user-specified function may also be provided. Using "identity" means collisions result in an error. Using "sum" or "mean" results in binning all matches.
chunksize	The (suggested) maximum number of elements which should be accessed at once by summary functions and linear algebra. Ignored when explicitly subsetting the dataset.
x	An object to check if it is a sparse matrix or coerce to a sparse matrix.
...	Additional arguments to be passed to constructor.

### Value

An object of class `sparse_mat`.

**Slots**

**data:** A length-2 'list' with elements 'keys' and 'values' which provide the halves of the key-value pairs of the non-zero elements.

**datamode:** The storage mode of the accessed data when read into R. This should a 'character' vector of length one with value 'integer' or 'numeric'.

**paths:** A 'character' vector of the paths to the files where the data are stored.

**filemode:** The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.

**chunksize:** The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.

**length:** The length of the data.

**dim:** Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.

**names:** The names of the data elements for vectors.

**dimnames:** Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.

**ops:** Delayed operations to be applied on atoms.

**keys** Either NULL or a vector with length equal to the number of rows (for CSC matrices) or the number of columns (for CSR matrices). If NULL, then the 'key' portion of the key-value pairs that make up the non-zero elements are assumed to be row or column indices. If a vector, then they define the how the non-zero elements are matched to rows or columns. The 'key' portion of each non-zero element is matched against this canonical set of keys using binary search. Allowed types for keys are 'integer', 'numeric', and 'character'.

**tolerance:** For 'numeric' keys, the tolerance used for floating-point equality when determining key matches. An attribute 'type' gives whether 'absolute' or 'relative' differences should be used for the comparison.

**combiner:** This is a function determining how the row- or column-vectors should be combined (or not) when key matching collisions occur.

**Warning**

If 'data' is given as a length-2 list of key-value pairs, no checking is performed on the validity of the key-value pairs, as this may be a costly operation if the list is stored in virtual memory. Each element of the 'keys' element must be *sorted* in increasing order, or behavior may be unexpected.

Assigning a new data element to the sparse matrix will always sort the key-value pairs of the row or column into which it was assigned.

**Extends**

[matter](#)

**Creating Objects**

sparse\_mat instances can be created through `sparse_mat()`.



## Methods

Standard generic methods:

`x[i, j, ..., drop]`, `x[i, j] <- value`: Get or set the elements of the sparse matrix. Use `drop = NULL` to return a subset of the same class as the object.

`cbind(x, ...)`, `rbind(x, ...)`: Combine sparse matrices by row or column.

`t(x)`: Transpose a matrix. This is a quick operation which only changes metadata and does not touch the data representation.

## Author(s)

Kylie A. Bemis

## See Also

[matter](#)

## Examples

```
keys <- list(
  c(1,4,8,10),
  c(2,3,5),
  c(1,2,7,9))

values <- list(
  rnorm(4),
  rnorm(3),
  rnorm(4))

init1 <- list(keys=keys, values=values)

x <- sparse_mat(init1, nrow=10)
x[]

init2 <- matrix(rbinom(100, 1, 0.2), nrow=10, ncol=10)

y <- sparse_mat(init2, keys=letters[1:10])
y[]
```

## Description

These functions allow calculation of streaming statistics. They are useful, for example, for calculating summary statistics on small chunks of a larger dataset, and then combining them to calculate the summary statistics for the whole dataset.

This is not particularly interesting for simpler, commutative statistics like `sum()`, but it is useful for calculating non-commutative statistics like running `sd()` or `var()` on pieces of a larger dataset.

## Usage

```
# calculate streaming univariate statistics
s_range(x, ..., na.rm = FALSE)

s_min(x, ..., na.rm = FALSE)

s_max(x, ..., na.rm = FALSE)

s_prod(x, ..., na.rm = FALSE)

s_sum(x, ..., na.rm = FALSE)

s_mean(x, ..., na.rm = FALSE)

s_var(x, ..., na.rm = FALSE)

s_sd(x, ..., na.rm = FALSE)

s_any(x, ..., na.rm = FALSE)

s_all(x, ..., na.rm = FALSE)

# calculate streaming matrix statistics
colstreamStats(x, stat, na.rm = FALSE, ...)

rowstreamStats(x, stat, na.rm = FALSE, ...)

# calculate combined summary statistics
stat_c(x, y, ...)
```

## Arguments

<code>x, y, ...</code>	Object(s) on which to calculate a summary statistic, or a summary statistic to combine.
<code>stat</code>	The name of a summary statistic to compute over the rows or columns of a matrix. Allowable values include: "range", "min", "max", "prod", "sum", "mean", "var", "sd", "any", and "all".
<code>na.rm</code>	If TRUE, remove NA values before summarizing.

## Details

These summary statistics methods are intended to be applied to chunks of a larger dataset. They can then be combined either with the individual summary statistic functions, or with `stat_c()`, to produce the combined summary statistic for the full dataset. This is most useful for calculating running variances and standard deviations iteratively, which would be difficult or impossible to calculate on the full dataset.

The variances and standard deviations are calculated using running sum of squares formulas which can be calculated iteratively and are accurate for large floating-point datasets (see reference).

**Value**

For all univariate functions except `s_range()`, a single number giving the summary statistic. For `s_range()`, two numbers giving the minimum and the maximum values.

For `colstreamStats()` and `rowstreamStats()`, a vector of summary statistics.

**Author(s)**

Kylie A. Bemis

**References**

B. P. Welford, "Note on a Method for Calculating Corrected Sums of Squares and Products," *Technometrics*, vol. 4, no. 3, pp. 1-3, Aug. 1962.

B. O'Neill, "Some Useful Moment Results in Sampling Problems," *The American Statistician*, vol. 68, no. 4, pp. 282-296, Sep. 2014.

**See Also**

[Summary](#)

**Examples**

```
set.seed(1)
x <- sample(1:100, size=10)
y <- sample(1:100, size=10)

sx <- s_var(x)
sy <- s_var(y)

var(c(x, y))
stat_c(sx, sy) # should be the same

sxy <- stat_c(sx, sy)

# calculate with 1 new observation
var(c(x, y, 99))
stat_c(sxy, 99)

# calculate over rows of a matrix
set.seed(2)
A <- matrix(rnorm(100), nrow=10)
B <- matrix(rnorm(100), nrow=10)

sx <- rowstreamStats(A, "var")
sy <- rowstreamStats(B, "var")

apply(cbind(A, B), 1, var)
stat_c(sx, sy) # should be the same
```

---

`struct`*C-Style Structs Stored in Virtual Memory*

---

### Description

This is a convenience function for creating and reading C-style structs in a single file stored in virtual memory.

### Usage

```
struct(..., filename = NULL, filemode = "rw", offset = 0)
```

### Arguments

<code>...</code>	Named integers giving the members of the struct. They should be of the form <code>name=c(type=length)</code> .
<code>filename</code>	A single string giving the name of the file.
<code>filemode</code>	The mode to use to open the file.
<code>offset</code>	A scalar integer giving the offset from the beginning of the file.

### Details

This is simply a convenient wrapper around the wrapper around [matter\\_list](#) that allows easy specification of C-style structs in a file.

### Value

A object of class [matter\\_list](#).

### Author(s)

Kylie A. Bemis

### See Also

[matter\\_list](#)

### Examples

```
x <- struct(first=c(int=1), second=c(double=1))

x$first <- 2L
x$second <- 3.33

x$first
x$second
```

## Description

These functions efficiently calculate summary statistics for `matter` objects. For matrices, they operate efficiently on both rows and columns.

## Usage

```
## S4 method for signature 'matter'  
range(x, na.rm)  
## S4 method for signature 'matter'  
min(x, na.rm)  
## S4 method for signature 'matter'  
max(x, na.rm)  
## S4 method for signature 'matter'  
prod(x, na.rm)  
## S4 method for signature 'matter'  
mean(x, na.rm)  
## S4 method for signature 'matter'  
sum(x, na.rm)  
## S4 method for signature 'matter'  
sd(x, na.rm)  
## S4 method for signature 'matter'  
var(x, na.rm)  
## S4 method for signature 'matter'  
any(x, na.rm)  
## S4 method for signature 'matter'  
all(x, na.rm)  
## S4 method for signature 'matter_mat'  
colMeans(x, na.rm)  
## S4 method for signature 'matter_mat'  
colSums(x, na.rm)  
## S4 method for signature 'matter_mat'  
colSds(x, na.rm)  
## S4 method for signature 'matter_mat'  
colVars(x, na.rm)  
## S4 method for signature 'matter_mat'  
rowMeans(x, na.rm)  
## S4 method for signature 'matter_mat'  
rowSums(x, na.rm)  
## S4 method for signature 'matter_mat'  
rowSds(x, na.rm)  
## S4 method for signature 'matter_mat'  
rowVars(x, na.rm)
```

## Arguments

<code>x</code>	A <code>matter</code> object.
<code>na.rm</code>	If TRUE, remove NA values before summarizing.

## Details

These summary statistics methods operate on chunks of data (equal to the chunksize of `x`) which are loaded into memory and then freed before reading the next chunk.

For row and column summaries on matrices, the iteration scheme is dependent on the layout of the data. Column-major matrices will always be iterated over by column, and row-major matrices will always be iterated over by row. Row statistics on column-major matrices and column statistics on row-major matrices are calculated iteratively.

The efficiency of these methods is entirely dependent on the chunksize of `x`. Larger chunks will yield faster calculations, but greater memory usage. The row and column summary methods may be more or less efficient than the equivalent call to [apply](#), depending on the chunk size.

Variance and standard deviation are calculated using a running sum of squares formula which can be calculated iteratively and is accurate for large floating-point datasets (see reference).

## Value

For mean, sd, and var, a single number. For the column summaries, a vector of length equal to the number of columns of the matrix. For the row summaries, a vector of length equal to the number of rows of the matrix.

## Author(s)

Kylie A. Bemis

## References

B. P. Welford, "Note on a Method for Calculating Corrected Sums of Squares and Products," *Technometrics*, vol. 4, no. 3, pp. 1-3, Aug. 1962.

## See Also

[stream\\_stat](#)

## Examples

```
x <- matrix(1:100, nrow=10, ncol=10)
```

```
sum(x)
mean(x)
var(x)
sd(x)
```

```
colSums(x)
colMeans(x)
colVars(x)
colSds(x)
```

```
rowSums(x)
rowMeans(x)
rowVars(x)
rowSds(x)
```

---

tolerance	<i>Get or Set Tolerance for an Object</i>
-----------	---

---

**Description**

This is a generic function for getting or setting 'tolerance' for an object which tests floating point equality.

**Usage**

```
tolerance(object, ...)  
  
tolerance(object, ...) <- value
```

**Arguments**

object	An object with tolerance.
...	Additional arguments.
value	The value to set the tolerance.

**Author(s)**

Kylie A. Bemis

**See Also**

[sparse\\_mat](#)

**Examples**

```
x <- sparse_mat(diag(10), keys=rnorm(10))  
tolerance(x)  
tolerance(x) <- c(absolute=0.1)  
x[]
```

---

uuid	<i>Universally Unique Identifiers</i>
------	---------------------------------------

---

**Description**

Generate a UUID.

**Usage**

```
uuid(uppercase = FALSE)  
  
hex2raw(x)  
  
raw2hex(x, uppercase = FALSE)
```

**Arguments**

`x` A vector of to convert between raw bytes and hexadecimal strings.  
`uppercase` Should the result be in uppercase?

**Details**

`uuid` generates a random universally unique identifier.  
`hex2raw` converts a hexadecimal string to a raw vector.  
`raw2hex` converts a raw vector to a hexadecimal string.

**Value**

For `uuid`, a list of length 2:

- `string`: A character vector giving the UUID.
- `bytes`: The raw bytes of the UUID.

For `hex2raw`, a raw vector.

For `raw2hex`, a character vector of length 1.

**Author(s)**

Kylie A. Bemis

**Examples**

```
id <- uuid()
id
hex2raw(id$string)
raw2hex(id$bytes)
```

---

virtual\_mat-class      *Virtual Matrices*

---

**Description**

The `virtual_mat` class implements virtual matrices, which may hold any matrix-like objects. It is provided primarily to allow combining of matter matrix classes that could not be combined otherwise.

**Usage**

```
## Instance creation
virtual_mat(data, datamode = "double", rowMaj = FALSE,
            dimnames = NULL, index = NULL, transpose = FALSE,
            chunksize = getOption("matter.default.chunksize"), ...)

# Check if an object is a virtual matrix
is.virtual(x)

# Coerce an object to a virtual matrix
```



```
as.virtual(x, ...)

## Additional methods documented below
```

### Arguments

<code>data</code>	A list of matrices or vectors to combine.
<code>datamode</code>	A 'character' vector giving the storage mode of the data in virtual memory. Allowable values are R numeric and logical types ('logical', 'integer', 'numeric') and their C equivalents.
<code>rowMaj</code>	Whether the matrices in <code>data</code> are combined by row (TRUE) or by column (FALSE).
<code>dimnames</code>	The names of the virtual matrix dimensions.
<code>index</code>	A length-2 list of row and column indices giving a submatrix, if desired.
<code>transpose</code>	Should the matrix be transposed?
<code>chunksize</code>	The (suggested) maximum number of elements which should be accessed at once by summary functions and linear algebra. Ignored when explicitly subsetting the dataset.
<code>x</code>	An object to check if it is a virtual matrix or coerce to a virtual matrix.
<code>...</code>	Additional arguments to be passed to constructor.

### Value

An object of class `virtual_mat`.

### Slots

**data:** A list of the original matrices or row/column-vectors.

**datamode:** The storage mode of the accessed data when read into R. This should be a 'character' vector of length one with value 'integer' or 'numeric'.

**paths:** A 'character' vector of the paths to the files where the data are stored.

**filemode:** The read/write mode of the files where the data are stored. This should be 'r' for read-only access, or 'rw' for read/write access.

**chunksize:** The maximum number of elements which should be loaded into memory at once. Used by methods implementing summary statistics and linear algebra. Ignored when explicitly subsetting the dataset.

**length:** The length of the data.

**dim:** Either 'NULL' for vectors, or an integer vector of length one or more giving the maximal indices in each dimension for matrices and arrays.

**names:** The names of the data elements for vectors.

**dimnames:** Either 'NULL' or the names for the dimensions. If not 'NULL', then this should be a list of character vectors of the length given by 'dim' for each dimension. This is always 'NULL' for vectors.

**ops:** Delayed operations to be applied on atoms.

**index** A length-2 list of row and column indices giving a virtual submatrix.

**transpose** TRUE if the virtual matrix should be transposed, and FALSE otherwise.

**Extends**

[matter](#)

**Creating Objects**

virtual\_mat instances can be created through `virtual_mat()`.

**Methods**

Standard generic methods:

`x[i, j, ..., drop]`: Get or set the elements of the virtual matrix. Use `drop = NULL` to return a subset of the same class as the object.

`cbind(x, ...)`, `rbind(x, ...)`: Combine virtual matrices by row or column.

`t(x)`: Transpose a matrix. This is a quick operation which only changes metadata and does not touch the data representation.

**Author(s)**

Kylie A. Bemis

**See Also**

[matter](#)

**Examples**

```
x <- matrix(runif(50), nrow=10, ncol=5)

x <- virtual_mat(list(x, x))
x[]
```

# Index

## \*Topic **IO**

- matter-class, 17
- matter-datypes, 19
- matter\_arr-class, 20
- matter\_df-class, 22
- matter\_fc-class, 24
- matter\_list-class, 26
- matter\_mat-class, 28
- matter\_str-class, 30
- matter\_vec-class, 32
- struct, 44

## \*Topic **arith**

- delayed-ops, 12

## \*Topic **array**

- matter-class, 17
- matter\_arr-class, 20
- matter\_df-class, 22
- matter\_fc-class, 24
- matter\_list-class, 26
- matter\_mat-class, 28
- matter\_str-class, 30
- matter\_vec-class, 32
- sparse\_mat-class, 38
- struct, 44
- virtual\_mat-class, 48

## \*Topic **classes**

- drle-class, 13
- matter-class, 17
- matter\_arr-class, 20
- matter\_df-class, 22
- matter\_fc-class, 24
- matter\_list-class, 26
- matter\_mat-class, 28
- matter\_str-class, 30
- matter\_vec-class, 32
- rep\_vt-class, 36
- sparse\_mat-class, 38
- virtual\_mat-class, 48

## \*Topic **methods**

- apply, 2
- chunk\_apply, 8
- colStats, 9
- delayed-ops, 12

- lapply, 15
- scale, 37
- stream-stats, 41
- summary-stats, 45

## \*Topic **misc**

- matter-options, 20

## \*Topic **models**

- biglm, 3

## \*Topic **multivariate**

- prcomp, 34

## \*Topic **regression**

- biglm, 3

## \*Topic **univar**

- colStats, 9
- stream-stats, 41
- summary-stats, 45

## \*Topic **utilities**

- binvec, 5
- bsearch, 6
- checksum, 7
- combine, 11
- combiner, 11
- keys, 14
- locmax, 16
- profmem, 35
- struct, 44
- tolerance, 47
- uuid, 47

- [,atoms,ANY,ANY,ANY-method  
(matter-class), 17

- [,atoms,ANY,missing,ANY-method  
(matter-class), 17

- [,atoms,missing,ANY,ANY-method  
(matter-class), 17

- [,drle,ANY,missing,missing-method  
(drle-class), 13

- [,drle,missing,missing,missing-method  
(drle-class), 13

- [,matter\_arr,ANY,ANY,ANY-method  
(matter\_arr-class), 20

- [,matter\_arr-method (matter\_arr-class),  
20

- [,matter\_fc,ANY,missing,ANY-method

- (matter\_fc-class), 24
- [,matter\_fc,ANY,missing,NULL-method (matter\_fc-class), 24
- [,matter\_fc-method (matter\_fc-class), 24
- [,matter\_list,ANY,missing,ANY-method (matter\_list-class), 26
- [,matter\_list,ANY,missing,NULL-method (matter\_list-class), 26
- [,matter\_list-method (matter\_list-class), 26
- [,matter\_mat,ANY,ANY,ANY-method (matter\_mat-class), 28
- [,matter\_mat,ANY,ANY,NULL-method (matter\_mat-class), 28
- [,matter\_mat-method (matter\_mat-class), 28
- [,matter\_str,ANY,missing,ANY-method (matter\_str-class), 30
- [,matter\_str,ANY,missing,NULL-method (matter\_str-class), 30
- [,matter\_str-method (matter\_str-class), 30
- [,matter\_vec,ANY,missing,ANY-method (matter\_vec-class), 32
- [,matter\_vec,ANY,missing,NULL-method (matter\_vec-class), 32
- [,matter\_vec-method (matter\_vec-class), 32
- [,rep\_vt,ANY,missing,missing-method (rep\_vt-class), 36
- [,rep\_vt,missing,missing,missing-method (rep\_vt-class), 36
- [,sparse\_mat,ANY,ANY,ANY-method (sparse\_mat-class), 38
- [,sparse\_mat,ANY,ANY,NULL-method (sparse\_mat-class), 38
- [,sparse\_mat-method (sparse\_mat-class), 38
- [,virtual\_df,ANY,ANY,ANY-method (matter\_df-class), 22
- [,virtual\_df,ANY,ANY,NULL-method (matter\_df-class), 22
- [,virtual\_df-method (matter\_df-class), 22
- [,virtual\_mat,ANY,ANY,ANY-method (virtual\_mat-class), 48
- [,virtual\_mat,ANY,ANY,NULL-method (virtual\_mat-class), 48
- [,virtual\_mat,ANY,missing,ANY-method (virtual\_mat-class), 48
- [,virtual\_mat,ANY,missing,NULL-method (virtual\_mat-class), 48
- [,virtual\_mat,missing,ANY,ANY-method (virtual\_mat-class), 48
- [,virtual\_mat,missing,ANY,NULL-method (virtual\_mat-class), 48
- [,virtual\_mat,missing,missing,ANY-method (virtual\_mat-class), 48
- [,virtual\_mat-method (virtual\_mat-class), 48
- [<-,matter\_arr,ANY,ANY,ANY-method (matter\_arr-class), 20
- [<-,matter\_arr-method (matter\_arr-class), 20
- [<-,matter\_fc,ANY,missing,ANY-method (matter\_fc-class), 24
- [<-,matter\_fc-method (matter\_fc-class), 24
- [<-,matter\_list,ANY,missing,ANY-method (matter\_list-class), 26
- [<-,matter\_list-method (matter\_list-class), 26
- [<-,matter\_mat,ANY,ANY,ANY-method (matter\_mat-class), 28
- [<-,matter\_mat-method (matter\_mat-class), 28
- [<-,matter\_str,ANY,missing,ANY-method (matter\_str-class), 30
- [<-,matter\_str-method (matter\_str-class), 30
- [<-,matter\_vec,ANY,missing,ANY-method (matter\_vec-class), 32
- [<-,matter\_vec-method (matter\_vec-class), 32
- [<-,sparse\_mat,ANY,ANY,ANY-method (sparse\_mat-class), 38
- [<-,sparse\_mat-method (sparse\_mat-class), 38
- [<-,virtual\_df,ANY,ANY,ANY-method (matter\_df-class), 22
- [<-,virtual\_df-method (matter\_df-class), 22
- [[,atoms,ANY,ANY-method (matter-class), 17
- [[,atoms-method (matter-class), 17
- [[,matter\_list,ANY,ANY-method (matter\_list-class), 26
- [[,rep\_vt,ANY,ANY-method (rep\_vt-class), 36
- [[,virtual\_df,ANY,missing-method (matter\_df-class), 22
- [[<-,matter\_list,ANY,ANY-method (matter\_list-class), 26
- [[<-,virtual\_df,ANY,missing-method

- (matter\_df-class), 22
- \$,matter\_list-method (matter\_list-class), 26
- \$,virtual\_df-method (matter\_df-class), 22
- \$<-,matter\_list-method (matter\_list-class), 26
- \$<-,virtual\_df-method (matter\_df-class), 22
- %\*%,matrix,matter\_mat-method (matter\_mat-class), 28
- %\*%,matrix,sparse\_matc-method (sparse\_mat-class), 38
- %\*%,matrix,sparse\_matr-method (sparse\_mat-class), 38
- %\*%,matrix,virtual\_matc-method (virtual\_mat-class), 48
- %\*%,matrix,virtual\_matr-method (virtual\_mat-class), 48
- %\*%,matter,matter-method (matter\_mat-class), 28
- %\*%,matter,numeric-method (matter\_mat-class), 28
- %\*%,matter\_mat,matrix-method (matter\_mat-class), 28
- %\*%,numeric,matter-method (matter\_mat-class), 28
- %\*%,sparse\_matc,matrix-method (sparse\_mat-class), 38
- %\*%,sparse\_matr,matrix-method (sparse\_mat-class), 38
- %\*%,virtual\_matc,matrix-method (virtual\_mat-class), 48
- %\*%,virtual\_matr,matrix-method (virtual\_mat-class), 48
  
- adata (matter-class), 17
- adata,matter-method (matter-class), 17
- all,matter-method (summary-stats), 45
- any,matter-method (summary-stats), 45
- apply, 2, 2, 3, 9, 46
- apply,matter\_mat-method (apply), 2
- apply,sparse\_mat-method (apply), 2
- apply,virtual\_mat-method (apply), 2
- Arith, 12
- Arith (delayed-ops), 12
- Arith,matter\_arr,matter\_arr-method (delayed-ops), 12
- Arith,matter\_arr,numeric-method (delayed-ops), 12
- Arith,matter\_fc,matter\_fc-method (delayed-ops), 12
- Arith,matter\_fc,numeric-method (delayed-ops), 12
- Arith,matter\_matc,matter\_matc-method (delayed-ops), 12
- Arith,matter\_matc,numeric-method (delayed-ops), 12
- Arith,matter\_matr,matter\_matr-method (delayed-ops), 12
- Arith,matter\_matr,numeric-method (delayed-ops), 12
- Arith,matter\_vec,matter\_vec-method (delayed-ops), 12
- Arith,matter\_vec,numeric-method (delayed-ops), 12
- Arith,numeric,matter\_arr-method (delayed-ops), 12
- Arith,numeric,matter\_fc-method (delayed-ops), 12
- Arith,numeric,matter\_matc-method (delayed-ops), 12
- Arith,numeric,matter\_matr-method (delayed-ops), 12
- Arith,numeric,matter\_vec-method (delayed-ops), 12
- as.array,matter\_arr-method (matter\_arr-class), 20
- as.array,matter\_vec-method (matter\_vec-class), 32
- as.character,matter\_str-method (matter\_str-class), 30
- as.character,matter\_vec-method (matter\_vec-class), 32
- as.data.frame,atoms-method (matter-class), 17
- as.data.frame,matter\_df-method (matter\_df-class), 22
- as.data.frame,virtual\_df-method (matter\_df-class), 22
- as.factor,matter\_fc-method (matter\_fc-class), 24
- as.integer,matter\_arr-method (matter\_arr-class), 20
- as.integer,matter\_mat-method (matter\_mat-class), 28
- as.integer,matter\_vec-method (matter\_vec-class), 32
- as.list,atoms-method (matter-class), 17
- as.list,drle-method (drle-class), 13
- as.list,matter\_list-method (matter\_list-class), 26
- as.list,rep\_vt-method (rep\_vt-class), 36
- as.logical,matter\_arr-method

- (matter\_arr-class), 20
- as.logical, matter\_mat-method (matter\_mat-class), 28
- as.logical, matter\_vec-method (matter\_vec-class), 32
- as.matrix, matter\_arr-method (matter\_arr-class), 20
- as.matrix, matter\_mat-method (matter\_mat-class), 28
- as.matrix, matter\_vec-method (matter\_vec-class), 32
- as.matrix, sparse\_mat-method (sparse\_mat-class), 38
- as.matrix, virtual\_mat-method (virtual\_mat-class), 48
- as.matter (matter-class), 17
- as.numeric, matter\_arr-method (matter\_arr-class), 20
- as.numeric, matter\_mat-method (matter\_mat-class), 28
- as.numeric, matter\_vec-method (matter\_vec-class), 32
- as.raw, matter\_arr-method (matter\_arr-class), 20
- as.raw, matter\_mat-method (matter\_mat-class), 28
- as.raw, matter\_vec-method (matter\_vec-class), 32
- as.sparse (sparse\_mat-class), 38
- as.vector, drle-method (drle-class), 13
- as.vector, matter\_arr-method (matter\_arr-class), 20
- as.vector, matter\_mat-method (matter\_mat-class), 28
- as.vector, matter\_str-method (matter\_str-class), 30
- as.vector, matter\_vec-method (matter\_vec-class), 32
- as.vector, rep\_vt-method (rep\_vt-class), 36
- as.virtual (virtual\_mat-class), 48
- atomdata (matter-class), 17
- atomdata, matter-method (matter-class), 17
- atomdata<- (matter-class), 17
- atomdata<-, matter-method (matter-class), 17
  
- bigglm, 3, 4, 35
- bigglm (biglm), 3
- bigglm, formula, matter\_mat-method (biglm), 3
- bigglm, formula, sparse\_mat-method (biglm), 3
- bigglm, formula, virtual\_df-method (biglm), 3
- bigglm, formula, virtual\_mat-method (biglm), 3
- biglm, 3, 3
- biglm, formula, virtual\_df-method (biglm), 3
- binvec, 5
- bplapply, 3, 8, 10, 15
- bsearch, 6
  
- c, atoms-method (matter-class), 17
- c, drle-method (drle-class), 13
- c, matter-method (matter-class), 17
- c, matter\_vec-method (matter\_vec-class), 32
- cbind, matter-method (matter\_mat-class), 28
- checksum, 7
- checksum, matter-method (checksum), 7
- chunk\_apply, 8
- chunksize (matter-class), 17
- chunksize, matter-method (matter-class), 17
- chunksize<- (matter-class), 17
- chunksize<-, matter-method (matter-class), 17
- chunksize<-, matter\_vt-method (matter-class), 17
- class:drle (drle-class), 13
- class:matter (matter-class), 17
- class:matter\_arr (matter\_arr-class), 20
- class:matter\_df (matter\_df-class), 22
- class:matter\_fc (matter\_fc-class), 24
- class:matter\_list (matter\_list-class), 26
- class:matter\_mat (matter\_mat-class), 28
- class:matter\_str (matter\_str-class), 30
- class:matter\_vec (matter\_vec-class), 32
- class:rep\_vt (rep\_vt-class), 36
- class:sparse\_mat (sparse\_mat-class), 38
- class:virtual\_df (matter\_df-class), 22
- class:virtual\_mat (virtual\_mat-class), 48
- class:virtual\_tbl (matter\_df-class), 22
- colMeans, 3
- colMeans, matter\_mat-method (summary-stats), 45
- colSds (summary-stats), 45
- colSds, matter\_mat-method (summary-stats), 45

- colStats, 9
- colStats, ANY-method (colStats), 9
- colStats, matter\_matr-method (colStats), 9
- colStats, sparse\_matr-method (colStats), 9
- colStats, virtual\_matr-method (colStats), 9
- colstreamStats, 10
- colstreamStats (stream-stats), 41
- colSums, 10
- colSums, matter\_mat-method (summary-stats), 45
- colVars (summary-stats), 45
- colVars, matter\_mat-method (summary-stats), 45
- combine, 11
- combine, ANY, ANY-method (combine), 11
- combine, atoms, ANY-method (matter-class), 17
- combine, drle, drle-method (drle-class), 13
- combine, drle, numeric-method (drle-class), 13
- combine, matter\_fc, ANY-method (matter\_fc-class), 24
- combine, matter\_list, ANY-method (matter\_list-class), 26
- combine, matter\_str, ANY-method (matter\_str-class), 30
- combine, matter\_vec, ANY-method (matter\_vec-class), 32
- combine, numeric, drle-method (drle-class), 13
- combine, stream\_stat, ANY-method (stream-stats), 41
- combiner, 11
- combiner, sparse\_mat-method (sparse\_mat-class), 38
- combiner<- (combiner), 11
- combiner<-, sparse\_mat-method (sparse\_mat-class), 38
- Compare, 12
- Compare (delayed-ops), 12
- Compare, character, matter\_fc-method (delayed-ops), 12
- Compare, factor, matter\_fc-method (delayed-ops), 12
- Compare, matter\_arr, matter\_arr-method (delayed-ops), 12
- Compare, matter\_arr, numeric-method (delayed-ops), 12
- Compare, matter\_arr, raw-method (delayed-ops), 12
- Compare, matter\_fc, character-method (delayed-ops), 12
- Compare, matter\_fc, factor-method (delayed-ops), 12
- Compare, matter\_fc, matter\_fc-method (delayed-ops), 12
- Compare, matter\_fc, numeric-method (delayed-ops), 12
- Compare, matter\_matc, matter\_matc-method (delayed-ops), 12
- Compare, matter\_matc, numeric-method (delayed-ops), 12
- Compare, matter\_matc, raw-method (delayed-ops), 12
- Compare, matter\_matr, matter\_matr-method (delayed-ops), 12
- Compare, matter\_matr, numeric-method (delayed-ops), 12
- Compare, matter\_matr, raw-method (delayed-ops), 12
- Compare, matter\_vec, matter\_vec-method (delayed-ops), 12
- Compare, matter\_vec, numeric-method (delayed-ops), 12
- Compare, matter\_vec, raw-method (delayed-ops), 12
- Compare, numeric, matter\_arr-method (delayed-ops), 12
- Compare, numeric, matter\_fc-method (delayed-ops), 12
- Compare, numeric, matter\_matc-method (delayed-ops), 12
- Compare, numeric, matter\_matr-method (delayed-ops), 12
- Compare, numeric, matter\_vec-method (delayed-ops), 12
- Compare, raw, matter\_arr-method (delayed-ops), 12
- Compare, raw, matter\_matc-method (delayed-ops), 12
- Compare, raw, matter\_matr-method (delayed-ops), 12
- Compare, raw, matter\_vec-method (delayed-ops), 12
- crossprod, ANY, matter-method (matter\_mat-class), 28
- crossprod, matter, ANY-method (matter\_mat-class), 28
- datamode (matter-class), 17
- datamode, atoms-method (matter-class), 17

- datamode,matter-method (matter-class),  
17
- datamode<- (matter-class), 17
- datamode<- ,atoms-method (matter-class),  
17
- datamode<- ,matter-method  
(matter-class), 17
- datamode<- ,matter\_vt-method  
(matter-class), 17
- datamode<- ,sparse\_mat-method  
(sparse\_mat-class), 38
- datamode<- ,virtual\_mat-method  
(virtual\_mat-class), 48
- datatypes (matter-datatypes), 19
- delayed-ops, 12
- digest, 7
- dim,atoms-method (matter-class), 17
- dim,matter-method (matter-class), 17
- dim,matter\_list-method  
(matter\_list-class), 26
- dim<- ,matter-method (matter-class), 17
- dim<- ,matter\_arr-method  
(matter\_arr-class), 20
- dim<- ,matter\_mat-method  
(matter\_mat-class), 28
- dim<- ,matter\_vec-method  
(matter\_vec-class), 32
- dimnames,matter-method (matter-class),  
17
- dimnames<- ,matter ,ANY-method  
(matter-class), 17
- dimnames<- ,virtual\_tbl ,ANY-method  
(matter\_df-class), 22
- drle, 13
- drle (drle-class), 13
- drle-class, 13
- exp,matter\_arr-method (delayed-ops), 12
- exp,matter\_fc-method (delayed-ops), 12
- exp,matter\_mat-method (delayed-ops), 12
- exp,matter\_vec-method (delayed-ops), 12
- filemode (matter-class), 17
- filemode,matter-method (matter-class),  
17
- filemode<- (matter-class), 17
- filemode<- ,matter-method  
(matter-class), 17
- filemode<- ,matter\_vt-method  
(matter-class), 17
- findInterval, 6
- gc, 36
- head,virtual\_tbl-method  
(matter\_df-class), 22
- hex2raw (uuid), 47
- irlba, 34, 35
- is.drle (drle-class), 13
- is.matter (matter-class), 17
- is.sparse (sparse\_mat-class), 38
- is.virtual (virtual\_mat-class), 48
- keys, 14
- keys,sparse\_mat-method  
(sparse\_mat-class), 38
- keys<- (keys), 14
- keys<- ,sparse\_mat-method  
(sparse\_mat-class), 38
- keys<- ,sparse\_matc-method  
(sparse\_mat-class), 38
- keys<- ,sparse\_matr-method  
(sparse\_mat-class), 38
- lapply, 9, 15, 15, 16
- lapply,matter\_list-method (lapply), 15
- lapply,virtual\_df-method (lapply), 15
- length,atoms-method (matter-class), 17
- length,drle-method (drle-class), 13
- length,matter-method (matter-class), 17
- length,rep\_vt-method (rep\_vt-class), 36
- length<- ,matter-method (matter-class),  
17
- lengths,matter-method (matter-class), 17
- lengths,matter\_list-method  
(matter\_list-class), 26
- lengths,matter\_str-method  
(matter\_str-class), 30
- levels,matter\_fc-method  
(matter\_fc-class), 24
- levels<- ,matter\_fc-method  
(matter\_fc-class), 24
- locmax, 16
- log,matter\_arr,numeric-method  
(delayed-ops), 12
- log,matter\_arr-method (delayed-ops), 12
- log,matter\_fc,numeric-method  
(delayed-ops), 12
- log,matter\_fc-method (delayed-ops), 12
- log,matter\_matc,numeric-method  
(delayed-ops), 12
- log,matter\_matc-method (delayed-ops), 12
- log,matter\_matr,numeric-method  
(delayed-ops), 12
- log,matter\_matr-method (delayed-ops), 12



- log,matter\_vec,numeric-method (delayed-ops), 12
- log,matter\_vec-method (delayed-ops), 12
- log10,matter\_arr-method (delayed-ops), 12
- log10,matter\_fc-method (delayed-ops), 12
- log10,matter\_mat-method (delayed-ops), 12
- log10,matter\_vec-method (delayed-ops), 12
- log2,matter\_arr-method (delayed-ops), 12
- log2,matter\_fc-method (delayed-ops), 12
- log2,matter\_mat-method (delayed-ops), 12
- log2,matter\_vec-method (delayed-ops), 12
- Logic, 12
- Logic (delayed-ops), 12
- Logic,logical,matter\_arr-method (delayed-ops), 12
- Logic,logical,matter\_matc-method (delayed-ops), 12
- Logic,logical,matter\_matr-method (delayed-ops), 12
- Logic,logical,matter\_vec-method (delayed-ops), 12
- Logic,matter\_arr,logical-method (delayed-ops), 12
- Logic,matter\_arr,matter\_arr-method (delayed-ops), 12
- Logic,matter\_matc,logical-method (delayed-ops), 12
- Logic,matter\_matc,matter\_matc-method (delayed-ops), 12
- Logic,matter\_matr,logical-method (delayed-ops), 12
- Logic,matter\_matr,matter\_matr-method (delayed-ops), 12
- Logic,matter\_vec,logical-method (delayed-ops), 12
- Logic,matter\_vec,matter\_vec-method (delayed-ops), 12
  
- match, 6
- Math, 12
- matter, 3, 4, 7, 12, 15, 17, 22–24, 26, 28, 30, 32, 34, 40, 41, 45, 50
- matter (matter-class), 17
- matter-class, 17
- matter-datatypes, 19
- matter-options, 20
- matter\_arr, 18, 21
- matter\_arr (matter\_arr-class), 20
- matter\_arr-class, 20
- matter\_df, 3, 18, 23
- matter\_df (matter\_df-class), 22
- matter\_df-class, 22
- matter\_fc, 18, 25
- matter\_fc (matter\_fc-class), 24
- matter\_fc-class, 24
- matter\_list, 15, 18, 27, 44
- matter\_list (matter\_list-class), 26
- matter\_list-class, 26
- matter\_mat, 2, 3, 18, 29, 34, 37, 38
- matter\_mat (matter\_mat-class), 28
- matter\_mat-class, 28
- matter\_matc, 3
- matter\_matc (matter\_mat-class), 28
- matter\_matc-class (matter\_mat-class), 28
- matter\_matr, 3
- matter\_matr (matter\_mat-class), 28
- matter\_matr-class (matter\_mat-class), 28
- matter\_str, 18, 31
- matter\_str (matter\_str-class), 30
- matter\_str-class, 30
- matter\_vec, 18, 26, 33
- matter\_vec (matter\_vec-class), 32
- matter\_vec-class, 32
- max,matter-method (summary-stats), 45
- mean (summary-stats), 45
- mean,matter-method (summary-stats), 45
- mem (profmem), 35
- min,matter-method (summary-stats), 45
  
- names,matter-method (matter-class), 17
- names<- ,matter-method (matter-class), 17
- names<- ,virtual\_tbl-method (matter\_df-class), 22
  
- Ops, 12
- Ops (delayed-ops), 12
  
- path,matter-method (matter-class), 17
- path<- ,matter-method (matter-class), 17
- paths (matter-class), 17
- paths,matter-method (matter-class), 17
- paths<- (matter-class), 17
- paths<- ,matter-method (matter-class), 17
- paths<- ,matter\_vt-method (matter-class), 17
  
- pmatch, 6
- prcomp, 34, 35
- prcomp,matter\_mat-method (prcomp), 34
- prod,matter-method (summary-stats), 45
- profmem, 35
  
- range,matter-method (summary-stats), 45
- raw2hex (uuid), 47

- rbind, matter-method (matter\_mat-class), 28
- readonly (matter-class), 17
- readonly, matter-method (matter-class), 17
- readonly<- (matter-class), 17
- readonly<-, matter-method (matter-class), 17
- readonly<-, matter\_vt-method (matter-class), 17
- rep, 36
- rep\_vt, 37
- rep\_vt (rep\_vt-class), 36
- rep\_vt-class, 36
- rle, 14
- rowMeans, 3
- rowMeans, matter\_mat-method (summary-stats), 45
- rowSds (summary-stats), 45
- rowSds, matter\_mat-method (summary-stats), 45
- rowStats (colStats), 9
- rowStats, ANY-method (colStats), 9
- rowStats, matter\_matc-method (colStats), 9
- rowStats, sparse\_matc-method (colStats), 9
- rowStats, virtual\_matc-method (colStats), 9
- rowstreamStats, 10
- rowstreamStats (stream-stats), 41
- rowSums, matter\_mat-method (summary-stats), 45
- rowVars (summary-stats), 45
- rowVars, matter\_mat-method (summary-stats), 45
- s\_all (stream-stats), 41
- s\_any (stream-stats), 41
- s\_max (stream-stats), 41
- s\_mean (stream-stats), 41
- s\_min (stream-stats), 41
- s\_prod (stream-stats), 41
- s\_range (stream-stats), 41
- s\_sd (stream-stats), 41
- s\_sum (stream-stats), 41
- s\_var (stream-stats), 41
- sapply (lapply), 15
- sapply, matter\_list-method (lapply), 15
- sapply, virtual\_df-method (lapply), 15
- scale, 37, 37, 38
- scale, matter\_mat-method (scale), 37
- scale.matter (scale), 37
- sd (summary-stats), 45
- sd, matter-method (summary-stats), 45
- sparse\_mat, 2, 12, 15, 39, 47
- sparse\_mat (sparse\_mat-class), 38
- sparse\_mat-class, 38
- sparse\_matc (sparse\_mat-class), 38
- sparse\_matc-class (sparse\_mat-class), 38
- sparse\_matr (sparse\_mat-class), 38
- sparse\_matr-class (sparse\_mat-class), 38
- stat\_c (stream-stats), 41
- stream-stats, 41
- stream\_stat, 46
- stream\_stat (stream-stats), 41
- struct, 44
- sum, matter-method (summary-stats), 45
- Summary, 43
- Summary (summary-stats), 45
- summary-stats, 45
- t, matter\_matc-method (matter\_mat-class), 28
- t, matter\_matr-method (matter\_mat-class), 28
- t, matter\_vec-method (matter\_vec-class), 32
- t, sparse\_matc-method (sparse\_mat-class), 38
- t, sparse\_matr-method (sparse\_mat-class), 38
- t, virtual\_mat-method (virtual\_mat-class), 48
- t.matter (matter\_mat-class), 28
- tail, virtual\_tbl-method (matter\_df-class), 22
- tcrossprod, ANY, matter-method (matter\_mat-class), 28
- tcrossprod, matter, ANY-method (matter\_mat-class), 28
- tempfile, 21, 25, 27, 29, 31, 33
- tolerance, 47
- tolerance, sparse\_mat-method (sparse\_mat-class), 38
- tolerance<- (tolerance), 47
- tolerance<- , sparse\_mat-method (sparse\_mat-class), 38
- uuid, 47
- var (summary-stats), 45
- var, matter-method (summary-stats), 45
- virtual\_df, 23
- virtual\_df (matter\_df-class), 22
- virtual\_df-class (matter\_df-class), 22

virtual\_mat, [2](#), [49](#)  
virtual\_mat (virtual\_mat-class), [48](#)  
virtual\_mat-class, [48](#)  
virtual\_matc (virtual\_mat-class), [48](#)  
virtual\_matc-class (virtual\_mat-class),  
[48](#)  
virtual\_matr (virtual\_mat-class), [48](#)  
virtual\_matr-class (virtual\_mat-class),  
[48](#)  
virtual\_tbl-class (matter\_df-class), [22](#)  
which, matter-method (matter-class), [17](#)