

Package ‘MSstats’

October 16, 2025

Title Protein Significance Analysis in DDA, SRM and DIA for Label-free or Label-based Proteomics Experiments

Version 4.16.1

Date 2025-03-05

Description A set of tools for statistical relative protein significance analysis in DDA, SRM and DIA experiments.

License Artistic-2.0

Depends R (>= 4.0)

Imports MSstatsConvert, data.table, checkmate, MASS, htmltools, limma, lme4, preprocessCore, survival, utils, Rcpp, ggplot2, ggrepel, gplots, plotly, marray, stats, grDevices, graphics, methods, statmod, parallel

Suggests BiocStyle, knitr, rmarkdown, tinytest, covr, markdown, mockery, kableExtra

VignetteBuilder knitr

biocViews ImmunoOncology, MassSpectrometry, Proteomics, Software, Normalization, QualityControl, TimeCourse

LazyData true

URL <http://msstats.org>

BugReports <https://groups.google.com/forum/#!forum/msstats>

RoxygenNote 7.3.2

Encoding UTF-8

NeedsCompilation no

LinkingTo Rcpp, RcppArmadillo

git_url <https://git.bioconductor.org/packages/MSstats>

git_branch RELEASE_3_21

git_last_commit a221510

git_last_commit_date 2025-07-02

Repository Bioconductor 3.21

Date/Publication 2025-10-15

Author Meena Choi [aut, cre],
 Mateusz Staniak [aut],
 Devon Kohler [aut],
 Tony Wu [aut],
 Deril Raju [aut],
 Tsung-Heng Tsai [aut],
 Ting Huang [aut],
 Olga Vitek [aut]

Maintainer Meena Choi <mnchoi67@gmail.com>

Contents

.addCoverageInfo	5
.addModelInformation	5
.addModelVariances	6
.addNInformativeInfo	6
.addNoisyFlag	7
.addOutlierCutoff	7
.addOutlierInformation	8
.addSurvivalPredictions	8
.adjustLRuns	9
.calculateOutlierCutoff	9
.calculatePower	10
.calculateProteinVariance	10
.checkContrastMatrix	11
.checkDataProcessParams	11
.checkExperimentDesign	12
.checkGCPlotsInput	12
.checkGroupComparisonInput	13
.checkSingleFeature	13
.checkSingleLabelProteins	14
.checkSingleSubject	14
.checkTechReplicate	15
.checkUnProcessedDataValidity	15
.countInformative	16
.countMissingPercentage	16
.documentFunction	17
.finalizeInput	18
.finalizeLinear	18
.finalizeTMP	19
.fitHuber	19
.fitLinearModel	20
.fitModelForGroupComparison	20
.fitModelSingleProtein	21
.fitTukey	22
.flagLowCoverage	22

.flagUninformativeSingleLabel	23
.getAllComparisons	23
.getColorKeyGGPlot2	24
.getColorKeyPlotly	24
.getContrast	24
.getContrastLabels	25
.getEmptyComparison	25
.getFeatureVariances	26
.getMedian	26
.getMedianSigmaSubject	27
.getModelParameters	27
.getNonMissingFilter	28
.getNonMissingFilterStats	28
.getNumSample	29
.getSingleProteinForProfile	29
.getVarComponent	30
.getWideTable	30
.getYaxis	31
.groupComparisonWithMultipleCores	31
.groupComparisonWithSingleCore	32
.handleEmptyConditions	32
.handleSingleContrast	33
.isSummarizable	34
.logDatasetInformation	34
.logMissingness	35
.logSingleLabeledProteins	35
.logSummaryStatistics	36
.makeComparison	36
.makeConditionPlot	37
.makeFactorColumns	38
.makeHeatmapPlotly	38
.makeProfilePlot	39
.makeQCPlot	40
.makeSummaryProfilePlot	42
.makeVolcano	43
.nicePrint	44
.normalizeGlobalStandards	44
.normalizeMedian	45
.normalizeQuantile	45
.onLoad	45
.plotComparison	46
.plotHeatmap	47
.plotVolcano	49
.prepareForDataProcess	50
.prepareLinear	51
.prepareSingleProteinForGC	51
.prepareSummary	52
.prepareTMP	52

.preProcessIntensities	53
.quantileNormalizationSingleLabel	53
.replaceZerosWithNA	54
.runTukey	54
.saveSessionInfo	55
.saveTable	55
.selectHighQualityFeatures	55
.selectTopFeatures	56
.setCensoredByThreshold	56
.updateColumnsForProcessing	57
.updateUnequalVariances	57
checkRepeatedDesign	58
dataProcess	58
dataProcessPlots	62
DDARawData	65
DDARawData.Skyline	66
designSampleSize	68
designSampleSizePlots	70
DIARawData	71
example_SDRF	72
extractSDRF	73
getProcessed	74
getSamplesInfo	75
getSelectedProteins	75
groupComparison	76
groupComparisonPlots	78
groupComparisonQCPlots	82
makePeptidesDictionary	84
modelBasedQCPlots	84
MSstatsContrastMatrix	86
MSstatsGroupComparison	87
MSstatsGroupComparisonOutput	88
MSstatsGroupComparisonSingleProtein	89
MSstatsHandleMissing	90
MSstatsMergeFractions	91
MSstatsNormalize	91
MSstatsPrepareForDataProcess	92
MSstatsPrepareForGroupComparison	93
MSstatsPrepareForSummarization	94
MSstatsSelectFeatures	95
MSstatsSummarizationOutput	96
MSstatsSummarizeSingleLinear	97
MSstatsSummarizeSingleTMP	98
MSstatsSummarizeWithMultipleCores	99
MSstatsSummarizeWithSingleCore	100
quantification	101
reexports	103
savePlot	103

<i>.addCoverageInfo</i>	5
-------------------------	---

SDRFtoAnnotation	104
SRMRawData	105
theme_msstats	106
validateAnnotation	107

Index	108
--------------	------------

<i>.addCoverageInfo</i>	<i>Add coverage information to a data.table</i>
-------------------------	---

Description

Add coverage information to a data.table

Usage

.addCoverageInfo(input)

Arguments

input data.table

Value

data.table

<i>.addModelInformation</i>	<i>Add model information</i>
-----------------------------	------------------------------

Description

Add model information

Usage

.addModelInformation(input)

Arguments

input data.table

Value

data.table

.addModelVariances	<i>Add model variances</i>
--------------------	----------------------------

Description

Add model variances

Usage

.addModelVariances(input)

Arguments

input	data.table
-------	------------

Value

data.table

.addNInformativeInfo	<i>Add information about number of informative features</i>
----------------------	---

Description

Add information about number of informative features

Usage

.addNInformativeInfo(input, min_feature_count, column)

Arguments

input	data.table
min_feature_count	minimum number of quality features to consider
column	name of a column used for filtering

Value

data.table

<code>.addNoisyFlag</code>	<i>Add flag for noisy features</i>
----------------------------	------------------------------------

Description

Add flag for noisy features

Usage

```
.addNoisyFlag(input)
```

Arguments

<code>input</code>	<code>data.table</code>
--------------------	-------------------------

Value

`data.table`

<code>.addOutlierCutoff</code>	<i>Add outlier cutoff</i>
--------------------------------	---------------------------

Description

Add outlier cutoff

Usage

```
.addOutlierCutoff(input, quantile_order = 0.01)
```

Arguments

<code>input</code>	<code>data.table</code>
<code>quantile_order</code>	quantile used to label outliers

Value

`data.table`

`.addOutlierInformation`*Add flag for outlier*

Description

Add flag for outlier

Usage

```
.addOutlierInformation(input, tol = 3, keep_run = FALSE)
```

Arguments

input	data.table
tol	cutoff for outliers
keep_run	if TRUE, completely missing runs will be kept

Value

logical

`.addSurvivalPredictions`*Get predicted values from a survival model*

Description

Get predicted values from a survival model

Usage

```
.addSurvivalPredictions(input)
```

Arguments

input	data.table
-------	------------

Value

numeric vector of predictions

<code>.adjustLRuns</code>	<i>Adjust summarized abundance based on the heavy channel</i>
---------------------------	---

Description

Adjust summarized abundance based on the heavy channel

Usage

```
.adjustLRuns(input, rename = FALSE)
```

Arguments

<code>input</code>	data.table
<code>rename</code>	if TRUE, rename the output column to LogIntensities

Value

data.table

<code>.calculateOutlierCutoff</code>	<i>Calculate cutoff to label outliers</i>
--------------------------------------	---

Description

Calculate cutoff to label outliers

Usage

```
.calculateOutlierCutoff(input, quantile_order = 0.01)
```

Arguments

<code>input</code>	data.table
<code>quantile_order</code>	quantile used to label outliers

Value

numeric

<code>.calculatePower</code>	<i>Power calculation</i>
------------------------------	--------------------------

Description

Power calculation

Usage

```
.calculatePower(
  desiredFC,
  FDR,
  delta,
  median_sigma_error,
  median_sigma_subject,
  numSample
)
```

Arguments

<code>desiredFC</code>	the range of a desired fold change which includes the lower and upper values of the desired fold change.
<code>FDR</code>	a pre-specified false discovery ratio (FDR) to control the overall false positive rate. Default is 0.05
<code>delta</code>	difference between means (?)
<code>median_sigma_error</code>	median of error standard deviation
<code>median_sigma_subject</code>	median standard deviation per subject
<code>numSample</code>	minimal number of biological replicates per condition. TRUE represents you require to calculate the sample size for this category, else you should input the exact number of biological replicates.

<code>.calculateProteinVariance</code>	<i>Calculate protein variances</i>
--	------------------------------------

Description

Calculate protein variances

Usage

```
.calculateProteinVariance(input)
```

Arguments

<code>input</code>	<code>data.table</code>
--------------------	-------------------------

Value

list of residuals, degree of freedom and variances

<code>.checkContrastMatrix</code>	<i>Check if contrast matrix includes all conditions</i>
-----------------------------------	---

Description

Check if contrast matrix includes all conditions

Usage

```
.checkContrastMatrix(contrast_matrix, input)
```

Arguments

<code>contrast_matrix</code>	contrast matrix
<code>input</code>	data.table of summarized data

<code>.checkDataProcessParams</code>	<i>Check validity of parameters to dataProcess function</i>
--------------------------------------	---

Description

Check validity of parameters to dataProcess function

Usage

```
.checkDataProcessParams(  
  log_base,  
  normalization_method,  
  standards_names,  
  feature_selection,  
  summarization,  
  imputation  
)
```

Arguments

log_base	of logarithmic transformation
normalization_method	string: "quantile", "equalizemedians", "FALSE", "NONE" or "globalStandards"
feature_selection	list with elements: remove_uninformative
summarization	list with elements: method.
imputation	list with elements: cutoff, symbol.

.checkExperimentDesign *Check if a given column exists in the data*

Description

Check if a given column exists in the data

Usage

`.checkExperimentDesign(input, column_name)`

Arguments

input	data.table
column_name	chr, name of a column to check

.checkGCPlotsInput *Check groupComparisonPlots parameters*

Description

Check groupComparisonPlots parameters

Usage

`.checkGCPlotsInput(type, log_base, selected_labels, all_labels)`

Arguments

type	type of a plot: HEATMAP/VOLCANOPLOT/COMPARISONPLOT
log_base	2 or 10
selected_labels	character vector of contrast labels
all_labels	character vector of all contrast labels

`.checkGroupComparisonInput`*Check if groupComparison input was processed by the dataProcess function*

Description

Check if groupComparison input was processed by the dataProcess function

Usage`.checkGroupComparisonInput(input)`**Arguments**

<code>input</code>	<code>data.table</code>
--------------------	-------------------------

`.checkSingleFeature` *Check if data has less than two features*

Description

Check if data has less than two features

Usage`.checkSingleFeature(input)`**Arguments**

<code>input</code>	<code>data.table</code>
--------------------	-------------------------

Value

logical

`.checkSingleLabelProteins`*Check if there are proteins with a single label in a labeled dataset*

Description

Check if there are proteins with a single label in a labeled dataset

Usage

```
.checkSingleLabelProteins(input)
```

Arguments

input	data.table
-------	------------

Value

TRUE invisibly

`.checkSingleSubject`*Check if there is only single subject*

Description

Check if there is only single subject

Usage

```
.checkSingleSubject(input)
```

Arguments

input	data.table
-------	------------

.checkTechReplicate	<i>Check if there are technical replicates</i>
---------------------	--

Description

Check if there are technical replicates

Usage

```
.checkTechReplicate(input)
```

Arguments

input	data.table
-------	------------

.checkUnProcessedDataValidity	<i>Check validity of data that were not processed by MSstats converter</i>
-------------------------------	--

Description

Check validity of data that were not processed by MSstats converter

Usage

```
.checkUnProcessedDataValidity(input, fix_missing, fill_incomplete)
```

Arguments

input	data.table
fix_missing	str, optional. Defaults to NULL, which means no action. If not NULL, must be one of the options: "zero_to_na" or "na_to_zero". If "zero_to_na", Intensity values equal exactly to 0 will be converted to NA. If "na_to_zero", missing values will be replaced by zeros.

.countInformative	Count informative features
-------------------	----------------------------

Description	
Count informative features	
Usage	
<code>.countInformative(input, column)</code>	
Arguments	
input	data.table
column	name of a column used for filtering
Value	
numeric	

.countMissingPercentage	Count percentage of missing values in given conditions
-------------------------	--

Description

Count percentage of missing values in given conditions

Usage

```
.countMissingPercentage(  
  contrast_matrix,  
  summarized,  
  result,  
  samples_info,  
  has_imputed  
)
```

Arguments

contrast_matrix	contrast matrix
summarized	data.table summarized by the dataProcess function
result	result of groupComparison
samples_info	number of runs per group
has_imputed	if TRUE, missing values have been imputed by dataProcess

<code>.documentFunction</code>	<i>A dummy function to store shared documentation items.</i>
--------------------------------	--

Description

A dummy function to store shared documentation items.

Usage

```
.documentFunction()
```

Arguments

<code>removeFewMeasurements</code>	TRUE (default) will remove the features that have 1 or 2 measurements across runs.
<code>useUniquePeptide</code>	TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
<code>summaryforMultipleRows</code>	max(default) or sum - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities.
<code>removeProtein_with1Feature</code>	TRUE will remove the proteins which have only 1 feature, which is the combination of peptide, precursor charge, fragment and charge. FALSE is default.
<code>removeProtein_with1Peptide</code>	TRUE will remove the proteins which have only 1 peptide and charge. FALSE is default.
<code>removeOxidationMpeptides</code>	TRUE will remove the peptides including 'oxidation (M)' in modification. FALSE is default.
<code>removeMpeptides</code>	TRUE will remove the peptides including 'M' sequence. FALSE is default.
<code>use_log_file</code>	logical. If TRUE, information about data processing will be saved to a file.
<code>append</code>	logical. If TRUE, information about data processing will be added to an existing log file.
<code>verbose</code>	logical. If TRUE, information about data processing will be printed to the console.
<code>log_file_path</code>	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

<code>.finalizeInput</code>	<i>Add summary statistics to dataProcess output</i>
-----------------------------	---

Description

Add summary statistics to dataProcess output

Usage

`.finalizeInput(input, summarized, method, impute, censored_symbol)`

Arguments

- `input` feature-level data
- `summarized` protein-level data (list)
- `method` summary method
- `impute` if TRUE, censored missing values were imputed
- `censored_symbol` censored missing value indicator

<code>.finalizeLinear</code>	<i>Summary statistics for linear model-based summarization</i>
------------------------------	--

Description

Summary statistics for linear model-based summarization

Usage

`.finalizeLinear(input, censored_symbol)`

Arguments

- `input` feature-level data
- `censored_symbol` censored missing value indicator

<code>.finalizeTMP</code>	<i>Summary statistics for output of TMP-based summarization</i>
---------------------------	---

Description

Summary statistics for output of TMP-based summarization

Usage

```
.finalizeTMP(input, censored_symbol, impute, summarized)
```

Arguments

<code>input</code>	feature-level data
<code>censored_symbol</code>	censored missing value indicator
<code>impute</code>	if TRUE, censored missing values were imputed
<code>summarized</code>	protein-level data (list)

<code>.fitHuber</code>	<i>Wrapper to fit robust linear model for one protein</i>
------------------------	---

Description

Wrapper to fit robust linear model for one protein

Usage

```
.fitHuber(input)
```

Value

rlm

<code>.fitLinearModel</code>	<i>Fit a linear model</i>
------------------------------	---------------------------

Description

Fit a linear model

Usage

```
.fitLinearModel(input, is_single_feature, is_labeled, equal_variances)
```

Arguments

<code>input</code>	<code>data.table</code>
<code>is_single_feature</code>	logical, if TRUE, data has single feature
<code>is_labeled</code>	logical, if TRUE, data comes from a labeled experiment
<code>equal_variances</code>	logical, if TRUE, equal variances are assumed

Value

lm or merMod

<code>.fitModelForGroupComparison</code>	<i>Choose a model type (fixed/mixed effects) and fit it for a single protein</i>
--	--

Description

Choose a model type (fixed/mixed effects) and fit it for a single protein

Usage

```
.fitModelForGroupComparison(
  input,
  repeated,
  is_single_subject,
  has_tech_replicates
)
```

Arguments

<code>input</code>	data.table of summarized data
<code>repeated</code>	if TRUE, experiment consists of repeated measurements
<code>is_single_subject</code>	if TRUE, experiment consists of a single subject
<code>has_tech_replicates</code>	if TRUE, there are technical replicates

`.fitModelSingleProtein`*Fit model and perform group comparison for a single protein*

Description

Fit model and perform group comparison for a single protein

Usage

```
.fitModelSingleProtein(  
  input,  
  contrast_matrix,  
  has_tech_replicates,  
  is_single_subject,  
  repeated,  
  groups,  
  samples_info,  
  save_fitted_models,  
  has_imputed  
)
```

Arguments

<code>input</code>	data.table of summarized data
<code>contrast_matrix</code>	contrast matrix
<code>has_tech_replicates</code>	if TRUE, there are technical replicates
<code>is_single_subject</code>	if TRUE, experiment consists of a single subject
<code>repeated</code>	if TRUE, experiment consists of repeated measurements
<code>groups</code>	unique labels for experimental conditions
<code>samples_info</code>	number of runs per group
<code>save_fitted_models</code>	if TRUE, fitted model will be saved. If FALSE, it will be replaced by NULL
<code>has_imputed</code>	if TRUE, missing values have been imputed by dataProcess

<code>.fitTukey</code>	<i>Fit tukey median polish for a data matrix</i>
------------------------	--

Description

Fit tukey median polish for a data matrix

Usage

```
.fitTukey(input)
```

Arguments

input	data.table with data for a single protein
-------	---

Value

data.table

<code>.flagLowCoverage</code>	<i>Flag for low coverage features</i>
-------------------------------	---------------------------------------

Description

Flag for low coverage features

Usage

```
.flagLowCoverage(input)
```

Arguments

input	data.table
-------	------------

Value

logical

```
.flagUninformativeSingleLabel
```

Flag uninformative features

Description

Flag uninformative features

Usage

```
.flagUninformativeSingleLabel(input, min_feature_count = 2)
```

Arguments

input	data.table
min_feature_count	minimum number of quality features to consider

Value

data.table

```
.getAllComparisons
```

Get all comparisons for a single protein and a contrast matrix

Description

Get all comparisons for a single protein and a contrast matrix

Usage

```
.getAllComparisons(input, fitted_model, contrast_matrix, groups, protein)
```

Arguments

input	summarized data
fitted_model	model fitted by the <code>.fitModelForGroupComparison</code> function
contrast_matrix	contrast matrix
groups	unique labels of experimental conditions
protein	name of a protein

<code>.getColorKeyGGPlot2</code>	<i>Create colorkey for ggplot2 heatmap</i>
----------------------------------	--

Description

Create colorkey for ggplot2 heatmap

Usage

```
.getColorKeyGGPlot2(my.colors, blocks)
```

Arguments

<code>my.colors</code>	<code>blocks</code>
------------------------	---------------------

<code>.getColorKeyPlotly</code>	<i>Create colorkey for plotly heatmap</i>
---------------------------------	---

Description

Create colorkey for plotly heatmap

Usage

```
.getColorKeyPlotly(my.colors, blocks)
```

Arguments

<code>my.colors</code>	<code>blocks</code>
------------------------	---------------------

<code>.getContrast</code>	<i>Create a contrast for a model with only group as a fixed effect</i>
---------------------------	--

Description

Create a contrast for a model with only group as a fixed effect

Usage

```
.getContrast(input, contrast, coefs, groups)
```

Arguments

<code>input</code>	summarized data for a single protein
<code>coefs</code>	coefficients of a linear model (named vector)
<code>groups</code>	unique group labels
<code>contrast_matrix</code>	row of a <code>contrast_matrix</code>

<code>.getContrastLabels</code>	<i>Get labels for contrasts</i>
---------------------------------	---------------------------------

Description

Get labels for contrasts

Usage

```
.getContrastLabels(contrasts)
```

Arguments

<code>contrasts</code>	list of lists of condition labels
------------------------	-----------------------------------

<code>.getEmptyComparison</code>	<i>Comparison output when there are measurements only in a single condition</i>
----------------------------------	---

Description

Comparison output when there are measurements only in a single condition

Usage

```
.getEmptyComparison(input, contrast_matrix, groups, protein)
```

Arguments

<code>input</code>	summarized data
<code>contrast_matrix</code>	contrast matrix
<code>groups</code>	unique labels of experimental conditions
<code>protein</code>	name of a protein

<code>.getFeatureVariances</code>	<i>Calculate variances of features</i>
-----------------------------------	--

Description

Calculate variances of features

Usage

```
.getFeatureVariances(input, tolerance = 3)
```

Arguments

<code>input</code>	<code>data.table</code>
<code>tolerance</code>	cutoff for outliers

Value

numeric

<code>.getMedian</code>	<i>Get median of protein abundances for a given label</i>
-------------------------	---

Description

Get median of protein abundances for a given label

Usage

```
.getMedian(df, label)
```

Arguments

<code>df</code>	<code>'data.table'</code>
<code>label</code>	"L" for light isotopes, "H" for heavy isotopes.

`.getMedianSigmaSubject`*Get median per subject or group by subject*

Description

Get median per subject or group by subject

Usage

```
.getMedianSigmaSubject(var_component)
```

Arguments

`var_component` data.frame, output of `.getVarComponent`

`.getModelParameters` *Get params (coefficients, covariance matrix, degrees of freedom) from a model*

Description

Get params (coefficients, covariance matrix, degrees of freedom) from a model

Usage

```
.getModelParameters(fitted_model)
```

Arguments

`fitted_model` object of class `lm` or `lmerMod`

`.getNonMissingFilter` *Identify non-missing values*

Description

Identify non-missing values

Usage

```
.getNonMissingFilter(input, impute, censored_symbol)
```

Arguments

<code>input</code>	'data.table' in MSstats format
<code>impute</code>	if TRUE, missing values are supposed to be imputed
<code>censored_symbol</code>	'censoredInt' parameter to dataProcess

`.getNonMissingFilterStats`

Get a logical vector for non-missing values to calculate summary statistics

Description

Get a logical vector for non-missing values to calculate summary statistics

Usage

```
.getNonMissingFilterStats(input, censored_symbol)
```

Arguments

<code>input</code>	data.table with data for a single protein
<code>censored_symbol</code>	Missing values are censored or at random. 'NA' (default) assumes that all 'NA's in 'Intensity' column are censored. '0' uses zero intensities as censored intensity. In this case, NA intensities are missing at random. The output from Skyline should use '0'. Null assumes that all NA intensities are randomly missing.

Value

data.table

<code>.getNumSample</code>	<i>Get sample size</i>
----------------------------	------------------------

Description

Get sample size

Usage

```
.getNumSample(  
    desiredFC,  
    power,  
    alpha,  
    delta,  
    median_sigma_error,  
    median_sigma_subject  
)
```

Arguments

<code>desiredFC</code>	the range of a desired fold change which includes the lower and upper values of the desired fold change.
<code>power</code>	a pre-specified statistical power which defined as the probability of detecting a true fold change. TRUE represent you require to calculate the power for this category, else you should input the average of power you expect. Default is 0.9
<code>alpha</code>	significance level
<code>delta</code>	difference between means (?)
<code>median_sigma_error</code>	median of error standard deviation
<code>median_sigma_subject</code>	median standard deviation per subject

<code>.getSingleProteinForProfile</code>	<i>Get data for a single protein to plot</i>
--	--

Description

Get data for a single protein to plot

Usage

```
.getSingleProteinForProfile(processed, all_proteins, i)
```

Arguments

<code>all_proteins</code>	character, set of protein names
<code>i</code>	integer, index of protein to use
<code>dataProcess</code>	output -> FeatureLevelData

<code>.getVarComponent</code>	<i>Get variances from models fitted by the groupComparison function</i>
-------------------------------	---

Description

Get variances from models fitted by the groupComparison function

Usage

```
.getVarComponent(fitted_models)
```

Arguments

<code>fitted_models</code>	FittedModels element of groupComparison output
----------------------------	--

<code>.getWideTable</code>	<i>Utility function for quantile normalization - get table in wide format</i>
----------------------------	---

Description

Utility function for quantile normalization - get table in wide format

Usage

```
.getWideTable(input, runs, label = "L", remove_missing = TRUE)
```

Arguments

<code>input</code>	'data.table' in MSstats standard format
<code>label</code>	"L" for light isotopes, "H" for heavy isotopes
<code>remove_missing</code>	if TRUE, only non-missing values will be considered
<code>vector</code>	of run labels

.getYaxis	<i>Get name for y-axis</i>
-----------	----------------------------

Description

Get name for y-axis

Usage

```
.getYaxis(temp)
```

Arguments

temp	data.table
------	------------

.groupComparisonWithMultipleCores	<i>Perform group comparison per protein in parallel</i>
-----------------------------------	---

Description

Perform group comparison per protein in parallel

Usage

```
.groupComparisonWithMultipleCores(  
  summarized_list,  
  contrast_matrix,  
  save_fitted_models,  
  repeated,  
  samples_info,  
  numberOfCores  
)
```

Arguments

summarized_list	output of MSstatsPrepareForGroupComparison
contrast_matrix	contrast matrix
save_fitted_models	if TRUE, fitted models will be included in the output
repeated	logical, output of checkRepeatedDesign function
samples_info	data.table, output of getSamplesInfo function
numberOfCores	Number of cores for parallel processing. A logfile named ‘MSstats_groupComparison_log_progress.log’ is created to track progress. Only works for Linux & Mac OS.

```
.groupComparisonWithSingleCore
```

Perform group comparison per protein iteratively with a single loop

Description

Perform group comparison per protein iteratively with a single loop

Usage

```
.groupComparisonWithSingleCore(  
  summarized_list,  
  contrast_matrix,  
  save_fitted_models,  
  repeated,  
  samples_info  
)
```

Arguments

<code>summarized_list</code>	output of <code>MSstatsPrepareForGroupComparison</code>
<code>contrast_matrix</code>	contrast matrix
<code>save_fitted_models</code>	if TRUE, fitted models will be included in the output
<code>repeated</code>	logical, output of <code>checkRepeatedDesign</code> function
<code>samples_info</code>	data.table, output of <code>getSamplesInfo</code> function

```
.handleEmptyConditions
```

Handle contrast when some of the conditions are missing

Description

Handle contrast when some of the conditions are missing

Usage

```
.handleEmptyConditions(  
  input,  
  fit,  
  contrast,  
  groups,
```

```
parameters,  
protein,  
empty_conditions,  
coefs  
)
```

Arguments

input	summarized data
contrast	single row of a contrast matrix
groups	unique labels of experimental conditions
parameters	parameters extracted from the model
protein	name of a protein
empty_conditions	labels of empty conditions
coefs	coefficient of the fitted model

.handleSingleContrast *Group comparison for a single contrast*

Description

Group comparison for a single contrast

Usage

```
.handleSingleContrast(input, fit, contrast, groups, parameters, protein, coefs)
```

Arguments

input	summarized data
contrast	single row of a contrast matrix
groups	unique labels of experimental conditions
parameters	parameters extracted from the model
protein	name of a protein
coefs	coefficient of the fitted model

<code>.isSummarizable</code>	<i>Check if a protein can be summarized with TMP</i>
------------------------------	--

Description

Check if a protein can be summarized with TMP

Usage

```
.isSummarizable(input, remove50missing)
```

Arguments

<code>input</code>	<code>data.table</code>
<code>remove50missing</code>	if TRUE, proteins with more than 50 in all runs will not be summarized

Value

`data.table`

<code>.logDatasetInformation</code>	<i>Log information about feature-level data</i>
-------------------------------------	---

Description

Log information about feature-level data

Usage

```
.logDatasetInformation(input)
```

Arguments

<code>input</code>	<code>data.table</code>
--------------------	-------------------------

Value

TRUE invisibly after successful logging

.logMissingness	<i>Log information about missing data</i>
-----------------	---

Description

Log information about missing data

Usage

```
.logMissingness(input)
```

Arguments

input	data.table
-------	------------

Value

TRUE invisibly

.logSingleLabeledProteins	<i>Print proteins with a single label to the log file</i>
---------------------------	---

Description

Print proteins with a single label to the log file

Usage

```
.logSingleLabeledProteins(input, label)
```

Arguments

input	data.table
label	label ("L" or "H")

Value

TRUE invisibly

`.logSummaryStatistics` *Print summary statistics to the log file*

Description

Print summary statistics to the log file

Usage

```
.logSummaryStatistics(input)
```

Arguments

input	data.table
-------	------------

Value

TRUE invisibly

`.makeComparison` *Create comparison plot*

Description

Create comparison plot

Usage

```
.makeComparison(  
  input,  
  log_base,  
  dot.size,  
  x.axis.size,  
  y.axis.size,  
  text.angle,  
  hjust,  
  vjust,  
  y.limdown,  
  y.limup  
)
```

Arguments

<code>input</code>	data.table
<code>log_base</code>	2 or 10
<code>dot.size</code>	size of dots in volcano plot and comparison plot. Default is 3.
<code>x.axis.size</code>	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
<code>y.axis.size</code>	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
<code>text.angle</code>	angle of x-axis labels represented each comparison at the bottom of graph in comparison plot. Default is 0.

<code>.makeConditionPlot</code>	<i>Make condition plot</i>
---------------------------------	----------------------------

Description

Make condition plot

Usage

```
.makeConditionPlot(  
  input,  
  scale,  
  single_protein,  
  y.limdown,  
  y.limup,  
  x.axis.size,  
  y.axis.size,  
  text.size,  
  text.angle,  
  legend.size,  
  dot.size.condition,  
  yaxis.name  
)
```

Arguments

<code>input</code>	data.table
<code>scale</code>	for "ConditionPlot" only, FALSE(default) means each conditional level is not scaled at x-axis according to its actual value (equal space at x-axis). TRUE means each conditional level is scaled at x-axis according to its actual value (unequal space at x-axis).
<code>single_protein</code>	data.table
<code>x.axis.size</code>	size of x-axis labeling for "Run" in Profile Plot and QC Plot, and "Condition" in Condition Plot. Default is 10.

<code>y.axis.size</code>	size of y-axis labels. Default is 10.
<code>text.size</code>	size of labels represented each condition at the top of graph in Profile Plot and QC plot. Default is 4.
<code>text.angle</code>	angle of labels represented each condition at the top of graph in Profile Plot and QC plot or x-axis labeling in Condition plot. Default is 0.
<code>legend.size</code>	size of feature legend (transition-level or peptide-level) above graph in Profile Plot. Default is 7.
<code>dot.size.condition</code>	size of dots in condition plot. Default is 3.

<code>.makeFactorColumns</code>	<i>Make factor columns where needed</i>
---------------------------------	---

Description

Make factor columns where needed

Usage

```
.makeFactorColumns(input)
```

Arguments

<code>input</code>	<code>data.table</code>
--------------------	-------------------------

<code>.makeHeatmapPlotly</code>	<i>Create heatmap</i>
---------------------------------	-----------------------

Description

Create heatmap

Usage

```
.makeHeatmapPlotly(
  input,
  my.colors,
  my.breaks,
  x.axis.size,
  y.axis.size,
  height,
  numProtein
)
```

Arguments

<code>input</code>	data.table
<code>x.axis.size</code>	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
<code>y.axis.size</code>	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
<code>height</code>	height of the saved file in pixels. Default is 600.
<code>numProtein</code>	For ggplot2: The number of proteins which will be presented in each heatmap. Default is 100. Maximum possible number of protein for one heatmap is 180. For Plotly: use this parameter to adjust the number of proteins to be displayed on the heatmap

<code>.makeProfilePlot</code>	<i>Create profile plot</i>
-------------------------------	----------------------------

Description

Create profile plot

Usage

```
.makeProfilePlot(  
  input,  
  is_censored,  
  featureName,  
  y.limdown,  
  y.limup,  
  x.axis.size,  
  y.axis.size,  
  text.size,  
  text.angle,  
  legend.size,  
  dot.size.profile,  
  ss,  
  s,  
  cumGroupAxis,  
  yaxis.name,  
  lineNameAxis,  
  groupNameetemp,  
  dot_colors  
)
```

Arguments

<code>input</code>	data.table
<code>is_censored</code>	TRUE if censored values were imputed

featureName	for "ProfilePlot" only, "Transition" (default) means printing feature legend in transition-level; "Peptide" means printing feature legend in peptide-level; "NA" means no feature legend printing.
x.axis.size	size of x-axis labeling for "Run" in Profile Plot and QC Plot, and "Condition" in Condition Plot. Default is 10.
y.axis.size	size of y-axis labels. Default is 10.
text.size	size of labels represented each condition at the top of graph in Profile Plot and QC plot. Default is 4.
text.angle	angle of labels represented each condition at the top of graph in Profile Plot and QC plot or x-axis labeling in Condition plot. Default is 0.
legend.size	size of feature legend (transition-level or peptide-level) above graph in Profile Plot. Default is 7.
dot.size.profile	size of dots in profile plot. Default is 2.

.makeQCPlot

Make QC plot

Description

To illustrate the quantitative data after data-preprocessing and quality control of MS runs, dataProcessPlots takes the quantitative data from function ([dataProcess](#)) as input and automatically generate three types of figures in pdf files as output : (1) profile plot (specify "ProfilePlot" in option type), to identify the potential sources of variation for each protein; (2) quality control plot (specify "QCPlot" in option type), to evaluate the systematic bias between MS runs; (3) mean plot for conditions (specify "ConditionPlot" in option type), to illustrate mean and variability of each condition per protein.

Usage

```
.makeQCPlot(
  input,
  all_proteins,
  y.limdown,
  y.limup,
  x.axis.size,
  y.axis.size,
  text.size,
  text.angle,
  legend.size,
  label.color,
  cumGroupAxis,
  groupName,
  lineNameAxis,
  yaxis.name
)
```

Arguments

<code>input</code>	<code>data.table</code>
<code>all_proteins</code>	character vector of protein names
<code>x.axis.size</code>	size of x-axis labeling for "Run" in Profile Plot and QC Plot, and "Condition" in Condition Plot. Default is 10.
<code>y.axis.size</code>	size of y-axis labels. Default is 10.
<code>text.size</code>	size of labels represented each condition at the top of graph in Profile Plot and QC plot. Default is 4.
<code>text.angle</code>	angle of labels represented each condition at the top of graph in Profile Plot and QC plot or x-axis labeling in Condition plot. Default is 0.
<code>legend.size</code>	size of feature legend (transition-level or peptide-level) above graph in Profile Plot. Default is 7.

Details

- **Profile Plot** : identify the potential sources of variation of each protein. `QuantData$FeatureLevelData` is used for plots. X-axis is run. Y-axis is log-intensities of transitions. Reference/endogenous signals are in the left/right panel. Line colors indicate peptides and line types indicate transitions. In summarization plots, gray dots and lines are the same as original profile plots with `QuantData$FeatureLevelData`. Dark dots and lines are for summarized intensities from `QuantData$ProteinLevelData`.
- **QC Plot** : illustrate the systematic bias between MS runs. After normalization, the reference signals for all proteins should be stable across MS runs. `QuantData$FeatureLevelData` is used for plots. X-axis is run. Y-axis is log-intensities of transition. Reference/endogenous signals are in the left/right panel. The pdf file contains (1) QC plot for all proteins and (2) QC plots for each protein separately.
- **Condition Plot** : illustrate the systematic difference between conditions. Summarized intensities from `QuantData$ProteinLevelData` are used for plots. X-axis is condition. Y-axis is summarized log transformed intensity. If scale is TRUE, the levels of conditions is scaled according to its actual values at x-axis. Red points indicate the mean for each condition. If interval is "CI", blue error bars indicate the confidence interval with 0.95 significant level for each condition. If interval is "SD", blue error bars indicate the standard deviation for each condition. The interval is not related with model-based analysis.

The input of this function is the quantitative data from function [dataProcess](#).

Examples

```
# Consider quantitative data (i.e. QuantData) from a yeast study with ten time points of interests,
# three biological replicates, and no technical replicates which is a time-course experiment.
# The goal is to provide pre-analysis visualization by automatically generate two types of figures
# in two separate pdf files.
# Protein IDHC (gene name IDP2) is differentially expressed in time point 1 and time point 7,
# whereas, Protein PMG2 (gene name GPM2) is not.

QuantData<-dataProcess(SRMRawData, use_log_file = FALSE)
head(QuantData$FeatureLevelData)
```

```
# Profile plot
dataProcessPlots(data=QuantData,type="ProfilePlot")
# Quality control plot
dataProcessPlots(data=QuantData,type="QCPlot")
# Quantification plot for conditions
dataProcessPlots(data=QuantData,type="ConditionPlot")
```

```
.makeSummaryProfilePlot
```

Make summary profile plot

Description

Make summary profile plot

Usage

```
.makeSummaryProfilePlot(
  input,
  is_censored,
  y.limdown,
  y.limup,
  x.axis.size,
  y.axis.size,
  text.size,
  text.angle,
  legend.size,
  dot.size.profile,
  cumGroupAxis,
  yaxis.name,
  lineNameAxis,
  groupNametemp
)
```

Arguments

<code>input</code>	data.table
<code>is_censored</code>	TRUE if censored values were imputed
<code>x.axis.size</code>	size of x-axis labeling for "Run" in Profile Plot and QC Plot, and "Condition" in Condition Plot. Default is 10.
<code>y.axis.size</code>	size of y-axis labels. Default is 10.
<code>text.size</code>	size of labels represented each condition at the top of graph in Profile Plot and QC plot. Default is 4.
<code>text.angle</code>	angle of labels represented each condition at the top of graph in Profile Plot and QC plot or x-axis labeling in Condition plot. Default is 0.

<code>legend.size</code>	size of feature legend (transition-level or peptide-level) above graph in Profile Plot. Default is 7.
<code>dot.size.profile</code>	size of dots in profile plot. Default is 2.

<code>.makeVolcano</code>	<i>Create a volcano plot</i>
---------------------------	------------------------------

Description

Create a volcano plot

Usage

```
.makeVolcano(  
  input,  
  label_name,  
  log_base_FC,  
  log_base_pval,  
  x.lim,  
  ProteinName,  
  dot.size,  
  y.limdown,  
  y.limup,  
  text.size,  
  FCcutoff,  
  sig,  
  x.axis.size,  
  y.axis.size,  
  legend.size,  
  log_adjp  
)
```

Arguments

<code>input</code>	data.table
<code>label_name</code>	contrast label
<code>log_base_FC</code>	2 or 10
<code>log_base_pval</code>	2 or 10
<code>ProteinName</code>	for volcano plot only, whether display protein names or not. TRUE (default) means protein names, which are significant, are displayed next to the points. FALSE means no protein names are displayed.
<code>dot.size</code>	size of dots in volcano plot and comparison plot. Default is 3.
<code>text.size</code>	size of ProteinName label in the graph for Volcano Plot. Default is 4.

FCcutoff	for volcano plot or heatmap, whether involve fold change cutoff or not. FALSE (default) means no fold change cutoff is applied for significance analysis. FC-cutoff = specific value means specific fold change cutoff is applied.
sig	FDR cutoff for the adjusted p-values in heatmap and volcano plot. level of significance for comparison plot. 100(1-sig)% confidence interval will be drawn. sig=0.05 is default.
x.axis.size	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
y.axis.size	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
legend.size	size of legend for color at the bottom of volcano plot. Default is 7.

<code>.nicePrint</code>	<i>Print a table nicely</i>
-------------------------	-----------------------------

Description

Print a table nicely

Usage

```
.nicePrint(string_vector)
```

Arguments

string_vector character

Value

character

<code>.normalizeGlobalStandards</code>	<i>Normalization based on standards</i>
--	---

Description

Normalization based on standards

Usage

```
.normalizeGlobalStandards(input, peptides_dict, standards)
```

Arguments

input	data.table in MSstats format
peptides_dict	'data.table' of names of peptides and their corresponding features.
standards	character vector with names of standards, required if "GLOBALSTANDARDS" method was selected.

.normalizeMedian	<i>Median normalization</i>
------------------	-----------------------------

Description

Median normalization

Usage

```
.normalizeMedian(input)
```

Arguments

input	'data.table' in standard MSstats format
-------	---

.normalizeQuantile	<i>Quantile normalization based on the 'preprocessCore' package</i>
--------------------	---

Description

Quantile normalization based on the 'preprocessCore' package

Usage

```
.normalizeQuantile(input)
```

Arguments

input	'data.table' in MSstats standard format
-------	---

.onLoad	<i>Set default logging object when package is loaded</i>
---------	--

Description

Set default logging object when package is loaded

Usage

```
.onLoad(...)
```

Arguments

...	ignored
-----	---------

Value

none, sets options called MSstatsLog and MSstatsMsg

.plotComparison

Preprocess data for comparison plots and create them

Description

Preprocess data for comparison plots and create them

Usage

```
.plotComparison(
  input,
  proteins,
  address,
  width,
  height,
  sig,
  ylimUp,
  ylimDown,
  text.angle,
  dot.size,
  x.axis.size,
  y.axis.size,
  log_base_FC,
  isPlotly
)
```

Arguments

input	data.table
address	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf" or "ComparisonPlot.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window.
width	width of the saved file in pixels. Default is 800.
height	height of the saved file in pixels. Default is 600.
sig	FDR cutoff for the adjusted p-values in heatmap and volcano plot. level of significance for comparison plot. 100(1-sig)% confidence interval will be drawn. sig=0.05 is default.
ylimUp	for all three plots, upper limit for y-axis. FALSE (default) for volcano plot/heatmap use maximum of -log2 (adjusted p-value) or -log10 (adjusted p-value). FALSE (default) for comparison plot uses maximum of log-fold change + CI.

<code>ylimDown</code>	for all three plots, lower limit for y-axis. FALSE (default) for volcano plot/heatmap use minimum of $-\log_2$ (adjusted p-value) or $-\log_{10}$ (adjusted p-value). FALSE (default) for comparison plot uses minimum of log-fold change - CI.
<code>text.angle</code>	angle of x-axis labels represented each comparison at the bottom of graph in comparison plot. Default is 0.
<code>dot.size</code>	size of dots in volcano plot and comparison plot. Default is 3.
<code>x.axis.size</code>	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
<code>y.axis.size</code>	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
<code>log_base_FC</code>	log base for log-fold changes - 2 or 10
<code>isPlotly</code>	This parameter is for MSstatsShiny application for plotly render, this cannot be used for saving PDF files as plotly do not have support for PDFs currently. address and isPlotly cannot be set as TRUE at the same time.

*.plotHeatmap**Prepare data for heatmaps and plot them*

Description

Prepare data for heatmaps and plot them

Usage

```
.plotHeatmap(
  input,
  log_base_pval,
  ylimUp,
  FCcutoff,
  sig,
  clustering,
  numProtein,
  colorkey,
  width,
  height,
  log_base_FC,
  x.axis.size,
  y.axis.size,
  address,
  isPlotly
)
```

Arguments

<code>input</code>	<code>data.table</code>
<code>log_base_pval</code>	log base for p-values
<code>ylimUp</code>	for all three plots, upper limit for y-axis. FALSE (default) for volcano plot/heatmap use maximum of $-\log_2$ (adjusted p-value) or $-\log_{10}$ (adjusted p-value). FALSE (default) for comparison plot uses maximum of log-fold change + CI.
<code>FCcutoff</code>	for volcano plot or heatmap, whether involve fold change cutoff or not. FALSE (default) means no fold change cutoff is applied for significance analysis. FC-cutoff = specific value means specific fold change cutoff is applied.
<code>sig</code>	FDR cutoff for the adjusted p-values in heatmap and volcano plot. level of significance for comparison plot. $100(1-\text{sig})\%$ confidence interval will be drawn. <code>sig=0.05</code> is default.
<code>clustering</code>	Determines how to order proteins and comparisons. Hierarchical cluster analysis with Ward method(minimum variance) is performed. 'protein' means that protein dendrogram is computed and reordered based on protein means (the order of row is changed). 'comparison' means comparison dendrogram is computed and reordered based on comparison means (the order of comparison is changed). 'both' means to reorder both protein and comparison. Default is 'protein'.
<code>numProtein</code>	For ggplot2: The number of proteins which will be presented in each heatmap. Default is 100. Maximum possible number of protein for one heatmap is 180. For Plotly: use this parameter to adjust the number of proteins to be displayed on the heatmap
<code>colorkey</code>	TRUE(default) shows colorkey.
<code>width</code>	width of the saved file in pixels. Default is 800.
<code>height</code>	height of the saved file in pixels. Default is 600.
<code>log_base_FC</code>	log base for log-fold changes - 2 or 10
<code>x.axis.size</code>	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
<code>y.axis.size</code>	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
<code>address</code>	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf" or "ComparisonPlot.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If <code>address=FALSE</code> , plot will be not saved as pdf file but showed in window.
<code>isPlotly</code>	This parameter is for MSstatsShiny application for plotly render, this cannot be used for saving PDF files as plotly do not have support for PDFs currently. address and isPlotly cannot be set as TRUE at the same time.

.plotVolcano

Preprocess data for volcano plots and create them

Description

Preprocess data for volcano plots and create them

Usage

```
.plotVolcano(  
  input,  
  which.Comparison,  
  address,  
  width,  
  height,  
  log_base_pval,  
  ylimUp,  
  ylimDown,  
  FCcutoff,  
  sig,  
  xlimUp,  
  ProteinName,  
  dot.size,  
  text.size,  
  legend.size,  
  x.axis.size,  
  y.axis.size,  
  log_base_FC,  
  isPlotly  
)
```

Arguments

which.Comparison

list of comparisons to draw plots. List can be labels of comparisons or order numbers of comparisons from levels(data\$Label), such as levels(testResultMultiComparisons\$Comparison). Default is "all", which generates all plots for each protein.

address

the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf" or "ComparisonPlot.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window.

width

width of the saved file in pixels. Default is 800.

height

height of the saved file in pixels. Default is 600.

<code>ylimUp</code>	for all three plots, upper limit for y-axis. FALSE (default) for volcano plot/heatmap use maximum of $-\log_2$ (adjusted p-value) or $-\log_{10}$ (adjusted p-value). FALSE (default) for comparison plot uses maximum of log-fold change + CI.
<code>ylimDown</code>	for all three plots, lower limit for y-axis. FALSE (default) for volcano plot/heatmap use minimum of $-\log_2$ (adjusted p-value) or $-\log_{10}$ (adjusted p-value). FALSE (default) for comparison plot uses minimum of log-fold change - CI.
<code>FCcutoff</code>	for volcano plot or heatmap, whether involve fold change cutoff or not. FALSE (default) means no fold change cutoff is applied for significance analysis. FC-cutoff = specific value means specific fold change cutoff is applied.
<code>sig</code>	FDR cutoff for the adjusted p-values in heatmap and volcano plot. level of significance for comparison plot. $100(1-\text{sig})\%$ confidence interval will be drawn. $\text{sig}=0.05$ is default.
<code>xlimUp</code>	for Volcano plot, the limit for x-axis. FALSE (default) for use maximum for absolute value of log-fold change or 3 as default if maximum for absolute value of log-fold change is less than 3.
<code>ProteinName</code>	for volcano plot only, whether display protein names or not. TRUE (default) means protein names, which are significant, are displayed next to the points. FALSE means no protein names are displayed.
<code>dot.size</code>	size of dots in volcano plot and comparison plot. Default is 3.
<code>text.size</code>	size of ProteinName label in the graph for Volcano Plot. Default is 4.
<code>legend.size</code>	size of legend for color at the bottom of volcano plot. Default is 7.
<code>x.axis.size</code>	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
<code>y.axis.size</code>	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
<code>isPlotly</code>	This parameter is for MSstatsShiny application for plotly render, this cannot be used for saving PDF files as plotly do not have support for PDFs currently. address and isPlotly cannot be set as TRUE at the same time.

`.prepareForDataProcess`

Check validity of data already processed by MSstats converter

Description

Check validity of data already processed by MSstats converter

Usage

```
.prepareForDataProcess(input, ...)
```

Arguments

<code>input</code>	data.frame of class 'MSstatsValidated'
<code>..</code>	additional parameters, currently ignored

.prepareLinear	<i>Prepare feature-level data for linear summarization</i>
----------------	--

Description

Prepare feature-level data for linear summarization

Usage

```
.prepareLinear(input, impute, censored_symbol)
```

Arguments

input	data.table
impute	logical
censored_symbol	"0"/"NA"

Value

data.table

.prepareSingleProteinForGC	<i>Prepare data for a single protein for group comparison</i>
----------------------------	---

Description

Prepare data for a single protein for group comparison

Usage

```
.prepareSingleProteinForGC(single_protein)
```

Arguments

single_protein	data.table
----------------	------------

<code>.prepareSummary</code>	<i>Prepare feature-level data for summarization</i>
------------------------------	---

Description

Prepare feature-level data for summarization

Usage

```
.prepareSummary(input, method, impute, censored_symbol)
```

Arguments

<code>input</code>	<code>data.table</code>
<code>method</code>	<code>"TMP" / "linear"</code>
<code>impute</code>	<code>logical</code>
<code>censored_symbol</code>	<code>"0"/"NA"</code>

Value

`data.table`

<code>.prepareTMP</code>	<i>Prepare feature-level data for TMP summarization</i>
--------------------------	---

Description

Prepare feature-level data for TMP summarization

Usage

```
.prepareTMP(input, impute, censored_symbol)
```

Arguments

<code>input</code>	<code>data.table</code>
<code>impute</code>	<code>logical</code>
<code>censored_symbol</code>	<code>"0"/"NA"</code>

Value

`data.table`

.preProcessIntensities

Create ABUNDANCE column and log-transform intensities

Description

Create ABUNDANCE column and log-transform intensities

Usage

```
.preProcessIntensities(input, log_base)
```

Arguments

input	data.table
log_base	base of the logarithm

.quantileNormalizationSingleLabel

Quantile normalization for a single label

Description

Quantile normalization for a single label

Usage

```
.quantileNormalizationSingleLabel(input, runs, label = "L")
```

Arguments

input	'data.table' in MSstats standard format
runs	run labels
label	"L" for light isotopes, "H" for heavy isotopes

.replaceZerosWithNA	<i>Utility function for normalization: replace 0s by NA</i>
---------------------	---

Description

Utility function for normalization: replace 0s by NA

Usage

```
.replaceZerosWithNA(vec)
```

Arguments

vec	vector
-----	--------

.runTukey	<i>Fit Tukey median polish</i>
-----------	--------------------------------

Description

Fit Tukey median polish

Usage

```
.runTukey(input, is_labeled, censored_symbol, remove50missing)
```

Arguments

input	data.table with data for a single protein
is_labeled	logical, if TRUE, data is coming from an SRM experiment
censored_symbol	Missing values are censored or at random. 'NA' (default) assumes that all 'NA's in 'Intensity' column are censored. '0' uses zero intensities as censored intensity. In this case, NA intensities are missing at random. The output from Skyline should use '0'. Null assumes that all NA intensities are randomly missing.
remove50missing	only for summaryMethod = "TMP". TRUE removes the proteins where every run has at least 50% missing values for each peptide. FALSE is default.

Value

data.table

<code>.saveSessionInfo</code>	<i>Save information about R session to sessionInfo.txt file.</i>
-------------------------------	--

Description

Save information about R session to sessionInfo.txt file.

Usage

```
.saveSessionInfo()
```

<code>.saveTable</code>	<i>Save a data table to a file</i>
-------------------------	------------------------------------

Description

Save a data table to a file

Usage

```
.saveTable(input, name_base, file_name)
```

Arguments

<code>input</code>	data.table
<code>name_base</code>	path to a folder (or "" for working directory)
<code>file_name</code>	name of a file to save. If this file already exists, an integer will be appended to this name

<code>.selectHighQualityFeatures</code>	<i>Select features of high quality</i>
---	--

Description

Select features of high quality

Usage

```
.selectHighQualityFeatures(input, min_feature_count)
```

Arguments

input	data.table
min_feature_count	minimum number of quality features to consider

Value

data.table

<i>.selectTopFeatures</i>	<i>Select features with highest average abundance</i>
---------------------------	---

Description

Select features with highest average abundance

Usage

```
.selectTopFeatures(input, top_n)
```

Arguments

input	data.table
top_n	number of top features to select

Value

data.table

<i>.setCensoredByThreshold</i>	<i>Set censored values based on minimum in run/feature/run or feature. This is used to initialize the AFT imputation model by supplying the maximum possible values for left-censored data as the ‘time‘ input to the Surv function.</i>
--------------------------------	--

Description

Set censored values based on minimum in run/feature/run or feature. This is used to initialize the AFT imputation model by supplying the maximum possible values for left-censored data as the ‘time‘ input to the Surv function.

Usage

```
.setCensoredByThreshold(input, censored_symbol, remove50missing)
```

Arguments

input	'data.table' in MSstats format
censored_symbol	censoredInt parameter to 'dataProcess'
remove50missing	if TRUE, features with at least 50 will be removed

.updateColumnsForProcessing

Create columns for data processing

Description

Create columns for data processing

Usage

```
.updateColumnsForProcessing(input)
```

Arguments

input	data.table
-------	------------

.updateUnequalVariances

Adjust model for unequal variances

Description

Adjust model for unequal variances

Usage

```
.updateUnequalVariances(input, fit, num_iter)
```

Arguments

input	data.table
fit	lm
num_iter	number of iterations

Value

merMod

checkRepeatedDesign	<i>Check if data represents repeated measurements design</i>
---------------------	--

Description

Check if data represents repeated measurements design

Usage

```
checkRepeatedDesign(summarization_output)
```

Arguments

summarization_output
output of the dataProcess function

Details

This extracts information required by the group comparison workflow

Value

logical, TRUE if data represent repeated measurements design

Examples

```
QuantData1 <- dataProcess(SRMRawData, use_log_file = FALSE)
checkRepeatedDesign(QuantData1)
```

dataProcess	<i>Process MS data: clean, normalize and summarize before differential analysis</i>
-------------	---

Description

Process MS data: clean, normalize and summarize before differential analysis

Usage

```
dataProcess(
  raw,
  logTrans = 2,
  normalization = "equalizeMedians",
  nameStandards = NULL,
  featureSubset = "all",
  remove_uninformative_feature_outlier = FALSE,
  min_feature_count = 2,
  n_top_feature = 3,
  summaryMethod = "TMP",
  equalFeatureVar = TRUE,
  censoredInt = "NA",
  MBimpute = TRUE,
  remove50missing = FALSE,
  fix_missing = NULL,
  maxQuantileforCensored = 0.999,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL,
  numberOfCores = 1
)
```

Arguments

raw	name of the raw (input) data set.
logTrans	base of logarithm transformation: 2 (default) or 10.
normalization	normalization to remove systematic bias between MS runs. There are three different normalizations supported: 'equalizeMedians' (default) represents constant normalization (equalizing the medians) based on reference signals is performed. 'quantile' represents quantile normalization based on reference signals 'globalStandards' represents normalization with global standards proteins. If FALSE, no normalization is performed. See MSstats vignettes for recommendations on which normalization option to use.
nameStandards	optional vector of global standard peptide names. Required only for normalization with global standard peptides.
featureSubset	"all" (default) uses all features that the data set has. "top3" uses top 3 features which have highest average of log-intensity across runs. "topN" uses top N features which has highest average of log-intensity across runs. It needs the input for n_top_feature option. "highQuality" flags uninformative feature and outliers. See MSstats vignettes for recommendations on which feature selection option to use.
remove_uninformative_feature_outlier	optional. Only required if featureSubset = "highQuality". TRUE allows to remove 1) noisy features (flagged in the column feature_quality with "Uninformative"), 2) outliers (flagged in the column, is_outlier with TRUE, before run-level

	summarization. FALSE (default) uses all features and intensities for run-level summarization.
min_feature_count	optional. Only required if featureSubset = "highQuality". Defines a minimum number of informative features a protein needs to be considered in the feature selection algorithm.
n_top_feature	optional. Only required if featureSubset = 'topN'. If that case, it specifies number of top features that will be used. Default is 3, which means to use top 3 features.
summaryMethod	"TMP" (default) means Tukey's median polish, which is robust estimation method. "linear" uses linear mixed model.
equalFeatureVar	only for summaryMethod = "linear". default is TRUE. Logical variable for whether the model should account for heterogeneous variation among intensities from different features. Default is TRUE, which assume equal variance among intensities from features. FALSE means that we cannot assume equal variance among intensities from features, then we will account for heterogeneous variation from different features.
censoredInt	Missing values are censored or at random. 'NA' (default) assumes that all 'NA's in 'Intensity' column are censored. '0' uses zero intensities as censored intensity. In this case, NA intensities are missing at random. The output from Skyline should use '0'. Null assumes that all NA intensities are randomly missing.
MBimpute	only for summaryMethod = "TMP" and censoredInt = 'NA' or '0'. TRUE (default) imputes missing values with 'NA' or '0' (depending on censoredInt option) by Accelerated failure model. If set to FALSE, no missing values are imputed. FALSE is appropriate only when missingness is assumed to be at random. See MSstats vignettes for recommendations on which imputation option to use.
remove50missing	only for summaryMethod = "TMP". TRUE removes the proteins where every run has at least 50% missing values for each peptide. FALSE is default.
fix_missing	Optional, same as the 'fix_missing' parameter in MSstatsConvert::MSstatsBalancedDesign function
maxQuantileforCensored	Maximum quantile for deciding censored missing values, default is 0.999
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.
numberOfCores	Number of cores for parallel processing. When > 1, a logfile named 'MSstats_dataProcess_log_progress.log' is created to track progress. Only works for Linux & Mac OS. Default is 1.

Value

A list containing:

FeatureLevelData A data frame with feature-level information after processing. Columns include:

PROTEIN Identifier for the protein associated with the feature.

PEPTIDE Identifier for the peptide sequence.

TRANSITION Identifier for the transition, typically representing a specific ion pair.

FEATURE Unique identifier for the feature, which could be a combination of peptide and transition.

LABEL Specifies the isotopic labeling of peptides, notably for SRM-based experiments. "L" indicates light-labeled peptides while "H" denotes heavy-labeled peptides.

GROUP Experimental group identifier.

RUN Identifier for the specific MS run.

SUBJECT Subject identifier within the experimental group.

FRACTION Fraction identifier if fractionation was performed.

originalRUN Original run identifier before any processing.

censored Logical indicator of whether the intensity value is considered missing or below limit of detection.

INTENSITY Original intensity measurement of the feature in the given run.

ABUNDANCE Processed abundance or intensity value after log-transformation and normalization.

newABUNDANCE The ABUNDANCE column but includes imputed missing values. It is the column that is used for protein summarization.

predicted Predicted intensity values for censored data, typically derived from a statistical model.

ProteinLevelData A data frame with run-level summarized information for each protein. Columns include:

RUN Identifier for the specific MS run.

Protein Identifier for the protein.

LogIntensities Log-transformed intensities for the protein in each run.

originalRUN Original run identifier before any processing.

GROUP Experimental group identifier.

SUBJECT Subject identifier within the experimental group.

TotalGroupMeasurements Total number of feature measurements for the protein in the given group.

NumMeasuredFeatures Number of features measured for the protein in the given run.

MissingPercentage Percentage of missing feature values for the protein in the given run.

more50missing Logical indicator of whether more than 50 percent of the features values are missing for the protein in the given run.

NumImputedFeature Number of features for which values were imputed due to missing or censored data for the protein in the given run.

Examples

```
# Consider a raw data (i.e. SRMRawData) for a label-based SRM experiment from a yeast study
# with ten time points (T1-T10) of interests and three biological replicates.
# It is a time course experiment. The goal is to detect protein abundance changes
# across time points.
head(SRMRawData)
# Log2 transformation and normalization are applied (default)
QuantData<-dataProcess(SRMRawData, use_log_file = FALSE)
head(QuantData$FeatureLevelData)
# Log10 transformation and normalization are applied
QuantData1<-dataProcess(SRMRawData, logTrans=10, use_log_file = FALSE)
head(QuantData1$FeatureLevelData)
# Log2 transformation and no normalization are applied
QuantData2<-dataProcess(SRMRawData,normalization=FALSE, use_log_file = FALSE)
head(QuantData2$FeatureLevelData)
```

dataProcessPlots

Visualization for explanatory data analysis

Description

To illustrate the quantitative data after data-preprocessing and quality control of MS runs, `dataProcessPlots` takes the quantitative data from function ([dataProcess](#)) as input and automatically generate three types of figures in pdf files as output : (1) profile plot (specify "ProfilePlot" in option type), to identify the potential sources of variation for each protein; (2) quality control plot (specify "QCPlot" in option type), to evaluate the systematic bias between MS runs; (3) mean plot for conditions (specify "ConditionPlot" in option type), to illustrate mean and variability of each condition per protein.

Usage

```
dataProcessPlots(
  data,
  type,
  featureName = "Transition",
  ylimUp = FALSE,
  ylimDown = FALSE,
  scale = FALSE,
  interval = "CI",
  x.axis.size = 10,
  y.axis.size = 10,
  text.size = 4,
  text.angle = 0,
  legend.size = 7,
  dot.size.profile = 2,
  dot.size.condition = 3,
  width = 800,
```

```

    height = 600,
    which.Protein = "all",
    originalPlot = TRUE,
    summaryPlot = TRUE,
    save_condition_plot_result = FALSE,
    remove_uninformative_feature_outlier = FALSE,
    address = "",
    isPlotly = FALSE
)

```

Arguments

data	name of the (output of dataProcess function) data set.
type	choice of visualization. "ProfilePlot" represents profile plot of log intensities across MS runs. "QCPlot" represents quality control plot of log intensities across MS runs. "ConditionPlot" represents mean plot of log ratios (Light/Heavy) across conditions.
featureName	for "ProfilePlot" only, "Transition" (default) means printing feature legend in transition-level; "Peptide" means printing feature legend in peptide-level; "NA" means no feature legend printing.
ylimUp	upper limit for y-axis in the log scale. FALSE(Default) for Profile Plot and QC Plot use the upper limit as rounded off maximum of log2(intensities) after normalization + 3. FALSE(Default) for Condition Plot is maximum of log ratio + SD or CI.
ylimDown	lower limit for y-axis in the log scale. FALSE(Default) for Profile Plot and QC Plot is 0. FALSE(Default) for Condition Plot is minimum of log ratio - SD or CI.
scale	for "ConditionPlot" only, FALSE(default) means each conditional level is not scaled at x-axis according to its actual value (equal space at x-axis). TRUE means each conditional level is scaled at x-axis according to its actual value (unequal space at x-axis).
interval	for "ConditionPlot" only, "CI"(default) uses confidence interval with 0.95 significant level for the width of error bar. "SD" uses standard deviation for the width of error bar.
x.axis.size	size of x-axis labeling for "Run" in Profile Plot and QC Plot, and "Condition" in Condition Plot. Default is 10.
y.axis.size	size of y-axis labels. Default is 10.
text.size	size of labels represented each condition at the top of graph in Profile Plot and QC plot. Default is 4.
text.angle	angle of labels represented each condition at the top of graph in Profile Plot and QC plot or x-axis labeling in Condition plot. Default is 0.
legend.size	size of feature legend (transition-level or peptide-level) above graph in Profile Plot. Default is 7.
dot.size.profile	size of dots in profile plot. Default is 2.

dot.size.condition	size of dots in condition plot. Default is 3.
width	width of the saved file in pixels. Default is 800 pixels.
height	height of the saved file in pixels. Default is 600 pixels.
which.Protein	Protein list to draw plots. List can be names of Proteins or order numbers of Proteins from levels(data\$FeatureLevelData\$PROTEIN). Default is "all", which generates all plots for each protein. For QC plot, "allonly" will generate one QC plot with all proteins.
originalPlot	TRUE(default) draws original profile plots.
summaryPlot	TRUE(default) draws profile plots with summarization for run levels.
save_condition_plot_result	TRUE saves the table with values using condition plots. Default is FALSE.
remove_uninformative_feature_outlier	It only works after users used featureSubset="highQuality" in dataProcess. TRUE allows to remove 1) the features are flagged in the column, feature_quality="Uninformative" which are features with bad quality, 2) outliers that are flagged in the column, is_outlier=TRUE in Profile plots. FALSE (default) shows all features and intensities in profile plots.
address	prefix for the filename that will store the results.
isPlotly	Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "ProfilePlot.pdf" or "QCplot.pdf" or "ConditionPlot.pdf" or "ConditionPlot_value.csv". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window.

Details

- **Profile Plot** : identify the potential sources of variation of each protein. QuantData\$FeatureLevelData is used for plots. X-axis is run. Y-axis is log-intensities of transitions. Reference/endogenous signals are in the left/right panel. Line colors indicate peptides and line types indicate transitions. In summarization plots, gray dots and lines are the same as original profile plots with QuantData\$FeatureLevelData. Dark dots and lines are for summarized intensities from QuantData\$ProteinLevelData.
- **QC Plot** : illustrate the systematic bias between MS runs. After normalization, the reference signals for all proteins should be stable across MS runs. QuantData\$FeatureLevelData is used for plots. X-axis is run. Y-axis is log-intensities of transition. Reference/endogenous signals are in the left/right panel. The pdf file contains (1) QC plot for all proteins and (2) QC plots for each protein separately.
- **Condition Plot** : illustrate the systematic difference between conditions. Summarized intensities from QuantData\$ProteinLevelData are used for plots. X-axis is condition. Y-axis is summarized log transformed intensity. If scale is TRUE, the levels of conditions is scaled according to its actual values at x-axis. Red points indicate the mean for each condition. If

interval is "CI", blue error bars indicate the confidence interval with 0.95 significant level for each condition. If interval is "SD", blue error bars indicate the standard deviation for each condition. The interval is not related with model-based analysis.

The input of this function is the quantitative data from function `dataProcess`.

Examples

```
# Consider quantitative data (i.e. QuantData) from a yeast study with ten time points of interests,
# three biological replicates, and no technical replicates which is a time-course experiment.
# The goal is to provide pre-analysis visualization by automatically generate two types of figures
# in two separate pdf files.
# Protein IDHC (gene name IDP2) is differentially expressed in time point 1 and time point 7,
# whereas, Protein PMG2 (gene name GPM2) is not.

QuantData<-dataProcess(SRMRawData, use_log_file = FALSE)
head(QuantData$FeatureLevelData)
# Profile plot
dataProcessPlots(data=QuantData,type="ProfilePlot")
# Quality control plot
dataProcessPlots(data=QuantData,type="QCPlot")
# Quantification plot for conditions
dataProcessPlots(data=QuantData,type="ConditionPlot")
```

DDARawData

Example dataset from a label-free DDA, a controlled spike-in experiment.

Description

This is a data set obtained from a published study (Mueller, et. al, 2007). A controlled spike-in experiment, where 6 proteins, (horse myoglobin, bovine carbonic anhydrase, horse Cytochrome C, chicken lysozyme, yeast alcohol dehydrogenase, rabbit aldolase A) were spiked into a complex background in known concentrations in a latin square design. The experiment contained 6 mixtures, and each mixture was analyzed in label-free LC-MS mode with 3 technical replicates (resulting in the total of 18 runs). Each protein was represented by 7-21 peptides, and each peptide was represented by 1-5 transition.

Usage

```
DDARawData
```

Format

```
data.frame
```

Details

The raw data (input data for MSstats) is required to contain variable of ProteinName, PeptideSequence, PrecursorCharge, FragmentIon, ProductCharge, IsotopeLabelType, Condition, BioReplicate, Run, Intensity. The variable names should be fixed.

If the information of one or more columns is not available for the original raw data, please retain the column variables and type in fixed value. For example, the original raw data does not contain the information of PrecursorCharge and ProductCharge, we retain the column PrecursorCharge and ProductCharge and then type in NA for all transitions in RawData.

Variable Intensity is required to be original signal without any log transformation and can be specified as the peak of height or the peak of area under curve.

Value

data.frame with the required format of MSstats.

Author(s)

Meena Choi, Olga Vitek.

Maintainer: Meena Choi (<mnchoi67@gmail.com>)

References

Meena Choi, Ching-Yun Chang, Timothy Clough, Daniel Broudy, Trevor Killeen, Brendan MacLean and Olga Vitek. "MSstats: an R package for statistical analysis of quantitative mass spectrometry-based proteomic experiments" *Bioinformatics*, 30(17):1514-1526, 2014.

Timothy Clough, Safia Thaminy, Susanne Ragg, Ruedi Aebersold, Olga Vitek. "Statistical protein quantification and significance analysis in label-free LC-M experiments with complex designs" *BMC Bioinformatics*, 13:S16, 2012.

Mueller, L. N., Rinner, O., Schmidt, A., Letarte, S., Bodenmiller, B., Brusniak, M., Vitek, O., Aebersold, R., and Muller, M. (2007). SuperHirn - a novel tool for high resolution LC-MS based peptide/protein profiling. *Proteomics*, 7, 3470-3480. 3, 34

Examples

```
head(DDARawData)
```

DDARawData.Skyline

Example dataset from a label-free DDA, a controlled spike-in experiment, processed by Skyline.

Description

This is a data set obtained from a published study (Mueller, et. al, 2007). A controlled spike-in experiment, where 6 proteins, (horse myoglobin, bovine carbonic anhydrase, horse Cytochrome C, chicken lysozyme, yeast alcohol dehydrogenase, rabbit aldolase A) were spiked into a complex background in known concentrations in a latin square design. The experiment contained 6 mixtures, and each mixture was analyzed in label-free LC-MS mode with 3 technical replicates (resulting in the total of 18 runs). Each protein was represented by 7-21 peptides, and each peptide was represented by 1-5 transition. Skyline is used for processing.

Usage

```
DDARawData.Skyline
```

Format

```
data.frame
```

Details

The raw data (input data for MSstats) is required to contain variable of ProteinName, PeptideSequence, PrecursorCharge, FragmentIon, ProductCharge, IsotopeLabelType, Condition, BioReplicate, Run, Intensity. The variable names should be fixed.

This is 'MSstats input' format from Skyline used by 'MSstats_report.skyr'. The column names, 'FileName' and 'Area', should be changed to 'Run' and 'Intensity'. There are two extra columns called 'StandardType' and 'Truncated'. 'StandardType' column can be used for normalization='globalStandard' in [dataProcess](#). 'Truncated' columns can be used to remove the truncated peaks with skylineReport=TRUE in [dataProcess](#).

If the information of one or more columns is not available for the original raw data, please retain the column variables and type in fixed value. For example, the original raw data does not contain the information of PrecursorCharge and ProductCharge, we retain the column PrecursorCharge and ProductCharge and then type in NA for all transitions in RawData.

Variable Intensity is required to be original signal without any log transformation and can be specified as the peak of height or the peak of area under curve.

Value

data.frame with the required format of MSstats.

Author(s)

Meena Choi, Olga Vitek.

Maintainer: Meena Choi (<mnchoi67@gmail.com>)

References

Meena Choi, Ching-Yun Chang, Timothy Clough, Daniel Broudy, Trevor Killeen, Brendan MacLean and Olga Vitek. "MSstats: an R package for statistical analysis of quantitative mass spectrometry-based proteomic experiments" *Bioinformatics*, 30(17):1514-1526, 2014.

Timothy Clough, Safia Thaminy, Susanne Ragg, Ruedi Aebersold, Olga Vitek. "Statistical protein quantification and significance analysis in label-free LC-M experiments with complex designs" *BMC Bioinformatics*, 13:S16, 2012.

Examples

```
head(DDARawData.Skyline)
```

designSampleSize	<i>Planning future experimental designs of Selected Reaction Monitoring (SRM), Data-Dependent Acquisition (DDA or shotgun), and Data-Independent Acquisition (DIA or SWATH-MS) experiments in sample size calculation</i>
------------------	---

Description

Calculate sample size for future experiments of a Selected Reaction Monitoring (SRM), Data-Dependent Acquisition (DDA or shotgun), and Data-Independent Acquisition (DIA or SWATH-MS) experiment based on intensity-based linear model. Two options of the calculation: (1) number of biological replicates per condition, (2) power.

Usage

```
designSampleSize(  
  data,  
  desiredFC,  
  FDR = 0.05,  
  numSample = TRUE,  
  power = 0.9,  
  use_log_file = TRUE,  
  append = FALSE,  
  verbose = TRUE,  
  log_file_path = NULL  
)
```

Arguments

data	'FittedModel' in testing output from function groupComparison.
desiredFC	the range of a desired fold change which includes the lower and upper values of the desired fold change.
FDR	a pre-specified false discovery ratio (FDR) to control the overall false positive rate. Default is 0.05
numSample	minimal number of biological replicates per condition. TRUE represents you require to calculate the sample size for this category, else you should input the exact number of biological replicates.

power	a pre-specified statistical power which defined as the probability of detecting a true fold change. TRUE represent you require to calculate the power for this category, else you should input the average of power you expect. Default is 0.9
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

Details

The function fits the model and uses variance components to calculate sample size. The underlying model fitting with intensity-based linear model with technical MS run replication. Estimated sample size is rounded to 0 decimal. The function can only obtain either one of the categories of the sample size calculation (numSample, numPep, numTran, power) at the same time.

Value

data.frame - sample size calculation results including variables: desiredFC, numSample, FDR, and power.

Author(s)

Meena Choi, Ching-Yun Chang, Olga Vitek.

Examples

```
# Consider quantitative data (i.e. QuantData) from yeast study.
# A time course study with ten time points of interests and three biological replicates.
QuantData <- dataProcess(SRMRawData)
head(QuantData$FeatureLevelData)
## based on multiple comparisons (T1 vs T3; T1 vs T7; T1 vs T9)
comparison1<-matrix(c(-1,0,1,0,0,0,0,0,0,0),nrow=1)
comparison2<-matrix(c(-1,0,0,0,0,0,1,0,0,0),nrow=1)
comparison3<-matrix(c(-1,0,0,0,0,0,0,0,1,0),nrow=1)
comparison<-rbind(comparison1,comparison2, comparison3)
row.names(comparison)<-c("T3-T1","T7-T1","T9-T1")
colnames(comparison)<-unique(QuantData$ProteinLevelData$GROUP)

testResultMultiComparisons<-groupComparison(contrast.matrix=comparison,data=QuantData)

## Calculate sample size for future experiments:
#(1) Minimal number of biological replicates per condition
designSampleSize(data=testResultMultiComparisons$FittedModel, numSample=TRUE,
                 desiredFC=c(1.25,1.75), FDR=0.05, power=0.8)
#(2) Power calculation
designSampleSize(data=testResultMultiComparisons$FittedModel, numSample=2,
```

```
desiredFC=c(1.25,1.75), FDR=0.05, power=TRUE)
```

designSampleSizePlots *Visualization for sample size calculation*

Description

To illustrate the relationship of desired fold change and the calculated minimal number sample size which are (1) number of biological replicates per condition, (2) number of peptides per protein, (3) number of transitions per peptide, and (4) power. The input is the result from function [designSampleSize](#).

Usage

```
designSampleSizePlots(data, isPlotly = FALSE)
```

Arguments

data	output from function designSampleSize .
isPlotly	Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files

Details

Data in the example is based on the results of sample size calculation from function [designSampleSize](#)

Value

Plot for estimated sample size with assigned variable.

Author(s)

Meena Choi, Ching-Yun Chang, Olga Vitek.

Examples

```
# Based on the results of sample size calculation from function designSampleSize,
# we generate a series of sample size plots for number of biological replicates, or peptides,
# or transitions or power plot.
QuantData<-dataProcess(SRMRawData)
head(QuantData$ProcessedData)
## based on multiple comparisons (T1 vs T3; T1 vs T7; T1 vs T9)
comparison1<-matrix(c(-1,0,1,0,0,0,0,0,0,0),nrow=1)
comparison2<-matrix(c(-1,0,0,0,0,0,0,1,0,0),nrow=1)
comparison3<-matrix(c(-1,0,0,0,0,0,0,0,1,0),nrow=1)
comparison<-rbind(comparison1,comparison2, comparison3)
row.names(comparison)<-c("T3-T1","T7-T1","T9-T1")
```

```

colnames(comparison)<-unique(QuantData$ProteinLevelData$GROUP)

testResultMultiComparisons<-groupComparison(contrast.matrix=comparison, data=QuantData)

# plot the calculated sample sizes for future experiments:
# (1) Minimal number of biological replicates per condition
result.sample<-designSampleSize(data=testResultMultiComparisons$FittedModel, numSample=TRUE,
                                desiredFC=c(1.25,1.75), FDR=0.05, power=0.8)
designSampleSizePlots(data=result.sample)
# (2) Power
result.power<-designSampleSize(data=testResultMultiComparisons$FittedModel, numSample=2,
                                desiredFC=c(1.25,1.75), FDR=0.05, power=TRUE)
designSampleSizePlots(data=result.power)

```

DIARawData

Example dataset from a label-free DIA, a group comparison study of S. Pyogenes.

Description

This example dataset was obtained from a group comparison study of *S. Pyogenes*. Two conditions, *S. Pyogenes* with 0% and 10% of human plasma added (denoted Strep 0% and Strep 10%), were profiled in two replicates, in the label-free mode, with a SWATH-MS-enabled AB SCIEX TripleTOF 5600 System. The identification and quantification of spectral peaks was assisted by a spectral library, and was performed using OpenSWATH software (<http://proteomics.ethz.ch/openswath.html>). For reasons of space, the example dataset only contains two proteins from this study. Protein FabG shows strong evidence of differential abundance, while protein Probable RNA helicase exp9 only shows moderate evidence of differential abundance between conditions.

Usage

DIARawData

Format

data.frame

Details

The raw data (input data for MSstats) is required to contain variable of ProteinName, PeptideSequence, PrecursorCharge, FragmentIon, ProductCharge, IsotopeLabelType, Condition, BioReplicate, Run, Intensity. The variable names should be fixed.

If the information of one or more columns is not available for the original raw data, please retain the column variables and type in fixed value. For example, the original raw data does not contain the information of PrecursorCharge and ProductCharge, we retain the column PrecursorCharge and ProductCharge and then type in NA for all transitions in RawData.

Variable Intensity is required to be original signal without any log transformation and can be specified as the peak of height or the peak of area under curve.

Value

data.frame with the required format of MSstats.

Author(s)

Meena Choi, Olga Vitek.

Maintainer: Meena Choi (<mnchoi67@gmail.com>)

Examples

```
head(DIARawData)
```

example_SDRF

Example SDRF.

Description

An example SDRF file which is used to store metadata for MS-based proteomics experiments.

Usage

```
example_SDRF
```

Format

data.frame

Details

An example SDRF file which is used to store metadata for MS-based proteomics experiments.

Value

data.frame example of an SDRF file.

Author(s)

Mateusz Staniak, Devon Kohler, Olga Vitek.

Examples

```
head(example_SDRF)
```

extractSDRF

*Extract experimental design from MSstats format into SDRF format***Description**

Extract experimental design from MSstats format into SDRF format

Usage

```
extractSDRF(
  data,
  run_name = "comment[data file]",
  condition_name = "characteristics[disease]",
  biological_replicate = "characteristics[biological replicate]",
  fraction = NULL,
  meta_data = NULL
)
```

Arguments

data	MSstats formatted data that is the output of a dedicated converter, such as ‘MaxQ-toMSstatsFormat’, ‘SkylinettoMSstatsFormat’, ect.
run_name	Run column name in SDRF data
condition_name	Condition column name in SDRF data
biological_replicate	Biological replicate column name in SDRF data
fraction	Fraction column name in SDRF data (if applicable). Default is ‘NULL’. If there are no fractions keep ‘NULL’.
meta_data	A data.frame including any additional meta data for the SDRF file that is not included in MSstats. This meta data will be added into the final SDRF file. Please ensure the run names in the meta data matches the run names in the MSstats data.

Examples

```
mq_ev = data.table::fread(system.file("tinytest/raw_data/MaxQuant/mq_ev.csv",
                                       package = "MSstatsConvert"))
mq_pg = data.table::fread(system.file("tinytest/raw_data/MaxQuant/mq_pg.csv",
                                       package = "MSstatsConvert"))
annot = data.table::fread(system.file("tinytest/raw_data/MaxQuant/annotation.csv",
                                       package = "MSstatsConvert"))
maxq_imported = MaxQtoMSstatsFormat(mq_ev, annot, mq_pg, use_log_file = FALSE)
head(maxq_imported)

SDRF_file = extractSDRF(maxq_imported)
```

getProcessed	<i>Get feature-level data to be used in the MSstatsSummarizationOutput function</i>
--------------	---

Description

Get feature-level data to be used in the MSstatsSummarizationOutput function

Usage

```
getProcessed(input)
```

Arguments

input	data.table processed by dataProcess subfunctions
-------	--

Value

data.table processed by dataProcess subfunctions

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
input = MSstatsNormalize(input, "EQUALIZEMEDIANS")
input = MSstatsMergeFractions(input)
input = MSstatsHandleMissing(input, "TMP", TRUE, "NA", 0.999)
input_all = MSstatsSelectFeatures(input, "all") # all features
input_5 = MSstatsSelectFeatures(data.table::copy(input),
"topN", top_n = 5) # top 5 features

proc1 = getProcessed(input_all)
proc2 = getProcessed(input_5)

proc1
proc2
```

getSamplesInfo	<i>Get information about number of measurements for each group</i>
----------------	--

Description

Get information about number of measurements for each group

Usage

```
getSamplesInfo(summarization_output)
```

Arguments

summarization_output
output of the dataProcess function

Details

This function extracts information required to compute percentages of missing and imputed values in group comparison.

Value

data.table

Examples

```
QuantData <- dataProcess(DDARawData, use_log_file = FALSE)
samples_info <- getSamplesInfo(QuantData)
samples_info
```

getSelectedProteins	<i>Get proteins based on names or integer IDs</i>
---------------------	---

Description

Get proteins based on names or integer IDs

Usage

```
getSelectedProteins(chosen_proteins, all_proteins)
```

Arguments

chosen_proteins
protein names or integers IDs
all_proteins all unique proteins

Value

character

groupComparison	Whole plot testing
-----------------	--------------------

Description

Whole plot testing

Usage

```
groupComparison(  
  contrast.matrix,  
  data,  
  save_fitted_models = TRUE,  
  log_base = 2,  
  use_log_file = TRUE,  
  append = FALSE,  
  verbose = TRUE,  
  log_file_path = NULL,  
  numberOfCores = 1  
)
```

Arguments

contrast.matrix	comparison between conditions of interests.
data	name of the (output of dataProcess function) data set.
save_fitted_models	logical, if TRUE, fitted models will be added to the output.
log_base	base of the logarithm used in dataProcess.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.
numberOfCores	Number of cores for parallel processing. When > 1, a logfile named 'MSstats_groupComparison_log_prog' is created to track progress. Only works for Linux & Mac OS. Default is 1.

Details

contrast.matrix : comparison of interest. Based on the levels of conditions, specify 1 or -1 to the conditions of interests and 0 otherwise. The levels of conditions are sorted alphabetically. Command `levels(QuantData$FeatureLevelData$GROUP_ORIGINAL)` can illustrate the actual order of the levels of conditions. The underlying model fitting functions are `lm` and `lmer` for the fixed effects model and mixed effects model, respectively. The input of this function is the quantitative data from function `(dataProcess)`.

Value

A list with the following components:

ComparisonResult A 'data.frame' containing the results of the statistical testing for each protein. The columns include:

Protein The name of the protein for which the comparison is made.

Label The label of the comparison, typically derived from the 'contrast.matrix'.

log2FC The log2 fold change between the conditions being compared. The base of the logarithm is specified by the 'log_base' parameter.

- 'log2FC = Inf' or '-Inf': This occurs when one condition has entirely missing measurements for a protein, resulting in an undefined ratio.
- 'log2FC' is a numeric value but all other columns are 'NA': This occurs when there is only one sample per condition. Fold change can be estimated, but variance cannot be estimated, so no statistical testing is possible.

SE The standard error of the log2 fold change estimate. May be 'NA' when variance cannot be estimated (e.g., when only one sample per group).

Tvalue The t-statistic value for the comparison. May be 'NA' when variance cannot be estimated (e.g., when only one sample per group).

DF The degrees of freedom associated with the t-statistic. A value of 0 indicates that, although variance could be estimated, the total number of observations is too small to support hypothesis testing.

pvalue The p-value for the statistical test of the comparison. Applicable if degrees of freedom is greater than 0

adj.pvalue The adjusted p-value using the Benjamini-Hochberg method for controlling the false discovery rate.

issue Any issues encountered during the comparison. NA indicates no issues. "oneCondition-Missing" occurs when data for one of the conditions being compared is entirely missing for a particular protein.

MissingPercentage The percentage of missing features for a given protein across all runs. This column is included only if missing values were imputed.

ImputationPercentage The percentage of features that were imputed for a given protein across all runs. This column is included only if missing values were imputed.

ModelQC A 'data.frame' containing quality control data used to fit models for group comparison. The columns include:

RUN Identifier for the specific MS run.

Protein Identifier for the protein.

ABUNDANCE Summarized intensity for the protein in a given run.

originalRUN Original run identifier before any processing.

GROUP Experimental group identifier.

SUBJECT Subject identifier within the experimental group.

TotalGroupMeasurements Total number of feature measurements for the protein in the given group.

NumMeasuredFeatures Number of features measured for the protein in the given run.

MissingPercentage Percentage of missing feature values for the protein in the given run.

more50missing Logical indicator of whether more than 50 percent of the features values are missing for the protein in the given run.

NumImputedFeature Number of features for which values were imputed due to missing or censored data for the protein in the given run.

residuals Contains the differences between the observed values and the values predicted by the fitted model.

fitted The predicted values obtained from the model for a protein measurement for a given run in the dataset.

FittedModel A list of fitted models for each protein. This is included only if 'save_fitted_models' is set to TRUE. Each element of the list corresponds to a protein and contains the fitted model object.

Examples

```
# Consider quantitative data (i.e. QuantData) from yeast study with ten time points of interests,
# three biological replicates, and no technical replicates.
# It is a time-course experiment and we attempt to compare differential abundance
# between time 1 and 7 in a set of targeted proteins.
# In this label-based SRM experiment, MSstats uses the fitted model with expanded scope of
# Biological replication.
QuantData <- dataProcess(SRMRawData, use_log_file = FALSE)
head(QuantData$FeatureLevelData)
levels(QuantData$ProteinLevelData$GROUP)
comparison <- matrix(c(-1,0,0,0,0,0,0,1,0,0,0),nrow=1)
row.names(comparison) <- "T7-T1"
groups = levels(QuantData$ProteinLevelData$GROUP)
colnames(comparison) <- groups[order(as.numeric(groups))]
# Tests for differentially abundant proteins with models:
# label-based SRM experiment with expanded scope of biological replication.
testResultOneComparison <- groupComparison(contrast.matrix=comparison, data=QuantData,
                                           use_log_file = FALSE)

# table for result
testResultOneComparison$ComparisonResult
```

Description

To summarize the results of log-fold changes and adjusted p-values for differentially abundant proteins, groupComparisonPlots takes testing results from function ([groupComparison](#)) as input and automatically generate three types of figures in pdf files as output : (1) volcano plot (specify "VolcanoPlot" in option type) for each comparison separately; (2) heatmap (specify "Heatmap" in option type) for multiple comparisons ; (3) comparison plot (specify "ComparisonPlot" in option type) for multiple comparisons per protein.

Usage

```
groupComparisonPlots(
  data,
  type,
  sig = 0.05,
  FCcutoff = FALSE,
  logBase.pvalue = 10,
  ylimUp = FALSE,
  ylimDown = FALSE,
  xlimUp = FALSE,
  x.axis.size = 10,
  y.axis.size = 10,
  dot.size = 3,
  text.size = 4,
  text.angle = 0,
  legend.size = 13,
  ProteinName = TRUE,
  colorkey = TRUE,
  numProtein = 100,
  clustering = "both",
  width = 800,
  height = 600,
  which.Comparison = "all",
  which.Protein = "all",
  address = "",
  isPlotly = FALSE
)
```

Arguments

data	'ComparisonResult' in testing output from function groupComparison.
type	choice of visualization. "VolcanoPlot" represents volcano plot of log fold changes and adjusted p-values for each comparison separately. "Heatmap" represents heatmap of adjusted p-values for multiple comparisons. "ComparisonPlot" represents comparison plot of log fold changes for multiple comparisons per protein.
sig	FDR cutoff for the adjusted p-values in heatmap and volcano plot. level of significance for comparison plot. 100(1-sig)% confidence interval will be drawn. sig=0.05 is default.

FCcutoff	for volcano plot or heatmap, whether involve fold change cutoff or not. FALSE (default) means no fold change cutoff is applied for significance analysis. FC-cutoff = specific value means specific fold change cutoff is applied.
logBase.pvalue	for volcano plot or heatmap, (-) logarithm transformation of adjusted p-value with base 2 or 10(default).
ylimUp	for all three plots, upper limit for y-axis. FALSE (default) for volcano plot/heatmap use maximum of -log2 (adjusted p-value) or -log10 (adjusted p-value). FALSE (default) for comparison plot uses maximum of log-fold change + CI.
ylimDown	for all three plots, lower limit for y-axis. FALSE (default) for volcano plot/heatmap use minimum of -log2 (adjusted p-value) or -log10 (adjusted p-value). FALSE (default) for comparison plot uses minimum of log-fold change - CI.
xlimUp	for Volcano plot, the limit for x-axis. FALSE (default) for use maximum for absolute value of log-fold change or 3 as default if maximum for absolute value of log-fold change is less than 3.
x.axis.size	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
y.axis.size	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
dot.size	size of dots in volcano plot and comparison plot. Default is 3.
text.size	size of ProteinName label in the graph for Volcano Plot. Default is 4.
text.angle	angle of x-axis labels represented each comparison at the bottom of graph in comparison plot. Default is 0.
legend.size	size of legend for color at the bottom of volcano plot. Default is 7.
ProteinName	for volcano plot only, whether display protein names or not. TRUE (default) means protein names, which are significant, are displayed next to the points. FALSE means no protein names are displayed.
colorkey	TRUE(default) shows colorkey.
numProtein	For ggplot2: The number of proteins which will be presented in each heatmap. Default is 100. Maximum possible number of protein for one heatmap is 180. For Plotly: use this parameter to adjust the number of proteins to be displayed on the heatmap
clustering	Determines how to order proteins and comparisons. Hierarchical cluster analysis with Ward method(minimum variance) is performed. 'protein' means that protein dendrogram is computed and reordered based on protein means (the order of row is changed). 'comparison' means comparison dendrogram is computed and reordered based on comparison means (the order of comparison is changed). 'both' means to reorder both protein and comparison. Default is 'protein'.
width	width of the saved file in pixels. Default is 800.
height	height of the saved file in pixels. Default is 600.
which.Comparison	list of comparisons to draw plots. List can be labels of comparisons or order numbers of comparisons from levels(data\$Label), such as levels(testResultMultiComparisons\$Comparison). Default is "all", which generates all plots for each protein.

which.Protein	Protein list to draw comparison plots. List can be names of Proteins or order numbers of Proteins from levels(testResultMultiComparisons\$ComparisonResult\$Protein). Default is "all", which generates all comparison plots for each protein.
address	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf" or "ComparisonPlot.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window.
isPlotly	This parameter is for MSstatsShiny application for plotly render, this cannot be used for saving PDF files as plotly do not have support for PDFs currently. address and isPlotly cannot be set as TRUE at the same time.

Details

- Volcano plot : illustrate actual log-fold changes and adjusted p-values for each comparison separately with all proteins. The x-axis is the log fold change. The base of logarithm transformation is the same as specified in "logTrans" from [dataProcess](#). The y-axis is the negative log2 or log10 adjusted p-values. The horizontal dashed line represents the FDR cutoff. The points below the FDR cutoff line are non-significantly abundant proteins (colored in black). The points above the FDR cutoff line are significantly abundant proteins (colored in red/blue for up-/down-regulated). If fold change cutoff is specified (FCcutoff = specific value), the points above the FDR cutoff line but within the FC cutoff line are non-significantly abundant proteins (colored in black)/
- Heatmap : illustrate up-/down-regulated proteins for multiple comparisons with all proteins. Each column represents each comparison of interest. Each row represents each protein. Color red/blue represents proteins in that specific comparison are significantly up-regulated/down-regulated proteins with FDR cutoff and/or FC cutoff. The color scheme shows the evidences of significance. The darker color it is, the stronger evidence of significance it has. Color gold represents proteins are not significantly different in abundance.
- Comparison plot : illustrate log-fold change and its variation of multiple comparisons for single protein. X-axis is comparison of interest. Y-axis is the log fold change. The red points are the estimated log fold change from the model. The blue error bars are the confidence interval with 0.95 significant level for log fold change. This interval is only based on the standard error, which is estimated from the model.

Examples

```
QuantData<-dataProcess(SRMRawData, use_log_file = FALSE)
head(QuantData$FeatureLevelData)
## based on multiple comparisons (T1 vs T3; T1 vs T7; T1 vs T9)
comparison1<-matrix(c(-1,0,1,0,0,0,0,0,0,0),nrow=1)
comparison2<-matrix(c(-1,0,0,0,0,0,1,0,0,0),nrow=1)
comparison3<-matrix(c(-1,0,0,0,0,0,0,0,1,0),nrow=1)
comparison<-rbind(comparison1,comparison2, comparison3)
row.names(comparison)<-c("T3-T1","T7-T1","T9-T1")
groups = levels(QuantData$ProteinLevelData$GROUP)
colnames(comparison) <- groups[order(as.numeric(groups))]
```

```

testResultMultiComparisons<-groupComparison(contrast.matrix=comparison,
data=QuantData,
use_log_file = FALSE)
testResultMultiComparisons$ComparisonResult
# Volcano plot with FDR cutoff = 0.05 and no FC cutoff
groupComparisonPlots(data=testResultMultiComparisons$ComparisonResult, type="VolcanoPlot",
logBase.pvalue=2, address="Ex1_")
# Volcano plot with FDR cutoff = 0.05, FC cutoff = 70, upper y-axis limit = 100,
# and no protein name displayed
# FCcutoff=70 is for demonstration purpose
groupComparisonPlots(data=testResultMultiComparisons$ComparisonResult, type="VolcanoPlot",
FCcutoff=70, logBase.pvalue=2, ylimUp=100, ProteinName=FALSE,address="Ex2_")
# Heatmap with FDR cutoff = 0.05
groupComparisonPlots(data=testResultMultiComparisons$ComparisonResult, type="Heatmap",
logBase.pvalue=2, address="Ex1_")
# Heatmap with FDR cutoff = 0.05 and FC cutoff = 70
# FCcutoff=70 is for demonstration purpose
groupComparisonPlots(data=testResultMultiComparisons$ComparisonResult, type="Heatmap",
FCcutoff=70, logBase.pvalue=2, address="Ex2_")
# Comparison Plot
groupComparisonPlots(data=testResultMultiComparisons$ComparisonResult, type="ComparisonPlot",
address="Ex1_")
# Comparison Plot
groupComparisonPlots(data=testResultMultiComparisons$ComparisonResult, type="ComparisonPlot",
ylimUp=8, ylimDown=-1, address="Ex2_")

```

groupComparisonQCPlots

Visualization for model-based quality control in fitting model

Description

To check the assumption of linear model for whole plot inference, groupComparisonQCPlots takes the results after fitting models from function ([groupComparison](#)) as input and automatically generate two types of figures in pdf files as output: (1) normal quantile-quantile plot (specify "QQPlot" in option type) for checking normally distributed errors.; (2) residual plot (specify "ResidualPlot" in option type).

Usage

```

groupComparisonQCPlots(
  data,
  type,
  axis.size = 10,
  dot.size = 3,
  width = 10,
  height = 10,
  which.Protein = "all",

```

```

    address = ""
  )

```

Arguments

data	output from function groupComparison.
type	choice of visualization. "QQPlots" represents normal quantile-quantile plot for each protein after fitting models. "ResidualPlots" represents a plot of residuals versus fitted values for each protein in the dataset.
axis.size	size of axes labels. Default is 10.
dot.size	size of points in the graph for residual plots and QQ plots. Default is 3.
width	width of the saved file. Default is 10.
height	height of the saved file. Default is 10.
which.Protein	Protein list to draw plots. List can be names of Proteins or order numbers of Proteins from levels(testResultOneComparison\$ComparisonResult\$Protein). Default is "all", which generates all plots for each protein.
address	name that will serve as a prefix to the name of output file.

Details

Results based on statistical models for whole plot level inference are accurate as long as the assumptions of the model are met. The model assumes that the measurement errors are normally distributed with mean 0 and constant variance. The assumption of a constant variance can be checked by examining the residuals from the model.

- **QQPlots** : a normal quantile-quantile plot for each protein is generated in order to check whether the errors are well approximated by a normal distribution. If points fall approximately along a straight line, then the assumption is appropriate for that protein. Only large deviations from the line are problematic.
- **ResidualPlots** : The plots of residuals against predicted(fitted) values. If it shows a random scatter, then the assumption is appropriate.

Value

produce a pdf file

Examples

```

QuantData <- dataProcess(SRMRawData, use_log_file = FALSE)
head(QuantData$FeatureLevelData)
levels(QuantData$FeatureLevelData$GROUP)
comparison <- matrix(c(-1,0,0,0,0,0,0,1,0,0,0),nrow=1)
row.names(comparison) <- "T7-T1"
colnames(comparison) <- unique(QuantData$ProteinLevelData$GROUP)
# Tests for differentially abundant proteins with models:
# label-based SRM experiment with expanded scope of biological replication.
testResultOneComparison <- groupComparison(contrast.matrix=comparison, data=QuantData,
use_log_file = FALSE)

```

```
# normal quantile-quantile plots
groupComparisonQCPlots(data=testResultOneComparison, type="QQPlots", address="")
# residual plots
groupComparisonQCPlots(data=testResultOneComparison, type="ResidualPlots", address="")
```

```
makePeptidesDictionary
```

Prepare a peptides dictionary for global standards normalization

Description

Prepare a peptides dictionary for global standards normalization

Usage

```
makePeptidesDictionary(input, normalization)
```

Arguments

input	'data.table' in MSstats standard format
normalization	normalization method

Details

This function extracts information required to perform normalization with global standards. It is useful for running the summarization workflow outside of the dataProcess function.

Examples

```
input = data.table::as.data.table(DDARawData)
peptides_dict = makePeptidesDictionary(input, "GLOBALSTANDARDS")
head(peptides_dict) # ready to be passed to the MSstatsNormalize function
```

```
modelBasedQCPlots
```

Visualization for model-based quality control in fitting model

Description

To check the assumption of linear model for whole plot inference, modelBasedQCPlots takes the results after fitting models from function ([groupComparison](#)) as input and automatically generate two types of figures in pdf files as output: (1) normal quantile-quantile plot (specify "QQPlot" in option type) for checking normally distributed errors.; (2) residual plot (specify "ResidualPlot" in option type).

Usage

```
modelBasedQCPlots(
  data,
  type,
  axis.size = 10,
  dot.size = 3,
  width = 10,
  height = 10,
  which.Protein = "all",
  address = "",
  displayDeprecationMessage = TRUE
)
```

Arguments

data	output from function groupComparison.
type	choice of visualization. "QQPlots" represents normal quantile-quantile plot for each protein after fitting models. "ResidualPlots" represents a plot of residuals versus fitted values for each protein in the dataset.
axis.size	size of axes labels. Default is 10.
dot.size	size of points in the graph for residual plots and QQ plots. Default is 3.
width	width of the saved file. Default is 10.
height	height of the saved file. Default is 10.
which.Protein	Protein list to draw plots. List can be names of Proteins or order numbers of Proteins from levels(testResultOneComparison\$ComparisonResult\$Protein). Default is "all", which generates all plots for each protein.
address	name that will serve as a prefix to the name of output file.

Details

Results based on statistical models for whole plot level inference are accurate as long as the assumptions of the model are met. The model assumes that the measurement errors are normally distributed with mean 0 and constant variance. The assumption of a constant variance can be checked by examining the residuals from the model.

- QQPlots : a normal quantile-quantile plot for each protein is generated in order to check whether the errors are well approximated by a normal distribution. If points fall approximately along a straight line, then the assumption is appropriate for that protein. Only large deviations from the line are problematic.
- ResidualPlots : The plots of residuals against predicted(fitted) values. If it shows a random scatter, then the assumption is appropriate.

Value

produce a pdf file

Examples

```
QuantData <- dataProcess(SRMRawData, use_log_file = FALSE)
head(QuantData$FeatureLevelData)
levels(QuantData$FeatureLevelData$GROUP)
comparison <- matrix(c(-1,0,0,0,0,0,1,0,0,0),nrow=1)
row.names(comparison) <- "T7-T1"
colnames(comparison) <- unique(QuantData$ProteinLevelData$GROUP)
# Tests for differentially abundant proteins with models:
# label-based SRM experiment with expanded scope of biological replication.
testResultOneComparison <- groupComparison(contrast.matrix=comparison, data=QuantData,
use_log_file = FALSE)
# normal quantile-quantile plots
modelBasedQCPlots(data=testResultOneComparison, type="QQPlots", address="")
# residual plots
modelBasedQCPlots(data=testResultOneComparison, type="ResidualPlots", address="")
```

MSstatsContrastMatrix *Create a contrast matrix for groupComparison function*

Description

Create a contrast matrix for groupComparison function

Usage

```
MSstatsContrastMatrix(contrasts, conditions, labels = NULL)
```

Arguments

contrasts	One of the following: i) list of lists. Each sub-list consists of two vectors that name conditions that will be compared. See the details section for more information ii) matrix. In this case, it's correctness will be checked iii) "pairwise". In this case, pairwise comparison matrix will be generated iv) data.frame. In this case, input will be converted to matrix
conditions	unique condition labels
labels	labels for contrasts (row.names of the contrast matrix)

MSstatsGroupComparison

Group comparison

Description

Group comparison

Usage

```
MSstatsGroupComparison(
  summarized_list,
  contrast_matrix,
  save_fitted_models,
  repeated,
  samples_info,
  numberOfCores = 1
)
```

Arguments

summarized_list	
	output of MSstatsPrepareForGroupComparison
contrast_matrix	
	contrast matrix
save_fitted_models	
	if TRUE, fitted models will be included in the output
repeated	logical, output of checkRepeatedDesign function
samples_info	data.table, output of getSamplesInfo function
numberOfCores	Number of cores for parallel processing. When > 1, a logfile named 'MSstats_groupComparison_log_prog' is created to track progress. Only works for Linux & Mac OS.

Examples

```
QuantData <- dataProcess(SRMRawData, use_log_file = FALSE)
group_comparison_input = MSstatsPrepareForGroupComparison(QuantData)
levels(QuantData$ProteinLevelData$GROUP)
comparison <- matrix(c(-1,0,0,0,0,0,1,0,0,0),nrow=1)
row.names(comparison) <- "T7-T1"
groups = levels(QuantData$ProteinLevelData$GROUP)
colnames(comparison) <- groups[order(as.numeric(groups))]
samples_info = getSamplesInfo(QuantData)
repeated = checkRepeatedDesign(QuantData)
group_comparison = MSstatsGroupComparison(group_comparison_input, comparison,
                                           FALSE, repeated, samples_info)
length(group_comparison) # list of length equal to number of proteins
group_comparison[[1]][[1]] # data used to fit linear model
```

```
group_comparison[[1]][[2]] # comparison result
group_comparison[[2]][[3]] # NULL, because we set save_fitted_models to FALSE
```

MSstatsGroupComparisonOutput

Create output of group comparison based on results for individual proteins

Description

Create output of group comparison based on results for individual proteins

Usage

```
MSstatsGroupComparisonOutput(input, summarization_output, log_base = 2)
```

Arguments

input	output of MSstatsGroupComparison function
summarization_output	output of dataProcess function
log_base	base of the logarithm used in fold-change calculation

Value

list, same as the output of ‘groupComparison’

Examples

```
QuantData <- dataProcess(SRMRawData, use_log_file = FALSE)
group_comparison_input = MSstatsPrepareForGroupComparison(QuantData)
levels(QuantData$ProteinLevelData$GROUP)
comparison <- matrix(c(-1,0,0,0,0,0,0,1,0,0,0),nrow=1)
row.names(comparison) <- "T7-T1"
groups = levels(QuantData$ProteinLevelData$GROUP)
colnames(comparison) <- groups[order(as.numeric(groups))]
samples_info = getSamplesInfo(QuantData)
repeated = checkRepeatedDesign(QuantData)
group_comparison = MSstatsGroupComparison(group_comparison_input, comparison,
                                           FALSE, repeated, samples_info)
group_comparison_final = MSstatsGroupComparisonOutput(group_comparison,
                                                       QuantData)
group_comparison_final[["ComparisonResult"]]
```

MSstatsGroupComparisonSingleProtein
Group comparison for a single protein

Description

Group comparison for a single protein

Usage

```
MSstatsGroupComparisonSingleProtein(
  single_protein,
  contrast_matrix,
  repeated,
  groups,
  samples_info,
  save_fitted_models,
  has_imputed
)
```

Arguments

single_protein	data.table with summarized data for a single protein
contrast_matrix	contrast matrix
repeated	if TRUE, repeated measurements will be modeled
groups	unique labels of experimental conditions
samples_info	number of runs per group
save_fitted_models	if TRUE, fitted model will be saved. If not, it will be replaced with NULL
has_imputed	TRUE if missing values have been imputed

Examples

```
QuantData <- dataProcess(SRMRawData, use_log_file = FALSE)
group_comparison_input <- MSstatsPrepareForGroupComparison(QuantData)
levels(QuantData$ProteinLevelData$GROUP)
comparison <- matrix(c(-1,0,0,0,0,0,0,1,0,0,0),nrow=1)
row.names(comparison) <- "T7-T1"
groups = levels(QuantData$ProteinLevelData$GROUP)
colnames(comparison) <- groups[order(as.numeric(groups))]
samples_info <- getSamplesInfo(QuantData)
repeated <- checkRepeatedDesign(QuantData)
single_output <- MSstatsGroupComparisonSingleProtein(
  group_comparison_input[[1]], comparison, repeated, groups, samples_info,
  FALSE, TRUE)
single_output # same as a single element of MSstatsGroupComparison output
```

MSstatsHandleMissing *Handle censored missing values*

Description

Handle censored missing values

Usage

```
MSstatsHandleMissing(
  input,
  summary_method,
  impute,
  missing_symbol,
  censored_cutoff
)
```

Arguments

input	‘data.table’ in MSstats data format
summary_method	summarization method (‘summaryMethod’ parameter to ‘dataProcess’)
impute	if TRUE, missing values are supposed to be imputed (‘MBimpute’ parameter to ‘dataProcess’)
missing_symbol	‘censoredInt’ parameter to ‘dataProcess’
censored_cutoff	‘maxQuantileforCensored’ parameter to ‘dataProcess’

Value

data.table

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
input = MSstatsNormalize(input, "EQUALIZEMEDIANS")
input = MSstatsMergeFractions(input)
input = MSstatsHandleMissing(input, "TMP", TRUE, "NA", 0.999)
head(input)
```

MSstatsMergeFractions *Re-format the data before feature selection*

Description

Re-format the data before feature selection

Usage

```
MSstatsMergeFractions(input)
```

Arguments

input 'data.table' in MSstats format

Value

data.table

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
input = MSstatsNormalize(input, "EQUALIZEMEDIANS")
input = MSstatsMergeFractions(input)
head(input)
```

MSstatsNormalize *Normalize MS data*

Description

Normalize MS data

Usage

```
MSstatsNormalize(
  input,
  normalization_method,
  peptides_dict = NULL,
  standards = NULL
)
```

Arguments

input data.table in MSstats format

normalization_method name of a chosen normalization method: "NONE" or "FALSE" for no normalization, "EQUALIZEMEDIANS" for median normalization, "QUANTILE" normalization for quantile normalization from 'preprocessCore' package, "GLOBALSTANDARDS" for normalization based on selected peptides or proteins.

peptides_dict 'data.table' of names of peptides and their corresponding features.

standards character vector with names of standards, required if "GLOBALSTANDARDS" method was selected.

Value

data.table

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
input = MSstatsNormalize(input, "EQUALIZEMEDIANS") # median normalization
head(input)
```

MSstatsPrepareForDataProcess

Prepare data for processing by 'dataProcess' function

Description

Prepare data for processing by 'dataProcess' function

Usage

```
MSstatsPrepareForDataProcess(input, log_base, fix_missing)
```

Arguments

input 'data.table' in MSstats format

log_base base of the logarithm to transform intensities

fix_missing str, optional. Defaults to NULL, which means no action. If not NULL, must be one of the options: "zero_to_na" or "na_to_zero". If "zero_to_na", Intensity values equal exactly to 0 will be converted to NA. If "na_to_zero", missing values will be replaced by zeros.

Value

data.table

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
head(input)
```

MSstatsPrepareForGroupComparison

Prepare output for dataProcess for group comparison

Description

Prepare output for dataProcess for group comparison

Usage

```
MSstatsPrepareForGroupComparison(summarization_output)
```

Arguments

summarization_output
output of dataProcess

Value

list of run-level data for each protein in the input. This list has a "has_imputed" attribute that indicates if missing values were imputed in the input dataset.

Examples

```
QuantData <- dataProcess(SRMRawData, use_log_file = FALSE)
group_comparison_input = MSstatsPrepareForGroupComparison(QuantData)
length(group_comparison_input) # list of length equal to number of proteins
# in protein-level data of QuantData
head(group_comparison_input[[1]])
```

MSstatsPrepareForSummarization

Prepare feature-level data for protein-level summarization

Description

Prepare feature-level data for protein-level summarization

Usage

```
MSstatsPrepareForSummarization(
  input,
  method,
  impute,
  censored_symbol,
  remove_uninformative_feature_outlier
)
```

Arguments

input	feature-level data processed by dataProcess subfunctions
method	summarization method - 'summaryMethod' parameter of the dataProcess function
impute	if TRUE, censored missing values will be imputed - 'MBimpute' parameter of the dataProcess function
censored_symbol	censored missing value indicator - 'censoredInt' parameter of the dataProcess function
remove_uninformative_feature_outlier	if TRUE, features labeled as outlier of uninformative by the MSstatsSelectFeatures function will not be used in summarization

Value

data.table

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
head(input)
```

MSstatsSelectFeatures *Feature selection before feature-level data summarization*

Description

Feature selection before feature-level data summarization

Usage

```
MSstatsSelectFeatures(input, method, top_n = 3, min_feature_count = 2)
```

Arguments

input	data.table
method	"all" / "highQuality", "topN"
top_n	number of features to use for "topN" method
min_feature_count	number of quality features for "highQuality" method

Value

data.table

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
input = MSstatsNormalize(input, "EQUALIZEMEDIANS")
input = MSstatsMergeFractions(input)
input = MSstatsHandleMissing(input, "TMP", TRUE, "NA", 0.999)
input_all = MSstatsSelectFeatures(input, "all") # all features
input_5 = MSstatsSelectFeatures(data.table::copy(input), "topN", top_n = 5) # top 5 features
input_informative = MSstatsSelectFeatures(input, "highQuality") # feature selection

head(input_all)
head(input_5)
head(input_informative)
```

MSstatsSummarizationOutput

Post-processing output from MSstats summarization

Description

Post-processing output from MSstats summarization

Usage

```
MSstatsSummarizationOutput(
  input,
  summarized,
  processed,
  method,
  impute,
  censored_symbol
)
```

Arguments

input	'data.table' in MSstats format
summarized	output of the 'MSstatsSummarizeWithSingleCore' function
processed	output of MSstatsSelectFeatures
method	name of the summarization method ('summaryMethod' parameter to 'dataProcess')
impute	if TRUE, censored missing values were imputed ('MBimpute' parameter to 'dataProcess')
censored_symbol	censored missing value indicator ('censoredInt' parameter to 'dataProcess')

Value

list that consists of the following elements:

- FeatureLevelData - feature-level data after processing
- ProteinLevelData - protein-level (summarized) data
- SummaryMethod (string) - name of summarization method that was used

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
MSstatsConvert::MSstatsLogsSettings(FALSE)
```

```

input = MSstatsPrepareForDataProcess(raw, 2, NULL)
input = MSstatsNormalize(input, "EQUALIZEMEDIANS")
input = MSstatsMergeFractions(input)
input = MSstatsHandleMissing(input, "TMP", TRUE, "NA", 0.999)
input = MSstatsSelectFeatures(input, "all")
processed = getProcessed(input)
input = MSstatsPrepareForSummarization(input, method, impute, cens, FALSE)
summarized = MSstatsSummarizeWithSingleCore(input, method, impute, cens, FALSE, TRUE)
output = output = MSstatsSummarizationOutput(input, summarized, processed,
method, impute, cens)

```

MSstatsSummarizeSingleLinear

Linear model-based summarization for a single protein

Description

Linear model-based summarization for a single protein

Usage

```
MSstatsSummarizeSingleLinear(single_protein, equal_variances = TRUE)
```

Arguments

`single_protein` feature-level data for a single protein
`equal_variances`
if TRUE, observation are assumed to be homoskedastic

Value

list with protein-level data

Examples

```

raw = DDARawData
method = "linear"
cens = NULL
impute = FALSE
# currently, MSstats only supports MBimpute = FALSE for linear summarization
MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
input = MSstatsNormalize(input, "EQUALIZEMEDIANS")
input = MSstatsMergeFractions(input)
input = MSstatsHandleMissing(input, "TMP", TRUE, "NA", 0.999)
input = MSstatsSelectFeatures(input, "all")
input = MSstatsPrepareForSummarization(input, method, impute, cens, FALSE)
input_split = split(input, input$PROTEIN)

```

```
single_protein_summary = MSstatsSummarizeSingleLinear(input_split[[1]])
head(single_protein_summary[[1]])
```

MSstatsSummarizeSingleTMP

Tukey Median Polish summarization for a single protein

Description

Tukey Median Polish summarization for a single protein

Usage

```
MSstatsSummarizeSingleTMP(
  single_protein,
  impute,
  censored_symbol,
  remove50missing
)
```

Arguments

single_protein feature-level data for a single protein

impute only for summaryMethod = "TMP" and censoredInt = 'NA' or '0'. TRUE (default) imputes 'NA' or '0' (depending on censoredInt option) by Accelerated failure model. FALSE uses the values assigned by cutoffCensored

censored_symbol Missing values are censored or at random. 'NA' (default) assumes that all 'NA's in 'Intensity' column are censored. '0' uses zero intensities as censored intensity. In this case, NA intensities are missing at random. The output from Skyline should use '0'. Null assumes that all NA intensities are randomly missing.

remove50missing only for summaryMethod = "TMP". TRUE removes the proteins where every run has at least 50% missing values for each peptide. FALSE is default.

Value

list of two data.tables: one with fitted survival model, the other with protein-level data

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
# currently, MSstats only supports MBimpute = FALSE for linear summarization
```

```

MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
input = MSstatsNormalize(input, "EQUALIZEMEDIANS")
input = MSstatsMergeFractions(input)
input = MSstatsHandleMissing(input, "TMP", TRUE, "NA", 0.999)
input = MSstatsSelectFeatures(input, "all")
input = MSstatsPrepareForSummarization(input, method, impute, cens, FALSE)
input_split = split(input, input$PROTEIN)
single_protein_summary = MSstatsSummarizeSingleTMP(input_split[[1]],
                                                    impute, cens, FALSE)

head(single_protein_summary[[1]])

```

MSstatsSummarizeWithMultipleCores

Feature-level data summarization with multiple cores

Description

Feature-level data summarization with multiple cores

Usage

```

MSstatsSummarizeWithMultipleCores(
  input,
  method,
  impute,
  censored_symbol,
  remove50missing,
  equal_variance,
  numberOfCores = 1
)

```

Arguments

input	feature-level data processed by dataProcess subfunctions
method	summarization method: "linear" or "TMP"
impute	only for summaryMethod = "TMP" and censoredInt = 'NA' or '0'. TRUE (default) imputes 'NA' or '0' (depending on censoredInt option) by Accelerated failure model. FALSE uses the values assigned by cutoffCensored
censored_symbol	Missing values are censored or at random. 'NA' (default) assumes that all 'NA's in 'Intensity' column are censored. '0' uses zero intensities as censored intensity. In this case, NA intensities are missing at random. The output from Skyline should use '0'. Null assumes that all NA intensities are randomly missing.
remove50missing	only for summaryMethod = "TMP". TRUE removes the proteins where every run has at least 50% missing values for each peptide. FALSE is default.

equal_variance	only for summaryMethod = "linear". Default is TRUE. Logical variable for whether the model should account for heterogeneous variation among intensities from different features. Default is TRUE, which assume equal variance among intensities from features. FALSE means that we cannot assume equal variance among intensities from features, then we will account for heterogeneous variation from different features.
numberOfCores	Number of cores for parallel processing. When > 1, a logfile named 'MSstats_dataProcess_log_progress.log' is created to track progress. Only works for Linux & Mac OS. Default is 1.

Value

list of length one with run-level data.

MSstatsSummarizeWithSingleCore
<i>Feature-level data summarization with 1 core</i>

Description

Feature-level data summarization with 1 core

Usage

```
MSstatsSummarizeWithSingleCore(  
  input,  
  method,  
  impute,  
  censored_symbol,  
  remove50missing,  
  equal_variance  
)
```

Arguments

input	feature-level data processed by dataProcess subfunctions
method	summarization method: "linear" or "TMP"
impute	only for summaryMethod = "TMP" and censoredInt = 'NA' or '0'. TRUE (default) imputes 'NA' or '0' (depending on censoredInt option) by Accelerated failure model. FALSE uses the values assigned by cutoffCensored
censored_symbol	Missing values are censored or at random. 'NA' (default) assumes that all 'NA's in 'Intensity' column are censored. '0' uses zero intensities as censored intensity. In this case, NA intensities are missing at random. The output from Skyline should use '0'. Null assumes that all NA intensities are randomly missing.
remove50missing	only for summaryMethod = "TMP". TRUE removes the proteins where every run has at least 50% missing values for each peptide. FALSE is default.

`equal_variance` only for `summaryMethod = "linear"`. Default is `TRUE`. Logical variable for whether the model should account for heterogeneous variation among intensities from different features. Default is `TRUE`, which assume equal variance among intensities from features. `FALSE` means that we cannot assume equal variance among intensities from features, then we will account for heterogeneous variation from different features.

Value

list of length one with run-level data.

Examples

```
raw = DDARawData
method = "TMP"
cens = "NA"
impute = TRUE
MSstatsConvert::MSstatsLogsSettings(FALSE)
input = MSstatsPrepareForDataProcess(raw, 2, NULL)
input = MSstatsNormalize(input, "EQUALIZEMEDIANS")
input = MSstatsMergeFractions(input)
input = MSstatsHandleMissing(input, "TMP", TRUE, "NA", 0.999)
input = MSstatsSelectFeatures(input, "all")
processed = getProcessed(input)
input = MSstatsPrepareForSummarization(input, method, impute, cens, FALSE)
summarized = MSstatsSummarizeWithSingleCore(input, method, impute, cens, FALSE, TRUE)
length(summarized) # list of summarization outputs for each protein
head(summarized[[1]][[1]]) # run-level summary
```

quantification

Protein sample quantification or group quantification

Description

Model-based quantification for each condition or for each biological sample per protein in a targeted Selected Reaction Monitoring (SRM), Data-Dependent Acquisition (DDA or shotgun), and Data-Independent Acquisition (DIA or SWATH-MS) experiment. Quantification takes the processed data set by [dataProcess](#) as input and automatically generate the quantification results (`data.frame`) in a long or matrix format.

Usage

```
quantification(
  data,
  type = "Sample",
  format = "matrix",
  use_log_file = TRUE,
  append = FALSE,
```

```

    verbose = TRUE,
    log_file_path = NULL
  )

```

Arguments

<code>data</code>	name of the (processed) data set.
<code>type</code>	choice of quantification. "Sample" or "Group" for protein sample quantification or group quantification.
<code>format</code>	choice of returned format. "long" for long format which has the columns named Protein, Condition, LogIntensities (and BioReplicate if it is subject quantification), NumFeature for number of transitions for a protein, and NumPeaks for number of observed peak intensities for a protein. "matrix" for data matrix format which has the rows for Protein and the columns, which are Groups(or Conditions) for group quantification or the combinations of BioReplicate and Condition (labeled by "BioReplicate"_"Condition") for sample quantification. Default is "matrix"
<code>use_log_file</code>	logical. If TRUE, information about data processing will be saved to a file.
<code>append</code>	logical. If TRUE, information about data processing will be added to an existing log file.
<code>verbose</code>	logical. If TRUE, information about data processing will be printed to the console.
<code>log_file_path</code>	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

Details

- Sample quantification : individual biological sample quantification for each protein. The label of each biological sample is a combination of the corresponding group and the sample ID. If there are no technical replicates or experimental replicates per sample, sample quantification is the same as run summarization from dataProcess. If there are technical replicates or experimental replicates, sample quantification is median among run quantification corresponding MS runs.
- Group quantification : quantification for individual group or individual condition per protein. It is median among sample quantification.
- The quantification for endogenous samples is based on run summarization from subplot model, with TMP robust estimation.

Value

data.frame as described in details.

Examples

```

# Consider quantitative data (i.e. QuantData) from a yeast study with ten time points of
# interests, three biological replicates, and no technical replicates which is

```

```
# a time-course experiment.
# Sample quantification shows model-based estimation of protein abundance in each biological
# replicate within each time point.
# Group quantification shows model-based estimation of protein abundance in each time point.
QuantData<-dataProcess(SRMRawData, use_log_file = FALSE)
head(QuantData$FeatureLevelData)
# Sample quantification
sampleQuant<-quantification(QuantData, use_log_file = FALSE)
head(sampleQuant)
# Group quantification
groupQuant<-quantification(QuantData, type="Group", use_log_file = FALSE)
head(groupQuant)
```

reexports

*Objects exported from other packages***Description**

These objects are imported from other packages. Follow the links below to see their documentation.

MSstatsConvert [DIANNtoMSstatsFormat](#), [DIAUmpiretoMSstatsFormat](#), [FragPipetoMSstatsFormat](#),
[MaxQtoMSstatsFormat](#), [OpenMStoMSstatsFormat](#), [OpenSWATHtoMSstatsFormat](#), [PDtoMSstatsFormat](#),
[ProgenesisToMSstatsFormat](#), [SkylinetoMSstatsFormat](#), [SpectronauttoMSstatsFormat](#)

savePlot

*Save a plot to pdf file***Description**

Save a plot to pdf file

Usage

```
savePlot(name_base, file_name, width, height)
```

Arguments

name_base	path to a folder (or "" for working directory)
file_name	name of a file to save. If this file already exists, an integer will be appended to this name
width	width of a plot
height	height of a plot

SDRFtoAnnotation

*Convert SDRF experimental design file into an MSstats annotation file***Description**

Takes an SDRF file and outputs an MSstats annotation file. Note the information in the SDRF file must be correctly annotated for MSstats so that MSstats can identify the experimental design. In particular the biological replicates must be correctly annotated, with group comparison experiments having a unique ID for each BioReplicate. For more information on this please see the Supplementary of the most recent [MSstats paper](#)

Usage

```
SDRFtoAnnotation(
  data,
  run_name = "comment[data file]",
  condition_name = "characteristics[disease]",
  biological_replicate = "characteristics[biological replicate]",
  fraction = NULL
)
```

Arguments

data	SDRF annotation file
run_name	Column name in SDRF file which contains the name of the MS run. The information in this column must match exactly with the run names in the PSM file
condition_name	Column name in SDRF file which contains information on the conditions in the data.
biological_replicate	Column name in SDRF file which contains the identifier for the biological replicates. Note MSstats uses this column to determine if the experiment is a repeated measure design. BioReplicate IDs should only be reused if the replicate was measured multiple times.
fraction	Column name in SDRF file which contains information on the fractionation in the data. Only required if data contains fractions. Default is 'NULL'

Examples

```
head(example_SDRF)

msstats_annotation = SDRFtoAnnotation(example_SDRF)

head(msstats_annotation)
```

SRMRawData

Example dataset from a SRM experiment with stable isotope labeled reference of a time course yeast study

Description

This is a partial data set obtained from a published study (Picotti, et. al, 2009). The experiment targeted 45 proteins in the glycolysis/gluconeogenesis/TCA cycle/glyoxylate cycle network, which spans the range of protein abundance from less than 128 to 10E6 copies per cell. Three biological replicates were analyzed at ten time points (T1-T10), while yeasts transited through exponential growth in a glucose-rich medium (T1-T4), diauxic shift (T5-T6), post-diauxic phase (T7-T9), and stationary phase (T10). Prior to trypsinization, the samples were mixed with an equal amount of proteins from the same N15-labeled yeast sample, which was used as a reference. Each sample was profiled in a single mass spectrometry run, where each protein was represented by up to two peptides and each peptide by up to three transitions. The goal of this study is to detect significantly change in protein abundance across time points. Transcriptional activity under the same experimental conditions has been previously investigated by (DeRisi et. al., 1997). Genes coding for 29 of the proteins are differentially expressed between conditions similar to those represented by T7 and T1 and could be treated as external sources to validate the proteomics analysis. In this example data set, two of the targeted proteins are selected and validated with gene expression study: Protein IDHC (gene name IDP2) is differentially expressed in time point 1 and time point 7, whereas, Protein PMG2 (gene name GPM2) is not. The protein names are based on Swiss Prot Name.

Usage

SRMRawData

Format

data.frame

Details

The raw data (input data for MSstats) is required to contain variable of ProteinName, PeptideSequence, PrecursorCharge, FragmentIon, ProductCharge, IsotopeLabelType, Condition, BioReplicate, Run, Intensity. The variable names should be fixed.

If the information of one or more columns is not available for the original raw data, please retain the column variables and type in fixed value. For example, the original raw data does not contain the information of ProductCharge, we retain the column ProductCharge and type in NA for all transitions in RawData.

The column BioReplicate should label with unique patient ID (i.e., same patients should label with the same ID).

Variable Intensity is required to be original signal without any log transformation and can be specified as the peak of height or the peak of area under curve.

Value

data.frame with the required format of MSstats.

Author(s)

Meena Choi, Olga Vitek.

Maintainer: Meena Choi (<mnchoi67@gmail.com>)

References

Ching-Yun Chang, Paola Picotti, Ruth Huttenhain, Viola Heinzelmann-Schwarz, Marko Jovanovic, Ruedi Aebersold, Olga Vitek. Protein significance analysis in selected reaction monitoring (SRM) measurements. *Molecular & Cellular Proteomics*, 11:M111.014662, 2012.

Examples

```
head(SRMRawData)
```

theme_msstats

Theme for MSstats plots

Description

Theme for MSstats plots

Usage

```
theme_msstats(  
  type,  
  x.axis.size = 10,  
  y.axis.size = 10,  
  legend_size = 13,  
  strip_background = element_rect(fill = "gray95"),  
  strip_text_x = element_text(colour = c("black"), size = 14),  
  legend_position = "top",  
  legend_box = "vertical",  
  text_angle = 0,  
  text_hjust = NULL,  
  text_vjust = NULL,  
  ...  
)
```

Arguments

type	type of a plot
x.axis.size	size of text on the x axis
y.axis.size	size of text on the y axis
legend_size	size of the legend
strip_background	background of facet
strip_text_x	size of text on facets
legend_position	position of the legend
legend_box	legend.box
text_angle	angle of text on the x axis (for condition and comparison plots)
text_hjust	hjust parameter for x axis text (for condition and comparison plots)
text_vjust	vjust parameter for x axis text (for condition and comparison plots)
...	additional parameters passed on to ggplot2::theme()

validateAnnotation	<i>Check if annotation matches intended experimental design</i>
--------------------	---

Description

Check if annotation matches intended experimental design

Usage

```
validateAnnotation(msstats_table, design_type = "group comparison")
```

Arguments

msstats_table	output of a converter function
design_type	character, "group comparison" or "repeated measures"

Value

TRUE if annotation file is consistent with intended experimental design. Otherwise, an error is thrown

Index

* internal

- .addCoverageInfo, [5](#)
- .addModelInformation, [5](#)
- .addModelVariances, [6](#)
- .addNInformativeInfo, [6](#)
- .addNoisyFlag, [7](#)
- .addOutlierCutoff, [7](#)
- .addOutlierInformation, [8](#)
- .addSurvivalPredictions, [8](#)
- .adjustLRuns, [9](#)
- .calculateOutlierCutoff, [9](#)
- .calculatePower, [10](#)
- .calculateProteinVariance, [10](#)
- .checkContrastMatrix, [11](#)
- .checkDataProcessParams, [11](#)
- .checkExperimentDesign, [12](#)
- .checkGCPlotsInput, [12](#)
- .checkGroupComparisonInput, [13](#)
- .checkSingleFeature, [13](#)
- .checkSingleLabelProteins, [14](#)
- .checkSingleSubject, [14](#)
- .checkTechReplicate, [15](#)
- .checkUnProcessedDataValidity, [15](#)
- .countInformative, [16](#)
- .countMissingPercentage, [16](#)
- .documentFunction, [17](#)
- .finalizeInput, [18](#)
- .finalizeLinear, [18](#)
- .finalizeTMP, [19](#)
- .fitHuber, [19](#)
- .fitLinearModel, [20](#)
- .fitModelForGroupComparison, [20](#)
- .fitModelSingleProtein, [21](#)
- .fitTukey, [22](#)
- .flagLowCoverage, [22](#)
- .flagUninformativeSingleLabel, [23](#)
- .getAllComparisons, [23](#)
- .getColorKeyGGPlot2, [24](#)
- .getColorKeyPlotly, [24](#)
- .getContrast, [24](#)
- .getContrastLabels, [25](#)
- .getEmptyComparison, [25](#)
- .getFeatureVariances, [26](#)
- .getMedian, [26](#)
- .getMedianSigmaSubject, [27](#)
- .getModelParameters, [27](#)
- .getNonMissingFilter, [28](#)
- .getNonMissingFilterStats, [28](#)
- .getNumSample, [29](#)
- .getSingleProteinForProfile, [29](#)
- .getVarComponent, [30](#)
- .getWideTable, [30](#)
- .getYaxis, [31](#)
- .groupComparisonWithMultipleCores, [31](#)
- .groupComparisonWithSingleCore, [32](#)
- .handleEmptyConditions, [32](#)
- .handleSingleContrast, [33](#)
- .isSummarizable, [34](#)
- .logDatasetInformation, [34](#)
- .logMissingness, [35](#)
- .logSingleLabeledProteins, [35](#)
- .logSummaryStatistics, [36](#)
- .makeComparison, [36](#)
- .makeConditionPlot, [37](#)
- .makeFactorColumns, [38](#)
- .makeHeatmapPlotly, [38](#)
- .makeProfilePlot, [39](#)
- .makeQCPlot, [40](#)
- .makeSummaryProfilePlot, [42](#)
- .makeVolcano, [43](#)
- .nicePrint, [44](#)
- .normalizeGlobalStandards, [44](#)
- .normalizeMedian, [45](#)
- .normalizeQuantile, [45](#)
- .onLoad, [45](#)
- .plotComparison, [46](#)
- .plotHeatmap, [47](#)

- [.plotVolcano, 49](#)
 - [.preProcessIntensities, 53](#)
 - [.prepareForDataProcess, 50](#)
 - [.prepareLinear, 51](#)
 - [.prepareSingleProteinForGC, 51](#)
 - [.prepareSummary, 52](#)
 - [.prepareTMP, 52](#)
 - [.quantileNormalizationSingleLabel, 53](#)
 - [.replaceZerosWithNA, 54](#)
 - [.runTukey, 54](#)
 - [.saveSessionInfo, 55](#)
 - [.saveTable, 55](#)
 - [.selectHighQualityFeatures, 55](#)
 - [.selectTopFeatures, 56](#)
 - [.setCensoredByThreshold, 56](#)
 - [.updateColumnsForProcessing, 57](#)
 - [.updateUnequalVariances, 57](#)
- [reexports, 103](#)
- [.addCoverageInfo, 5](#)
- [.addModelInformation, 5](#)
- [.addModelVariances, 6](#)
- [.addNInformativeInfo, 6](#)
- [.addNoisyFlag, 7](#)
- [.addOutlierCutoff, 7](#)
- [.addOutlierInformation, 8](#)
- [.addSurvivalPredictions, 8](#)
- [.adjustLRuns, 9](#)
- [.calculateOutlierCutoff, 9](#)
- [.calculatePower, 10](#)
- [.calculateProteinVariance, 10](#)
- [.checkContrastMatrix, 11](#)
- [.checkDataProcessParams, 11](#)
- [.checkExperimentDesign, 12](#)
- [.checkGCPlotsInput, 12](#)
- [.checkGroupComparisonInput, 13](#)
- [.checkSingleFeature, 13](#)
- [.checkSingleLabelProteins, 14](#)
- [.checkSingleSubject, 14](#)
- [.checkTechReplicate, 15](#)
- [.checkUnProcessedDataValidity, 15](#)
- [.countInformative, 16](#)
- [.countMissingPercentage, 16](#)
- [.documentFunction, 17](#)
- [.finalizeInput, 18](#)
- [.finalizeLinear, 18](#)
- [.finalizeTMP, 19](#)
- [.fitHuber, 19](#)
- [.fitLinearModel, 20](#)
- [.fitModelForGroupComparison, 20](#)
- [.fitModelSingleProtein, 21](#)
- [.fitTukey, 22](#)
- [.flagLowCoverage, 22](#)
- [.flagUninformativeSingleLabel, 23](#)
- [.getAllComparisons, 23](#)
- [.getColorKeyGGPlot2, 24](#)
- [.getColorKeyPlotly, 24](#)
- [.getContrast, 24](#)
- [.getContrastLabels, 25](#)
- [.getEmptyComparison, 25](#)
- [.getFeatureVariances, 26](#)
- [.getMedian, 26](#)
- [.getMedianSigmaSubject, 27](#)
- [.getModelParameters, 27](#)
- [.getNonMissingFilter, 28](#)
- [.getNonMissingFilterStats, 28](#)
- [.getNumSample, 29](#)
- [.getSingleProteinForProfile, 29](#)
- [.getVarComponent, 30](#)
- [.getWideTable, 30](#)
- [.getYaxis, 31](#)
- [.groupComparisonWithMultipleCores, 31](#)
- [.groupComparisonWithSingleCore, 32](#)
- [.handleEmptyConditions, 32](#)
- [.handleSingleContrast, 33](#)
- [.isSummarizable, 34](#)
- [.logDatasetInformation, 34](#)
- [.logMissingness, 35](#)
- [.logSingleLabeledProteins, 35](#)
- [.logSummaryStatistics, 36](#)
- [.makeComparison, 36](#)
- [.makeConditionPlot, 37](#)
- [.makeFactorColumns, 38](#)
- [.makeHeatmapPlotly, 38](#)
- [.makeProfilePlot, 39](#)
- [.makeQCPlot, 40](#)
- [.makeSummaryProfilePlot, 42](#)
- [.makeVolcano, 43](#)
- [.nicePrint, 44](#)
- [.normalizeGlobalStandards, 44](#)
- [.normalizeMedian, 45](#)
- [.normalizeQuantile, 45](#)
- [.onLoad, 45](#)
- [.plotComparison, 46](#)
- [.plotHeatmap, 47](#)
- [.plotVolcano, 49](#)

- .preProcessIntensities, [53](#)
- .prepareForDataProcess, [50](#)
- .prepareLinear, [51](#)
- .prepareSingleProteinForGC, [51](#)
- .prepareSummary, [52](#)
- .prepareTMP, [52](#)
- .quantileNormalizationSingleLabel, [53](#)
- .replaceZerosWithNA, [54](#)
- .runTukey, [54](#)
- .saveSessionInfo, [55](#)
- .saveTable, [55](#)
- .selectHighQualityFeatures, [55](#)
- .selectTopFeatures, [56](#)
- .setCensoredByThreshold, [56](#)
- .updateColumnsForProcessing, [57](#)
- .updateUnequalVariances, [57](#)

- checkRepeatedDesign, [58](#)

- dataProcess, [40](#), [41](#), [58](#), [62](#), [65](#), [67](#), [81](#), [101](#)
- dataProcessPlots, [62](#)
- DDARawData, [65](#)
- DDARawData.Skyline, [66](#)
- designSampleSize, [68](#), [70](#)
- designSampleSizePlots, [70](#)
- DIANNtoMSstatsFormat, [103](#)
- DIANNtoMSstatsFormat (reexports), [103](#)
- DIARawData, [71](#)
- DIAUmpiretoMSstatsFormat, [103](#)
- DIAUmpiretoMSstatsFormat (reexports), [103](#)

- example_SDRF, [72](#)
- extractSDRF, [73](#)

- FragPipetoMSstatsFormat, [103](#)
- FragPipetoMSstatsFormat (reexports), [103](#)

- getProcessed, [74](#)
- getSamplesInfo, [75](#)
- getSelectedProteins, [75](#)
- groupComparison, [76](#), [79](#), [82](#), [84](#)
- groupComparisonPlots, [78](#)
- groupComparisonQCPlots, [82](#)

- makePeptidesDictionary, [84](#)
- MaxQtoMSstatsFormat, [103](#)
- MaxQtoMSstatsFormat (reexports), [103](#)
- modelBasedQCPlots, [84](#)
- MSstatsContrastMatrix, [86](#)
- MSstatsGroupComparison, [87](#)
- MSstatsGroupComparisonOutput, [88](#)
- MSstatsGroupComparisonSingleProtein, [89](#)
- MSstatsHandleMissing, [90](#)
- MSstatsMergeFractions, [91](#)
- MSstatsNormalize, [91](#)
- MSstatsPrepareForDataProcess, [92](#)
- MSstatsPrepareForGroupComparison, [93](#)
- MSstatsPrepareForSummarization, [94](#)
- MSstatsSelectFeatures, [95](#)
- MSstatsSummarizationOutput, [96](#)
- MSstatsSummarizeSingleLinear, [97](#)
- MSstatsSummarizeSingleTMP, [98](#)
- MSstatsSummarizeWithMultipleCores, [99](#)
- MSstatsSummarizeWithSingleCore, [100](#)

- OpenMStoMSstatsFormat, [103](#)
- OpenMStoMSstatsFormat (reexports), [103](#)
- OpenSWATHtoMSstatsFormat, [103](#)
- OpenSWATHtoMSstatsFormat (reexports), [103](#)

- PDtoMSstatsFormat, [103](#)
- PDtoMSstatsFormat (reexports), [103](#)
- ProgenesistoMSstatsFormat, [103](#)
- ProgenesistoMSstatsFormat (reexports), [103](#)

- quantification, [101](#)

- reexports, [103](#)

- savePlot, [103](#)
- SDRFtoAnnotation, [104](#)
- SkylinetoMSstatsFormat, [103](#)
- SkylinetoMSstatsFormat (reexports), [103](#)
- SpectronauttoMSstatsFormat, [103](#)
- SpectronauttoMSstatsFormat (reexports), [103](#)
- SRMRawData, [105](#)

- theme_msstats, [106](#)

- validateAnnotation, [107](#)