

# Package ‘GeuvadisTranscriptExpr’

September 4, 2025

**Type** Package

**Title** Data package with transcript expression and bi-allelic genotypes  
from the GEUVADIS project

**Version** 1.36.0

**Date** 2021-11-21

**Description** Provides transcript expression and bi-allelic genotypes  
corresponding to the chromosome 19 for CEU individuals from the  
GEUVADIS project, Lappalainen et al.

**Depends** R (>= 3.3.0)

**License** GPL (>= 3)

**LazyData** true

**biocViews** Homo\_sapiens\_Data, SNPData, Genome, RNASeqData,  
SequencingData, ExpressionData

**VignetteBuilder** knitr

**Suggests** limma, rtracklayer, GenomicRanges, Rsamtools,  
VariantAnnotation, tools, BiocStyle, knitr, testthat

**NeedsCompilation** no

**Author** Malgorzata Nowicka [aut, cre]

**Maintainer** Malgorzata Nowicka <gosia.nowicka@uzh.ch>

**git\_url** <https://git.bioconductor.org/packages/GeuvadisTranscriptExpr>

**git\_branch** RELEASE\_3\_21

**git\_last\_commit** 2a8d54d

**git\_last\_commit\_date** 2025-04-15

**Repository** Bioconductor 3.21

**Date/Publication** 2025-09-04

## Contents

|                  |   |
|------------------|---|
| counts . . . . . | 2 |
| Index            | 4 |

---

`counts`

---

*Sample data for sQTL analysis*

---

**Description**

Subsets of raw data available in this package and saved as Rdata objects for faster loading.

**Usage**`counts``gene_ranges``genotypes``snp_ranges`**Format**

`counts` is a data frame with subset of counts from `TrQuantCount_CEU_chr19.tsv`

`gene_ranges` is a `GRanges` object containing subset of gene coordinates from `genes_chr19.bed`

`genotypes` is a data frame with subset of genotypes from `genotypes_CEU_chr19.tsv`

`snp_ranges` is a `Granges` object containing subset of SNP coordinates from `genotypes_CEU_chr19.tsv`

For all the details on how these data sets were produced, see examples.

**Value**

`counts`, `gene_ranges`, `genotypes`, `snp_ranges`

**Source**

Lappalainen T, Sammeth M, Friedlander MR, et al. Transcriptome and genome sequencing uncovers functional variation in humans. *Nature*. 2013;501(7468):506-11

**Examples**

```
library(rtracklayer)
data_dir <- system.file("extdata", package = "GeuvadisTranscriptExpr")

gene_id_subset <- readLines(file.path(data_dir, "gene_id_subset.txt"))
snp_id_subset <- readLines(file.path(data_dir, "snp_id_subset.txt"))

# Load gene ranges with names!
gene_ranges <- import(file.path(data_dir, "genes_chr19.bed"))
names(gene_ranges) <- mcols(gene_ranges)$name

gene_ranges <- gene_ranges[gene_id_subset, ]
```

```
# Load transcript counts
counts <- read.table(file.path(data_dir, "TrQuantCount_CEU_chr19.tsv"),
                     header = TRUE, sep = "\t", as.is = TRUE)

counts <- counts[counts$Gene_Symbol %in% gene_id_subset, ]

# Load genotypes
genotypes <- read.table(file.path(data_dir, "genotypes_CEU_chr19.tsv"),
                        header = TRUE, sep = "\t", as.is = TRUE)

genotypes <- genotypes[genotypes$snpId %in% snp_id_subset, ]

# Create SNP ranges with names!
snp_ranges <- GRanges(Rle(genotypes$chr), IRanges(genotypes$start,
                                                  genotypes$end))
names(snp_ranges) <- genotypes$snpId
```

# Index

\* **datasets**

counts, [2](#)

counts, [2](#)

gene\_ranges (counts), [2](#)

genotypes (counts), [2](#)

snp\_ranges (counts), [2](#)