

# Package ‘alabaster.vcf’

December 1, 2025

**Title** Save and Load Variant Data to/from File

**Version** 1.10.0

**Date** 2024-01-02

**Description** Save variant calling SummarizedExperiment to file and load them back as VCF objects.  
This is a more portable alternative to serialization of such objects into RDS files.  
Each artifact is associated with metadata for further interpretation;  
downstream applications can enrich this metadata with context-specific properties.

**License** MIT + file LICENSE

**Depends** alabaster.base, VariantAnnotation

**Imports** methods, S4Vectors, alabaster.se, alabaster.string, Rsamtools

**Suggests** knitr, rmarkdown, BiocStyle, testthat

**RoxygenNote** 7.2.3

**VignetteBuilder** knitr

**biocViews** DataImport, DataRepresentation

**git\_url** <https://git.bioconductor.org/packages/alabaster.vcf>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 5ff4dad

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2025-12-01

**Author** Aaron Lun [aut, cre]

**Maintainer** Aaron Lun <[infinite.monkeys.with.keyboards@gmail.com](mailto:infinite.monkeys.with.keyboards@gmail.com)>

## Contents

|                                 |          |
|---------------------------------|----------|
| readVCF . . . . .               | 2        |
| saveObject,VCF-method . . . . . | 3        |
| <b>Index</b>                    | <b>4</b> |

---

|         |                                    |
|---------|------------------------------------|
| readVCF | <i>Read a VCF object from disk</i> |
|---------|------------------------------------|

---

## Description

Read a [VCF](#) object from its on-disk representation.

## Usage

```
readVCF(path, metadata, ...)
```

## Arguments

|          |  |
|----------|--|
| path     | String containing a path to a directory, usually generated by the <a href="#">saveObject</a> method for <a href="#">VCF</a> objects. |
| metadata | Named list of metadata for this object, see <a href="#">readObjectFile</a> for details.  |
| ...      | Further arguments passed to internal <a href="#">altReadObject</a> calls.  |

## Value

A [VCF](#) object.

## Author(s)

Aaron Lun

## See Also

[saveObject, VCF-method](#), to save VCF objects to disk.

## Examples

```
f1 <- system.file("extdata", "structural.vcf", package="VariantAnnotation")
vcf <- readVcf(f1)

tmp <- tempfile()
saveObject(vcf, tmp)
readObject(tmp)
```

---

saveObject, VCF-method    *Save a VCF object to disk*

---

### Description

Save a [VCF](#) object to its on-disk representation, namely a VCF file with the same contents.

### Usage

```
## S4 method for signature 'VCF'
saveObject(x, path, ...)
```

### Arguments

|      |   |
|------|---|
| x    | Any instance of a <a href="#">VCF</a> class or one of its subclasses. |
| path | String containing the path to a directory in which to save x.         |
| ...  | Further arguments to pass to specific methods.                        |

### Value

x is saved to file inside path, and NULL is returned.

### Author(s)

Aaron Lun

### See Also

[readVCF](#), to read a VCF object back to the R session.

### Examples

```
f1 <- system.file("extdata", "structural.vcf", package="VariantAnnotation")
vcf <- readVcf(f1)

tmp <- tempfile()
saveObject(vcf, tmp)
```

# Index

altReadObject, [2](#)

loadVCF (readVCF), [2](#)  
loadVCFHeader (readVCF), [2](#)

readObjectFile, [2](#)  
readVCF, [2](#), [3](#)

saveObject, [2](#)  
saveObject, VCF-method, [3](#)  
stageObject, VCF-method  
    (saveObject, VCF-method), [3](#)  
stageObject, VCFHeader-method  
    (saveObject, VCF-method), [3](#)

VCF, [2](#), [3](#)