

# Package ‘ChIPDBData’

May 21, 2026

**Title** ChIP-seq Target Databases for TFEA.ChIP

**Version** 1.3.0

**Description** Provides curated gene target databases derived from ChIP-seq datasets, formatted as ChIPDB objects for use with TFEA.ChIP.

**License** GPL-3

**Imports** ExperimentHub

**Suggests** knitr, rmarkdown, BiocStyle, AnnotationHub, TFEA.ChIP, DESeq2, testthat (>= 3.0.0)

**biocViews** ExperimentData, ExperimentHub, Homo\_sapiens\_Data, ENCODE, SequencingData

**VignetteEngine** knitr::rmarkdown

**VignetteBuilder** knitr

**URL** <https://github.com/yberda/ChIPDBData>

**BugReports** <https://github.com/yberda/ChIPDBData/issues>

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/ChIPDBData>

**git\_branch** devel

**git\_last\_commit** c6e5ccf

**git\_last\_commit\_date** 2026-04-28

**Repository** Bioconductor 3.24

**Date/Publication** 2026-05-21

**Author** Yosra Berrouayel [aut, cre] (ORCID:

<<https://orcid.org/0000-0002-0768-5933>>),

Luis del Peso [aut] (ORCID: <<https://orcid.org/0000-0003-4014-5688>>)

**Maintainer** Yosra Berrouayel <yosraberrouayel@gmail.com>

## Contents

ChIPDBData	2
getChIPDB	2

**Index****4**

ChIPDBData

*ChIPDBData: A package for curated ChIP-seq TF target databases***Description**

The ChIPDBData package provides curated ChIP-seq transcription factor target databases designed for use with TFEA.ChIP

**Package contents**

- Functions provided: getChIPDB (for loading the dataset)

**Author(s)**

**Maintainer:** Yosra Berrouayel <yosraberrouayel@gmail.com> ([ORCID](#))

**Authors:**

- Luis del Peso <lpeso@iib.uam.es> ([ORCID](#))

**See Also**

Useful links:

- <https://github.com/yberda/ChIPDBData>
- Report bugs at <https://github.com/yberda/ChIPDBData/issues>

getChIPDB

*Retrieve ChIPDB dataset from ExperimentHub***Description**

This function fetches ChIPDB objects (lists of transcription factor–target gene associations) for use with the TFEA.ChIP package. Available datasets include ENCODE, CREDB, and GeneHancer-derived collections.

**Usage**

```
getChIPDB(
  name = c("ENCODE_rE2G", "ENCODE_rE2G_25score", "ENCODE_rE2G_50score",
    "ENCODE_rE2G_75score", "ENCODE_rE2G_50depth", "ENCODE_rE2G_100depth",
    "ENCODE_rE2G_200depth", "ENCODE_rE2G_300depth", "CREdb", "GeneHancer")
)
```

**Arguments**

**name** A character string naming the dataset to retrieve. Options: "ENCODE\_rE2G", "ENCODE\_rE2G\_25score", "ENCODE\_rE2G\_50score", "ENCODE\_rE2G\_75score", "ENCODE\_rE2G\_50depth", "ENCODE\_rE2G\_100depth", "ENCODE\_rE2G\_200depth", "ENCODE\_rE2G\_300depth", "CREdb", "GeneHancer".

**Value**

A list object of class `ChIPDB` containing transcription factor–target gene mappings.

**Examples**

```
ChIPDB <- getChIPDB("ENCODE_rE2G_300depth")
```

# Index

\* **internal**

ChIPDBData, [2](#)

ChIPDBData, [2](#)

ChIPDBData-package (ChIPDBData), [2](#)

getChIPDB, [2](#)