

# Package ‘MOSClip’

July 1, 2025

**Title** Multi Omics Survival Clip

**Version** 1.3.2

**Depends** R (>= 4.4.0)

**Description** Topological pathway analysis tool able to integrate multi-omics data. It finds survival-associated modules or significant modules for two-class analysis. This tool have two main methods: pathway tests and module tests. The latter method allows the user to dig inside the pathways itself.

**License** AGPL-3

**Imports** MultiAssayExperiment, methods, survminer, graph, graphite, AnnotationDbi, checkmate, ggplot2, gridExtra, igraph, pheatmap, survival, RColorBrewer, SuperExactTest, reshape, NbClust, S4Vectors, grDevices, graphics, stats, utils, ComplexHeatmap, FactoMineR, circlize, corpcor, coxrobust, elasticnet, gRbase, ggplotify, qgraph, org.Hs.eg.db, Matrix

**Suggests** RUnit, BiocGenerics, MASS, BiocStyle, knitr, EDASeq, rmarkdown, kableExtra, testthat (>= 3.0.0)

**Encoding** UTF-8

**LazyData** false

**biocViews** Software, StatisticalMethod, GraphAndNetwork, Survival, Regression, DimensionReduction, Pathways, Reactome

**BugReports** <https://github.com/CaluraLab/MOSClip/issues>

**URL** <https://github.com/CaluraLab/MOSClip/>

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/MOSClip>

**git\_branch** devel

**git\_last\_commit** d29262d

**git\_last\_commit\_date** 2025-05-19

**Repository** Bioconductor 3.22

**Date/Publication** 2025-06-30

**Author** Paolo Martini [aut, cre] (ORCID: <https://orcid.org/0000-0002-0146-1031>),  
 Anna Bortolato [aut] (ORCID: <https://orcid.org/0009-0009-9327-6084>),  
 Anna Tanada [aut] (ORCID: <https://orcid.org/0000-0003-3224-0538>),  
 Enrica Calura [aut] (ORCID: <https://orcid.org/0000-0001-8463-2432>),  
 Stefania Pirrotta [aut] (ORCID: <https://orcid.org/0009-0004-0030-217X>),  
 Federico Agostinis [aut]

**Maintainer** Paolo Martini <paolo.martini@unibs.it>

## Contents

|                                               |    |
|-----------------------------------------------|----|
| annotatePathwayToFather . . . . .             | 3  |
| availableOmicMethods . . . . .                | 5  |
| checkOrder . . . . .                          | 5  |
| compPCs . . . . .                             | 6  |
| computeFreqs . . . . .                        | 7  |
| computeOmicsIntersections . . . . .           | 7  |
| computePCs . . . . .                          | 8  |
| convertPathway . . . . .                      | 9  |
| createCoxObj . . . . .                        | 10 |
| createDataModule . . . . .                    | 10 |
| createMOMView . . . . .                       | 11 |
| downloadPathwayRelationFromReactome . . . . . | 11 |
| estimateExprCov . . . . .                     | 12 |
| extractCliquesFromDag . . . . .               | 12 |
| extractSummaryFromBinary . . . . .            | 13 |
| extractSummaryFromCluster . . . . .           | 13 |
| extractSummaryFromNumberOfEvents . . . . .    | 14 |
| extractSummaryFromPCA . . . . .               | 15 |
| getPathFathers . . . . .                      | 16 |
| glmTest . . . . .                             | 16 |
| guessInvolvement . . . . .                    | 17 |
| guessInvolvementPathway . . . . .             | 18 |
| id2name . . . . .                             | 18 |
| makeOmics . . . . .                           | 19 |
| makePositiveDefinite . . . . .                | 20 |
| mapPathwaysIDfromGraphite . . . . .           | 21 |
| minOrNA . . . . .                             | 21 |
| MOSClip . . . . .                             | 22 |
| multiOmics . . . . .                          | 23 |
| MultiOmicsModules-class . . . . .             | 24 |
| MultiOmicsPathway-class . . . . .             | 24 |
| multiOmicsSurvivalModuleTest . . . . .        | 25 |
| multiOmicsSurvivalPathwayTest . . . . .       | 26 |
| multiOmicsTopo . . . . .                      | 27 |
| multiOmicsTwoClassModuleTest . . . . .        | 27 |
| multiOmicsTwoClassPathwayTest . . . . .       | 29 |
| multiPathwayModuleReport . . . . .            | 30 |
| multiPathwayReport . . . . .                  | 31 |
| Omics-class . . . . .                         | 31 |

|                                                |           |
|------------------------------------------------|-----------|
| ovarianDataset . . . . .                       | 32        |
| plotFrequencies . . . . .                      | 33        |
| plotModuleHeat . . . . .                       | 34        |
| plotModuleInGraph . . . . .                    | 35        |
| plotModuleKM . . . . .                         | 36        |
| plotModuleReport . . . . .                     | 38        |
| plotMultiPathwayReport . . . . .               | 39        |
| plotPathwayHeat . . . . .                      | 40        |
| plotPathwayKM . . . . .                        | 42        |
| pvalueSummary . . . . .                        | 43        |
| reactSmall . . . . .                           | 44        |
| removeSelfLoops . . . . .                      | 44        |
| resamplingModulesSurvival . . . . .            | 45        |
| resamplingModulesTwoClass . . . . .            | 46        |
| runSupertest . . . . .                         | 47        |
| selectStablePathwaysModules . . . . .          | 49        |
| showModule . . . . .                           | 50        |
| showMOSpalette . . . . .                       | 50        |
| showOmics . . . . .                            | 51        |
| showPathway . . . . .                          | 51        |
| sparseCompPCs . . . . .                        | 52        |
| stripModulesFromPathways . . . . .             | 53        |
| summarizeInCluster . . . . .                   | 53        |
| summarizeOmicsResByMinPvalue . . . . .         | 54        |
| summarizeToBinaryDirectionalEvents . . . . .   | 55        |
| summarizeToBinaryEvents . . . . .              | 56        |
| summarizeToNumberOfDirectionalEvents . . . . . | 57        |
| summarizeToNumberOfEvents . . . . .            | 58        |
| summarizeWithPca . . . . .                     | 59        |
| survivalcox . . . . .                          | 60        |
| survivalcoxr . . . . .                         | 60        |
| topoCompPCs . . . . .                          | 61        |
| <b>Index</b>                                   | <b>62</b> |

---

annotatePathwayToFather *Find Pathway Fathers*

---

## Description

Given the hierarchy of the pathways, this formula finds the fathers of the respective pathway (e.g. pathway: 'PI3K Cascade'; father: 'Signaling Pathways'). This function is necessary for calculating the contribution of different omics to survival prediction in different biological processes, grouping the pathways by hierarchy.

## Usage

```
annotatePathwayToFather(pathways, graphiteDB, hierarchy)
```



---

|                      |                                                |
|----------------------|------------------------------------------------|
| availableOmicMethods | <i>Get available Omics Summarizing Methods</i> |
|----------------------|------------------------------------------------|

---

**Description**

Gives a vector of the available methods to summarize omics.

**Usage**

```
availableOmicMethods()
```

**Value**

character vector with the implemented methods.

**Examples**

```
availableOmicMethods()
```

---

|            |                                                                           |
|------------|---------------------------------------------------------------------------|
| checkOrder | <i>Check if all the list object have the same order of pathway module</i> |
|------------|---------------------------------------------------------------------------|

---

**Description**

For internal use only

For internal use only

For internal use only

For internal use only

For internal use only

Prepare subset of patients for permutations

**Usage**

```
checkOrder(li)
```

```
resolveAndOrder(li)
```

```
mergeCol(li, col = "PC1", resolve = FALSE)
```

```
filterExpr(exp, samples)
```

```
filterMultiOmicsForSamples(M0, samples)
```

```
preparePerms(fullMultiOmics, nperm = 100, nPatients = 3)
```

**Arguments**

|                |                                             |
|----------------|---------------------------------------------|
| li             | a list of summaries                         |
| col            | the column to merge                         |
| resolve        | weather to resolve the issues               |
| exp            | a matrix                                    |
| samples        | the vector of samples to select             |
| MO             | a multiOmic object                          |
| fullMultiOmics | a multiOmic object                          |
| nperm          | number of permutations                      |
| nPatients      | number of patients to remove for resampling |

**Value**

a matrix  
 a filtered matrix  
 a filtered MultiOmics objects  
 list of sampled patients for each permutation

---

 compPCs

*Regular PCA*


---

**Description**

Regular PCA

**Usage**

```
compPCs(exp, shrink, k)
```

**Arguments**

|        |                                    |
|--------|------------------------------------|
| exp    | a matrix                           |
| shrink | logical, whether to shrink or not. |
| k      | the number of components to use    |

**Value**

a list with the following elements:

|          |                                            |
|----------|--------------------------------------------|
| x        | the computed PCs                           |
| sdev     | the standard deviation captured by the PCs |
| loadings | the loadings                               |

---

`computeFreqs`*Compute Frequencies in a Named List*

---

**Description**

Compute frequencies in a named list. This function is necessary for [plotFrequencies](#), in which it will calculate the frequency of each pathway father for every omics intersection.

**Usage**

```
computeFreqs(elementsIntersections)
```

**Arguments**

```
elementsIntersections  
  a named list
```

**Value**

a data.frame of the frequencies

**Examples**

```
omicsIntersection <- list(  
  "exp;met" = c("PathwayA", "PathwayB", "PathwayC"),  
  "exp;mut" = c("PathwayA", "PathwayC"),  
  "cnv;mut" = c("PathwayB")  
)  
freqDf <- computeFreqs(omicsIntersection)
```

---

`computeOmicsIntersections`*Compute Omics Intersections*

---

**Description**

Finds the modules that have any intersection among the available omics

**Usage**

```
computeOmicsIntersections(  
  multiPathwayReportData,  
  pvalueThr = 0.05,  
  zscoreThr = 0.05,  
  resamplingThr = NULL,  
  excludeColumns = NULL  
)
```

**Arguments**

**multiPathwayReportData** data.frame, the output of the [multiPathwayReport](#) or [multiPathwayModuleReport](#) functions.

**pvalueThr** numeric value. Overall pvalue cut-off to be used

**zscoreThr** numeric value. Covariates coefficient cut-off to be used.

**resampligThr** numeric value. Filters the modules according to the number of success in the resampling procedure, takes only the modules above this threshold.

**excludeColumns** a vector of characters listing the columns of multiPathwayReportData object to be excluded by the analysis. In the case multiPathwayReportData derives from [multiPathwayModuleReport](#) you should set excludeColumns = c('pathway', 'module').

**Value**

a list of pathway modules present for every intersection of omics present

**Examples**

```
df <- data.frame(
  pvalue = c(0.06, 0.04, 0.04, 0.03, 0.02),
  cnv = c(0.07, 0.03, 0.02, 0.04, 0.01),
  mut = c(0.08, 0.02, 0.01, 0.04, 0.04),
  row.names = c(
    "PathwayA", "PathwayB", "PathwayC",
    "PathwayD", "PathwayE"
  )
)

omicsClasses2Pathways <- computeOmicsIntersections(df,
  pvalueThr = 0.1,
  zscoreThr = 0.1
)
```

---

computePCs

*compute PCs.*


---

**Description**

For internal use only. Performs Principal Component analysis.

**Usage**

```
computePCs(
  exp,
  shrink = FALSE,
  method = c("regular", "topological", "sparse"),
  cliques = NULL,
  maxPCs = 3
)
```

**Arguments**

|         |                                                      |
|---------|------------------------------------------------------|
| exp     | a matrix                                             |
| shrink  | logical, whether to shrink or not.                   |
| method  | one of 'regular', 'topological' and 'sparse'         |
| cliques | the pathway topology summarized in a list of cliques |
| maxPCs  | the maximum number of PCs to consider                |

**Details**

Three methods are implemented:

- regular: a regular PCA ('prcomp')
- topological: PCA using a pathway topology.
- sparse: sparse PCA analysis implemented by 'elasticnet'

**Value**

a list with the following elements:

|          |                                            |
|----------|--------------------------------------------|
| x        | the computed PCs                           |
| sdev     | the standard deviation captured by the PCs |
| loadings | the loadings                               |

---

|                |                                              |
|----------------|----------------------------------------------|
| convertPathway | <i>A generic function to convert pathway</i> |
|----------------|----------------------------------------------|

---

**Description**

A generic function to convert pathway

**Usage**

```
convertPathway(graph, useTheseGenes)
```

**Arguments**

|               |                          |
|---------------|--------------------------|
| graph         | a graphNEL object        |
| useTheseGenes | list of genes to be used |

**Value**

NULL. No value is returned

---

|              |                          |
|--------------|--------------------------|
| createCoxObj | <i>Create Cox Object</i> |
|--------------|--------------------------|

---

**Description**

Create the coxObj from the covariates used in the test

**Usage**

```
createCoxObj(colData, moView)
```

**Arguments**

|         |                                                                            |
|---------|----------------------------------------------------------------------------|
| colData | colData from multiOmic object                                              |
| moView  | modulesView or pathView from multiOmicsModules or multiOmicsPathway object |

**Value**

data.frame, samples in the rows, covariates in the columns

---

|                  |                           |
|------------------|---------------------------|
| createDataModule | <i>Create Data Module</i> |
|------------------|---------------------------|

---

**Description**

Extract sub-matrix for the genes of a module or pathway from data matrix of a specific omic

**Usage**

```
createDataModule(omic, multiOmicObj)
```

**Arguments**

|              |                                |
|--------------|--------------------------------|
| omic         | modulesView or pathView object |
| multiOmicObj | object of class 'Omics'        |

**Value**

matrix, genes in the rows, samples in the columns

---

|               |                                                           |
|---------------|-----------------------------------------------------------|
| createMOMView | Create the list of covariates that are going to be tested |
|---------------|-----------------------------------------------------------|

---

**Description**

Create the list of covariates that are going to be tested

**Usage**

```
createMOMView(omicsObj, genes)
```

**Arguments**

|          |                     |
|----------|---------------------|
| omicsObj | Omics class object  |
| genes    | genes of the clique |

**Value**

list with 1 reduced representation of the omics 2 sdev 3 loadings or eigenvector 4 usedGenes 5 method 6 namesCov 7 omicName

---

|                                     |                                     |
|-------------------------------------|-------------------------------------|
| downloadPathwayRelationFromReactome | Download Reactome Pathway Relations |
|-------------------------------------|-------------------------------------|

---

**Description**

Download Pathway Relations from Reactome. The file is retrieved from the [url](#)

**Usage**

```
downloadPathwayRelationFromReactome(url = NULL, speciesAbbr = "HSA")
```

**Arguments**

|             |                                                                                 |
|-------------|---------------------------------------------------------------------------------|
| url         | the location of the file. Can be local. If NULL pick the package reactome file. |
| speciesAbbr | species acronym                                                                 |

**Value**

A data frame with 2 columns:

|        |                                                |
|--------|------------------------------------------------|
| parent | The Reactome pathway ID of the parent pathway. |
| child  | The Reactome pathway ID of the child pathway.  |

**Examples**

```
downloadPathwayRelationFromReactome()
```

---

|                 |                                          |
|-----------------|------------------------------------------|
| estimateExprCov | <i>Estimate Single Covariance Matrix</i> |
|-----------------|------------------------------------------|

---

**Description**

For internal use only. Estimate Covariance from one matrix

**Usage**

```
estimateExprCov(expr, shrink)
```

**Arguments**

|        |                                     |
|--------|-------------------------------------|
| expr   | a numeric matrix                    |
| shrink | logical wheter to shrink the matrix |

**Value**

a covariance matrix

---

|                       |                                    |
|-----------------------|------------------------------------|
| extractCliquesFromDag | <i>Extract the maximal cliques</i> |
|-----------------------|------------------------------------|

---

**Description**

For internal use only. Extract the cliques.

For internal use only. Force Moralization

**Usage**

```
extractCliquesFromDag(dag, root = NULL)

mmmoralize(graph)
```

**Arguments**

|       |                          |
|-------|--------------------------|
| dag   | a Directed Aciclic Graph |
| root  | a node to use as root    |
| graph | a graphNEL object        |

**Value**

list of nodes cliques

---

extractSummaryFromBinary

*Extract Summary Binary from MultiOmics Objects*


---

### Description

Given an omic summarized by 'summarizeToBinaryEvents' extract the most important features.

### Usage

```
extractSummaryFromBinary(omic, multiOmicObj, n = 3)
```

### Arguments

|              |                                        |
|--------------|----------------------------------------|
| omic         | a summarized omic                      |
| multiOmicObj | Omics object                           |
| n            | maximum number of features to retrieve |

### Value

Meant for internal use only. The summary for omic summarized using binary events.

|                |                                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------|
| sigModule      | the original data for significant features                                                           |
| discrete       | the discrete version of the significant covariates converted (when needed) into the discrete version |
| subset         | data.frame(row.names=names(topGenes), cov=sum binary events)                                         |
| covsConsidered | the name of the considered omic                                                                      |

---

extractSummaryFromCluster

*Extract Summary Cluster from MultiOmics Objects*


---

### Description

Given an omic summarized by 'summarizeInCluster' extract the most important features.

### Usage

```
extractSummaryFromCluster(omic, multiOmicObj, n = 3)
```

### Arguments

|              |                                        |
|--------------|----------------------------------------|
| omic         | a summarized omic                      |
| multiOmicObj | Omics object                           |
| n            | maximum number of features to retrieve |

**Value**

|                |                                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------|
|                | summary for omic summarized using clusters                                                           |
| sigModule      | the original data for significant features                                                           |
| discrete       | the discrete version of the significant covariates converted (when needed) into the discrete version |
| subset         | data.frame(row.names=names(topGenes), metClust=topGenes)                                             |
| pvalues        | Kruskal Wallis pvalues of the selected features                                                      |
| covsConsidered | the name of the considered omic                                                                      |

---

extractSummaryFromNumberOfEvents

*Extract Summary Binary from MultiOmics Objects*

---

**Description**

Given an omic summarized by 'summarizeToNumberOfEvents' extract the most important features.

**Usage**

```
extractSummaryFromNumberOfEvents(
  omic,
  multiOmicObj,
  moduleCox,
  analysis,
  n = 3,
  minprop = 0.1,
  labels = c("few", "many")
)
```

**Arguments**

|              |                                        |
|--------------|----------------------------------------|
| omic         | a summarized omic                      |
| multiOmicObj | Omics object                           |
| moduleCox    | the coxObj of the interesting module   |
| analysis     | two-class or survival type             |
| n            | maximum number of features to retrieve |
| minprop      | the minimal proportion of cutp         |
| labels       | the category labels                    |

**Value**

Meant for internal use only. The summary for omic summarized using counting of events.

|                |                                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------|
| sigModule      | the original data for significant features                                                           |
| discrete       | the discrete version of the significant covariates converted (when needed) into the discrete version |
| subset         | data.frame(row.names=names(topGenes), covariates=covariate)                                          |
| covsConsidered | the name of the considered omic                                                                      |

---

extractSummaryFromPCA *Extract Summary PCA from MultiOmics Objects*

---

## Description

Given an omic summarized by 'summarizeWithPca' extract the most important features.

## Usage

```
extractSummaryFromPCA(  
  omic,  
  multiOmicObj,  
  moduleCox,  
  analysis,  
  loadThr = 0.6,  
  atleast = 1,  
  minprop = 0.1  
)
```

## Arguments

|              |                                                                             |
|--------------|-----------------------------------------------------------------------------|
| omic         | a summarized omic                                                           |
| multiOmicObj | Omics object                                                                |
| moduleCox    | the coxObj of the interesting module                                        |
| analysis     | two-class or survival type                                                  |
| loadThr      | the thr value to select the most influent features according to the loading |
| atleast      | the minimum number of gene to retrieve                                      |
| minprop      | the minimal proportion of cutp                                              |

## Value

|                                       |                                                                                                      |
|---------------------------------------|------------------------------------------------------------------------------------------------------|
| summary for omic summarized using pca |                                                                                                      |
| sigModule                             | the original data for significant features                                                           |
| discrete                              | the discrete version of the significant covariates converted (when needed) into the discrete version |
| subset                                | data.frame(row.names=names(topGenes), covariate)                                                     |
| covsConsidered                        | the name of the considered omic                                                                      |

---

|                |                                     |
|----------------|-------------------------------------|
| getPathFathers | <i>Retrieves pathways relatives</i> |
|----------------|-------------------------------------|

---

**Description**

For internal use only. Retrieves relatives given a pathway id.

**Usage**

```
getPathFathers(pathway, hierarchyGraph, ord = 3, plot = FALSE)
```

**Arguments**

|                |                                      |
|----------------|--------------------------------------|
| pathway        | a pathway id                         |
| hierarchyGraph | a igraph with pathway hierarchy      |
| ord            | how far you need to go backward      |
| plot           | plot relatives. For checking purpose |

**Details**

Pathway Hierarchy is needed as igraph object.

**Value**

a character vector with the relatives

---

|         |                              |
|---------|------------------------------|
| glmTest | <i>Two-classes glm test.</i> |
|---------|------------------------------|

---

**Description**

Two-classes glm test.

**Usage**

```
glmTest(data, fullModelFormula, nullModelFormula)
```

**Arguments**

|                  |                    |
|------------------|--------------------|
| data             | data               |
| fullModelFormula | complete model     |
| nullModelFormula | null model formula |

**Value**

Two-classes glm test results

---

|                  |                                                                                        |
|------------------|----------------------------------------------------------------------------------------|
| guessInvolvement | <i>Guess the most influent features from MultiOmics Survival or Two-class results.</i> |
|------------------|----------------------------------------------------------------------------------------|

---

## Description

Given a pathway analyzed by `multiOmicsModuleSurvivalTest` or `multiOmicsTwoClassModuleTest`, it retrieves for each omic the most influent features.

## Usage

```
guessInvolvement(
  pathway,
  moduleNumber,
  loadThr = 0.6,
  n = 3,
  atleast = 1,
  min_prop_pca = 0.1,
  min_prop_events = 0.1,
  ...
)
```

## Arguments

|                              |                                                                   |
|------------------------------|-------------------------------------------------------------------|
| <code>pathway</code>         | MultiOmicsModules object from a pathway                           |
| <code>moduleNumber</code>    | the module number                                                 |
| <code>loadThr</code>         | the loading threshold to select genes (PCA only)                  |
| <code>n</code>               | the maximum number of genes to retrieve (cluster and binary only) |
| <code>atleast</code>         | the minimum number of features to select (PCA only)               |
| <code>min_prop_pca</code>    | the minimal proportion to compute the PCA classes                 |
| <code>min_prop_events</code> | the minimal proportion to compute the event classes               |
| <code>...</code>             | additional arguments passed to get function                       |

## Value

a list. Each item of the list corresponds to an omic that is summarized with the specific 'extract-Summary' functions. Each item is the summary for an omic summarized using the setted method: pvalues are present only for cluster method.

---

guessInvolvementPathway

*Guess the most influent features from MultiOmics Survival or Two-class results.*

---

### Description

Given a pathway analyzed by `multiOmicsSurvivalPathwayTest` or `multiOmicsTwoClassPathwayTest`, it retrieves for each omic the most influent features.

### Usage

```
guessInvolvementPathway(
  pathway,
  loadThr = 0.6,
  n = 3,
  atleast = 1,
  min_prop_pca = 0.1,
  min_prop_events = 0.1,
  ...
)
```

### Arguments

|                              |                                                                   |
|------------------------------|-------------------------------------------------------------------|
| <code>pathway</code>         | <code>MultiOmicsModules</code> object from a pathway              |
| <code>loadThr</code>         | the loading threshold to select genes (PCA only)                  |
| <code>n</code>               | the maximum number of genes to retrieve (cluster and binary only) |
| <code>atleast</code>         | the minimum number of features to select (PCA only)               |
| <code>min_prop_pca</code>    | the minimal proportion to compute the PCA classes                 |
| <code>min_prop_events</code> | the minimal proportion to compute the event classes               |
| <code>...</code>             | additional arguments passed to get function                       |

### Value

a list. Each item of the list corresponds to an omic that is summarized with the specific 'extract-Summary' functions. Each item is the summary for an omic summarized using the setted method: pvalues are present only for cluster method.

---

id2name

*Convert id to pathway name*

---

### Description

For internal use only. Retrieves name from pathway id.

### Usage

```
id2name(idList, namedVect)
```

**Arguments**

|           |                      |
|-----------|----------------------|
| idList    | a list of pathway id |
| namedVect | a named vector       |

**Details**

You must provide a namedVect to be used as translator.

**Value**

a character vector with the names

---

|           |                                         |
|-----------|-----------------------------------------|
| makeOmics | <i>Omics class initializer function</i> |
|-----------|-----------------------------------------|

---

**Description**

makeOmics creates the Omics object necessary to perform most of the analyses of this package. It contains all the omics data in the format of a ExperimentList, the clinical data, and all the information necessary for the dimensionality reduction step.

**Usage**

```
makeOmics(
  experiments = ExperimentList(),
  colData = S4Vectors::DataFrame(),
  sampleMap = S4Vectors::DataFrame(assay = factor(), primary = character(), colname =
    character()),
  metadata = list(),
  drops = list(),
  modelInfo = character(),
  specificArgs = list()
)
```

**Arguments**

|              |                                                                                                 |
|--------------|-------------------------------------------------------------------------------------------------|
| experiments  | A list or <a href="#">ExperimentList</a> of all combined experiments                            |
| colData      | A <a href="#">DataFrame</a> or data.frame of characteristics for all biological units           |
| sampleMap    | A DataFrame or data.frame of assay names, sample identifiers, and colname samples               |
| metadata     | An optional argument of 'ANY' class (usually list) for content describing the experiments       |
| drops        | A list of unmatched information (included after subsetting)                                     |
| modelInfo    | A list with length equal to length(data) that are modelInfo to process each dataset             |
| specificArgs | a list with length equal to length(data) to set additional parameters specific of the modelInfo |

**Value**

an Omics class object

## Examples

```
data(ovarianDataset)

myColData <- data.frame(
  status = sample(c(0, 1), 50, replace = TRUE),
  days = sample(c(0, 500), 50, replace = TRUE),
  row.names = colnames(ovarianDataset$exp)
)

myOmicsObj <- makeOmics(
  experiments = ovarianDataset,
  colData = myColData,
  modelInfo = c(
    "summarizeWithPca",
    "summarizeInCluster",
    "summarizeToNumberOfEvents",
    "summarizeToNumberOfDirectionalEvents"
  ),
  specificArgs = list(
    pcaArgs = list(
      name = "exp", shrink = "FALSE",
      method = "sparse", maxPCs = 3
    ),
    clusterArgs = list(
      name = "met",
      max_cluster_number = 3
    ),
    countEvent = list(name = "mut", min_prop = 0.05),
    cnvAgv = list(name = "cnv", min_prop = 0.05)
  )
)
```

---

makePositiveDefinite    *Make positive and definite covariance matrix*

---

## Description

Make positive and definite covariance matrix

## Usage

```
makePositiveDefinite(m1, m2 = NULL, m3 = NULL, threshold = 0.1)
```

## Arguments

|           |                         |
|-----------|-------------------------|
| m1        | matrix 1                |
| m2        | matrix 2                |
| m3        | matrix 3                |
| threshold | threshold of difference |

**Value**

list with

|            |                                     |
|------------|-------------------------------------|
| m1         | the matrix m1 positive and definite |
| m2         | the matrix m2 positive and definite |
| m3         | the matrix m3 positive and definite |
| correction | the magneturde of the correction    |
| value      | the value                           |

---

mapPathwaysIDfromGraphite
*Map Pathways ID from Graphite***Description**

For internal use only. Retrieve pathway id and names from Pathways object.

**Usage**

mapPathwaysIDfromGraphite(pathways, pathwayNames = NULL)

**Arguments**

|              |                                             |
|--------------|---------------------------------------------|
| pathways     | a PathwayList object                        |
| pathwayNames | in not NULL, a subset of pathway to extract |

**Value**

a data frame, id and pathway name

---

minOrNA
*Minimum or NA***Description**

For internal use only. Get back minimum or NA.

**Usage**

minOrNA(x)

**Arguments**

|   |           |
|---|-----------|
| x | a numeric |
|---|-----------|

**Value**

a numeric. The minimum or NA

## Examples

```
# minOrNA(c(1,5,0.1,NA))
# minOrNA(c(NA,NA,NA))
```

---

MOSClip

MOSClip: Multi-Omics Survival Clip

---

## Description

MOSClip R package implements a statistical approach able to integrate multi-omic data and look for survival associated gene modules. It integrates multiple omics - transcriptomics, methylomics, genomic mutations, and genomic copy number variations - using various data dimensionality reduction strategies and multivariate models. Exploiting graph theory, pathways can be decomposed into their connected components, that we call modules. The analysis can then be performed at the level of entire pathways or pathway modules. MOSClip pathway analysis serves two primary purposes: testing the survival association of pathways or modules using the Cox proportional hazard model, and conducting a two-class analysis with a generalized linear model. Additionally, the package offers valuable graphical tools to visualize and interpret the results.

## Details

To conduct a multi-omic survival analysis on pathways or modules use:

- [multiOmicsSurvivalPathwayTest](#)
- [multiOmicsSurvivalModuleTest](#)

To perform a two-class comparison enrichment analysis on pathways or modules use:

- [multiOmicsTwoClassPathwayTest](#)
- [multiOmicsTwoClassModuleTest](#)

## Author(s)

**Maintainer:** Paolo Martini <paolo.martini@unibs.it> ([ORCID](#))

**Authors:**

- Anna Bortolato <anna.bortolato@unipd.it> ([ORCID](#))
- Anna Tanada <annacarolinaemi.delimatanada@phd.unipd.it> ([ORCID](#))
- Enrica Calura <enrica.calura@unipd.it> ([ORCID](#))
- Stefania Pirrotta <stefania.pirrotta@phd.unipd.it> ([ORCID](#))
- Federico Agostinis <federico.agostinis@outlook.com>

## References

Paolo Martini, Monica Chiogna, Enrica Calura, and Chiara Romualdi. 2019. “MOSClip: Multi-Omic and Survival Pathway Analysis for the Identification of Survival Associated Gene and Modules.” *Nucleic Acids Research* 47 (14): e80. <https://doi.org/10.1093/nar/gkz324>

**See Also**

Useful links:

- <https://github.com/CaluraLab/MOSClip/>
- Report bugs at <https://github.com/CaluraLab/MOSClip/issues>

---

multiOmics

*Omics class object with TCGA ovarian data*


---

**Description**

An Omics class object containing data from TCGA ovarian cancer. The TCGA data was manually selected and preprocessed. It contains 4 omics: expression, methylation, mutation, and copy number variation. Additionally, it contains specific arguments to perform the dimensionality reduction. The datasets were downloaded from TCGA using TCGABiolink R package, selecting only patients with primary solid tumors. Expression matrix was processed first, converting gene identifiers into Entrez IDs. The profiles of genes present more than once were averaged. Genes with at least 100 counts in at least one patients were selected, to avoid data sparsity. Mutation matrix was filtered, keeping only genes with expression data available. We chose to consider only missense and non-sense mutations and mutation impact was also considered following Mutect2 pipeline. CNV values were transformed into numeric values. Methylation data were processed with Methyl Mix R package. Patients that had both normal and primary tumors samples were selected. With the help of a dictionary array probes were connected to CpG clusters, and finally CpG clusters were mapped to genes (Entrez ID). Survival annotation curated by Liu et al. (2018) was used to extract PFS information. Only patients with matched data across the four omics were considered. After the selection of patients and genes, we performed expression normalization and log2 of the counts+1 transformation. This will ensure us to work with expression data approximately close to a normal distribution, the most suitable distribution for the subsequent MOSClip tests. Genes and samples were manually selected to create this small example dataset for demonstration purposes.

**Usage**

```
data('multiOmics')
```

**Format**

multiOmics:

An Omics with 4 omics:

**exp** Matrix with 151 rows and 50 columns of RNA expression values

**met** A matrix with 178 rows and 50 columns of methylation data with probes clustered

**mut** A matrix with 107 rows and 50 columns of mutation counts

**cnv** A matrix with matrix with 145 rows and 50 columns of copy number ...

---

MultiOmicsModules-class

*Multi Omics Modules.*


---

### Description

This class organizes the results of the Multi Omics Module Test analysis, in which corresponds to one pathway decomposed into modules.

### Usage

```
## S4 method for signature 'MultiOmicsModules'
showModule(object)
```

### Arguments

object                    an object of class MultiOmicsModules

### Methods (by generic)

- showModule(MultiOmicsModules): shows module info

### Slots

alphas   a numeric vector of the pvalues of all the modules.

zlists   a list of numeric vectors with the zs of the covariates for each module.

modulesView   a list of module information: for each omic, the name of the omic, the genes used, the method, the name of the covariates analyzed and other specific information based on the omic.

modules   a list with the genes that belong to the module.

title   the name of the pathway.

analysis   the type of analysis done: survival or two-class.

---

MultiOmicsPathway-class

*Multi Omics Pathway.*


---

### Description

This class organize the results of the Multi-Omics Pathway Survival Test analysis.

### Usage

```
## S4 method for signature 'MultiOmicsPathway'
showPathway(object)
```

### Arguments

object                    an object of class MultiOmicsPathway

**Methods (by generic)**

- `showPathway(MultiOmicsPathway)`: shows module info

**Slots**

`pvalue` a numeric vector of the pvalues of the pathways.  
`zlist` a numeric vector with the zs of all the covariates.  
`pathView` a list of pathway information: for each omic, the name of the omic, the genes used, the method, the name of the covariates analyzed and other specific information based on the omic.  
`title` the name of the pathway.  
`analysis` the type of analysis done: survival or two-class.

---

`multiOmicsSurvivalModuleTest`

*Compute Multi Omics Survival in Pathway Modules*

---

**Description**

Performs survival analysis using an Omics object. The pathway (graph) used is decomposed in modules (cliques) using graph theory.

**Usage**

```
multiOmicsSurvivalModuleTest(
  omicsObj,
  graph,
  survFormula = "Surv(days, status) ~",
  autoCompleteFormula = TRUE,
  useTheseGenes = NULL,
  pathName = NULL,
  robust = FALSE,
  include_from_annot = FALSE
)
```

**Arguments**

|                                  |                                                                                      |
|----------------------------------|--------------------------------------------------------------------------------------|
| <code>omicsObj</code>            | Object of class Omics                                                                |
| <code>graph</code>               | a pathway in graphNEL, Pathway or geneset format                                     |
| <code>survFormula</code>         | a character with the formula to compute survival                                     |
| <code>autoCompleteFormula</code> | logical. If TRUE autocomplete the survFormula using all the available covariates     |
| <code>useTheseGenes</code>       | vector of genes used to filter pathways                                              |
| <code>pathName</code>            | title of the pathway. If NULL and graph is Pathway, graph@title is used as title     |
| <code>robust</code>              | logical, whether the robust mode should be used for cox model analysis               |
| <code>include_from_annot</code>  | logical. If TRUE compute cox model analysis using additional covariates from colData |

**Value**

MultiOmicsModules object

**Examples**

```
data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

MOM_survival <- multiOmicsSurvivalModuleTest(multiOmics, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)
```

---

multiOmicsSurvivalPathwayTest

*Compute Multi Omics Survival in Pathways*

---

**Description**

Performs topological survival analysis using an Omics object.

**Usage**

```
multiOmicsSurvivalPathwayTest(
  omicsObj,
  graph,
  survFormula = "Surv(days, status) ~",
  autoCompleteFormula = TRUE,
  useTheseGenes = NULL,
  pathName = NULL,
  robust = FALSE,
  include_from_annot = FALSE
)
```

**Arguments**

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| omicsObj            | Object of class Omics                                                                |
| graph               | a pathway in graphNEL, Pathway or geneset format                                     |
| survFormula         | a character with the formula to compute survival                                     |
| autoCompleteFormula | logical. If TRUE autocomplete the survFormula using all the available covariates     |
| useTheseGenes       | vector of genes used to filter pathways                                              |
| pathName            | title of the pathway. If NULL and graph is Pathway, graph@title is used as title     |
| robust              | logical, whether the robust mode should be used for cox model analysis               |
| include_from_annot  | logical. If TRUE compute cox model analysis using additional covariates from colData |

**Value**

MultiOmicsPathway object

**Examples**

```
data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

MOP_survival <- multiOmicsSurvivalPathwayTest(multiOmics, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)
```

---

multiOmicsTopo

*Omics class object with TCGA ovarian data for topological analysis*

---

**Description**

An Omics class object containing data from TCGA ovarian cancer. The data are the same as in [multiOmics](#) object. Arguments in specificArgs slot have been set to efficiently run a topological pathway analysis, i.e., the topological method is used for PCA and shrink parameter is set to TRUE. This method can't be used for analyses on modules.

**Usage**

```
data('multiOmicsTopo')
```

**Format**

multiOmicsTopo:

An Omics with 4 omics:

**exp** Matrix with 151 rows and 50 columns of RNA expression values

**met** A matrix with 178 rows and 50 columns of methylation data with probes clustered

**mut** A matrix with 107 rows and 50 columns of mutation counts

**cnv** A matrix with matrix with 145 rows and 50 columns of copy number ...

---

multiOmicsTwoClassModuleTest

*Computes Multi Omics Two-Class in Pathway Modules*

---

**Description**

Performs topological two-class analysis using an Omics object. It decomposes graphs (pathways) into modules.

**Usage**

```
multiOmicsTwoClassModuleTest(
  omicsObj,
  graph,
  classAnnot,
  baseFormula = "classes ~",
  autoCompleteFormula = TRUE,
  useTheseGenes = NULL,
  nullModel = "classes ~ 1",
  pathName = NULL
)
```

**Arguments**

|                     |                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| omicsObj            | object of class Omics                                                                                                                            |
| graph               | a pathway as a graphNEL object.                                                                                                                  |
| classAnnot          | a data.frame with the class annotation. It is necessary at least a column with the classes labels, and the row.names as the samples labels       |
| baseFormula         | model formula to be used for the test. It should be written as 'classes ~ ', while 'classes' being the column name for the class labels          |
| autoCompleteFormula | a logical value. If TRUE. It autocompletes the formula used to fit generalized linear models function using all the available covariates (omics) |
| useTheseGenes       | (optional) vector of specific genes to be used                                                                                                   |
| nullModel           | the null model formula. It should be written the same as the baseFormula, followed by ' 1'. (e.g. 'classes ~ 1')                                 |
| pathName            | (optional) title of the pathway. If NULL, graph@title is used as title                                                                           |

**Value**

MultiOmicsModule object

**Examples**

```
data("multiOmics")
data("reactSmall")

genesToUse <- row.names(multiOmics[[1]])

classAnnot <- data.frame(
  "treatment" = c(rep("A", 25), rep("B", 25)),
  row.names = colnames(multiOmics[[1]])
)

MOM_twoclasses <- multiOmicsTwoClassModuleTest(
  multiOmics, reactSmall[[1]], classAnnot,
  baseFormula = "treatment ~ ", nullModel = "treatment ~ 1",
  useTheseGenes = genesToUse
)
```

---

multiOmicsTwoClassPathwayTest

*Compute Multi Omics Two-Class in Pathways*


---

## Description

Performs topological two-class analysis using an Omics object.

## Usage

```
multiOmicsTwoClassPathwayTest(
  omicsObj,
  graph,
  classAnnot,
  baseFormula = "classes ~ ",
  autoCompleteFormula = TRUE,
  useTheseGenes = NULL,
  nullModel = "classes ~ 1",
  pathName = NULL
)
```

## Arguments

|                     |                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| omicsObj            | object of class Omics                                                                                                                            |
| graph               | a pathway as a graphNEL object.                                                                                                                  |
| classAnnot          | a data.frame with the class annotation. It is necessary at least a column with the classes labels, and the row.names as the samples labels       |
| baseFormula         | model formula to be used for the test. It should be written as 'classes ~ ', while 'classes' being the column name for the class labels          |
| autoCompleteFormula | a logical value. If TRUE. It autocompletes the formula used to fit generalized linear models function using all the available covariates (omics) |
| useTheseGenes       | (optional) vector of specific genes to be used                                                                                                   |
| nullModel           | the null model formula. It should be written the same as the baseFormula, followed by ' 1'. (e.g. 'classes ~ 1')                                 |
| pathName            | (optional) title of the pathway. If NULL, graph@title is used as title                                                                           |

## Value

MultiOmicsPathway object

## Examples

```
data("multiOmics")
data("reactSmall")

genesToUse <- row.names(multiOmics[[1]])

classAnnot <- data.frame(
  "treatment" = c(rep("A", 25), rep("B", 25)),
```

```

    row.names = colnames(multiOmics[[1]])
  )

MOP_twoClasses <- multiOmicsTwoClassPathwayTest(
  multiOmics, reactSmall[[1]], classAnnot,
  baseFormula = "treatment ~ ", nullModel = "treatment ~ 1",
  useTheseGenes = genesToUse
)

```

---

multiPathwayModuleReport

*Provides a Table of the Modules Test Results*

---

### Description

Summarizes the results of a multi omics module test given a list of MultiOmicsModules objects

### Usage

```
multiPathwayModuleReport(multiPathwayModuleList, priority_to = NULL)
```

### Arguments

|                        |                                                                                                  |
|------------------------|--------------------------------------------------------------------------------------------------|
| multiPathwayModuleList | a list of MultiOmicsModules objects resulting from a multi-omics module test.                    |
| priority_to            | a vector with the covariates (the omics names) that should appear first in the dataframe columns |

### Value

a dataframe class object. Rows correspond to the modules, and the columns to the overall and covariates pvalues of the test.

### Examples

```

data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

MOM_list <- lapply(reactSmall[1:2], function(g) {
  fcl <- multiOmicsSurvivalModuleTest(multiOmics, g,
    survFormula = "Surv(days, status) ~",
    autoCompleteFormula = TRUE,
    useTheseGenes = genesToUse
  )
  fcl
})

moduleSummary <- multiPathwayModuleReport(MOM_list)

```

---

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| multiPathwayReport | <i>Summarize pathways' info from a list of MultiOmicsPathway objects (MOP)</i> |
|--------------------|--------------------------------------------------------------------------------|

---

### Description

Given the list of MOPs, it creates the table.

### Usage

```
multiPathwayReport(multiPathwayList, priority_to = NULL)
```

### Arguments

|                  |                                                                                |
|------------------|--------------------------------------------------------------------------------|
| multiPathwayList | a list of MultiOmicsPathway objects resulting from a multi-omics pathway test. |
| priority_to      | a vector with the covariates (omic name) that should go first.                 |

### Value

a data.frame, pathways in rows, overall pvalue of the coxph, followed by covariates pvalues, in columns.

### Examples

```
data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

MOP_list <- lapply(reactSmall, function(g) {
  fcl <- multiOmicsSurvivalPathwayTest(multiOmics, g,
    survFormula = "Surv(days, status) ~",
    autoCompleteFormula = TRUE,
    useTheseGenes = genesToUse
  )
  fcl
})

pathwaysSummary <- multiPathwayReport(MOP_list)
```

---

|             |               |
|-------------|---------------|
| Omics-class | <i>Omics.</i> |
|-------------|---------------|

---

### Description

This class is the storage for the different omic datasets that we need to analyze. It is based on MultiAssayExperiment.

**Usage**

```
## S4 method for signature 'Omics'
showOmics(object)
```

**Arguments**

**object**                      an object of class Omics

**Methods (by generic)**

- `showOmics(Omics)`: shows model parameters

**Slots**

**modelInfo** a list with length equal to `length(data)` that are `modelInfo` to process each dataset.

**specificArgs** a list with length equal to `length(data)` to set additional parameters specific of the `modelInfo`.

---

ovarianDataset

*ExperimentList class object with TCGA ovarian data*


---

**Description**

An `ExperimentList` class object containing data from TCGA ovarian cancer. The TCGA data was manually selected and preprocessed. It contains 4 omics: expression, methylation, mutation, and copy number variation.

**Usage**

```
data('ovarianDataset')
```

**Format**

**ExperimentList:**

An `ExperimentList` with 4 omics:

**exp** Matrix with 101 rows and 50 columns of RNA expression values

**met** A matrix with 97 rows and 50 columns of methylation data with probes clustered

**mut** A matrix with 55 rows and 50 columns of mutation counts

**cnv** A matrix with matrix with 101 rows and 50 columns of copy number ...

---

plotFrequencies

*Plot Frequencies of Pathway Fathers for Omics intersection*


---

### Description

Plots the frequencies of the pathway fathers by every omics intersection from a data.frame of the frequencies returned with the function [computeFreqs](#).

### Usage

```
plotFrequencies(
  frequencies,
  manualColors = NULL,
  minSize = 4,
  maxSize = 20,
  width = 20,
  relMagnificationOfLegend = 0.5,
  lineSize = 1
)
```

### Arguments

|                          |                                                                         |
|--------------------------|-------------------------------------------------------------------------|
| frequencies              | a data.frame created from 'computeFreqs'                                |
| manualColors             | optional vector of colors to be used                                    |
| minSize                  | the minimal font size. Maximal frequencies will be added for each class |
| maxSize                  | the maximal font size dimension, all values above are clipped           |
| width                    | the number of character to wrap the labels                              |
| relMagnificationOfLegend | the relative magnification of the text of the legend                    |
| lineSize                 | the thickness of the lines                                              |

### Value

a circular plot of the frequencies of pathway fathers

### Examples

```
df <- data.frame(
  category = c("PathwayA", "PathwayB", "PathwayC", "PathwayD"),
  frequencies = c(1, 2, 1, 3),
  class = rep("Mut", 4), stringsAsFactors = FALSE
)
plotFrequencies(df)
```

---

|                |                                            |
|----------------|--------------------------------------------|
| plotModuleHeat | <i>Plot a Heatmap of a Module by Omics</i> |
|----------------|--------------------------------------------|

---

## Description

It creates a heatmap of the most involved genes of each omic of a specific module from a `MultiOmicsModule` object.

## Usage

```
plotModuleHeat(
  moduleobj,
  moduleNumber,
  sortBy = NULL,
  paletteNames = NULL,
  additionalAnnotations = NULL,
  additionalPaletteNames = NULL,
  withSampleNames = TRUE,
  fontsize_row = 10,
  fontsize_col = 1,
  nrowsHeatmaps = 3,
  orgDbi = "org.Hs.eg.db",
  discr_prop_pca = 0.15,
  discr_prop_events = 0.05,
  ...
)
```

## Arguments

|                                     |                                                                              |
|-------------------------------------|------------------------------------------------------------------------------|
| <code>moduleobj</code>              | <code>MultiOmicsModule</code> class object                                   |
| <code>moduleNumber</code>           | module number of interest                                                    |
| <code>sortBy</code>                 | a covariate (omic) to sort by                                                |
| <code>paletteNames</code>           | a palette containing three colors                                            |
| <code>additionalAnnotations</code>  | optional additional sample annotations                                       |
| <code>additionalPaletteNames</code> | optional additional colors for annotations                                   |
| <code>withSampleNames</code>        | show sample names                                                            |
| <code>fontsize_row</code>           | font size for row labels                                                     |
| <code>fontsize_col</code>           | font size for column labels                                                  |
| <code>nrowsHeatmaps</code>          | magnification respect to annotation of sample (annotations take 1 row)       |
| <code>orgDbi</code>                 | a <code>Dbi</code> organism to be used. Default is <code>org.Hs.eg.db</code> |
| <code>discr_prop_pca</code>         | the minimal proportion to compute the PCA classes                            |
| <code>discr_prop_events</code>      | the minimal proportion to compute the event classes                          |
| <code>...</code>                    | additional arguments passed to <code>guessInvolvement</code> function        |

**Value**

A heatmap of a pathway module (results of the module test)

**Examples**

```
data(multiOmics)
data(reactSmall)

survAnnot <- data.frame(
  status = multiOmics$status,
  days = multiOmics$days,
  row.names = colnames(multiOmics[[1]])
)

genesToUse <- row.names(multiOmics[[1]])

MOM_survival <- multiOmicsSurvivalModuleTest(multiOmics, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)

plotModuleHeat(MOM_survival, 1,
  sortBy = c("mut", "expPC1", "status", "days"),
  additionalAnnotations = survAnnot,
  additionalPaletteNames = list(status = "teal", days = "violet"),
  withSampleNames = F
)
```

---

plotModuleInGraph

---

*Plot a Directed Graph of the MultiOmicsModules Object*


---

**Description**

From a MultiOmicsModules object, it plots the position of a given module in the pathway. The omics are also represented in the graph.

**Usage**

```
plotModuleInGraph(
  modulesobj,
  pathList,
  moduleNumber,
  orgDbi = "org.Hs.eg.db",
  paletteNames = NULL,
  legendLabels = NULL,
  fileName = NULL,
  discr_prop_pca = 0.15,
  discr_prop_events = 0.05,
  pathTitle = NULL,
  ...
)
```

**Arguments**

|                   |                                                                           |
|-------------------|---------------------------------------------------------------------------|
| modulesobj        | a MultiOmicsModule class object                                           |
| pathList          | a PathwayList from graphite package that contains the pathways to be used |
| moduleNumber      | a module number                                                           |
| orgDbi            | if needed, indicates an organism Dbi to translate the vectors             |
| paletteNames      | named vector of MOSpalettes, names replace makeLegend arguments           |
| legendLabels      | set up your favourite names for the omics                                 |
| fileName          | optional filenames to save the plot                                       |
| discr_prop_pca    | the minimal proportion to compute the PCA classes                         |
| discr_prop_events | the minimal proportion to compute the event classes                       |
| pathTitle         | title of the graph, to be searched in pathList                            |
| ...               | additional arguments passed to guessInvolvement function                  |

**Value**

a MOSClip plot in form of a list class object

**Examples**

```
data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

MOM_survival <- multiOmicsSurvivalModuleTest(multiOmics, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)

plotModuleInGraph(MOM_survival, reactSmall,
  moduleNumber = 1,
  paletteNames = c(exp = "red", met = "green",
    mut = "blue", cnv = "yellow")
)
```

---

plotModuleKM

---

*Plot Kaplan-Meier survival curves of a specific module*


---

**Description**

Given a MultiOmicsModule class object and a specific module number, it plots Kaplan-Meier curves, in which the strata corresponds to the omics

**Usage**

```
plotModuleKM(
  MOM,
  moduleNumber,
  formula = "Surv(days, status) ~ PC1",
  fileName = NULL,
  paletteNames = NULL,
  h = 9,
  w = 7,
  risk.table = TRUE,
  pval = TRUE,
  size = 1,
  inYears = FALSE,
  discr_prop_pca = 0.15,
  discr_prop_events = 0.05,
  additional_discrete = NULL,
  additional_continuous = NULL,
  ...
)
```

**Arguments**

|                       |                                                                                                                                                                                       |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MOM                   | a MultiOmicsModule class object                                                                                                                                                       |
| moduleNumber          | numeric value. The module number of interest                                                                                                                                          |
| formula               | a formula for the survival analysis. It should be written as 'Surv(days, status) ~ omic'. To plot more than one omic, write them separated by a '+' character after the separator (~) |
| fileName              | optional filenames to save the plot                                                                                                                                                   |
| paletteNames          | a palette name to be used                                                                                                                                                             |
| h                     | the height of the plot                                                                                                                                                                |
| w                     | the width of the plot                                                                                                                                                                 |
| risk.table            | logical value. If TRUE, shows the risk.table. Default is TRUE.                                                                                                                        |
| pval                  | logical value. If TRUE, shows the p-value of the curves. Default is TRUE.                                                                                                             |
| size                  | line width of the KM curves                                                                                                                                                           |
| inYears               | set time in years                                                                                                                                                                     |
| discr_prop_pca        | the minimal proportion to compute the PCA classes                                                                                                                                     |
| discr_prop_events     | the minimal proportion to compute the event classes                                                                                                                                   |
| additional_discrete   | names of the additional discrete variables to include                                                                                                                                 |
| additional_continuous | names of the additional continuous variables to include                                                                                                                               |
| ...                   | additional arguments passed to guessInvolvement and get function                                                                                                                      |

**Value**

a ggsurvplot class object

**Examples**

```

data(multiOmic)
data(reactSmall)

genesToUse <- row.names(multiOmic[[1]])

MOM_survival <- multiOmicSurvivalModuleTest(multiOmic, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)

plotModuleKM(MOM_survival, 1,
  formula = "Surv(days, status) ~ mut + expPC2",
  paletteNames = "Paired", inYears = TRUE
)

```

---

|                  |                                                        |
|------------------|--------------------------------------------------------|
| plotModuleReport | <i>Plot a table of a MultiOmicModules (MOM) object</i> |
|------------------|--------------------------------------------------------|

---

**Description**

Given a MultiOmicModules object, it plots its results in a tabular fashion

**Usage**

```

plotModuleReport(
  modulesObj,
  MOcolors = NULL,
  priority_to = NULL,
  fontsize = 12,
  ...
)

```

**Arguments**

|             |                                                                                                                |
|-------------|----------------------------------------------------------------------------------------------------------------|
| modulesObj  | MultiOmicModules class object                                                                                  |
| MOcolors    | character vector with the omic colors. The colors should be among the colors in <a href="#">showMOSpalette</a> |
| priority_to | a vector with the covariates (omic names) that should go first                                                 |
| fontsize    | Size of the font to be used in the plot                                                                        |
| ...         | additional argument to be passed to pheatmap                                                                   |

**Value**

a Heatmap list object from ComplexHeatmap package of the results contained in the MultiOmicModules object provided

**Examples**

```

data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

MOM_survival <- multiOmicsSurvivalModuleTest(multiOmics, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)

plotModuleReport(MOM_survival,
  MOcolors = c(
    exp = "red", met = "green", mut = "blue",
    cnv = "yellow"
  )
)

```

---

plotMultiPathwayReport

*Summarize and plot pathways' info from a list of MultiOmicsPathway (MOP)*

---

**Description**

Given the list of MOPs, it plots a table of its results.

**Usage**

```

plotMultiPathwayReport(
  multiPathwayList,
  top = 25,
  MOcolors = NULL,
  priority_to = NULL,
  fontsize = 6,
  ...
)

```

**Arguments**

|                  |                                                                                                                |
|------------------|----------------------------------------------------------------------------------------------------------------|
| multiPathwayList | a list of MultiOmicsPathway class objects                                                                      |
| top              | numeric value. Plot only the top number of pathways                                                            |
| MOcolors         | character vector with the omic colors. The colors should be among the colors in <a href="#">showMOSpalette</a> |
| priority_to      | a vector with the covariates (omic names) that should go first                                                 |
| fontsize         | the font size to be used. Default is 12.                                                                       |
| ...              | additional argument to be passed to pheatmap                                                                   |

**Value**

a Heatmap list object from ComplexHeatmap package of the results contained in the `MultiOmicsPathway` object provided

**Examples**

```
data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

MOP_list <- lapply(reactSmall, function(g) {
  fc1 <- multiOmicsSurvivalPathwayTest(multiOmics, g,
    survFormula = "Surv(days, status) ~",
    autoCompleteFormula = TRUE,
    useTheseGenes = genesToUse
  )
  fc1
})

plotMultiPathwayReport(MOP_list,
  MOcolors = c(
    exp = "red", met = "green", mut = "blue",
    cnv = "yellow"
  ),
  fontsize = 12
)
```

---

plotPathwayHeat

*Plot heatmaps of the pathway by omics*


---

**Description**

Given the pathway, it creates the heatmaps of the mostly involved genes for each omic.

**Usage**

```
plotPathwayHeat(
  pathway,
  sortBy = NULL,
  paletteNames = NULL,
  additionalAnnotations = NULL,
  additionalPaletteNames = NULL,
  discr_prop_pca = 0.15,
  discr_prop_events = 0.05,
  withSampleNames = TRUE,
  nrowsHeatmaps = 3,
  orgDbi = "org.Hs.eg.db",
  ...
)
```

**Arguments**

|                        |                                                                                                        |
|------------------------|--------------------------------------------------------------------------------------------------------|
| pathway                | MultiOmicsPathway class object                                                                         |
| sortBy                 | one or more covariates to sort the samples                                                             |
| paletteNames           | name of the colors for each omic                                                                       |
| additionalAnnotations  | optional additional sample annotations (e.g. survival annotation)                                      |
| additionalPaletteNames | colors for additional annotations. The colors available are the ones in <a href="#">showMOSpalette</a> |
| discr_prop_pca         | the minimal proportion to compute the PCA classes                                                      |
| discr_prop_events      | the minimal proportion to compute the event classes                                                    |
| withSampleNames        | show the sample names in the plot                                                                      |
| nrowsHeatmaps          | magnification respect to annotation of sample (annotations take 1 row)                                 |
| orgDbi                 | a DbI organism to be used. Default is org.Hs.eg.db                                                     |
| ...                    | additional arguments passed to guessInvolvementPathway function (internal use)                         |

**Value**

An object of class ggplot plotted with ComplexHeatMap package.

**Examples**

```
data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

survAnnot <- data.frame(
  status = multiOmics$status,
  days = multiOmics$days,
  row.names = colnames(multiOmics[[1]])
)

# Creating the MultiOmicsPathway object
MOP_survival <- multiOmicsSurvivalPathwayTest(multiOmics, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)

# Plotting
plotPathwayHeat(MOP_survival,
  sortBy = c("expPC2", "mut", "status", "days"),
  paletteNames = c(exp = "red", met = "green",
    mut = "blue", cnv = "yellow"),
  additionalAnnotations = survAnnot,
  additionalPaletteNames = list(status = "teal", days = "violet"),
  nrowsHeatmaps = 2, withSampleNames = F
)
```

---

|               |                                                                |
|---------------|----------------------------------------------------------------|
| plotPathwayKM | <i>Plot Kaplan-Meier survival curves of a specific pathway</i> |
|---------------|----------------------------------------------------------------|

---

### Description

Given a MultiOmicsPathway class object, it plots Kaplan-Meier curves, in which the strata corresponds to the chosen omics

### Usage

```
plotPathwayKM(
  pathway,
  formula = "Surv(days, status) ~ PC1",
  fileName = NULL,
  paletteNames = NULL,
  h = 9,
  w = 7,
  risk.table = TRUE,
  pval = TRUE,
  size = 1,
  inYears = FALSE,
  discr_prop_pca = 0.15,
  discr_prop_events = 0.05,
  additional_discrete = NULL,
  additional_continuous = NULL,
  ...
)
```

### Arguments

|                       |                                                                                        |
|-----------------------|----------------------------------------------------------------------------------------|
| pathway               | MultiOmicsPathway class object                                                         |
| formula               | a formula to compute the plot                                                          |
| fileName              | optional filenames to save the plot                                                    |
| paletteNames          | a palette containing three colors                                                      |
| h                     | the height of the plot                                                                 |
| w                     | the width of the plot                                                                  |
| risk.table            | logical value. If TRUE, shows the risk.table. Default is TRUE.                         |
| pval                  | logical value. Shows p-value of the curves                                             |
| size                  | line width of the KM curves                                                            |
| inYears               | logical value. If TRUE, converts days to years                                         |
| discr_prop_pca        | the minimal proportion to compute the PCA classes                                      |
| discr_prop_events     | the minimal proportion to compute the event classes                                    |
| additional_discrete   | names of the additional discrete variables to include                                  |
| additional_continuous | names of the additional continuous variables to include                                |
| ...                   | additional arguments passed to guessInvolvementPathway and get function (internal use) |

**Value**

a ggsurvplot class object

**Examples**

```
data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

# Creating the MultiOmicsPathway object
MOP_survival <- multiOmicsSurvivalPathwayTest(multiOmics, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)

plotPathwayKM(MOP_survival,
  formula = "Surv(days, status) ~ mut + expPC2",
  paletteNames = "Paired", inYears = TRUE
)
```

---

|               |                               |
|---------------|-------------------------------|
| pvalueSummary | <i>Compute pvalue Summary</i> |
|---------------|-------------------------------|

---

**Description**

Compute pvalue Summary

**Usage**

```
pvalueSummary(multiPathwayReportData, excludeColumns = NULL, as.list = FALSE)
```

**Arguments**

|                        |                                                                                                                                                                                                                                                              |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| multiPathwayReportData | data.frame, the output of the <a href="#">multiPathwayReport</a> or <a href="#">multiPathwayModuleReport</a> functions.                                                                                                                                      |
| excludeColumns         | a vector of characters listing the columns of multiPathwayReportData object to be excluded by the analysis. In the case multiPathwayReportData derives from <a href="#">multiPathwayModuleReport</a> you should set excludeColumns = c('pathway', 'module'). |
| as.list                | return a list rather than a data.frame                                                                                                                                                                                                                       |

**Value**

a list

---

|            |                                              |
|------------|----------------------------------------------|
| reactSmall | <i>PathwayList of pathways from Reactome</i> |
|------------|----------------------------------------------|

---

### Description

A PathwayList with three pathways necessary for the analysis: 'Activation of Matrix Metalloproteinases', 'FGFR1 mutant receptor activation', and 'VEGFA-VEGFR2 Pathway'. Pathways were downloaded using graphite package and the names of the nodes were converted into Entrez IDs.

### Usage

```
data('reactSmall')
```

### Format

```
reactSmall:
A PathwayList with Reactome pathways for hsapiens
entries Three Reactome pathways with their nodes
```

---

|                 |                                          |
|-----------------|------------------------------------------|
| removeSelfLoops | <i>Remove self loops from a graphNEL</i> |
|-----------------|------------------------------------------|

---

### Description

Remove the self loops that are present in the graph graphNEL object

### Usage

```
removeSelfLoops(graph)
```

### Arguments

```
graph          a graphNEL object
```

### Value

```
a graphNEL object
#' @rdname graph-processing
```

---

`resamplingModulesSurvival`*Resampling function for survival analysis on modules*

---

## Description

Resampling function for survival analysis on modules

Resampling function for pathways (survival analysis)

## Usage

```
resamplingModulesSurvival(  
  fullMultiOmics,  
  pathdb,  
  nperm = 100,  
  pathwaySubset = NULL,  
  nPatients = 3,  
  genesToConsider = NULL  
)
```

```
resamplingPathwaySurvival(  
  fullMultiOmics,  
  pathdb,  
  nperm = 100,  
  pathwaySubset = NULL,  
  nPatients = 3,  
  genesToConsider = NULL  
)
```

## Arguments

|                              |                                                                                                                        |
|------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <code>fullMultiOmics</code>  | a multiOmic object                                                                                                     |
| <code>pathdb</code>          | pathway database                                                                                                       |
| <code>nperm</code>           | number of permutations                                                                                                 |
| <code>pathwaySubset</code>   | a list of pathways to resample                                                                                         |
| <code>nPatients</code>       | number of patients to remove for resampling                                                                            |
| <code>genesToConsider</code> | vector of genes used to filter pathways; if NULL, genes found in the first experiment of the multiOmic object are used |

## Value

list of the resampling tables of results

list of the resampling tables of results

**Examples**

```

data(multiOmics)
data(reactSmall)

perms <- resamplingModulesSurvival(
  fullMultiOmics = multiOmics, reactSmall,
  nperm = 10,
  pathwaySubset =
    "FGFR1 mutant receptor activation"
)

```

---

resamplingModulesTwoClass

*Resampling function for two-class analysis on modules*


---

**Description**

Resampling function for two-class analysis on modules

Resampling function for pathways (two-class analysis)

**Usage**

```

resamplingModulesTwoClass(
  fullMultiOmics,
  classAnnot,
  pathdb,
  nperm = 100,
  pathwaySubset = NULL,
  nPatients = 3,
  genesToConsider = NULL
)

resamplingPathwayTwoClass(
  fullMultiOmics,
  classAnnot,
  pathdb,
  nperm = 100,
  pathwaySubset = NULL,
  nPatients = 3,
  genesToConsider = NULL
)

```

**Arguments**

|                |                                |
|----------------|--------------------------------|
| fullMultiOmics | a multiOmic object             |
| classAnnot     | patients class annotations     |
| pathdb         | pathway database               |
| nperm          | number of permutations         |
| pathwaySubset  | a list of pathways to resample |

nPatients            number of patients to remove for resampling  
genesToConsider        vector of genes used to filter pathways; if NULL, genes found in the first experiment of the multiOmic object are used

### Value

list of the resampling tables of results  
list of the resampling tables of results

### Examples

```
data(multiOmics)
data(reactSmall)

classAnnot <- data.frame(
  "treatment" = c(rep("A", 25), rep("B", 25)),
  row.names = colnames(multiOmics[[1]])
)

perms <- resamplingModulesTwoClass(
  fullMultiOmics = multiOmics,
  classAnnot, reactSmall,
  nperm = 10,
  pathwaySubset =
    "FGFR1 mutant receptor activation"
)
```

---

|              |                                                               |
|--------------|---------------------------------------------------------------|
| runSupertest | <i>Performs a Exact test - analysis of omics intersection</i> |
|--------------|---------------------------------------------------------------|

---

### Description

This function performs a exact test implementing a theoretical framework using the SuperExactTest package. It calculates the statistical distributions of multi omics set intersections. It can be used with both a MultiOmicsModules or MultiOmicsPathway class objects.

### Usage

```
runSupertest(
  multiPathwayReportData,
  pvalueThr = 0.05,
  zscoreThr = 0.05,
  resampligThr = NULL,
  plot = c("circular", "landscape", "noplot"),
  sort.by = c("set", "size", "degree", "p-value"),
  excludeColumns = NULL,
  color.on = "#f6bb42",
  color.off = "#D3D3D3"
)
```

## Arguments

|                                     |                                                                                                                                                                                                                                                                                                   |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>multiPathwayReportData</code> | data.frame, the output of the <code>multiPathwayReport</code> or <code>multiPathwayModuleReport</code> functions.                                                                                                                                                                                 |
| <code>pvalueThr</code>              | numeric value. Overall pvalue cut-off to be used                                                                                                                                                                                                                                                  |
| <code>zscoreThr</code>              | numeric value. Covariates coefficient cut-off to be used.                                                                                                                                                                                                                                         |
| <code>resampligThr</code>           | numeric value. Filters the modules according to the number of success in the resampling procedure, takes only the modules above this threshold.                                                                                                                                                   |
| <code>plot</code>                   | character indicating the layout for plotting. It is one of <code>circular</code> , <code>landscape</code> or <code>noplot</code> . By default, <code>plot='circular'</code> , if <code>plot='noplot'</code> no plot will be provided.                                                             |
| <code>sort.by</code>                | character indicating how to sort the intersections in the plot. It is one of <code>'set'</code> (by omics), <code>'size'</code> (by intersection size), <code>'degree'</code> (by number of intersected omics), and <code>'p-value'</code> .                                                      |
| <code>excludeColumns</code>         | a vector of characters listing the columns of <code>multiPathwayReportData</code> object to be excluded by the analysis. In the case <code>multiPathwayReportData</code> derives from <code>multiPathwayModuleReport</code> you should set <code>excludeColumns = c('pathway', 'module')</code> . |
| <code>color.on</code>               | color that represent the active omics in the sector                                                                                                                                                                                                                                               |
| <code>color.off</code>              | color that represent the omics mnot considered in the sector                                                                                                                                                                                                                                      |

## Details

This function calculates intersection sizes between multiple set of pathways or modules and performs statistical test of the intersections using the total amount of analyzed pathways or modules as background. The super exact test of this function was described in Wang et al 2015.

## Value

a data.frame containing all the numeric information of the plot included the pathways shared by different omics.

## References

Minghui Wang, Yongzhong Zhao, and Bin Zhang (2015). Efficient Test and Visualization of Multi-Set Intersections. Scientific Reports 5: 16923.

## Examples

```
df <- data.frame(
  pvalue = c(0.06, 0.04, 0.04, 0.03, 0.02),
  cnv = c(0.07, 0.03, 0.02, 0.04, 0.01),
  mut = c(0.08, 0.02, 0.01, 0.04, 0.04),
  row.names = c(
    "PathwayA", "PathwayB", "PathwayC",
    "PathwayD", "PathwayE"
  )
)

runSupertest(df, pvalueThr = 0.05, zscoreThr = 0.05)
```

---

selectStablePathwaysModules

*Select stable pathway modules*


---

### Description

Select stable pathway modules

Count the resampling success

Add resampling counts to module summary

### Usage

```
selectStablePathwaysModules(perms, moduleSummary, success = 90, col = "pvalue")
```

```
getPathwaysModulesSuccess(perms, moduleSummary, col = "pvalue", thr = 0.05)
```

```
addResamplingCounts(moduleSummary, resamplingCounts)
```

### Arguments

|                  |                                                                                             |
|------------------|---------------------------------------------------------------------------------------------|
| perms            | a list. Result of resampling function                                                       |
| moduleSummary    | summary of modules or pathways obtained from multiPathwayModuleReport or multiPathwayReport |
| success          | number of success to consider the pathway or module stable                                  |
| col              | the name of the column in the summary to be used to evaluate resampling success             |
| thr              | the threshold for significance                                                              |
| resamplingCounts | the counts of success obtained with getPathwaysModulesSuccess                               |

### Value

the subset of stable modules

the counts of success for each pathway or module

a module or pathway summary with resampling counts column appended

### Examples

```
data("multiOmics")
data("reactSmall")

perms <- resamplingPathwaySurvival(multiOmics, reactSmall, nperm = 5)
res <- lapply(reactSmall, function(g) {
  multiOmicsSurvivalPathwayTest(multiOmics, g,
    useTheseGenes = row.names(multiOmics[[1]])
  )
})
pathSummary <- multiPathwayReport(res)
getPathwaysModulesSuccess(perms, pathSummary)
```

---

|            |                                                         |
|------------|---------------------------------------------------------|
| showModule | <i>A generic function showing pathway's module info</i> |
|------------|---------------------------------------------------------|

---

**Description**

A generic function showing pathway's module info

**Usage**

```
showModule(object)
```

**Arguments**

object                    an object of class MultiOmicsModules

**Value**

NULL. No value is returned

**Examples**

```
data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

MOM_survival <- multiOmicsSurvivalModuleTest(multiOmics, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)

showModule(MOM_survival)
```

---

|                |                                   |
|----------------|-----------------------------------|
| showMOSpalette | <i>Shows the MOSClip palette.</i> |
|----------------|-----------------------------------|

---

**Description**

This function shows the MOSClip palette. Each omic should be coupled to a color panel, this match will be preserved in plots.

**Usage**

```
showMOSpalette()
```

**Value**

NULL. No value is returned

**Examples**

```
showMOSpalette()
```

---

```
showOmics
```

*A generic functions showing parameter associated with each omics*

---

**Description**

A generic functions showing parameter associated with each omics

**Usage**

```
showOmics(object)
```

**Arguments**

object            an object of class Omics

**Value**

NULL. No value is returned

**Examples**

```
data(multiOmics)
```

```
showOmics(multiOmics)
```

---

```
showPathway
```

*A generic function showing pathway info*

---

**Description**

A generic function showing pathway info

**Usage**

```
showPathway(object)
```

**Arguments**

object            an object of class MultiOmicsPathway

**Value**

NULL. No value is returned

**Examples**

```

data(multiOmics)
data(reactSmall)

genesToUse <- row.names(multiOmics[[1]])

MOP_survival <- multiOmicsSurvivalPathwayTest(multiOmics, reactSmall[[1]],
  survFormula = "Surv(days, status) ~", autoCompleteFormula = TRUE,
  useTheseGenes = genesToUse
)

showPathway(MOP_survival)

```

---

sparseCompPCs

*Sparse PCA*


---

**Description**

Sparse PCA

**Usage**

```
sparseCompPCs(exp, shrink, k)
```

**Arguments**

|        |                                    |
|--------|------------------------------------|
| exp    | a matrix                           |
| shrink | logical, whether to shrink or not. |
| k      | the number of components to use    |

**Value**

a list with the following elements:

|          |                                            |
|----------|--------------------------------------------|
| x        | the computed PCs                           |
| sdev     | the standard deviation captured by the PCs |
| loadings | the loadings                               |

---

`stripModulesFromPathways`*Remove Module Number From Pathway Name*

---

**Description**

Function to remove the suffix corresponding to the module number of the pathway name. Necessary step for [annotatePathwayToFather](#) and [plotFrequencies](#)

**Usage**

```
stripModulesFromPathways(pathways)
```

**Arguments**

`pathways`                vector of pathway names

**Value**

list of pathway names without the module number

**Examples**

```
pathwaysModules <- list(
  "Intrinsic Pathway for Apoptosis.1",
  "Intrinsic Pathway for Apoptosis.2",
  "Opioid Signalling.1", "Opioid Signalling.2"
)

resPathwayNames <- stripModulesFromPathways(pathwaysModules)
```

---

`summarizeInCluster`*Summarize Using Cluster Analysis*

---

**Description**

Given a matrix it summarize in classes

**Usage**

```
summarizeInCluster(
  data,
  features,
  name = "clu",
  dictionary = NULL,
  max_cluster_number = 3,
  cliques = NULL
)
```

**Arguments**

|                    |                                                              |
|--------------------|--------------------------------------------------------------|
| data               | a data matrix                                                |
| features           | a vector with the features to analyze                        |
| name               | prefix of the covariates                                     |
| dictionary         | translate features (genes) into sets (row.names of the data) |
| max_cluster_number | the maximum number of cluster to evaluate                    |
| cliques            | the features organized in cliques. Only use for topology     |

**Details**

The user can define a maximum of classes. The function guess the optimal number of clusters using NbClust methods.

**Value**

|                                  |                                                   |
|----------------------------------|---------------------------------------------------|
| a list with summary of the omic: |                                                   |
| x                                | summary of the omic for each sample               |
| usedGenes                        | genes list of genes used to calculate the summary |
| namesCov                         | names of the covariates                           |
| cls                              | the genes in clusters                             |
| method                           | method used for the analysis                      |
| omicName                         | name of the omic                                  |

---

summarizeOmicsResByMinPvalue

*Summarize Omics Covaraites By Min Pvalue*


---

**Description**

For internal use only. for each line extrac 'col' and get the minimum.

**Usage**

```
summarizeOmicsResByMinPvalue(col, mat)
```

**Arguments**

|     |                                                               |
|-----|---------------------------------------------------------------|
| col | columns to extract from the line                              |
| mat | the matrix to be summarized (were to extract lines and 'col') |

**Value**

a summarized version of the matrix.

**Examples**

```
# summarizeOmicsResByMinPvalue(2:3, mat=matrix(c(1,2,4,1,2,5), nrow=2))
```

---

`summarizeToBinaryDirectionalEvents`*Summarize To Binary Directional Events*

---

**Description**

Given a matrix it summarize the positive and negative to 0 or 1 in two vectors

**Usage**

```
summarizeToBinaryDirectionalEvents(  
  data,  
  features,  
  name = "dirBin",  
  binaryClassMin = 10,  
  eventThr = 2,  
  cliques = NULL  
)
```

**Arguments**

|                             |                                                          |
|-----------------------------|----------------------------------------------------------|
| <code>data</code>           | a data matrix                                            |
| <code>features</code>       | a vector with the features to analyze                    |
| <code>name</code>           | prefix of the covariates                                 |
| <code>binaryClassMin</code> | the minimum number of event to include the covariate     |
| <code>eventThr</code>       | the absolute value to threshold an event                 |
| <code>cliques</code>        | the features organized in cliques. Only use for topology |

**Value**

a list with summary of the omic:

|                        |                                                   |
|------------------------|---------------------------------------------------|
| <code>x</code>         | summary of the omic for each sample               |
| <code>usedGenes</code> | genes list of genes used to calculate the summary |
| <code>namesCov</code>  | names of the covariates                           |
| <code>method</code>    | method used for the analysis                      |
| <code>omicName</code>  | name of the omic                                  |
| <code>evenThr</code>   | threshold fot event counting                      |

---

`summarizeToBinaryEvents`*Summarize To Binary Events*

---

## Description

Given a matrix it summarize to a 0 or 1

## Usage

```
summarizeToBinaryEvents(  
  data,  
  features,  
  name = "bin",  
  binaryClassMin = 10,  
  cliques = NULL  
)
```

## Arguments

|                             |                                                          |
|-----------------------------|----------------------------------------------------------|
| <code>data</code>           | a data matrix                                            |
| <code>features</code>       | a vector with the features to analyze                    |
| <code>name</code>           | prefix of the covariates                                 |
| <code>binaryClassMin</code> | the minimum number of event to include the covariate     |
| <code>cliques</code>        | the features organized in cliques. Only use for topology |

## Value

a list with summary of the omic:

|                        |                                                   |
|------------------------|---------------------------------------------------|
| <code>x</code>         | summary of the omic for each sample               |
| <code>usedGenes</code> | genes list of genes used to calculate the summary |
| <code>namesCov</code>  | names of the covariates                           |
| <code>method</code>    | method used for the analysis                      |
| <code>omicName</code>  | name of the omic                                  |
| <code>evenThr</code>   | threshold fot event counting                      |

---

`summarizeToNumberOfDirectionalEvents`*Summarize With Directed Sum*

---

## Description

Given a matrix it summarize the positive and negative in two vectors, with counts of the events

## Usage

```
summarizeToNumberOfDirectionalEvents(  
  data,  
  features,  
  name = "dCount",  
  eventThr = 2,  
  min_prop = 0.1,  
  cliques = NULL  
)
```

## Arguments

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| <code>data</code>     | a data matrix                                            |
| <code>features</code> | a vector with the features to analyze                    |
| <code>name</code>     | prefix of the covariates                                 |
| <code>eventThr</code> | the absolute value to threshold an event                 |
| <code>min_prop</code> | minimal proportion in classes                            |
| <code>cliques</code>  | the features organized in cliques. Only use for topology |

## Value

a list with summary of the omic:

|                        |                                                                             |
|------------------------|-----------------------------------------------------------------------------|
| <code>x</code>         | summary of the omic for each sample                                         |
| <code>usedGenes</code> | genes list of genes used to calculate the summary                           |
| <code>namesCov</code>  | names of the covariates                                                     |
| <code>method</code>    | method used for the analysis                                                |
| <code>omicName</code>  | name of the omic                                                            |
| <code>evenThr</code>   | threshold fot event counting                                                |
| <code>min_prop</code>  | minimum proportion of samples to exclude to check the variability of values |

---

`summarizeToNumberOfEvents`*Summarize To Number of Binary Events*

---

## Description

Given a matrix it summarize to a 0 or 1

## Usage

```
summarizeToNumberOfEvents(  
  data,  
  features,  
  name = "event",  
  min_prop = 0.1,  
  cliques = NULL  
)
```

## Arguments

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| <code>data</code>     | a data matrix                                            |
| <code>features</code> | a vector with the features to analyze                    |
| <code>name</code>     | prefix of the covariates                                 |
| <code>min_prop</code> | minimal proportion in classes                            |
| <code>cliques</code>  | the features organized in cliques. Only use for topology |

## Value

a list with summary of the omic:

|                        |                                                                             |
|------------------------|-----------------------------------------------------------------------------|
| <code>x</code>         | summary of the omic for each sample                                         |
| <code>usedGenes</code> | genes list of genes used to calculate the summary                           |
| <code>namesCov</code>  | names of the covariates                                                     |
| <code>method</code>    | method used for the analysis                                                |
| <code>omicName</code>  | name of the omic                                                            |
| <code>evenThr</code>   | threshold fot event counting                                                |
| <code>min_prop</code>  | minimum proportion of samples to exclude to check the variability of values |

---

|                  |                            |
|------------------|----------------------------|
| summarizeWithPca | <i>Summarize Using PCA</i> |
|------------------|----------------------------|

---

## Description

Given a matrix it summarize to principal components. The user can specify the number of principal components. Default 3.

## Usage

```
summarizeWithPca(
  data,
  features,
  name = "pca",
  shrink = FALSE,
  method = "regular",
  cliques = NULL,
  maxPCs = 3,
  loadThr = 0.6
)
```

## Arguments

|          |                                                           |
|----------|-----------------------------------------------------------|
| data     | a data matrix                                             |
| features | a vector with the features to analyze                     |
| name     | prefix of the covariates                                  |
| shrink   | shrink or not the covariance matrix.                      |
| method   | either 'regular', 'sparse' or 'topological'               |
| cliques  | the features organized in cliques. Only use for topology. |
| maxPCs   | maximum number of pcs to consider                         |
| loadThr  | loading threshold                                         |

## Value

a list with summary of the omic:

|           |                                                            |
|-----------|------------------------------------------------------------|
| x         | summary of the omic for each sample (principal components) |
| sdev      | standard deviation of the principal components             |
| loadings  | loadings of PCA                                            |
| usedGenes | genes list of genes used to calculate the summary          |
| namesCov  | names of the covariates                                    |
| method    | method used for the analysis                               |
| omicName  | name of the omic                                           |

---

|             |                           |
|-------------|---------------------------|
| survivalcox | <i>Cox Model Analysis</i> |
|-------------|---------------------------|

---

**Description**

Cox Analysis

**Usage**

```
survivalcox(coxObj, formula)
```

**Arguments**

|         |                                   |
|---------|-----------------------------------|
| coxObj  | data.frame: patients x covariates |
| formula | formula to use                    |

**Details**

For internal use only

**Value**

A list with

|        |                                            |
|--------|--------------------------------------------|
| pvalue | pvalue of the model                        |
| zlist  | pvalues of single covariates               |
| coxObj | the original coxObj passed to the function |

---

|              |                                  |
|--------------|----------------------------------|
| survivalcoxr | <i>Cox Robust Model Analysis</i> |
|--------------|----------------------------------|

---

**Description**

Cox Robust Analysis

**Usage**

```
survivalcoxr(coxObj, formula)
```

```
coxrsummary(x)
```

**Arguments**

|         |                                   |
|---------|-----------------------------------|
| coxObj  | data.frame: patients x covariates |
| formula | formula to use                    |
| x       | a coxr.obj                        |

**Details**

For internal use only

**Value**

A list with

|        |                                                           |
|--------|-----------------------------------------------------------|
| pvalue | pvalue of the model                                       |
| zlist  | pvalues of single covariates                              |
| coxObj | the original coxObj passed to the function                |
|        | a list with wald test and robust and partial coefficients |

---

|             |                        |
|-------------|------------------------|
| topoCompPCs | <i>Topological PCA</i> |
|-------------|------------------------|

---

**Description**

Topological PCA

**Usage**

```
topoCompPCs(exp, shrink, cliques, k)
```

**Arguments**

|         |                                                      |
|---------|------------------------------------------------------|
| exp     | a matrix                                             |
| shrink  | logical, whether to shrink or not.                   |
| cliques | the pathway topology summarized in a list of cliques |
| k       | the number of components to use                      |

**Value**

a list with the following elements:

|          |                                            |
|----------|--------------------------------------------|
| x        | the computed PCs                           |
| sdev     | the standard deviation captured by the PCs |
| loadings | the loadings                               |

# Index

- \* **datasets**
  - multiOmics, [23](#)
  - multiOmicsTopo, [27](#)
  - ovarianDataset, [32](#)
  - reactSmall, [44](#)
- addResamplingCounts
  - (selectStablePathwaysModules), [49](#)
- annotatePathwayToFather, [3](#), [53](#)
- availableOmicMethods, [5](#)
- checkOrder, [5](#)
- compPCs, [6](#)
- computeFreqs, [7](#), [33](#)
- computeOmicIntersections, [7](#)
- computePCs, [8](#)
- convertPathway, [9](#)
- coxrsurvival (survivalcox), [60](#)
- createCoxObj, [10](#)
- createDataModule, [10](#)
- createMOMView, [11](#)
- DataFrame, [19](#)
- downloadPathwayRelationFromReactome, [11](#)
- estimateExprCov, [12](#)
- ExperimentList, [19](#)
- extractCliquesFromDag, [12](#)
- extractSummaryFromBinary, [13](#)
- extractSummaryFromCluster, [13](#)
- extractSummaryFromNumberOfEvents, [14](#)
- extractSummaryFromPCA, [15](#)
- filterExpr (checkOrder), [5](#)
- filterMultiOmicsForSamples
  - (checkOrder), [5](#)
- getPathFathers, [16](#)
- getPathwaysModulesSuccess
  - (selectStablePathwaysModules), [49](#)
- glmTest, [16](#)
- guessInvolvement, [17](#)
- guessInvolvementPathway, [18](#)
- id2name, [18](#)
- makeOmic, [19](#)
- makePositiveDefinite, [20](#)
- mapPathwaysIDfromGraphite, [21](#)
- mergeCol (checkOrder), [5](#)
- minOrNA, [21](#)
- mmoralize (extractCliquesFromDag), [12](#)
- MOSClip, [22](#)
- MOSClip-package (MOSClip), [22](#)
- multiOmics, [23](#), [27](#)
- MultiOmicsModules-class, [24](#)
- MultiOmicsPathway-class, [24](#)
- multiOmicsSurvivalModuleTest, [22](#), [25](#)
- multiOmicsSurvivalPathwayTest, [22](#), [26](#)
- multiOmicsTopo, [27](#)
- multiOmicsTwoClassModuleTest, [22](#), [27](#)
- multiOmicsTwoClassPathwayTest, [22](#), [29](#)
- multiPathwayModuleReport, [8](#), [30](#), [43](#), [48](#)
- multiPathwayReport, [8](#), [31](#), [43](#), [48](#)
- Omics (Omics-class), [31](#)
- Omics-class, [31](#)
- ovarianDataset, [32](#)
- plotFrequencies, [7](#), [33](#), [53](#)
- plotModuleHeat, [34](#)
- plotModuleInGraph, [35](#)
- plotModuleKM, [36](#)
- plotModuleReport, [38](#)
- plotMultiPathwayReport, [39](#)
- plotPathwayHeat, [40](#)
- plotPathwayKM, [42](#)
- preparePerms (checkOrder), [5](#)
- pvalueSummary, [43](#)
- reactSmall, [44](#)
- removeSelfLoops, [44](#)
- resamplingModulesSurvival, [45](#)
- resamplingModulesTwoClass, [46](#)
- resamplingPathwaySurvival
  - (resamplingModulesSurvival), [45](#)

- resamplingPathwayTwoClass
  - (resamplingModulesTwoClass), [46](#)
- resolveAndOrder (checkOrder), [5](#)
- runSupertest, [47](#)
  
- selectStablePathwaysModules, [49](#)
- showModule, [50](#)
- showModule, MultiOmicsModules-method
  - (MultiOmicsModules-class), [24](#)
- showMOSpalette, [38](#), [39](#), [41](#), [50](#)
- showOmics, [51](#)
- showOmics, Omics-method (Omics-class), [31](#)
- showPathway, [51](#)
- showPathway, MultiOmicsPathway-method
  - (MultiOmicsPathway-class), [24](#)
- sparseCompPCs, [52](#)
- stripModulesFromPathways, [53](#)
- summarizeInCluster, [53](#)
- summarizeOmicsResByMinPvalue, [54](#)
- summarizeToBinaryDirectionalEvents, [55](#)
- summarizeToBinaryEvents, [56](#)
- summarizeToNumberOfDirectionalEvents,
  - [57](#)
- summarizeToNumberOfEvents, [58](#)
- summarizeWithPca, [59](#)
- survivalcox, [60](#)
- survivalcoxr, [60](#)
  
- topoCompPCs, [61](#)