

# ind1KG

October 5, 2010

---

c6snp

*SNP metadata used in calling for 1000 genomes pilot data*

---

## Description

SNP metadata used in calling for 1000 genomes pilot data – restricted to chr6

## Usage

```
data(c6snp)
```

## Format

A data frame with 1143009 observations on the following 16 variables.

`chr` a numeric vector

`chrPosFrom` a numeric vector

`chrPosTo` a numeric vector

`rs` a factor with levels rs1000 rs1000009 rs1000025 rs10000302 ...

`ChrAllele` a factor with levels – A AA AAA AAAA AAAAA AAAAAA AAAAAA ...

`variantAllele` a factor with levels (CA) 11/12/13/14/- (G) 14/15/16/18/19/20/21/22/23/C  
(G) 20/21/22/23/24/25/27/-/G/GGG (LAREDELETION) /-/A ...

`snpAlleleChrOrien` a factor with levels (A) 1/13/15/G (A) 10/12 (A) 10/14 (C) 10/11

(CA) 10/11/13/14/15 (CA) 10/14/15/16/17/18/20/21 (CA) 10/17/18/19/20/21/22/23/24

(CA) 11/12/13/14/-/CACA (CA) 11/12/13/14/15/16/17 ...

`snp2chrOrien` a numeric vector

`snpClassAbbrev` a factor with levels Microsatellite Named snp dips mixed multi-  
base single base

`snpClassCode` a numeric vector

`mapLocType` a numeric vector

`mapLocCnt` a numeric vector

`mapWeight` a numeric vector

`contigLabel` a factor with levels DR53 c6\_COX c6\_QBL reference

`unPlacedContig` a factor with levels NT\_113898.1 NT\_113899.1

## Details

Column headings: ===== chr,chrPosFrom, chrPosTo, rs,ChrAllele,variantAllele,snpAlleleChrOrien, snp2chrOrien, snpClassAbbrev,snpClassCode,mapLocType,mapLocCnt,mapWeight, contigLabel,unPlacedContig

Column description: ===== Col1: Chr Col2: chrPosFrom: all chromosome positions are 1 based, that is the first base is counted as 1. Position is for each base, not "interbase".

Col3: chrPosTo: Col4: rs Col5: ChrAllele: the base or bases on the chromosomes at the snp position or ranges. Col6: variantAllele: This is the other allele that is not on the chromosome. For ex. Snp is A/C, chromosome has A, variantAllele will be "C". Col7: snpAlleleChrOrien: This is the list of alleles for the snp in the chromosome orientation. Col8: : the alignment orientation between snp flank and the chromosome sequence. #orien: 0 - same; 1 - opposite Col9: snpClassAbbrev: the variation type of the snp. Details at: <http://www.ncbi.nlm.nih.gov/bookshelf/br.fcgi?book=helpsnpfaq&part=Reports#Reports>.Var

Col10: snpClassCode: The numeric code for snp variation class. possible snpClassCode, SnpClass-Abbrev and descriptions are below:

1 single base Only single base variation.ex.A/G. 2 dips indel or dips: deletion insertion polymorphism.ex.-/T.ex.ss149071 obs=AA/GCCTG 3 HETEROZYGOUS HETEROZYGOUS 4 Microsatellite Microsatellite 5 Named snp observed field starts with '(', and not class 3 an 4.ex.(Alu) 6 NOVARIATION NOVARIATION 7 mixed If the subsnp's in an rs cluster have different snp class. 8 multi-base Multiple Nucleotide Polymorphism, where all alleles are same length, and length > 1.ex.ss2421179 AT/GA

Col11: mapLocType: The alignment type at snp site. Possible values and meanings are: 1 Insertion on contig: snp is always represented as one base and this one base in the snp sequence is substituted with more than one bases on the contig sequence in the alignment. 2 Contig allele is one base long.snp is always represented as one base and this one base in the snp sequence is substituted with exactly one base on the contig. 3 Deletion on the contig: part of the snp flanking sequence including the snp was absent on the contig sequence in the alignment. 4 In the alignment, part of the snp flanking sequence including snp is replaced with the contig sequence of longer length. 5 In the alignment, part of the snp flanking sequence including snp is replaced with the contig sequence of exactly the same length. 6 In the alignment, part of the snp flanking sequence including snp is replaced with the contig sequence of a shorter length.

Col12: mapLocCnt: the total number of locations the snp maps to within the assembly. Col13: Mapweight: A number that codes for the mapping quality of the snp on each assembly: 1 = snp aligns at exactly one location 2 = snp aligns at two locus on same chromosome 3 = snp aligns at two locus on different chromosomes or more than 3 and less than 10 locations 10= snp aligns at 10 or more 10 locations

Col14: ContigLabel: This is used to show when a snp maps to alternative haplotypes or PAR region. Possible values are: DR53 PAR c22\\_H2 c5\\_H2 c6\\_COX c6\\_QBL mitochondrial genome reference

col15: unPlacedContig: This field only has value when a snp hits an unplaced contig, there is no chromosome positions for the snp. chrPosFrom and chrPosTo will be NULL. In this case, unPlacedContig will have the actually contig accession that is unplaced on a chromosome.

## Source

1000 genomes pilot data

## Examples

```
data(c6snp)
c6snp[1:3, ]
```

n240

*NA19240 – 3 million reads from chromosome 6 derived from 1000 genomes bam file*

## Description

NA19240 – 3 million reads from chromosome 6 derived from 1000 genomes bam file

## Usage

data(n240)

## Format

The format is:

List of 1

\$ :List of 13

```

..$ qname : chr [1:3000000] "EAS254_13:7:88:1639:15041" "EAS139_43:2:31:1128:9551" "EAS254_13:8:68:520:6861"
"BGI-FC20AHFAAXX_6_26_477:352" ...
..$ flag : int [1:3000000] 35 35 35 16 35 35 35 0 35 35 ...
..$ rname : Factor w/ 1 level "6": 1 1 1 1 1 1 1 1 1 1 ...
..$ strand: Factor w/ 3 levels "-", "+", "*": 2 2 2 1 2 2 2 2 2 2 ...
..$ pos : int [1:3000000] 5001 5002 5004 5004 5005 5010 5012 5018 5018 5023 ...
..$ qwidth: int [1:3000000] 51 51 51 36 51 51 36 36 36 45 ...
..$ mapq : int [1:3000000] 0 0 0 0 0 0 0 0 0 0 ...
..$ cigar : chr [1:3000000] "51M" "51M" "51M" "36M" ...
..$ mrnm : Factor w/ 1 level "6": 1 1 1 NA 1 1 1 NA 1 1 ...
..$ mpos : int [1:3000000] 5163 5203 5170 NA 5156 5183 5199 NA 5252 5273 ...
..$ isize : int [1:3000000] 214 253 218 NA 203 225 224 NA 271 296 ...
..$ seq :Formal class 'DNAStringSet' [package "Biostrings"] with 5 slots
.. ..@ super :Formal class 'DNAString' [package "Biostrings"] with 6 slots
.. .. ..@ xdata :Formal class 'RawPtr' [package "IRanges"] with 2 slots
.. .. .. ..@ xp :<externalptr>
.. .. .. ..@ .link_to_cached_object:<environment: 0xc5354b8>
.. .. .. ..@ offset : int 0
.. .. .. ..@ length : int 118321039
.. .. .. ..@ elementMetadata: NULL
.. .. .. ..@ elementType : chr "ANYTHING"
.. .. .. ..@ metadata : list()
.. ..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
.. .. ..@ start : int [1:3000000] 1 52 103 154 190 241 292 328 364 400 ...
.. .. ..@ width : int [1:3000000] 51 51 51 36 51 51 36 36 36 45 ...
.. .. ..@ NAMES : NULL
.. .. ..@ elementMetadata: NULL
.. .. ..@ elementType : chr "integer"
.. .. ..@ metadata : list()
.. ..@ elementMetadata: NULL
.. ..@ elementType : chr "ANYTHING"
.. ..@ metadata : list()
..$ qual :Formal class 'PhredQuality' [package "Biostrings"] with 5 slots
.. ..@ super :Formal class 'BString' [package "Biostrings"] with 6 slots

```

```

.. .. ..@ xdata :Formal class 'RawPtr' [package "IRanges"] with 2 slots
.. .. ..@ xp :<externalptr>
.. .. ..@ .link_to_cached_object:<environment: 0xc5354b8>
.. .. ..@ offset : int 0
.. .. ..@ length : int 118321039
.. .. ..@ elementMetadata: NULL
.. .. ..@ elementType : chr "ANYTHING"
.. .. ..@ metadata : list()
.. ..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
.. .. ..@ start : int [1:3000000] 1 52 103 154 190 241 292 328 364 400 ...
.. .. ..@ width : int [1:3000000] 51 51 51 36 51 51 36 36 36 45 ...
.. .. ..@ NAMES : NULL
.. .. ..@ elementMetadata: NULL
.. .. ..@ elementType : chr "integer"
.. .. ..@ metadata : list()
.. ..@ elementMetadata: NULL
.. ..@ elementType : chr "ANYTHING"
.. ..@ metadata : list()

```

### Details

result of Rsamtools scanBam applied to a 3mm line excerpt from the SLX chr6 aligned reads for NA19240

### Source

1000 genomes pilot data

### Examples

```

data(n240)
sapply(n240[[1]], class)

```

---

pup240\_disc

*parsed samtools pileup result excerpt*

---

### Description

parsed samtools pileup result excerpt – only locations where the called base differs from the reference

### Usage

```
data(pup240_disc)
```

### Format

A data frame with 31243 observations on the following 5 variables.

loc location

ref reference base

`indiv` call for NA19240  
`depth` coverage depth at this base  
`pileup` pileup

### **Details**

asterisks are to denote deletions...

### **Examples**

```
data(pup240_disc)  
pup240_disc[1:4, ]
```

# Index

## \*Topic **datasets**

c6snp, 1

n240, 3

pup240\_disc, 4

c6snp, 1

n240, 3

pup240\_disc, 4