

Package ‘DriverNet’

July 31, 2025

Type Package

Title Drivernet: uncovering somatic driver mutations modulating transcriptional networks in cancer

Version 1.49.0

Date 2012-03-21

Author Ali Bashashati, Reza Haffari, Jiarui Ding, Gavin Ha, Kenneth Liu, Jamie Rosner and Sohrab Shah

Maintainer Jiarui Ding <jiaruid@cs.ubc.ca>

Description DriverNet is a package to predict functional important driver genes in cancer by integrating genome data (mutation and copy number variation data) and transcriptome data (gene expression data). The different kinds of data are combined by an influence graph, which is a gene-gene interaction network deduced from pathway data. A greedy algorithm is used to find the possible driver genes, which may mutated in a larger number of patients and these mutations will push the gene expression values of the connected genes to some extreme values.

License GPL-3

LazyLoad yes

Depends R (>= 2.10), methods

biocViews Network

git_url <https://git.bioconductor.org/packages/DriverNet>

git_branch devel

git_last_commit ccbf561

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-07-31

Contents

DriverNet-package	2
actualEvents	3
computeDrivers	4
computeRandomizedResult	5

DriverNetResult-class	6
drivers	7
getPatientOutlierMatrix	7
preprocessMatrices	8
resultSummary	9
sampleDriversList	10
sampleGeneNames	10
sampleInfluenceGraph	11
samplePatientExpressionMatrix	11
samplePatientMutationMatrix	12
samplePatientOutlierMatrix	12
sampleRandomDriversResult	13
totalEvents	13
Index	14

DriverNet-package	<i>Drivernet: uncovering somatic driver mutations modulating transcriptional networks in cancer</i>
-------------------	---

Description

Description: DriverNet is a package to predict functional important driver genes in cancer by integrating genome data (mutation and copy number variation data) and transcriptome data (gene expression data). The different kinds of data are combined by an influence graph, which is a gene-gene interaction network deduced from pathway data. A greedy algorithm is used to find the possible driver genes, which may mutated in a larger number of patients and these mutations will push the gene expression values of the connected genes to some extreme values.

Details

Package:	DriverNet
Type:	Package
Version:	1.0.0
Date:	2012-03-21
License:	GPL-3
LazyLoad:	yes
Depends:	methods

Users would call preprocess_matrices on the three matrices to remove unnecessary data. The matrices returned are then be passed to other functions.

Author(s)

Ali Bashashati, Reza Haffari, Jiarui Ding, Gavin Ha, Kenneth Liu, Jamie Rosner and Sohrab Shah
Maintainer: Jiarui Ding <jiaruid@cs.ubc.ca>

References

Drivernet: uncovering somatic driver mutations modulating transcriptional networks in cancer, submitted.

Examples

```
data(samplePatientMutationMatrix)
data(samplePatientOutlierMatrix)
data(sampleInfluenceGraph)
data(sampleGeneNames)

driversList = computeDrivers(samplePatientMutationMatrix, samplePatientOutlierMatrix,
sampleInfluenceGraph, outputFolder=NULL, printToConsole=FALSE)

drivers(driversList)[1:10]

randomDriversResult = computeRandomizedResult(patMutMatrix=samplePatientMutationMatrix,
patOutMatrix=samplePatientOutlierMatrix, influenceGraph=sampleInfluenceGraph,
geneNameList= sampleGeneNames, outputFolder=NULL, printToConsole=FALSE,
numberOfRandomTests=20, weight=FALSE, perturbGraph=FALSE, perturbData=TRUE)

res = resultSummary(driversList, randomDriversResult, samplePatientMutationMatrix,
sampleInfluenceGraph, outputFolder=NULL, printToConsole=FALSE)
```

actualEvents	<i>Actual events covered by driver mutations</i>
--------------	--

Description

It gives a detailed list of events covered by the driver mutations selected by DriverNet.

Usage

```
actualEvents(x)
```

Arguments

x

See Also

computeDrivers DriverNetResult-class

Examples

```
data(sampleDriversList)
actualEvents(sampleDriversList)
```

computeDrivers	<i>Compute a list of driver mutations</i>
----------------	---

Description

Use a greedy algorithm to rank a list of driver mutations.

Usage

```
computeDrivers(patMutMatrix, patOutMatrix, influenceGraph, outputFolder = NULL,
printToConsole = FALSE, weighted = FALSE)
```

Arguments

patMutMatrix	Patient Mutation Matrix
patOutMatrix	Patient Outlier Matrix
influenceGraph	Influence Graph Matrix
outputFolder	The folder to store the log. If set to NULL, no log files will be written. If set to "", the log will be written to the current folder.
printToConsole	If set to TRUE, progress and result of the function will be printed to the console.
weighted	Must be set to FALSE in this version.

Value

An object of DriverNetResult class that can be passed to the resultSummary method.

Author(s)

Ali Bashashati, Reza Haffari, Jiarui Ding, Gavin Ha, Kenneth Liu, Jamie Rosner and Sohrab Shah
Maintainer: Jiarui Ding <jiaruid@cs.ubc.ca>

Examples

```
data(samplePatientMutationMatrix)
data(samplePatientOutlierMatrix)
data(sampleInfluenceGraph)
driversList = computeDrivers(samplePatientMutationMatrix, samplePatientOutlierMatrix,
sampleInfluenceGraph, outputFolder=NULL, printToConsole=FALSE)

drivers(driversList)[1:10]
```

computeRandomizedResult

Randomly compute lists of driver mutations

Description

It renames the mutations in patMutMatrix with a randomized list of gene names and computes a list of driver mutations. It will repeat this process by numberOfRandomTests times. The result could be passed to the resultSummary method to calculate p-value for the driver mutations.

Usage

```
computeRandomizedResult(patMutMatrix, patOutMatrix, influenceGraph,
geneNameList, outputFolder = NULL, printToConsole = FALSE,
numberOfRandomTests = 500, weighted = FALSE, perturbGraph = FALSE,
perturbData = TRUE)
```

Arguments

patMutMatrix	Patient Mutation Matrix
patOutMatrix	Patient Expression(Outlier) Matrix
influenceGraph	Influence Graph Matrix
geneNameList	A list of gene names that the new mutation names will be randomly chosen from.
outputFolder	The folder to store the log. If set to NULL, no log files will be written. If set to "", the log will be written to the current folder.
printToConsole	If set to TRUE, progress and result of the function will be printed to the console.
numberOfRandomTests	Number of lists of randomized driver mutations to be generated.
weighted	Must be set to FALSE in this version.
perturbGraph	Must be set to FALSE in this version.
perturbData	Must be set to TRUE in this version.

Value

A list of numeric vectors where each vector stores the number of events covered by the randomly identified drivers. The list can be passed to the resultSummary method to compute p-values.

Author(s)

Ali Bashashati, Reza Haffari, Jiarui Ding, Gavin Ha, Kenneth Liu, Jamie Rosner and Sohrab Shah

Maintainer: Jiarui Ding <jiaruid@cs.ubc.ca>

Examples

```
data(samplePatientMutationMatrix)
data(samplePatientOutlierMatrix)
data(sampleInfluenceGraph)
data(sampleGeneNames)

randomDriversResult = computeRandomizedResult(patMutMatrix=samplePatientMutationMatrix,
patOutMatrix=samplePatientOutlierMatrix, influenceGraph=sampleInfluenceGraph,
geneNameList=sampleGeneNames, outputFolder=NULL, printToConsole=FALSE,
numberOfRandomTests=20, weight=FALSE, purturbGraph=FALSE, purturbData=TRUE)
```

DriverNetResult-class *Class "DriverNetResult"*

Description

A class storing the result from running the computeDrivers function. It contains the list of driver mutations found, the detailed events covered by these drivers and the total number of events in the test data.

Objects from the Class

Objects can be created by calls of the form `new("DriverNetResult", drivers=..., actualEvents=..., totalEvents=...)`.

Slots

```
drivers: Object of class "character" ~~
actualEvents: Object of class "list" ~~
totalEvents: Object of class "numeric" ~~
```

Methods

```
actualEvents signature(x = "DriverNetResult"): ...
drivers signature(x = "DriverNetResult"): ...
totalEvents signature(x = "DriverNetResult"): ...
```

Author(s)

Ali Bashashati, Reza Haffari, Jiarui Ding, Gavin Ha, Kenneth Liu, Jamie Rosner and Sohrab Shah
Maintainer: Jiarui Ding <jiaruid@cs.ubc.ca>

See Also

[computeDrivers](#)

Examples

```
data(sampleDriversList)
drivers(sampleDriversList)[1:10]
```

`drivers`*List of driver mutations identified by DriverNet*

Description

It gives the list of driver mutations identified by DriverNet ranked by the number of events that they cover.

Usage

```
drivers(x)
```

Arguments

`x`

See Also

`computeDrivers` `DriverNetResult`-class

Examples

```
data(sampleDriversList)
actualEvents(sampleDriversList)
```

`getPatientOutlierMatrix`*Compute the patient outlier matrix*

Description

Given a real-value patient expression matrix, compute the patient outlier matrix and remove the genes which are not expressed.

Usage

```
getPatientOutlierMatrix(patExpMatrix, th=2)
```

Arguments

`patExpMatrix` Patient Expression Matrix

`th` The threshold, the default value is 2 (the gene expression values outside the 2 standard deviation range are considered as outliers).

Value

The output `patOutMatrix` is an input to the `computeDrivers` method

Author(s)

Ali Bashashati, Reza Haffari, Jiarui Ding, Gavin Ha, Kenneth Liu, Jamie Rosner and Sohrab Shah

Maintainer: Jiarui Ding <jiaruid@cs.ubc.ca>

See Also

computeDrivers

Examples

```
data(samplePatientExpressionMatrix)
samplePatientOutlierMatrix = getPatientOutlierMatrix(samplePatientExpressionMatrix)
```

preprocessMatrices	<i>Remove unnecessary entries from matrices</i>
--------------------	---

Description

Remove patients (rows) which are not in both matrices from patMutMatrix and patOutMatrix. Remove mutations (columns) from patMutMatrix if they are not a row of influenceGraph. Remove expressions (columns) from patOutMatrix if they are not a column of influenceGraph.

Usage

```
preprocessMatrices(patMutMatrix, patOutMatrix, influenceGraph)
```

Arguments

patMutMatrix	Patient Mutation Matrix
patOutMatrix	Patient Outlier Matrix
influenceGraph	Influence Graph Matrix

Value

1	Reduced version of Patient Mutation Matrix
2	Reduced version of Patient Expression(Outlier) Matrix
3	Influence Graph Matrix

Note

The dimension of influenceGraph is not changed.

Author(s)

Ali Bashashati, Reza Haffari, Jiarui Ding, Gavin Ha, Kenneth Liu, Jamie Rosner and Sohrab Shah

Maintainer: Jiarui Ding <jiaruid@cs.ubc.ca>

Examples

```

data(samplePatientMutationMatrix)
data(samplePatientOutlierMatrix)
data(sampleInfluenceGraph)
tmp = preprocessMatrices(samplePatientMutationMatrix, samplePatientOutlierMatrix,
sampleInfluenceGraph)

smallerPatientMutationMatrix = tmp[[1]]
smallerPatientOutlierMatrix = tmp[[2]]
influenceGraph = tmp[[3]]

```

resultSummary	<i>Summarize result for drivers ranking.</i>
---------------	--

Description

Ranks the drivers.

Usage

```

resultSummary(mainResult, randResult, patMutMatrix, influenceGraph,
outputFolder = NULL, printToConsole = FALSE)

```

Arguments

mainResult	An object of DriverNetResult class created by the computeDrivers method.
randResult	A list of vectors representing driver coverage generated by computeRandomizedResult.
patMutMatrix	Patient Mutation Matrix
influenceGraph	Influence Graph Matrix
outputFolder	The folder to store the summary file. If set to NULL, no files will be written. If set to "", the files will be written to the current folder.
printToConsole	If set to TRUE, progress and result of the function will be printed to the console.

Value

A matrix storing the summary result.

Author(s)

Ali Bashashati, Reza Haffari, Jiarui Ding, Gavin Ha, Kenneth Liu, Jamie Rosner and Sohrab Shah
Maintainer: Jiarui Ding <jiaruid@cs.ubc.ca>

Examples

```

data(sampleDriversList)
data(sampleRandomDriversResult)
data(samplePatientMutationMatrix)
data(sampleInfluenceGraph)
res = resultSummary(sampleDriversList, sampleRandomDriversResult,
samplePatientMutationMatrix, sampleInfluenceGraph, outputFolder=NULL,
printToConsole=FALSE)

```

sampleDriversList	<i>Sample DriverNet result</i>
-------------------	--------------------------------

Description

An object of DriverNetResult class that obtained from running the codecomputeDrivers function.

Usage

```
data(sampleDriversList)
```

Format

Formal class 'DriverNetResult' with 3 slots (1) @ drivers: a character vector of the driver gene name; (2) @ actualEvents: the covered events in each mutated patient; (3) @totalEvents: the total number of outliers

See Also

computeDrivers

Examples

```
data(sampleDriversList)

drivers(sampleDriversList)[1:10]
```

sampleGeneNames	<i>Sample gene names</i>
-----------------	--------------------------

Description

A list of gene names used to generate permutation of names in computeRandomizedResult method.

Usage

```
data(sampleGeneNames)
```

Format

A factor of gene names

Examples

```
data(sampleGeneNames)
```

sampleInfluenceGraph	<i>Sample influence graph</i>
----------------------	-------------------------------

Description

A binary matrix representing influence graph between genes.

Usage

```
data(sampleInfluenceGraph)
```

Format

A two-dimensional binary matrix. The row and column names are gene names. If two genes i and j are in the same pathway, `sampleInfluenceGraph[i, j] = 1`.

Examples

```
data(sampleInfluenceGraph)
```

samplePatientExpressionMatrix	<i>Sample patient expression matrix</i>
-------------------------------	---

Description

A real-value matrix representing gene expressions in patients.

Usage

```
data(samplePatientExpressionMatrix)
```

Format

A two-dimensional real value matrix. The row names are patients, and column names are genes. The entry `samplePatientExpressionMatrix[i,j]` is the gene expression values of gene j in patient i .

Examples

```
data(samplePatientExpressionMatrix)
```

`samplePatientMutationMatrix`*Sample patient mutation matrix*

Description

A binary matrix representing gene mutations in patients.

Usage

```
data(samplePatientMutationMatrix)
```

Format

A two-dimensional binary matrix. The row names are patients, and column names are genes. If gene j is mutated in patient i , `samplePatientMutationMatrix[i, j]=1`.

Examples

```
data(samplePatientMutationMatrix)
```

`samplePatientOutlierMatrix`*Sample patient outlier matrix*

Description

A binary matrix representing gene expressions in patients.

Usage

```
data(samplePatientOutlierMatrix)
```

Format

A two-dimensional binary matrix. The row names are patients, and column names are genes. If genes j is an outlier in patient i , `samplePatientOutlierMatrix[i, j] = 1`.

Examples

```
data(samplePatientOutlierMatrix)
```

sampleRandomDriversResult	<i>Sample Result from computeRandomizedResult</i>
---------------------------	---

Description

A sample result from running computeRandomizedResult with numberOfRandomTests = 20.

Usage

data(sampleRandomDriversResult)

Format

A list of predicted drivers from different runs.

See Also

computeRandomizedResult

Examples

data(sampleRandomDriversResult)

totalEvents	<i>Total number of events in the data</i>
-------------	---

Description

Total number of events in the data

Usage

totalEvents(x)

Arguments

x

See Also

computeDrivers DriverNetResult-class

Examples

data(sampleDriversList)
totalEvents(sampleDriversList)

Index

- * **classes**
 - DriverNetResult-class, [6](#)
- * **datasets**
 - sampleDriversList, [10](#)
 - sampleGeneNames, [10](#)
 - sampleInfluenceGraph, [11](#)
 - samplePatientExpressionMatrix, [11](#)
 - samplePatientMutationMatrix, [12](#)
 - samplePatientOutlierMatrix, [12](#)
 - sampleRandomDriversResult, [13](#)
- * **methods**
 - actualEvents, [3](#)
 - computeDrivers, [4](#)
 - computeRandomizedResult, [5](#)
 - drivers, [7](#)
 - getPatientOutlierMatrix, [7](#)
 - preprocessMatrices, [8](#)
 - resultSummary, [9](#)
 - totalEvents, [13](#)
- * **package**
 - DriverNet-package, [2](#)

[actualEvents, \[3\]\(#\)](#)

[actualEvents, DriverNetResult-method \(DriverNetResult-class\), \[6\]\(#\)](#)

[computeDrivers, \[4\]\(#\), \[6\]\(#\)](#)

[computeRandomizedResult, \[5\]\(#\)](#)

[DriverNet \(DriverNet-package\), \[2\]\(#\)](#)

[DriverNet-package, \[2\]\(#\)](#)

[DriverNetResult-class, \[6\]\(#\)](#)

[drivers, \[7\]\(#\)](#)

[drivers, DriverNetResult-method \(DriverNetResult-class\), \[6\]\(#\)](#)

[getPatientOutlierMatrix, \[7\]\(#\)](#)

[preprocessMatrices, \[8\]\(#\)](#)

[resultSummary, \[9\]\(#\)](#)

[sampleDriversList, \[10\]\(#\)](#)

[sampleGeneNames, \[10\]\(#\)](#)

[sampleInfluenceGraph, \[11\]\(#\)](#)

[samplePatientExpressionMatrix, \[11\]\(#\)](#)

[samplePatientMutationMatrix, \[12\]\(#\)](#)

[samplePatientOutlierMatrix, \[12\]\(#\)](#)

[sampleRandomDriversResult, \[13\]\(#\)](#)

[totalEvents, \[13\]\(#\)](#)

[totalEvents, DriverNetResult-method \(DriverNetResult-class\), \[6\]\(#\)](#)