Package 'ImageArray'

May 6, 2026

Type Package

Title A framework for on-disk and in-memory image arrays

Version 1.1.0

Date 2026-01-20

Description ImageArray provides a framework for on-disk and in-memory image arrays, specifically for pyramidal images stored in HDF5, Zarr and life sciences image file formats (OME Bio-Formats).

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

biocViews Software, Visualization

Depends R (>= 4.5.0), EBImage

Imports methods, grDevices, S4Arrays, S4Vectors, DelayedArray, rhdf5, HDF5Array, Rarr, ZarrArray, magick, tools

Suggests testthat (>= 3.0.0), knitr, ggplot2, shiny, RBioFormats, BiocFileCache, BiocStyle

Config/testthat/edition 3

VignetteBuilder knitr

URL https://github.com/BIMSBbioinfo/ImageArray

BugReports https://github.com/BIMSBbioinfo/ImageArray/issues

git_url https://git.bioconductor.org/packages/ImageArray

git_branch devel

git_last_commit 052d69d

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-05-05

Author Artür Manukyan [aut, cre, fnd] (ORCID: <https://orcid.org/0000-0002-0441-9517>)

Maintainer Artür Manukyan <artur-man@hotmail.com>

Contents

BFArray-methods 2
createImageArray 3
create_zarr 4
create_zarr_group 4
getImageInfo 5
ImageArray-methods 6
writeImageArray 9

Index **11**

`BFArray-methods` *BFArray constructor method*

Description

A function for creating objects of BFArray class

Usage

```
BFArray(image.file, series, resolution)

## S4 method for signature 'BFArraySeed'
dim(x)

## S4 method for signature 'BFArraySeed'
type(x)
```

Arguments

`image.file`	the path to the image read by RBioFormats
`series`	the series IDs of the pyramidal image, typical an integer starting from 1
`resolution`	the resolution IDs of the pyramidal image, typical an integer starting from 1
`x`	A BFArray object

Value

A BFArray object

Functions

- `dim(BFArraySeed)`: dim function for BFArray objects
- `type(BFArraySeed)`: type function for BFArray objects

Examples

```
# get image
library(RBioFormats)
img.file <- system.file("extdata",
                        "xy_12bit__plant.ome.tiff",
                        package = "ImageArray")
bfa <- BFArray(img.file, series = 1, resolution = 2)
dim(bfa)
type(bfa)
```

`createImageArray` *createImageArray*

Description

creates an object of ImageArray class

Usage

```
createImageArray(
  image,
  n.levels = NULL,
  series = NULL,
  resolution = NULL,
  max.pixel.threshold = 700,
  engine = "EBImage",
  verbose = FALSE
)
```

Arguments

`image`	the image
`n.levels`	the number of levels of the pyramidal image, typical an integer starting from 1
`series`	the series IDs of the pyramidal image, typical an integer starting from 1.
`resolution`	the resolution IDs of the pyramidal image, typical an integer starting from 1.
`max.pixel.threshold`	the maximum width and height pixel dimension that the lowest level of the image pyramid should have, thus the image will be downscaled two folds until both width and height is below the threshold. Default is 700 pixels. If `n.levels` is provided, this parameter will be ignored.
`engine`	the package to use for each image layer: either `EBImage` or `magick-image`
`verbose`	verbose

Value

An ImageArray object

Examples

```
# get image
library(EBImage)
img.file <- system.file("images", "sample.png", package="EBImage")

# create ImageArray
imgarray <- createImageArray(img.file, n.levels = 3)
imgarray_raster <- as.raster(imgarray, max.pixel.size = 300)
plot(imgarray_raster)
```

`create_zarr` *create_zarr*

Description

Create zarr store

Usage

```
create_zarr(store, version = "v2")
```

Arguments

`store`	the location of zarr store
`version`	zarr version

Value

'NULL'

Examples

```
store <- tempfile(fileext = ".zarr")
create_zarr(store)
```

`create_zarr_group` *create_zarr_group*

Description

Create a zarr group

Usage

```
create_zarr_group(store, name, version = "v2")
```

Arguments

store	the location of (zarr) store
name	name of the group
version	zarr version

Value

'NULL'

Examples

```
store <- tempfile(fileext = ".zarr")
create_zarr(store)
create_zarr_group(store, "gp")
```

---

getImageInfo *getImageInfo*

Description

get information of an ImageArray object

Usage

```
getImageInfo(object)
```

Arguments

object	an ImageArray object

Value

a data frame of width and height info

Examples

```
# get image
library(EBImage)
img.file <- system.file("images", "sample.png", package="EBImage")

# create ImageArray
dir.create(td <- tempfile())
output_h5 <- tempfile(fileext = ".h5")
imgarray <- writeImageArray(img.file,
                            output = output_h5,
                            name = "image",
                            verbose = FALSE)
getImageInfo(imgarray)

# create ImageArray
imgarray <- createImageArray(img.file, n.levels = 3)
imgarray_raster <- as.raster(imgarray, max.pixel.size = 300)
getImageInfo(imgarray)
```

ImageArray-methods *Methods for ImageArray*

Description

Methods for ImageArray objects

Usage

```
## S4 method for signature 'ImageArray,ANY,ANY,ANY'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'ImageArray,numeric'
x[[i]]

## S4 replacement method for signature 'ImageArray,numeric'
x[[i, j, ...]] <- value

## S4 method for signature 'ImageArray'
dim(x)

## S4 method for signature 'ImageArray'
type(x)

## S4 method for signature 'ImageArray'
length(x)

ImageArray(meta, levels)

## S4 method for signature 'ImageArray'
realize(x, level = NULL, max.pixel.size = NULL, min.pixel.size = NULL)

## S3 method for class 'ImageArray'
as.raster(x, level = NULL, max.pixel.size = NULL, min.pixel.size = NULL, ...)

## S4 method for signature 'ImageArray'
rotate(x, angle)

## S4 method for signature 'ImageArray'
aperm(a, perm)

## S4 method for signature 'ImageArray'
negate(object)

## S4 method for signature 'ImageArray'
modulate(object, brightness)

## S4 method for signature 'ImageArray'
flip(x)

## S4 method for signature 'ImageArray'
```

```
flop(x)

## S4 method for signature 'ImageArray'
crop(object, index)

## S4 method for signature 'ImageArray'
axes(object)

## S4 method for signature 'ImageArray'
meta(object)

## S4 method for signature 'ImageArray'
path(object)

## S4 replacement method for signature 'ImageArray'
path(object) <- value
```

Arguments

x, a, object	An ImageArray object
i, j, value	Depends on the usage
	[[, [[<- Here i is the level of the image pyramid. You can use the length function to get the number of the layers in the pyramid. When used with crop, arguments i and j are associated with indices of image dimensions (e.g. width, height)
...	Arguments passed to other methods
drop	ignored
meta	the metadata of the ImageArray object.
levels	levels of the pyramid image, typically a vector of integers starting with 1
level	level
max.pixel.size	maximum pixel size
min.pixel.size	minimum pixel size
angle	value between 0 and 360 for degrees to rotate
perm	perm
brightness	the brightness of the new image in percentage, e.g. 120
index	a named or unnamed list of indices for cropping/subsetting the

Value

dim of the first level of the ImageArray object

type of ImageArray object

length of ImageArray object

An ImageArray object

Functions

- `x[i`: subset and crop for `ImageArray` objects
- `x[[i`: Layer access for `ImageArray` objects
- `` `[[`(x = ImageArray, i = numeric) <- value ``: Layer access for `ImageArray` objects
- `dim(ImageArray)`: dimensions of an ImageArray
- `type(ImageArray)`: dimensions of an ImageArray
- `length(ImageArray)`: length of an ImageArray
- `ImageArray()`: ImageArray constructor method
  A function for creating objects of ImageArray class
- `realize(ImageArray)`: realize the array
- `as.raster(ImageArray)`: create a raster object
- `rotate(ImageArray)`: rotate image array to 90, 180, 270 degrees
- `aperm(ImageArray)`: permute image
- `negate(ImageArray)`: negate image
- `modulate(ImageArray)`: modulate image
- `flip(ImageArray)`: vertical flipping image
- `flop(ImageArray)`: horizontal flipping image
- `crop(ImageArray)`: cropping image
- `axes(ImageArray)`: get axes metadata of the ImageArray object
- `meta(ImageArray)`: get metadata of the ImageArray object
- `path(ImageArray)`: path of an ImageArray object
- `path(ImageArray) <- value`: replace method for path(ImageArray)

Examples

```
# get image
library(EBImage)
img.file <- system.file("images", "sample.png", package="EBImage")

# create ImageArray
imgarray <- createImageArray(img.file, n.levels = 3)

# access layers
imgarray[[1]]
imgarray[[2]]

# dimensions and length
dim(imgarray)
length(imgarray)

# manipulate images
imgarray <- crop(imgarray, ind = list(100:200, 100:200))
imgarray <- crop(imgarray, ind = list(x = 10:20, y = 10:20))
imgarray <- rotate(imgarray, angle = 90)
imgarray <- flip(imgarray)
imgarray <- flop(imgarray)

# create ImageArray on disk as HDF5 format
```

```
dir.create(td <- tempfile())
output_h5 <- tempfile(fileext = ".h5")
imgarray <- writeImageArray(img.file,
                            output = output_h5,
                            name = "image",
                            verbose = FALSE)

# as.raster
imgarray_raster <- as.raster(imgarray)

# realize
imgarray <- realize(imgarray)
```

`writeImageArray` *writeImageArray*

Description

Writing image arrays on disk

Usage

```
writeImageArray(
  image,
  output = "my_image",
  name = "",
  format = NULL,
  replace = FALSE,
  n.levels = NULL,
  chunkdim = NULL,
  level = NULL,
  engine = "EBImage",
  verbose = FALSE,
  ...
)
```

Arguments

`image`	an Image object (EBImage), a magick object or the path to an image file,
`output`	output file name
`name`	name of the group
`format`	on disk format, either "h5" for HDF5 format, "zarr" for zarr format, or "in-memory" for in-memory ImageArray object. If not provided, the format will be inferred from the file extension of the output path.
`replace`	Should the existing file be removed or not
`n.levels`	the number of levels if the image supposed to be pyramidal.
`chunkdim`	The dimensions of the chunks to use for writing the data to disk.
`level`	The compression level to use for writing the data to disk.
`engine`	the package to use for each image layer: either `EBImage` or `magick-image`
`verbose`	verbose
`...`	additional parameters passed to createImageArray.

Value

An ImageArray object

Examples

```
# get image
library(EBImage)
img.file <- system.file("images", "sample.png", package="EBImage")

# create ImageArray
dir.create(td <- tempfile())
output_h5 <- tempfile(fileext = ".h5")
imgarray <- writeImageArray(img.file,
                            output = output_h5,
                            name = "image",
                            verbose = FALSE)
imgarray_raster <- as.raster(imgarray)
plot(imgarray_raster)
```

Index

[,ImageArray,ANY,ANY,ANY-method
(ImageArray-methods), 6
[[,ImageArray,numeric-method
(ImageArray-methods), 6
[[<-,ImageArray,numeric-method
(ImageArray-methods), 6

aperm,ImageArray-method
(ImageArray-methods), 6
as.raster (ImageArray-methods), 6
as.raster,ImageArray-method
(ImageArray-methods), 6
as.raster.ImageArray
(ImageArray-methods), 6
axes (ImageArray-methods), 6
axes,ImageArray-method
(ImageArray-methods), 6

BFArray (BFArray-methods), 2
BFArray-methods, 2

create_zarr, 4
create_zarr_group, 4
createImageArray, 3, 9
crop (ImageArray-methods), 6
crop,ImageArray-method
(ImageArray-methods), 6

dim,BFArraySeed-method
(BFArray-methods), 2
dim,ImageArray-method
(ImageArray-methods), 6

flip (ImageArray-methods), 6
flip,ImageArray-method
(ImageArray-methods), 6
flop (ImageArray-methods), 6
flop,ImageArray-method
(ImageArray-methods), 6

getImageInfo, 5

ImageArray (ImageArray-methods), 6
ImageArray-methods, 6

length,ImageArray-method
(ImageArray-methods), 6

meta (ImageArray-methods), 6
meta,ImageArray-method
(ImageArray-methods), 6
modulate (ImageArray-methods), 6
modulate,ImageArray-method
(ImageArray-methods), 6

negate (ImageArray-methods), 6
negate,ImageArray-method
(ImageArray-methods), 6

path (ImageArray-methods), 6
path,ImageArray-method
(ImageArray-methods), 6
path<-,ImageArray-method
(ImageArray-methods), 6

realize (ImageArray-methods), 6
realize,ImageArray-method
(ImageArray-methods), 6
rotate (ImageArray-methods), 6
rotate,ImageArray-method
(ImageArray-methods), 6

type,BFArraySeed-method
(BFArray-methods), 2
type,ImageArray-method
(ImageArray-methods), 6

writeImageArray, 9