

Package ‘CSOA’

September 26, 2025

Type Package

Title Calculate per-cell gene signature scores using cell set overlaps

Version 0.99.2

Description Cell Set Overlap Analysis (CSOA) is a tool for calculating per-cell gene signature scores in a scRNA-seq dataset. CSOA constructs a set for each gene in the signature, consisting of the cells that highly express the gene. Next, all overlaps of pairs of cell sets are computed, ranked, filtered and scored. The CSOA per-cell score is calculated by summing up all products of the overlap scores and the min-max-normalized expression of the two involved genes. CSOA can run on a Seurat object, a SingleCellExperiment object, a matrix and a dgCMatix.

License MIT + file LICENSE

Imports bayesbio, dplyr, ggeasy, ggforce, ggnewscale, ggplot2, ggraph, ggrepel, graphics, grDevices, kerntools, methods, qs, reshape2, Seurat, SeuratObject, SingleCellExperiment, SummarizedExperiment, sgof, spatstat.utils, stats, textshape, tidygraph, viridis, wesanderson

Encoding UTF-8

RoxygenNote 7.3.3

Suggests BiocStyle, knitr, patchwork, rmarkdown, scRNAseq, scuttle, stringr, testthat (>= 3.0.0)

biocViews Software, SingleCell, GeneSetEnrichment, GeneExpression

VignetteBuilder knitr

URL <https://github.com/andrei-stoica26/CSOA>

BugReports <https://github.com/andrei-stoica26/CSOA/issues>

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/CSOA>

git_branch devel

git_last_commit c31b17a

git_last_commit_date 2025-09-19

Repository Bioconductor 3.22

Date/Publication 2025-09-26

Author Andrei-Florian Stoica [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-5253-0826>>)

Maintainer Andrei-Florian Stoica <andreistoica@foxmail.com>

Contents

attachCellScores.default	2
basicHeatmap	3
borderCoords	4
breakWeakTies	5
byCorrectDF	6
cellDistribution	6
cellSetsOverlaps	7
circleCoords	7
computePairScores	8
computePCPairScores	8
connectedComponents	9
edgeLists.default	9
expMat	10
featureWes	11
geneRadialPlot	12
generateOverlaps	13
getPairs	14
networkPlot	14
networkPlotDF	15
overlapCutoffPlot	16
overlapGenes	16
overlapPairs	17
percentileSets	17
processOverlaps	18
qGrab	19
runCSOA	19
scoreCells	21
scoreCellsCore	22
scoreModules	23
wesBinaryGradient	24
Index	25

attachCellScores.default

Attach CSOA scores to object

Description

This function attaches the data frame of CSOA scores to the input object.

Usage

```
## Default S3 method:
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'Seurat'
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'SingleCellExperiment'
```

```
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'matrix'
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'dgCMatrx'
attachCellScores(scObj, scoreDF, ...)

attachCellScores(scObj, ...)
```

Arguments

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
scoreDF	Dataframe of CSOA scores
...	Additional arguments.

Details

If the input object is of the Seurat or SingleCellExpression class, it will be returned with added CSOA scores. Otherwise, a list containing the expression matrix and the CSOA scores data frame will be returned.

Value

A Seurat object with CSOA scores added to metadata.

A SingleCellExperiment object with CSOA scores added to colData.

A list containing the expression matrix and the CSOA scores data frame.

A list containing the expression matrix and the CSOA scores data frame.

Examples

```
library(Seurat)
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- sample(20, 8000, TRUE)
seuratObj <- CreateSeuratObject(mat)
seuratObj <- NormalizeData(seuratObj)
scores <- data.frame(CSOA = runif(300))
seuratObj <- attachCellScores(seuratObj, scores)
head(seuratObj$CSOA)
```

basicHeatmap

Plot a simple heatmap

Description

This function plots a simple heatmap, with clustering but no dendograms.

Usage

```
basicHeatmap(
  mat,
  aesNames = c("x", "y", "Score"),
  title = "Heatmap",
  axisTextSize = 7,
  palType = "fillCont",
  wesPal = "Royal1",
  wesLow = 3,
  wesHigh = 2
)
```

Arguments

mat	A matrix.
aesNames	A character vector of length 3 representing the y, x and fill aes elements.
title	Plot title.
axisTextSize	Axis text size.
palType	Palette type: color or fill, continuous or discrete. Accepted values are 'colorCont', 'fillCont', 'colDis' and 'fillDis'. The function shows a warning and does not change the color scheme if a different value is passed here.
wesPal	A wesanderson palette.
wesLow	Index of color marking low values.
wesHigh	Index of color marking high values.

Value

A ggplot object.

Examples

```
mat <- matrix(0, 10, 20)
mat[sample(length(mat), 50)] <- runif(50, max = 2.5)
basicHeatmap(mat)
```

borderCoords	<i>Find the coordinates where vertical or horizontal line intersects the hull</i>
--------------	---

Description

This function finds the coordinates where vertical or horizontal line intersects the hull.

Usage

```
borderCoords(df, axis, axisIntersect)
```

Arguments

df	A four-column data frame representing segments.
axis	An integer representing the axis intersected by the vertical or horizontal line, x (1) or y (2).
axisIntersect	The coordinate where the vertical or horizontal line intersects the relevant axis.

Value

A vector of size two representing the coordinates of the two intersection points between the vertical or horizontal line and the convex hull on the axis different from the input axis.

breakWeakTies	<i>Remove overlap pairs with low Jaccard scores</i>
---------------	---

Description

This function iteratively removes all overlap pairs with neighbor Jaccard score below a fixed cutoff until no overlap pairs can be removed. Subsequently, overlap ranks are recalculated.

Usage

```
breakWeakTies(overlapDF, cutoff = 1/3, doConnComp = FALSE)
```

Arguments

overlapDF	An overlap data frame.
cutoff	A cutoff used in the filtering of edges with low Jaccard scores.
doConnComp	Whether to calculate the connected components.

Details

The functions removes overlaps for which the two involved genes record too few shared neighbors—genes whose cell set significantly overlaps with those of both overlap genes.

Value

An overlap data frame in which edges with low Jaccard scores have been removed.

Examples

```
overlapDF <- data.frame(gene1=paste0('G', c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),
  gene2=paste0('G', c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),
  ratio=runif(10, 2, 10),
  pval=runif(10, 0, 1e-10))
breakWeakTies(overlapDF, cutoff=0.1)
```

byCorrectDF	<i>Perform multiple testing correction and filtering with Benjamini-Yekutieli</i>
-------------	---

Description

This function performs the Benjamini-Yekutieli correction for multiple testing in a dataframe column of p-values and filters the data-frame based on p-values.

Usage

```
byCorrectDF(df, pvalThr = 0.05, colStr = "pval")
```

Arguments

df	A dataframe with a column of p-values.
pvalThr	p-value threshold.
colStr	Name of the column of p-values.

Value

The data frame with Benjamini-Yekutieli-corrected p-values.

cellDistribution	<i>Show the distribution of cell sets among cells</i>
------------------	---

Description

This function returns a logical matrix that shows the representation of cell sets among all cells.

Usage

```
cellDistribution(cellSets, allCells)
```

Arguments

cellSets	A list of character vectors.
allCells	Names of all cells in the dataset.

Value

A logical matrix with genes as rows and cells as columns.

Examples

```
cellSets <- list(c('A', 'H', 'J'),
c('B', 'D', 'E', 'F', 'J'),
c('C', 'I', 'L'))
allCells <- LETTERS[seq(15)]
cellDistribution(cellSets, allCells)
```

cellSetsOverlaps	<i>Calculates the significance of overlaps of pairs of cells sets</i>
------------------	---

Description

This function computes the statistical significance of overlaps of pairs of cell sets.

Usage

```
cellSetsOverlaps(cellSets, nCells, pairs = NULL)
```

Arguments

cellSets	A list of character arrays.
nCells	The total number of cells in the Seurat object.
pairs	Pairs of cell sets to be assessed. If NULL (as default), all pairs will be assessed.

Value

A data frame listing statistics for all cell set overlaps: cell set sizes, recorded and expected shared cells, the recorded-over-expected ratio and the hypergeometric p-value.

Examples

```
cellSets <- list(G1 = c('A', 'H', 'J'),
  G2 = c('B', 'D', 'E', 'F', 'J'),
  G3 = c('C', 'I', 'L'))
cellSetsOverlaps(cellSets, 40)
```

circleCoords	<i>Store the radii of the circles and the corresponding number of edges</i>
--------------	---

Description

This function store the radii of the circles and the corresponding number of edges

Usage

```
circleCoords(geneCoordsDF, extraCircles = 0)
```

Arguments

geneCoordsDF	Dataframe with gene coordinates
extraCircles	Number of circles drawn beyond those needed to include the points representing the genes.

Value

A data frame containing the radius and the number of edges for each circle

computePairScores	<i>Compute aggregate gene pair scores</i>
-------------------	---

Description

This function assesses the relative contribution of each gene pair to the CSOA score

Usage

```
computePairScores(
  overlapDF,
  pcPairScores,
  pairFileName = "pairs",
  keepOverlapOrder = FALSE
)
```

Arguments

overlapDF	An overlap data frame.
pcPairScores	A data frame of pair scores in each cell for each pair in the overlap data frame.
pairFileName	The name of the file where the pair data frame will be saved.
keepOverlapOrder	Whether to keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order.

Value

A data frame with overlap and pair scores and ranks.

computePCPairScores	<i>Compute per-cell gene pair scores</i>
---------------------	--

Description

This function scores each gene pair corresponding to a top overlap in each cell.

Usage

```
computePCPairScores(overlapDF, normExp)
```

Arguments

overlapDF	An overlap data frame.
normExp	A min-max normalized expression matrix of the genes involved in top overlaps.

Details

The score is calculated by multiplying the overlap score with the min-max-normalized expression of the two corresponding genes.

Value

A data frame with gene pairs as rows and cells as columns.

connectedComponents	<i>Find the connected components of the graph determined by the overlaps</i>
---------------------	--

Description

This function finds the connected components of the graph having the filtered overlaps as edges.

Usage

```
connectedComponents(df, colName = "component")
```

Arguments

df	A data frame with gene1 and gene2 columns.
colName	Name of the connected components column to be added.

Value

An overlap data frame with a column indicated the number of the connected component.

Examples

```
df <- data.frame(
  gene1 = paste('G', c(1, 2, 6, 7, 8, 9,
    11, 25, 32, 17, 18)),
  gene2 = paste('G', c(2, 8, 8, 8, 1, 25,
    32, 24, 24, 26, 26))
)
connectedComponents(df)
```

edgeLists.default	<i>Extract the edge list from overlap data frame or list of overlap data frames</i>
-------------------	---

Description

This function creates a list of data frames with three columns: gene1, gene2 and group. If overlapObj is an overlap data frame, the groups correspond to the connected components. If it is a list of overlap data frames, the groups must be specified as groupNames.

Usage

```
## Default S3 method:
edgeLists(overlapObj, ...)

## S3 method for class 'data.frame'
edgeLists(overlapObj, ...)

## S3 method for class 'list'
edgeLists(overlapObj, groupNames, cutoff = NULL, ...)

edgeLists(overlapObj, ...)
```

Arguments

overlapObj	An overlap data frame or list of overlap data frames.
...	Additional arguments.
groupNames	Names of groups. If provided, must be a vector of the same length as the list of overlap data frames
cutoff	Number of retained edges from each overlap data frame after refiltering. If NULL (as default), no refiltering will be performed

Value

A list of data frames.

expMat	<i>Extracts the data expression matrix from object</i>
--------	--

Description

This function extracts the data expression matrix from object as a non-sparse matrix. Selected genes can be specified as input.

Usage

```
expMat(scObj, ...)

## Default S3 method:
expMat(scObj, genes = NULL, ...)

## S3 method for class 'Seurat'
expMat(scObj, ...)

## S3 method for class 'SingleCellExperiment'
expMat(scObj, ...)

## S3 method for class 'dgCMatix'
expMat(scObj, ...)

## S3 method for class 'matrix'
expMat(scObj, ...)
```

Arguments

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
...	Additional arguments.
genes	Genes retained in the expression matrix. If NULL, all genes will be retained

Value

An expression matrix.

Examples

```
library(Seurat)
mat <- matrix(0, 6, 4)
mat[sample(length(mat), 7)] <- sample(3, 7, TRUE)
seuratObj <- CreateSeuratObject(counts = mat)
seuratObj <- NormalizeData(seuratObj)
expMat(seuratObj)
```

featureWes

A feature plot with a more distinctive color scheme.

Description

This function customizes the appearance of `Seurat::FeaturePlot` for improved distinctiveness and aesthetics.

Usage

```
featureWes(
  seuratObj,
  feature,
  title = feature,
  idClass = NULL,
  labelSize = 3,
  titleSize = 12,
  wesPal = "Royal1",
  wesLow = 3,
  wesHigh = 2,
  ...
)
```

Arguments

seuratObj	A Seurat object.
feature	Seurat feature.
title	Plot title.
idClass	Column to be used for labelling. If NULL, no column-based labels will be generated.
labelSize	Size of labels. Ignored if idClass is NULL.

titleSize	Title size.
wesPal	A wesanderson palette.
wesLow	Index of color marking low values.
wesHigh	Index of color marking high values.
...	Additional arguments passed to <code>Seurat::FeaturePlot</code> .

Value

A ggplot object.

Examples

```
library(Seurat)
mat <- matrix(0, 3000, 800)
mat[sample(length(mat), 90000)] <- sample(8, 90000, TRUE)
seuratObj <- CreateSeuratObject(counts = mat)
seuratObj <- FindVariableFeatures(seuratObj, nfeatures=200)
seuratObj <- NormalizeData(seuratObj)
seuratObj <- ScaleData(seuratObj)
seuratObj <- RunPCA(seuratObj, verbose=FALSE)
seuratObj <- RunUMAP(seuratObj, dims=1:20, verbose=FALSE)
featureWes(seuratObj, 'Feature3')
```

geneRadialPlot

Radial plot for an overlap data frame

Description

This function draws a radial plot for an overlap data frame to illustrate gene participation in top overlaps.

Usage

```
geneRadialPlot(
  overlapObj,
  groupLegendName = NULL,
  groupNames = NULL,
  cutoff = NULL,
  title = "Top overlap genes plot",
  extraCircles = 2
)
```

Arguments

overlapObj	An overlap data frame or list of overlap data frames.
groupLegendName	The title of the group legend; if NULL, no groups will be distinguished.
groupNames	Names of groups. If provided, must be a vector of the same length as the list of overlap data frames

cutoff	Number of retained edges from each overlap data frame after refiltering. If NULL (as default), no refiltering will be performed
title	Plot title.
extraCircles	Number of circles drawn beyond those needed to include the points representing the genes.

Details

The function can separate genes by groups. The groups can be, for instance, different gene sets, or different connected components of the same overlap data frame.

Value

A ggplot object.

Examples

```
edgesDF <- data.frame(gene1 = paste0('G', c(1, 2, 3, 4, 7, 8, 10,
11, 11, 10, 10, 10)),
gene2 = paste0('G', c(2, 5, 1, 8, 4, 9, 12,
13, 14, 13, 16, 14)))
edgesDF <- connectedComponents(edgesDF, 'group')
geneRadialPlot(edgesDF, 'component', extraCircles=1)
```

generateOverlaps	<i>Generate overlaps of cell sets for input genes</i>
------------------	---

Description

This function constructs, for each gene in the expression matrix, a set of cells expressing the gene at or above the input percentile. Subsequently, overlaps of pairs of the constructed cell sets are assessed for statistical significance.

Usage

```
generateOverlaps(geneSetExp, percentile = 90, pairs = NULL)
```

Arguments

geneSetExp	A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.
percentile	A positive number under 100.
pairs	Pairs of cell sets to be assessed. If NULL (as default), all pairs will be assessed.

Details

Wrapper around percentileSets and cellSetsOverlaps.

Value

A data frame listing statistics for all cell set overlaps

Examples

```
mat <- matrix(0, 2000, 500)
rownames(mat) <- paste0('G', seq(2000))
colnames(mat) <- paste0('C', seq(500))
mat[sample(length(mat), 270000)] <- sample(50, 270000, TRUE)
mat <- mat[paste0('G', sample(2000, 5)), ]
generateOverlaps(mat)
```

getPairs

Get all unordered pairs of two elements from a vector

Description

This function returns all unordered pairs of two elements from a vector.

Usage

```
getPairs(v)
```

Arguments

v A vector.

Value

A list of vectors of length 2.

Examples

```
v <- c('ASD', 'VBN', 'HJKL')
getPairs(v)
```

networkPlot

Plot the overlaps as a network

Description

This function plots the graph of the overlap data frame, with genes as vertices and overlaps as edges.

Usage

```
networkPlot(
  overlapDF,
  title = "Top overlaps network plot",
  rankCol = "rank",
  edgeScale = 2,
  nodePointSize = 10,
  nodeTextSize = 2.3,
  ...
)
```

Arguments

overlapDF	Overlap data frame.
title	Plot title.
rankCol	Name of the rank column.
edgeScale	Scaling factor used in generating edge weights.
nodePointSize	Point size of graph nodes.
nodeTextSize	Text size of graph nodes.
...	Additional parameters passed to titlePlot.

Value

A network plot.

Examples

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 5, 6, 7, 17)),
  gene2 = paste0('G', c(2, 5, 8, 11, 11, 11)),
  rank = c(1, 1, 3, 3, 3, 3))
networkPlot(overlapDF)
```

networkPlotDF	<i>Prepare overlap data frame for network plot</i>
---------------	--

Description

This function prepares a ranked and filtered overlap data frame for network plot.

Usage

```
networkPlotDF(overlapDF, rankCol = "rank", edgeScale = 2)
```

Arguments

overlapDF	Overlap data frame.
rankCol	Name of the rank column.
edgeScale	Scaling factor used in generating edge weights.

Value

A data frame ready to serve as input to networkPlot.

overlapCutoffPlot	<i>Plot the selection of overlaps</i>
-------------------	---------------------------------------

Description

This function illustrates the process of selecting the overlap rank cutoff by plotting rank frequencies against ranks and showcasing the convex hull of the rank-frequency points.

Usage

```
overlapCutoffPlot(overlapDF, title = "Overlap cutoff plot")
```

Arguments

overlapDF	Processed overlap data frame created with processOverlaps.
title	Plot title.

Value

A ggplot object.

Examples

```
overlapDF <- data.frame(gene1=paste0('G', c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),  
  gene2=paste0('G', c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),  
  rank=c(1, 2, 3, 4, 4, 6, 7, 7, 7, 10))  
overlapCutoffPlot(overlapDF)
```

overlapGenes	<i>Get all genes from an overlap data frame</i>
--------------	---

Description

This function gets all genes from an overlap data frame.

Usage

```
overlapGenes(overlapDF)
```

Arguments

overlapDF	Overlap data frame.
-----------	---------------------

Value

A character vector of genes.

Examples

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 3)),
  gene1 = paste0('G', c(2, 7, 8)))
overlapGenes(overlapDF)
```

 overlapPairs

Extract gene pairs from overlap data frame

Description

This function extracts the gene pairs from an overlap data frame.

Usage

```
overlapPairs(overlapDF)
```

Arguments

overlapDF Overlap data frame.

Value

A list of gene pairs.

Examples

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 3)),
  gene1 = paste0('G', c(2, 7, 8)))
overlapPairs(overlapDF)
```

 percentileSets

Generates cell expressing input genes at an input percentile

Description

This function constructs, for each gene in the expression matrix, a set of cells expressing the gene at or above the input percentile.

Usage

```
percentileSets(geneSetExp, percentile = 90)
```

Arguments

geneSetExp A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.

percentile A positive number under 100.

Value

A named list of character vectors of length equaling the number of input genes. Each vector stores the cells expressing the gene at or above the input percentile.

Examples

```
mat <- matrix(0, 1000, 500)
rownames(mat) <- paste0('G', seq(1000))
colnames(mat) <- paste0('C', seq(500))
mat[sample(length(mat), 70000)] <- sample(50, 70000, TRUE)
mat <- mat[paste0('G', sample(1000, 3)), ]
percentileSets(mat)
```

processOverlaps

Process data frame of overlaps of cell sets

Description

This function filters, ranks and scores previously generated overlaps of cell sets.

Usage

```
processOverlaps(
  overlapDF,
  pvalThr = 0.05,
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax")
)
```

Arguments

overlapDF	Overlap data frame.
pvalThr	P-value threshold used for initial filtering.
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".

Details

Wrapper around `byCorrectDF`, `rankOverlaps`, `prepareFiltering`, `filterOverlaps` and `scoreOverlaps`. If `jaccardCutoff` is not NULL, it also calls `breakWeakTies` between `filterOverlaps` and `scoreOverlaps`.

Value

A data frame consisting of filtered, ranked and scored cell sets overlaps

Examples

```

overlapDF <- data.frame(gene1=paste0('G',
c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),
gene2=paste0('G',
c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),
ratio=runif(10, 2, 10),
pval=runif(10, 0, 1e-10))
processOverlaps(overlapDF)

```

qGrab

*Read and delete a .qs file***Description**

This functions reads a .qs file, deletes it, and returns its content.

Usage

```
qGrab(qsFile)
```

Arguments

qsFile Name of .qs file with path.

Value

The content of the .qs file.

Examples

```

library(qs)
qsave(c(1, 2, 3), 'temp.qs')
qGrab('temp.qs')

```

runCSOA

*Run the CSOA pipeline***Description**

This function generates cell set overlaps for input gene sets based on percentiles of gene expression, computes the significance of these overlaps, ranks, filters and scores the overlaps, and builds a per-cell score by summing the products of overlap scores and the min-max-normalized expression of the corresponding pairs of genes.

Usage

```
runCSOA(
  scObj,
  geneSets,
  percentile = 90,
  pvalThr = 0.05,
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileTemplate = NULL,
  keepOverlapOrder = FALSE
)
```

Arguments

<code>scObj</code>	A Seurat object, SingleCellExperiment object, or expression matrix.
<code>geneSets</code>	Named list of character vectors of which each must contain at least two genes.
<code>percentile</code>	A positive number under 100.
<code>pvalThr</code>	P-value threshold used for initial filtering.
<code>jaccardCutoff</code>	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
<code>osMethod</code>	Method used to compute overlap scores. Options are "log" and "minmax".
<code>pairFileTemplate</code>	Character object used in the naming of the files where the pair data frames will be saved. Default is NULL (the pair data frames will not be saved).
<code>keepOverlapOrder</code>	Keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order. Ignored if <code>pairFileTemplate</code> is NULL.

Details

#' @details Wrapper around `expMat`, `generateOverlaps`, `scoreCellsMultiple` and `attachCellScores`.

Value

An object of the same class as `scObj` with per-gene-set CSOA scores assigned for each cell.

Examples

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes <- paste0('G', seq(200))
mat[genes, 20:50] <- matrix(runif(200 * 31, min = 14, max = 15),
  nrow = 200, ncol = 31)
geneSet1 <- paste0('G', seq(1, 150))
geneSet2 <- paste0('G', seq(50, 200))
df <- runCSOA(mat, list(a = geneSet1, b = geneSet2))
head(df)
```

scoreCells

*Generate CSOA scores from overlap data frame and list of pairs***Description**

This function scores an overlap data frame using its associated list of pairs. The overlap data frame is split based on the overlaps corresponding to each gene set and scored, and the output is rejoined as a data frame.

Usage

```
scoreCells(
  geneSetExp,
  overlapDF,
  setPairs,
  geneSetNames,
  pvalThr = 0.05,
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileTemplate = NULL,
  keepOverlapOrder = FALSE
)
```

Arguments

geneSetExp	A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.
overlapDF	Overlap data frame.
setPairs	A list of overlaps corresponding to each input gene set.
geneSetNames	Character vector of names of gene sets.
pvalThr	P-value threshold used for initial filtering.
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".
pairFileTemplate	Character object used in the naming of the files where the pair data frames will be saved. Default is NULL (the pair data frames will not be saved).
keepOverlapOrder	Keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order. Ignored if pairFileTemplate is NULL.

Details

This function calls scoreCells to score each gene set data frame split from the full overlap data frame.

Value

A data frame whose columns correspond to the CSOA scores of the input gene sets.

Examples

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes <- paste0('G', seq(200))
mat[genes, 20:50] <- matrix(runif(200 * 31, min=14, max=15),
  nrow=200, ncol=31)
geneSet1 <- paste0('G', seq(1, 150))
geneSet2 <- paste0('G', seq(50, 200))
geneSets <- list(geneSet1, geneSet2)
geneSets <- lapply(geneSets, sort)
setPairs <- lapply(geneSets, getPairs)
pairs <- Reduce(union, setPairs)
genes <- union(geneSet1, geneSet2)
mat <- mat[genes, ]
overlapDF <- generateOverlaps(mat, pairs=pairs)
scoreDF <- scoreCells(mat, overlapDF, setPairs, c('set1', 'set2'))
head(scoreDF)
```

scoreCellsCore

Generate CSOA scores from overlap data frame for a single gene set

Description

This function computes per-cell CSOA scores from overlap data frame for a single gene set.

Usage

```
scoreCellsCore(
  geneSetExp,
  overlapDF,
  colStr = "CSOA",
  pvalThr = 0.05,
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileName = NULL,
  keepOverlapOrder = FALSE
)
```

Arguments

geneSetExp	A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.
overlapDF	Overlap data frame.
colStr	Name of column where CSOA scores will be stored.
pvalThr	P-value threshold used for initial filtering.
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".

pairFileName The name of the file where the pair data frame will be saved.
 keepOverlapOrder Whether to keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order.

Value

A data frame with a column corresponding to the CSOA scores.

scoreModules	<i>Run CSOA separately on the connected components of the overlap graph</i>
--------------	---

Description

This function runs CSOA on the connected components of the graph having the filtered overlaps as edges.

Usage

```
scoreModules(scObj, df, components, colStrTemplate = "CSOA_component", ...)
```

Arguments

scObj A Seurat object, SingleCellExperiment object, or expression matrix.
 df A data frame with gene1, gene2 and component columns.
 components Vector of connected components that will be scored
 colStrTemplate Character used in the naming of the component gene sets.
 ... Additional parameters passed to runCSOAMultiple.

Value

An object of the same class as scObj with CSOA scores corresponding to the genes defining each connected components assigned for each cell.

Examples

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes1 <- paste0('G', seq(100))
mat[genes1, 20:50] <- matrix(runif(100 * 31, min = 14, max = 15),
  nrow = 100, ncol = 31)
genes2 <- paste0('G', seq(101, 200))
mat[genes2, 70:100] <- matrix(runif(100 * 31, min = 14, max = 15),
  nrow = 100, ncol = 31)
genes <- union(genes1, genes2)
mat <- mat[genes, ]
overlapDF <- generateOverlaps(mat)
overlapDF <- processOverlaps(overlapDF)
overlapDF <- connectedComponents(overlapDF)
```

```
df <- scoreModules(mat, overlapDF, unique(overlapDF$component))[[2]]  
head(df)
```

wesBinaryGradient	<i>Adds a gradient color scale using two wesanderson colors</i>
-------------------	---

Description

This function adds a gradient color scale to a ggplot object using a wesanderson palette, an index marking low values, and an index marking high values. The indices are used to select colors from the wesanderson palette of choice.

Usage

```
wesBinaryGradient(p, palType, wesPal = "Royal1", wesLow = 3, wesHigh = 2, ...)
```

Arguments

p	A ggplot object.
palType	Palette type: color or fill, continuous or discrete. Accepted values are 'color-Cont', 'fillCont', 'colDis' and 'fillDis'. The function shows a warning and does not change the color scheme if a different value is passed here.
wesPal	A wesanderson palette.
wesLow	Index of color marking low values.
wesHigh	Index of color marking high values.
...	Arguments passed to other functions.

Value

A ggplot object with a new color scheme.

Index

* internal

- borderCoords, [4](#)
- byCorrectDF, [6](#)
- circleCoords, [7](#)
- computePairScores, [8](#)
- computePCPairScores, [8](#)
- edgeLists.default, [9](#)
- networkPlotDF, [15](#)
- scoreCellsCore, [22](#)
- wesBinaryGradient, [24](#)

- attachCellScores
 - (attachCellScores.default), [2](#)
- attachCellScores.default, [2](#)

- basicHeatmap, [3](#)
- borderCoords, [4](#)
- breakWeakTies, [5](#)
- byCorrectDF, [6](#)

- cellDistribution, [6](#)
- cellSetsOverlaps, [7](#)
- circleCoords, [7](#)
- computePairScores, [8](#)
- computePCPairScores, [8](#)
- connectedComponents, [9](#)

- edgeLists (edgeLists.default), [9](#)
- edgeLists.default, [9](#)
- expMat, [10](#)

- featureWes, [11](#)

- geneRadialPlot, [12](#)
- generateOverlaps, [13](#)
- getPairs, [14](#)

- networkPlot, [14](#)
- networkPlotDF, [15](#)

- overlapCutoffPlot, [16](#)
- overlapGenes, [16](#)
- overlapPairs, [17](#)

- percentileSets, [17](#)

- processOverlaps, [18](#)

- qGrab, [19](#)

- runCSOA, [19](#)

- scoreCells, [21](#)
- scoreCellsCore, [22](#)
- scoreModules, [23](#)

- wesBinaryGradient, [24](#)