

# Package ‘scRNAseqApp’

September 23, 2024

**Title** A single-cell RNAseq Shiny app-package

**Version** 1.4.0

**Description** The scRNAseqApp is a Shiny app package designed for interactive visualization of single-cell data. It is an enhanced version derived from the ShinyCell, repackaged to accommodate multiple datasets. The app enables users to visualize data containing various types of information simultaneously, facilitating comprehensive analysis. Additionally, it includes a user management system to regulate database accessibility for different users.

**License** GPL-3

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.1

**VignetteBuilder** knitr

**biocViews** Visualization, SingleCell, RNASeq

**Depends** R (>= 4.3.0)

**Imports** bibtex, bslib, circlize, ComplexHeatmap, data.table, DBI, DT, GenomicRanges, GenomeInfoDb, ggdendro, ggforce, ggplot2, ggrepel, ggridges, grDevices, grid, gridExtra, htmltools, IRanges, jsonlite, magrittr, methods, patchwork, plotly, RColorBrewer, RefManageR, rhdf5, Rsamtools, RSQLite, rtracklayer, S4Vectors, scales, sscript, Seurat, SeuratObject, shiny, shinyhelper, shinymanager, slingshot, SingleCellExperiment, sortable, stats, tools, xfun, xml2, utils

**Suggests** rmarkdown, knitr, testthat, BiocStyle

**Enhances** celldex, future, SingleR, SummarizedExperiment, tricycle

**URL** <https://github.com/jianhong/scRNAseqApp>

**BugReports** <https://github.com/jianhong/scRNAseqApp/issues>

**git\_url** <https://git.bioconductor.org/packages/scRNAseqApp>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** c90cf34

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-09-22

**Author** Jianhong Ou [aut, cre] (<<https://orcid.org/0000-0002-8652-2488>>)

**Maintainer** Jianhong Ou <jianhong.ou@duke.edu>

## Contents

APPconf-class . . . . .	2
APPconf-methods . . . . .	3
createAppConfig . . . . .	5
createDataSet . . . . .	6
createSeuFromCellRanger . . . . .	7
createSeuFromMatrix . . . . .	8
scInit . . . . .	8
scRNAseqApp . . . . .	9

<b>Index</b>	<b>11</b>
--------------	-----------

---

APPconf-class	<i>Class "APPconf"</i>
---------------	------------------------

---

### Description

An object of class "APPconf" represents the metadata for a dataset.

### Usage

```
APPconf(...)
```

### Arguments

... Each argument in ... becomes an slot in the new "APPconf"-class.

### Value

A APPconf object.

**Slots**

title character(1). Title of the data  
 id character(1). Folder name of the data  
 species character(1). species  
 ref Reference information in a list with element bib, doi, pmid and entry. Entry must be an object of [bibentry](#)  
 type character(1). Type of the data, scRNAseq or scATACseq.  
 markers list. A list of data.frame represents cell markers.  
 keywords character. A vector of characters represents the keywords of the study.  
 groupCol character. The key group column name to separate the cells.

**Examples**

```

appconf <- readRDS(system.file("extdata", "data",
                              "pbmc_small", "appconf.rds", package="scRNAseqApp"))
appconf

```

---

APPconf-methods

*The methods for [APPconf-class](#)*


---

**Description**

The assessment and replacement methods for [APPconf-class](#)

**Usage**

```

## S4 method for signature 'APPconf'
show(object)

## S4 method for signature 'APPconf'
x$name

## S4 replacement method for signature 'APPconf'
x$name <- value

## S4 method for signature 'APPconf,ANY,ANY'
x[[i, j, ..., exact = TRUE]]

## S4 replacement method for signature 'APPconf,ANY,ANY,ANY'
x[[i, j, ...]] <- value

## S4 method for signature 'APPconf,ANY,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'APPconf'

```

```

as.list(x, ...)

## S4 method for signature 'APPconf'
as.character(x, ...)

## S4 method for signature 'APPconf'
markers(x)

## S4 method for signature 'APPconf'
lapply(X, FUN, ...)

## S4 method for signature 'APPconf'
unlist(x, recursive = TRUE, use.names = TRUE)

```

### Arguments

object	an object of APPconf
x	APPconf object.
name	A literal character string or a name (possibly backtick quoted).
value	value to replace.
i, j	indices specifying elements to extract or replace.
...	Named or unnamed arguments to form a signature.
exact	see <a href="#">Extract</a>
drop	see <a href="#">drop</a>
X	an APPconf cobject.
FUN	function used by lapply
recursive, use.names	function used by <a href="#">unlist</a>

### Value

A named character vector.

### Examples

```

appconf <- readRDS(system.file("extdata", "data",
  "pbmc_small", "appconf.rds", package="scRNAseqApp"))
appconf
appconf$title
appconf[["title"]]
as.list(appconf)
as.character(appconf)
markers(appconf)
lapply(appconf, print)
unlist(appconf)

```

---

createAppConfig      *Create a metadata to describe the dataset*

---

## Description

The function will return a APPconf object which contain the reference, keywords for the dataset.

## Usage

```
createAppConfig(  
  title,  
  destinationFolder,  
  species,  
  doi,  
  pmid,  
  bibentry,  
  datatype = c("scRNAseq", "scATACseq", "scMultiome"),  
  markers,  
  keywords,  
  abstract  
)
```

## Arguments

title	The title of the dataset
destinationFolder	The destination folder name of the dataset without the root folder of the datasets. The data will be saved as appdataFolder/destinationFolder
species	The species of the dataset
doi, pmid	The DOI or PMID of the reference
bibentry	An object of bibentry
datatype	character(1). Type of the data, scRNAseq, scATACseq or scMultiome.
markers	A list of data.frame with gene symbols as rownames or a character vector.
keywords	The keywords for the dataset. For example the condition, cell type, tissue information The keywords will be used for whole database search
abstract	The abstract of the reference.

## Value

An object of [APPconf](#) object

**Examples**

```

if(interactive()){
  config <- createAppConfig(
    title="pbmc_small",
    destinationFolder = "pbmc_small",
    species = "Homo sapiens",
    doi="10.1038/nbt.3192",
    datatype = "scRNAseq")
}

```

---

createDataSet	<i>Create a dataset Create a dataset from a Seurat object. The function will try to find the markers in the Misc data named as 'markers'. The misc data should be output of function FindAllMarkers.</i>
---------------	--

---

**Description**

Create a dataset Create a dataset from a Seurat object. The function will try to find the markers in the Misc data named as 'markers'. The misc data should be output of function FindAllMarkers.

**Usage**

```

createDataSet(
  appconf,
  seu,
  config,
  contrast,
  assayName,
  gexSlot = c("data", "scale.data", "counts"),
  atacAssayName,
  atacSlot = c("data", "scale.data", "counts"),
  LOCKER = FALSE,
  datafolder = "data",
  default.symbol = "rownames"
)

```

**Arguments**

appconf	a list object represent the information about the dataset
seu	a Seurat object
config	config file for makeShinyFiles
contrast	The contrast group
assayName	assay in single-cell data object to use for plotting gene expression, which must match one of the following: <ul style="list-style-type: none"> <li>Seurat objects: "RNA" or "integrated" assay, default is "RNA"</li> </ul>

gexSlot layer in single-cell assay to plot. Default is to use the "data" layer  
 atacAssayName assay in single-cell data object to use for plotting open chromatin.  
 atacSlot layer in single-cell atac assay to plot. Default is to use the "data" layer  
 LOCKER Set locker if the file is required login  
 datafolder app data folder  
 default.symbol character(1L) specifying the default rownames to be used. If use default, the gene symbols will be the row names of the assay. If one column name of the meta.feature of the assay is supplied, the function will try to extract the symbols from the meta.feature slot of the assay.

**Value**

The updated Seurat object.

**Examples**

```

library(Seurat)
if(interactive()){
  appconf <- createAppConfig(
    title="pbmc_small",
    destinationFolder = "pbmc_small",
    species = "Homo sapiens",
    doi="10.1038/nbt.3192",
    datatype = "scRNAseq")
  createDataSet(appconf, pbmc_small, datafolder=tempdir())
}

```

---

createSeuFromCellRanger  
*load data from cellRanger*

---

**Description**

load data from cellRanger

**Usage**

```
createSeuFromCellRanger(outsFolder)
```

**Arguments**

outsFolder the outs folder of cellRanger

**Value**

An SeuratObject

---

`createSeuFromMatrix`    *load data from a count matrix*

---

### Description

load data from a count matrix

### Usage

```
createSeuFromMatrix(matrix, meta, genes, cluster, ...)
```

### Arguments

<code>matrix</code>	count matrix
<code>meta</code>	cell-level meta data
<code>genes</code>	character. gene names, will be the rownames of the matrix
<code>cluster</code>	the cluster coordinates
<code>...</code>	The parameter passed to <code>read.delim</code> when read cluster file.

### Value

An `SeuratObject`

---

`scInit`    *Create a scRNAseqApp project*

---

### Description

To run `scRNAseqApp`, you need to first create a directory which contains the required files.

### Usage

```
scInit(
  app_path = getwd(),
  root = "admin",
  password = "scRNAseqApp",
  datafolder = "data",
  overwrite = FALSE,
  app_title = "scRNAseq Database",
  app_description =
    "This database is a collection of\n          single cell RNA-seq data.",
  passphrase = NULL
)
```



**Arguments**

app\_path            path, a directory where do you want to create the app  
 root                character(1), the user name for administrator  
 password            character(1), the password for administrator  
 datafolder         the folder where saved the dataset for the app  
 overwrite          logical(1), overwrite the app\_path if there is a project.  
 app\_title, app\_description    character(1). The title and description of the home page.  
 passphrase         A password to protect the data inside the database.

**Value**

no returns. This function will copy files to app\_path

**Examples**

```

if(interactive()){
  scInit()
}

```

---

scRNAseqApp	<i>scRNAseqApp main function</i>
-------------	----------------------------------

---

**Description**

create a scRNAseqApp once the initialization is done.

**Usage**

```

scRNAseqApp(
  app_path = getwd(),
  datafolder = "data",
  defaultDataset = "pbmc_small",
  windowTitle = "scRNAseq/scATACseq database",
  banner = system.file("assets", "img", "banner.png", package = "scRNAseqApp"),
  footer = tagList(HTML("&copy;"), "2020 -", format(Sys.Date(), "%Y"), "jianhong@duke"),
  maxRequestSize = 1073741824,
  timeout = 30,
  theme = bs_theme(bootswatch = "lumen"),
  use_bs_themer = FALSE,
  ...
)

```

**Arguments**

app_path	path, a directory where do you want to create the app
datafolder	the folder where saved the dataset for the app
defaultDataset	default dataset for the app.
windowTitle	The title that should be displayed by the browser window.
banner	The banner image.
footer	The footer html contents.
maxRequestSize	Maximal upload file size. Default is 1G.
timeout	Timeout session (minutes) before logout if sleeping. Default to 30. 0 to disable.
theme	A theme.
use_bs_themer	logical(1). Used to determine the theme.
...	parameters can be passed to shinyApp except ui and server.

**Value**

An object that represents the app.

**Examples**

```
if(interactive()){  
  app_path=tempdir()  
  scInit(app_path=app_path)  
  setwd(app_path)  
  scRNAseqApp()  
}
```

# Index

- \* **APPconf**
  - APPconf-methods, 3
  - [, APPconf, ANY, ANY, ANY-method (APPconf-methods), 3
  - [[, APPconf, ANY, ANY-method (APPconf-methods), 3
  - [[<- , APPconf, ANY, ANY, ANY-method (APPconf-methods), 3
  - \$, APPconf-method (APPconf-methods), 3
  - \$<- , APPconf-method (APPconf-methods), 3
  
- APPconf, 5
- APPconf (APPconf-class), 2
- APPconf-class, 2, 3
- APPconf-methods, 3
- as.character, APPconf-method (APPconf-methods), 3
- as.list, APPconf-method (APPconf-methods), 3
  
- bibentry, 3
  
- createAppConfig, 5
- createDataSet, 6
- createSeuFromCellRanger, 7
- createSeuFromMatrix, 8
  
- drop, 4
  
- Extract, 4
  
- lapply, APPconf-method (APPconf-methods), 3
  
- markers (APPconf-methods), 3
- markers, APPconf-method (APPconf-methods), 3
  
- scInit, 8
- scRNAseqApp, 9
- show, APPconf-method (APPconf-methods), 3
  
- unlist, 4
- unlist, APPconf-method (APPconf-methods), 3