

Package ‘IterativeHardThresholding’

January 20, 2025

Type Package

Title Iterative Hard Thresholding Extensions to Cyclops

Version 1.0.2

Date 2022-9-7

Maintainer Marc A. Suchard <msuchard@ucla.edu>

Description Fits large-scale regression models with a penalty that restricts the maximum number of non-zero regression coefficients to a prespecified value. While Chu et al (2020) <[doi:10.1101/gigascience/giaa044](https://doi.org/10.1101/gigascience/giaa044)> describe the basic algorithm, this package uses Cyclops for an efficient implementation.

License Apache License 2.0

Depends R (>= 3.2.2), Cyclops (>= 1.3.0)

Imports ParallelLogger

Suggests testthat, knitr, rmarkdown

Encoding UTF-8

RoxigenNote 7.2.0

NeedsCompilation no

Author Marc A. Suchard [aut, cre],
Patrick Ryan [aut],
Observational Health Data Sciences and Informatics [cph]

Repository CRAN

Date/Publication 2022-09-08 06:42:59 UTC

Contents

createFastIhtPrior	2
createIhtPrior	3

Index

4

`createFastIhtPrior` *Create a fastIHT Cyclops prior object*

Description

`createFastIhtPrior` creates a fastIHT Cyclops prior object for use with [fitCyclopsModel](#).

Usage

```
createFastIhtPrior(
  K,
  penalty = 0,
  exclude = c(),
  forceIntercept = FALSE,
  fitBestSubset = FALSE,
  initialRidgeVariance = 10000,
  tolerance = 1e-08,
  maxIterations = 10000,
  threshold = 1e-06
)
```

Arguments

<code>K</code>	Maximum # of non-zero covariates
<code>penalty</code>	Specifies the IHT penalty
<code>exclude</code>	A vector of numbers or covariateId names to exclude from prior
<code>forceIntercept</code>	Logical: Force intercept coefficient into regularization
<code>fitBestSubset</code>	Logical: Fit final subset with no regularization
<code>initialRidgeVariance</code>	Numeric: variance used for algorithm initiation
<code>tolerance</code>	Numeric: maximum abs change in coefficient estimates from successive iterations to achieve convergence
<code>maxIterations</code>	Numeric: maximum iterations to achieve convergence
<code>threshold</code>	Numeric: absolute threshold at which to force coefficient to 0

Value

An IHT Cyclops prior object of class inheriting from "cyclopsPrior" for use with [fitCyclopsModel](#).

Examples

```
nobs = 500; ncovs = 100
prior <- createFastIhtPrior(K = 3, penalty = log(ncovs), initialRidgeVariance = 1 / log(ncovs))
```

createIhtPrior*Create an IHT Cyclops prior object*

Description

`createIhtPrior` creates an IHT Cyclops prior object for use with [fitCyclopsModel](#).

Usage

```
createIhtPrior(  
  K,  
  penalty = "bic",  
  exclude = c(),  
  forceIntercept = FALSE,  
  fitBestSubset = FALSE,  
  initialRidgeVariance = 0.1,  
  tolerance = 1e-08,  
  maxIterations = 10000,  
  threshold = 1e-06,  
  delta = 0  
)
```

Arguments

K	Maximum # of non-zero covariates
penalty	Specifies the IHT penalty; possible values are ‘BIC’ or ‘AIC’ or a numeric value
exclude	A vector of numbers or covariateId names to exclude from prior
forceIntercept	Logical: Force intercept coefficient into regularization
fitBestSubset	Logical: Fit final subset with no regularization
initialRidgeVariance	Numeric: variance used for algorithm initiation
tolerance	Numeric: maximum abs change in coefficient estimates from successive iterations to achieve convergence
maxIterations	Numeric: maximum iterations to achieve convergence
threshold	Numeric: absolute threshold at which to force coefficient to 0
delta	Numeric: change from 2 in ridge norm dimension

Value

An IHT Cyclops prior object of class inheriting from "cyclopsPrior" for use with [fitCyclopsModel](#).

Examples

```
prior <- createIhtPrior(K = 10)
```

Index

`createFastIhtPrior`, 2

`createIhtPrior`, 3

`fitCyclopsModel`, 2, 3