

Package ‘SlidingWindows’

January 20, 2025

Type Package

Title Methods for Time Series Analysis

Description A collection of functions to perform Detrended Fluctuation Analysis (DFA exponent), GUEDES et al. (2019) <[doi:10.1016/j.physa.2019.04.132](https://doi.org/10.1016/j.physa.2019.04.132)>, Detrended cross-correlation coefficient (RHODCCA), GUEDES & ZEBENDE (2019) <[doi:10.1016/j.physa.2019.121286](https://doi.org/10.1016/j.physa.2019.121286)>, DMCA cross-correlation coefficient and Detrended multiple cross-correlation coefficient (DMC), GUEDES & SILVA-FILHO & ZEBENDE (2018) <[doi:10.1016/j.physa.2021.125990](https://doi.org/10.1016/j.physa.2021.125990)>, both with sliding windows approach.

Version 0.2.0

Date 2021-04-10

Maintainer Everaldo Freitas Guedes <efgestatistico@gmail.com>

License GPL-3

URL <https://github.com/efguedes/SlidingWindows>

BugReports <https://github.com/efguedes/SlidingWindows>

NeedsCompilation no

Encoding UTF-8

Imports stats, DCCA, PerformanceAnalytics, nonlinearTseries,
TSEntropies

Suggests xts, zoo, quantmod

RoxigenNote 7.1.1

Author Everaldo Freitas Guedes [aut, cre]
(<<https://orcid.org/0000-0002-2986-7367>>),
Ivan Costa da Cunha Lima [aut]
(<<https://orcid.org/0000-0002-4525-2346>>),
Gilney Figueira Zebende [aut] (<<https://orcid.org/0000-0003-2420-9805>>),
Aloísio Machado Silva-Filho [aut]
(<<https://orcid.org/0000-0001-8250-1527>>)

Repository CRAN

Date/Publication 2021-04-11 04:20:02 UTC

Contents

descriptive.SlidingWindows	2
dfa.SlidingWindows	3
dmc.SlidingWindows	4
dmca.SlidingWindows	5
entropy.SlidingWindows	6
rhodcca.SlidingWindows	7
SlidingWindows	8
Index	9

descriptive.SlidingWindows

Descriptive statistics with sliding windows.

Description

This function generates descriptive statistics of a univariate time series with sliding windows approach.

Usage

```
descriptive.SlidingWindows(y, w = 99, skewness = "moment", kurtosis = "moment")
```

Arguments

- | | |
|----------|--|
| y | A vector containing univariate time series. |
| w | An integer value indicating the window size $w < \text{length}(y)$. If $w = \text{length}(y)$, will be computed the function will not slide. |
| skewness | A non-numeric value. See PerformanceAnalytics package. |
| kurtosis | A non-numeric value. See PerformanceAnalytics package. |

Details

This function include following measures: min, max, mean, median, standard deviation, skewness and kurtosis.

Value

A list containing "w", "min", "max", "mean", "median", "standard deviation", "skewness" and "kurtosis".

References

Guedes, E.F. Modelo computacional para análise de movimentos e co-movimentos de mercados financeiros, Ph.D. thesis, Programa de Pós-graduação em Modelagem Computacional e Tecnologia Industrial. Centro Universitário Senai Cimatec, 2019.

Examples

```
y <- rnorm(100)
descriptive.SlidingWindows(y, w=99, skewness="moment", kurtosis="moment")
```

dfa.SlidingWindows *Detrended Fluctuation Analysis with sliding windows.*

Description

This function generates scaling exponents (long-range correlations) of a univariate time series with sliding windows approach.

Usage

```
dfa.SlidingWindows(y, w = 98, k = 10, npoints = 15)
```

Arguments

y	A vector containing univariate time series.
w	An integer value indicating the window size $w < \text{length}(y)$. If $w = \text{length}(y)$, will be computed the function will not slide.
k	An integer value indicating the boundary of the division (N/k). The smallest value of k is 4.
npoints	The number of different time scales that will be used to estimate the Fluctuation function in each zone. See nonlinearTseries package.

Details

This function include following measures: alpha_dfa, se_alpha_dfa, r2_alpha_dfa.

Value

A list contaning "w", "alpha_dfa", "se_alpha_dfa", "r2_alpha_dfa".

References

GUEDES, E.F.; FERREIRA, P.; DIONISIO, A.; ZEBENDE, G.F. An econophysics approach to study the effect of BREXIT referendum on European Union stock markets. PHYSICA A, v.523, p.1175-1182, 2019. doi = "doi.org/10.1016/j.physa.2019.04.132".

FERREIRA, P.; DIONISIO, A.; GUEDES, E.F.; ZEBENDE, G.F. A sliding windows approach to analyse the evolution of bank shares in the European Union. PHYSICA A, v.490, p.1355-1367, 2018. doi = "doi.org/10.1016/j.physa.2017.08.095".

Examples

```
y <- rnorm(100)
dfa.SlidingWindows(y,w=99,k=10,npoints=15)
```

dmc.SlidingWindows *Detrended multiple cross-correlation coefficient with sliding windows.*

Description

This function generates DMC Coefficient of three time series with sliding windows approach.

Usage

```
dmc.SlidingWindows(x1, x2, y, w = 98, k = 10, method = "rhodcca", nu = 0)
```

Arguments

x1	A vector containing univariate time series.
x2	A vector containing univariate time series.
y	A vector containing univariate time series.
w	An integer value indicating the window size $w < \text{length}(y)$. If $w = \text{length}(y)$, will be computed the function will not slide.
k	An integer value indicating the boundary of the division (N/k). The smallest value of k is 4.
method	A character string indicating which correlation coefficient is to be used. If method = "rhodcca" (default) the dmc coefficient is generated from the DCCA coefficient. If method = "dmca", the dmc coefficient is generated from the DMCA coefficient.
nu	An integer value. See the DCCA package.

Details

This function include following measures: w, timescale, dmc and cross-correlation between: yx1, yx2, x1x2

Value

A list containing "w", "dmc", "yx1", "yx2", "x1x2".

References

ZEBENDE, G.; SILVA-FILHO, A.M. Detrended multiple cross-correlation coefficient, Physica A 510, 91-97, 2018. doi="doi.org/10.1016/j.physa.2018.06.119".

GUEDES,E.F.;SILVA-FILHO, A.M.; ZEBENDE, G.F. Detrended multiple cross-correlation coefficient with sliding windows approach. Physica A, 125990, 2021. doi="doi.org/10.1016/j.physa.2021.125990".

Examples

```
x1 <- rnorm(100)
x2 <- rnorm(100)
y <- rnorm(100)
dmc.SlidingWindows(x1,x2,y,w=99,k=10,nu=0, method="rhodcca")
dmc.SlidingWindows(x1,x2,y,w=99,k=10,nu=0, method="dmca")
```

dmca.SlidingWindows *DMCA coefficient with sliding windows.*

Description

This function generates Detrending moving-average cross-correlation coefficient of two time series with sliding windows approach.

Usage

```
dmca.SlidingWindows(x, y, w = 98, k = 10)
```

Arguments

- x A vector containing univariate time series.
- y A vector containing univariate time series.
- w An integer value indicating the window size $w < \text{length}(y)$. If $w = \text{length}(y)$, will be computed the function will not slide.
- k An integer value indicating the boundary of the division (N/k). The smallest value of k is 4.

Details

This function include following measures: w, timescale, dmca

Value

A list containing "w", "timescale", "dmca".

References

KRISTOUFEK, L. Detrending moving-average cross-correlation coefficient: Measuring cross-correlations between non-stationary series. PHYSICA A, v.406, p.169-175, 2014. doi="doi.org/10.1016/j.physa.2014.03.015".

Examples

```
x <- rnorm(100)
y <- rnorm(100)
dmca.SlidingWindows(x,y,w=99,k=10)
```

entropy.SlidingWindows

Approximate entropy with sliding windows.

Description

This function computes approximate entropy of a univariate time series with sliding windows approach.

Usage

```
entropy.SlidingWindows(y, w = 99, k = 4, dim = 2, r = 0.5, lag = 1)
```

Arguments

y	A vector containing univariate time series.
w	An integer value indicating the window size $w < \text{length}(y)$. If $w = \text{length}(y)$, will be computed the function will not slide.
k	An integer value indicating the boundary of the division (N/k). The smallest value of k is 4.
dim	The dimension of given time series. See TSEntropies package.
r	The radius of searched areas. See TSEntropies package.
lag	The downsampling. See TSEntropies package.

Details

This function return the list with time series sliding windows.

Value

A list contaning "w", "ApEn", "FastApEn".

References

Pincus, S.M. (1991). Approximate entropy as a measure of system complexity. Proc. Natl. Acad. Sci. USA, Vol. 88, pp. 2297–2301. doi="doi.org/10.1073/pnas.88.6.2297".

Examples

```
y <- rnorm(100)
entropy.SlidingWindows(y, w=99, k=4, dim=2, r=.2, lag=1)
```

rhodcca.SlidingWindows

Detrended Cross-Correlation Coefficient with sliding windows.

Description

This function generates Detrended Cross-Correlation Coefficient of two time series with sliding windows approach.

Usage

```
rhodcca.SlidingWindows(x, y, w = 98, k = 10, nu = 0)
```

Arguments

x	A vector containing univariate time series.
y	A vector containing univariate time series.
w	An integer value indicating the window size $w < \text{length}(y)$. If $w = \text{length}(y)$, will be computed the function will not slide.
k	An integer value indicating the boundary of the division (N/k). The smallest value of k is 4.
nu	An integer value. See DCCA package.

Details

This function include following measures:

w, timescale, rhodcca

Value

A list containing "w", "timescale", "rhodcca".

References

GUEDES, E.F.; ZEBENDE, G.F. DCCA cross-correlation coefficient with sliding windows approach. PHYSICA A, v.527, p.121286, 2019. doi="doi.org/10.1016/j.physa.2010.10.022".

ZEBENDE, G.F. DCCA cross-correlation coefficient: Quantifying level of cross-correlation, Physica A, v. 390, n. 4, p. 614-618, 2011. doi="doi.org/10.1016/j.physa.2019.121286".

Examples

```
x <- rnorm(100)
y <- rnorm(100)
rhodcca.SlidingWindows(x,y,w=99,k=10,nu=0)
```

SlidingWindows*Sliding Windows.*

Description

This function generates sliding windows approach of a time series.

Usage

```
SlidingWindows(y, w = 99)
```

Arguments

- | | |
|---|--|
| y | A vector containing univariate time series. |
| w | An integer value indicating the window size $w < \text{length}(y)$. If $w = \text{length}(y)$, will be computed the function will not slide. |

Details

This function return the matrix with time series sliding windows.

Value

A list containing "w", "SlidingWindows".

References

Guedes, E.F. Modelo computacional para análise de movimentos e co-movimentos de mercados financeiros, Ph.D. thesis, Programa de Pós-graduação em Modelagem Computacional e Tecnologia Industrial. Centro Universitário Senai Cimatec, 2019.

Examples

```
y <- rnorm(100)
SlidingWindows(y,w=99)
```

Index

descriptive.SlidingWindows, 2

dfa.SlidingWindows, 3

dmc.SlidingWindows, 4

dmca.SlidingWindows, 5

entropy.SlidingWindows, 6

rhodcca.SlidingWindows, 7

SlidingWindows, 8