

Package ‘pam’

August 27, 2025

Type Package

Title Fast and Efficient Processing of PAM Data

Version 1.0.6

URL <https://github.com/biotoolbox/pam>

BugReports <https://github.com/biotoolbox/pam/issues>

Description Processing Chlorophyll Fluorescence & P700 Absorbance data generated by WALZ hardware. Four models are provided for the regression of Pi curves, which can be compared with each other in order to select the most suitable model for the data set. Control plots ensure the successful verification of each regression. Bundled output of alpha, ETRmax, Ik etc. enables fast and reliable further processing of the data.

License GPL-3

Encoding UTF-8

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

RoxygenNote 7.3.2

Imports rlang, data.table, dplyr, ggplot2, minpack.lm, cowplot,
gridExtra, ggthemes

NeedsCompilation no

Author Julien Böhm [cre, aut] (ORCID: <<https://orcid.org/0009-0002-2704-2289>>),
Philipp Schrag [aut] (ORCID: <<https://orcid.org/0009-0002-7697-5536>>)

Maintainer Julien Böhm <julien.boehm@uni-rostock.de>

Repository CRAN

Date/Publication 2025-08-27 16:20:10 UTC

Contents

combo_plot_control	2
compare_regression_models_ETR_I	3
compare_regression_models_ETR_II	5
eilers_peeters_default_start_value_a	6

eilers_peeters_default_start_value_b	7
eilers_peeters_default_start_value_c	7
eilers_peeters_generate_regression_ETR_I	8
eilers_peeters_generate_regression_ETR_II	9
eilers_peeters_modified	10
platt_default_start_value_alpha	12
platt_default_start_value_beta	12
platt_default_start_value_ps	12
platt_generate_regression_ETR_I	13
platt_generate_regression_ETR_II	14
platt_modified	15
plot_control	17
read_dual_pam_data	18
read_junior_pam_data	19
vollenweider_default_start_value_a	20
vollenweider_default_start_value_alpha	20
vollenweider_default_start_value_n	21
vollenweider_default_start_value_pmax	21
vollenweider_generate_regression_ETR_I	22
vollenweider_generate_regression_ETR_II	23
vollenweider_modified	24
walsby_default_start_value_alpha	26
walsby_default_start_value_beta	26
walsby_default_start_value_etr_max	27
walsby_generate_regression_ETR_I	27
walsby_generate_regression_ETR_II	28
walsby_modified	30
write_model_result_csv	31
Index	33

combo_plot_control	<i>Combined ETR Plot and Summary Table</i>
--------------------	--

Description

Generates a plot of ETR data with different regression model predictions and a summary table.

Usage

```
combo_plot_control(title, data, model_results, name_list, color_list)
```

Arguments

title	Character. Plot title.
data	Data frame. ETR and PAR data.
model_results	List. Regression data and parameters.
name_list	List. Names for models (legend and table).
color_list	List. Colors for model lines.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#combo_control_plot.

Value

A plot with ETR data, regression results, and a summary table.

```
#' @examples path <- file.path(system.file("extdata", package = "pam"), "20240925.csv") data <-
read_dual_pam_data(path)

model_results_eilers_peeters <- eilers_peeters_generate_regression_ETR_I(data) model_results_platt
<- platt_generate_regression_ETR_I(data) model_results <- list(eilers_peeters_modified(model_results),
platt_modified(model_results)) name_list <- c("Eilers-Peeters", "Platt") color_list <- c("red", "pink")
plot <- combo_plot_control("test", data, model_results, name_list, color_list)
```

compare_regression_models_ETR_I

Compare Regression Models for ETR I

Description

Compares multiple regression models for electron transport rate (ETR) data using predefined performance metrics.

Usage

```
compare_regression_models_ETR_I(data_dir)
```

Arguments

data_dir	A character string specifying the directory containing input data files.
----------	--

Details

This function compares the performance of the following models:

- Eilers-Peeters (1988)
- Platt (1980)
- Vollenweider (1965)
- Walsby (1997)

Models are ranked based on the deviation between observed and predicted values. The results guide users in selecting the most appropriate model for their dataset. Start values for parameters cannot be adjusted within this function. A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#walsby_modified

Value

A vector with total points assigned to each regression model based on their performance. Models are ranked as follows:

- 1st place: 3 points
- 2nd place: 2 points
- 3rd place: 1 point
- 4th place: 0 points

If regression is not possible for a model, no points are awarded for any of the models for the respective file.

References

- Eilers, P. H. C., & Peeters, J. C. H. (1988). *A model for the relationship between light intensity and the rate of photosynthesis in phytoplankton*. Ecological Modelling, 42(3-4), 199-215. Available at: doi: [10.1016/03043800\(88\)900579](https://doi.org/10.1016/03043800(88)900579)
- Platt, T., Gallegos, C. L., & Harrison, W. G. (1980). *Photoinhibition of photosynthesis in natural assemblages of marine phytoplankton*. Journal of Marine Research, 38(4). Available at: https://elischolar.library.yale.edu/journal_of_marine_research/1525/.
- Romoth, K., Nowak, P., Kempke, D., Dietrich, A., Porsche, C., & Schubert, H. (2019). *Acclimation limits of Fucus evanescens along the salinity gradient of the southwestern Baltic Sea*. Botanica Marina, 62(1), 1-12. Available at: doi: [10.1515/bot20180098](https://doi.org/10.1515/bot20180098).
- Vollenweider, R. A. (1965). *Calculation models of photosynthesis-depth curves and some implications regarding day rate estimates in primary production measurements*. In C. R. Goldman (Ed.), *Primary Productivity in Aquatic Environments* (pp. 427-457). Mem. Ist. Ital. Idrobiol., 18 Suppl., University of California Press, Berkeley.
- Walsby, A. E. (1997). *Numerical integration of phytoplankton photosynthesis through time and depth in a water column*. New Phytologist, 136(2), 189-209. Available at: doi: [10.1046/j.1469-8137.1997.00736.x](https://doi.org/10.1046/j.1469-8137.1997.00736.x).

Examples

```
path <- file.path(system.file("extdata", package = "pam"))
points <- compare_regression_models_ETR_I(path)
```

`compare_regression_models_ETR_II`*Compare Regression Models for ETR II*

Description

Compares multiple regression models for electron transport rate (ETR) data using predefined performance metrics.

Usage

```
compare_regression_models_ETR_II(data_dir)
```

Arguments

`data_dir` A character string specifying the directory containing input data files.

Details

This function compares the performance of the following models:

- Eilers-Peeters (1988)
- Platt (1980)
- Vollenweider (1965)
- Walsby (1997)

Models are ranked based on the deviation between observed and predicted values. The results guide users in selecting the most appropriate model for their dataset. Start values for parameters cannot be adjusted within this function. A detailed documentation can be found in the README.

Value

A vector with total points assigned to each regression model based on their performance. Models are ranked as follows:

- 1st place: 3 points
- 2nd place: 2 points
- 3rd place: 1 point
- 4th place: 0 points

If regression is not possible for a model, no points are awarded for any of the models for the respective file.

References

- Eilers, P. H. C., & Peeters, J. C. H. (1988). *A model for the relationship between light intensity and the rate of photosynthesis in phytoplankton*. Ecological Modelling, 42(3-4), 199-215. Available at: doi: [10.1016/03043800\(88\)900579](https://doi.org/10.1016/03043800(88)900579)
- Platt, T., Gallegos, C. L., & Harrison, W. G. (1980). *Photoinhibition of photosynthesis in natural assemblages of marine phytoplankton*. Journal of Marine Research, 38(4). Available at: https://elischolar.library.yale.edu/journal_of_marine_research/1525/.
- Romoth, K., Nowak, P., Kempke, D., Dietrich, A., Porsche, C., & Schubert, H. (2019). *Acclimation limits of Fucus evanescens along the salinity gradient of the southwestern Baltic Sea*. Botanica Marina, 62(1), 1-12. Available at: doi: [10.1515/bot20180098](https://doi.org/10.1515/bot20180098).
- Vollenweider, R. A. (1965). *Calculation models of photosynthesis-depth curves and some implications regarding day rate estimates in primary production measurements*. In C. R. Goldman (Ed.), *Primary Productivity in Aquatic Environments* (pp. 427-457). Mem. Ist. Ital. Idrobiol., 18 Suppl., University of California Press, Berkeley.
- Walsby, A. E. (1997). *Numerical integration of phytoplankton photosynthesis through time and depth in a water column*. New Phytologist, 136(2), 189-209. Available at: doi: [10.1046/j.1469-8137.1997.00736.x](https://doi.org/10.1046/j.1469-8137.1997.00736.x).

Examples

```
path <- file.path(system.file("extdata", package = "pam"))
points <- compare_regression_models_ETR_II(path)
```

```
eilers_peeters_default_start_value_a
```

Default start value

Description

Default start value

Usage

```
eilers_peeters_default_start_value_a
```

Format

An object of class numeric of length 1.

eilers_peeters_default_start_value_b
<i>Default start value</i>

Description

Default start value

Usage

eilers_peeters_default_start_value_b

Format

An object of class numeric of length 1.

eilers_peeters_default_start_value_c
<i>Default start value</i>

Description

Default start value

Usage

eilers_peeters_default_start_value_c

Format

An object of class numeric of length 1.

```
eilers_peeters_generate_regression_ETR_I
```

Eilers-Peeters Regression for ETR I

Description

Fits a regression model for ETR I based on Eilers-Peeters (1988), considering photoinhibition.

Usage

```
eilers_peeters_generate_regression_ETR_I(
  data,
  a_start_value = eilers_peeters_default_start_value_a,
  b_start_value = eilers_peeters_default_start_value_b,
  c_start_value = eilers_peeters_default_start_value_c
)
```

Arguments

<code>data</code>	A <code>data.table</code> from <code>read_dual_pam_data</code> .
<code>a_start_value</code>	Numeric. Starting value for a . Default: <code>a_start_values_eilers_peeters_default</code> .
<code>b_start_value</code>	Numeric. Starting value for b . Default: <code>b_start_values_eilers_peeters_default</code> .
<code>c_start_value</code>	Numeric. Starting value for c . Default: <code>c_start_values_eilers_peeters_default</code> .

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#eilers_peeters_generate_regression_etr_i-and-eilers_peeters_generate_regression_etr_ii.

Value

A list containing:

- `etr_regression_data`: Predicted ETR values.
- `sdiff`: Deviation between actual and predicted values.
- `a`, `b`, `c`: Fitted parameters.
- `pm`: Maximum ETR (p_m).
- `s`: Initial slope (s).
- `ik`: Transition point from light limitation to light saturation (I_k).
- `im`: PAR at maximum ETR (I_m).
- `w`: Peak sharpness (w).

References

Eilers, P. H. C., & Peeters, J. C. H. (1988). *A model for the relationship between light intensity and the rate of photosynthesis in phytoplankton*. Ecological Modelling, 42(3-4), 199-215. Available at: doi: [10.1016/03043800\(88\)900579](https://doi.org/10.1016/03043800(88)900579)

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- eilers_peeters_generate_regression_ETR_I(data)
```

eilers_peeters_generate_regression_ETR_II
Eilers-Peeters Regression for ETR II

Description

Fits a regression model for ETR II based on Eilers-Peeters (1988), considering photoinhibition.

Usage

```
eilers_peeters_generate_regression_ETR_II(
  data,
  a_start_value = eilers_peeters_default_start_value_a,
  b_start_value = eilers_peeters_default_start_value_b,
  c_start_value = eilers_peeters_default_start_value_c
)
```

Arguments

data	A data.table from read_dual_pam_data.
a_start_value	Numeric. Starting value for <i>a</i> . Default: a_start_values_eilers_peeters_default.
b_start_value	Numeric. Starting value for <i>b</i> . Default: b_start_values_eilers_peeters_default.
c_start_value	Numeric. Starting value for <i>c</i> . Default: c_start_values_eilers_peeters_default.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#eilers_peeters_generate_regression_etr_i-and-eilers_peeters_generate_regression_etr_ii.

Value

A list containing:

- `etr_regression_data`: Predicted ETR values.
- `sdiff`: Deviation between actual and predicted values.
- `a`, `b`, `c`: Fitted parameters.
- `pm`: Maximum ETR (p_m).
- `s`: Initial slope (s).
- `ik`: Transition point from light limitation to light saturation (I_k).
- `im`: PAR at maximum ETR (I_m).
- `w`: Peak sharpness (w).

References

Eilers, P. H. C., & Peeters, J. C. H. (1988). *A model for the relationship between light intensity and the rate of photosynthesis in phytoplankton*. Ecological Modelling, 42(3-4), 199-215. Available at: doi: [10.1016/03043800\(88\)900579](https://doi.org/10.1016/03043800(88)900579)

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- eilers_peeters_generate_regression_ETR_II(data)
```

eilers_peeters_modified

Eilers & Peeters Model Modification

Description

This function enhances the Eilers and Peeters (1988) model by adding parameters not originally included in the model, which were introduced by other models. It also renames parameters to a standardized naming convention used across all models.

Usage

```
eilers_peeters_modified(model_result)
```

Arguments

`model_result` A list containing the results of the model, including parameters such as `a`, `b`, `c`, `s`, `pm`, `ik`, `im`, and `w`.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#eilers_peeters_modified

Value

A modified model result as a list with the following elements:

- `etr_type`: ETR Type based on the model result.
- `etr_regression_data`: Regression data with ETR predictions based on the fitted model.
- `sdiff`: The difference between observed and predicted ETR values.
- `a`: The obtained parameter a.
- `b`: The obtained parameter b.
- `c`: The obtained parameter c.
- `d`: Not available, set to `NA_real_`.
- `alpha`: The initial slope of the light curve, transferred unchanged as `s`.
- `beta`: Not available, set to `NA_real_`.
- `etrmax_with_photoinhibition`: The maximum electron transport rate with photoinhibition, transferred as `pm`.
- `etrmax_without_photoinhibition`: Not available, set to `NA_real_`.
- `ik_with_photoinhibition`: PAR where the transition point from light limitation to light saturation is achieved with photoinhibition, transferred as `ik`.
- `ik_without_photoinhibition`: Not available, set to `NA_real_`.
- `im_with_photoinhibition`: The PAR at which the maximum electron transport rate is achieved with photoinhibition, transferred as `im`.
- `w`: The sharpness of the peak, transferred as `w`.
- `ib`: Not available, set to `NA_real_`.
- `etrmax_with_without_ratio`: Not available, set to `NA_real_`.

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- eilers_peeters_generate_regression_ETR_II(data)
modified_result <- eilers_peeters_modified(result)
```

platt_default_start_value_alpha
<i>Default start value</i>

Description

Default start value

Usage

platt_default_start_value_alpha

Format

An object of class numeric of length 1.

platt_default_start_value_beta
<i>Default start value</i>

Description

Default start value

Usage

platt_default_start_value_beta

Format

An object of class numeric of length 1.

platt_default_start_value_ps
<i>Default start value</i>

Description

Default start value

Usage

platt_default_start_value_ps

Format

An object of class numeric of length 1.

```
platt_generate_regression_ETR_I
```

Platt Regression for ETR I

Description

Fits the Platt (1980) regression model using original naming conventions.

Usage

```
platt_generate_regression_ETR_I(
  data,
  alpha_start_value = platt_default_start_value_alpha,
  beta_start_value = platt_default_start_value_beta,
  ps_start_value = platt_default_start_value_ps
)
```

Arguments

`data` A `data.table` from `read_dual_pam_data`.

`alpha_start_value` Numeric. Initial value for α . Default: `alpha_start_value_platt_default`.

`beta_start_value` Numeric. Initial value for β . Default: `beta_start_value_platt_default`.

`ps_start_value` Numeric. Initial value for P_s . Default: `ps_start_value_platt_default`.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#platt_generate_regression_etr_i-and-platt_generate_regression_etr_ii.

Value

A list containing:

- `etr_regression_data`: Predicted ETR values.
- `sdiff`: Deviation between actual and predicted ETR.
- `ps`: Maximum electron transport rate without photoinhibition (P_s).
- `alpha`: Initial slope of the light curve (α).
- `beta`: Photoinhibition (β).
- `pm`: Maximum electron transport rate with photoinhibition (P_m).
- `ik`: Transition PAR with photoinhibition (I_k).
- `is`: Transition PAR without photoinhibition (I_s).
- `im`: PAR at maximum ETR with photoinhibition (I_m).
- `ib`: (I_b)

References

Platt, T., Gallegos, C. L., & Harrison, W. G. (1980). *Photoinhibition of photosynthesis in natural assemblages of marine phytoplankton*. *Journal of Marine Research*, 38(4). Retrieved from https://elischolar.library.yale.edu/journal_of_marine_research/1525/.

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- platt_generate_regression_ETR_I(data)
```

platt_generate_regression_ETR_II
Platt Regression for ETR II

Description

Fits the Platt (1980) regression model using original naming conventions.

Usage

```
platt_generate_regression_ETR_II(
  data,
  alpha_start_value = platt_default_start_value_alpha,
  beta_start_value = platt_default_start_value_beta,
  ps_start_value = platt_default_start_value_ps
)
```

Arguments

data A data.table from read_dual_pam_data.

alpha_start_value Numeric. Initial value for α . Default: alpha_start_value_platt_default.

beta_start_value Numeric. Initial value for β . Default: beta_start_value_platt_default.

ps_start_value Numeric. Initial value for P_s . Default: ps_start_value_platt_default.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#platt_generate_regression_etr_i-and-platt_generate_regression_etr_ii.

Value

A list containing:

- `etr_regression_data`: Predicted ETR values.
- `sdiff`: Deviation between actual and predicted ETR.
- `ps`: Maximum electron transport rate without photoinhibition (P_s).
- `alpha`: Initial slope of the light curve (α).
- `beta`: Photoinhibition (β).
- `pm`: Maximum electron transport rate with photoinhibition (P_m).
- `ik`: Transition PAR with photoinhibition (I_k).
- `is`: Transition PAR without photoinhibition (I_s).
- `im`: PAR at maximum ETR with photoinhibition (I_m).
- `ib`: (I_b)

References

Platt, T., Gallegos, C. L., & Harrison, W. G. (1980). *Photoinhibition of photosynthesis in natural assemblages of marine phytoplankton*. *Journal of Marine Research*, 38(4). Retrieved from https://elischolar.library.yale.edu/journal_of_marine_research/1525/.

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- platt_generate_regression_ETR_II(data)
```

platt_modified

Platt Model Modification

Description

This function enhances the Platt (1980) model by adding parameters not originally included in the model, which were introduced by other models. It also renames parameters to a standardized naming convention used across all models.

Usage

```
platt_modified(model_result)
```

Arguments

`model_result` A list containing the results of the model, including parameters such as `etr_max`, `alpha`, and `beta`.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#platt_modified

Value

A modified model result as a list with the following elements:

- `etr_type`: ETR Type based on the model result.
- `etr_regression_data`: Regression data with ETR predictions based on the fitted model.
- `sdiff`: The difference between observed and predicted ETR values.
- `a`: Obtained parameter a, equal to `etrmax_without_photoinhibition`.
- `b`: Obtained parameter b, equal to `alpha`.
- `c`: Obtained parameter c, equal to `beta`.
- `d`: Not available, set to `NA_real_`.
- `alpha`: The initial slope of the light curve, transferred unchanged as `alpha`.
- `beta`: The photoinhibition of the light curve, transferred unchanged as `beta`.
- `etrmax_with_photoinhibition`: The maximum electron transport rate with photoinhibition, transferred as `pm`.
- `etrmax_without_photoinhibition`: The maximum electron transport rate without photoinhibition, transferred as `ps`.
- `ik_with_photoinhibition`: PAR where the transition point from light limitation to light saturation is achieved with photoinhibition, transferred as `ik`.
- `ik_without_photoinhibition`: PAR where the transition point from light limitation to light saturation is achieved without photoinhibition, transferred as `is`.
- `im_with_photoinhibition`: The PAR at which the maximum electron transport rate is achieved with photoinhibition, transferred as `im`.
- `w`: Not available, set to `NA_real_`.
- `ib`: Transferred unchanged as `ib`.
- `etrmax_with_without_ratio`: Ratio of `etrmax_with_photoinhibition` to `etrmax_without_photoinhibition`, and `ik_with_photoinhibition` to `ik_without_photoinhibition`.

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- platt_generate_regression_ETR_II(data)
modified_result <- platt_modified(result)
```

plot_control	<i>Plot Control</i>
--------------	---------------------

Description

This function creates a control plot for the used model based on the provided data and model results.

Usage

```
plot_control(data, model_result, title, color = "black")
```

Arguments

data	A 'data.table' containing the original ETR and yield data for the plot.
model_result	A list containing the fitting results of the used model and the calculated paramters (alpha, ik...).
title	A character string that specifies the title of the plot.
color	A color specification for the regression line in the plot.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#plot_control

Value

A plot displaying the original ETR and Yield values and the regression data. A table below the plot shows the calculated data (alpha, ik...)

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- eilers_peeters_generate_regression_ETR_I(data)
plot_control(data, result, "Control Plot")
```

read_dual_pam_data	<i>Read and Process DualPAM Data</i>
--------------------	--------------------------------------

Description

Reads raw CSV files generated by DualPAM software, calculates electron transport rate (ETR) values, and returns a cleaned dataset. Customization may be needed for non-DualPAM devices.

Usage

```
read_dual_pam_data(
  csv_path,
  remove_recovery = TRUE,
  etr_factor = 0.84,
  fraction_photosystem_I = 0.5,
  fraction_photosystem_II = 0.5
)
```

Arguments

csv_path	File path to the CSV file.
remove_recovery	Logical. Removes recovery measurements if TRUE. Default is TRUE.
etr_factor	Numeric. Factor for ETR calculation. Default is 0.84.
fraction_photosystem_I	Numeric. Relative distribution of absorbed PAR to photosystem I. Default is 0.5.
fraction_photosystem_II	Numeric. Relative distribution of absorbed PAR to photosystem II. Default is 0.5.

Details

Calculates ETR using:

$$\text{ETR} = \text{PAR} \cdot \text{ETR-Factor} \cdot \text{Fraction of Photosystem (I or II)} \cdot \text{Yield (I or II)}$$

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#read_dual_pam_data

Value

A ‘data.table’ with processed data and calculated ETR values.

References

Heinz Walz GmbH. (2024). *DUAL-PAM-100 DUAL-PAM/F MANUAL, 5th Edition, April 2024, Chapter 7 (pp. 162-172)*. Heinz Walz GmbH, Effeltrich, Germany. Available at: <https://www.walz.com/files/downloads/dualpamed05.pdf>

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)
```

read_junior_pam_data *Read and Process Junior PAM Data*

Description

Reads raw CSV files generated by Junior PAM software, calculates electron transport rate (ETR) values, and returns a cleaned dataset. Customization may be needed for non-DualPAM devices.

Usage

```
read_junior_pam_data(
  csv_path,
  remove_recovery = TRUE,
  etr_factor = 0.84,
  fraction_photosystem_I = 0.5,
  fraction_photosystem_II = 0.5
)
```

Arguments

csv_path	File path to the CSV file.
remove_recovery	Logical. Removes recovery measurements if TRUE. Default is TRUE.
etr_factor	Numeric. Factor for ETR calculation. Default is 0.84.
fraction_photosystem_I	Numeric. Relative distribution of absorbed PAR to photosystem I. Default is 0.5.
fraction_photosystem_II	Numeric. Relative distribution of absorbed PAR to photosystem II. Default is 0.5.

Details

Calculates ETR II using:

$$\text{ETR II} = \text{PAR} \cdot \text{ETR-Factor} \cdot \text{Fraction of Photosystem (II)} \cdot \text{Yield (II)}$$

A detailed documentation can be found under <https://github.com/biotoolbox/pam?tab=readme-ov-file>

Value

A 'data.table' with processed data and calculated ETR values.

References

Heinz Walz GmbH. (2024). *DUAL-PAM-100 DUAL-PAM/F MANUAL, 5th Edition, April 2024, Chapter 7 (pp. 162-172)*. Heinz Walz GmbH, Effeltrich, Germany. Available at: <https://www.walz.com/files/downloads/dualpamed05.pdf>

Examples

```
path <- file.path(system.file("extdata/junior_pam", package = "pam"), "junior_pam_20250613.csv")
data <- read_junior_pam_data(path)
```

```
vollenweider_default_start_value_a
```

Default start value

Description

Default start value

Usage

```
vollenweider_default_start_value_a
```

Format

An object of class `numeric` of length 1.

```
vollenweider_default_start_value_alpha
```

Default start value

Description

Default start value

Usage

```
vollenweider_default_start_value_alpha
```

Format

An object of class `numeric` of length 1.

vollenweider_default_start_value_n
<i>Default start value</i>

Description

Default start value

Usage

vollenweider_default_start_value_n

Format

An object of class numeric of length 1.

vollenweider_default_start_value_pmax
<i>Default start value</i>

Description

Default start value

Usage

vollenweider_default_start_value_pmax

Format

An object of class numeric of length 1.

vollenweider_generate_regression_ETR_I
Vollenweider Regression for ETR I

Description

Fits the Vollenweider (1965) regression model using original naming conventions from the publication.

Usage

```
vollenweider_generate_regression_ETR_I(
  data,
  pmax_start_value = vollenweider_default_start_value_a,
  a_start_value = vollenweider_default_start_value_a,
  alpha_start_value = vollenweider_default_start_value_alpha,
  n_start_value = vollenweider_default_start_value_n
)
```

Arguments

data	A data.table from read_dual_pam_data.
pmax_start_value	Numeric. Initial value for p_{max} . Default: pmax_start_values_vollenweider_default.
a_start_value	Numeric. Initial value for a . Default: a_start_values_vollenweider_default.
alpha_start_value	Numeric. Initial value for α . Default: alpha_start_values_vollenweider_default.
n_start_value	Numeric. Initial value for n . Default: n_start_values_vollenweider_default.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#vollenweider_generate_regression_etr_i-and-vollenweider_generate_regression_etr_ii.

Value

A list containing:

- `etr_regression_data`: Predicted ETR values.
- `sdiff`: Deviation between actual and predicted ETR.
- `pmax`: Maximum electron transport rate (p_{max}).
- `a`: Parameter a .
- `alpha`: Parameter α .
- `n`: Parameter n .

- `popt`: Maximum electron transport rate with photoinhibition (p_{opt}).
- `ik`: Transition point from light limitation to light saturation without photoinhibition (I_k).
- `iik`: Transition point from light limitation to light saturation with photoinhibition (I'_k).
- `pmax_popt_and_ik_iik_ratio`: Ratio of p_{max} to p_{opt} and I_k to I'_k .

References

Vollenweider, R. A. (1965). *Calculation models of photosynthesis-depth curves and some implications regarding day rate estimates in primary production measurements*, p. 427-457. In C. R. Goldman [ed.], *Primary Productivity in Aquatic Environments*. Mem. Ist. Ital. Idrobiol., 18 Suppl., University of California Press, Berkeley.

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- vollengewider_generate_regression_ETR_I(data)
```

vollenweider_generate_regression_ETR_II
Vollenweider Regression for ETR II

Description

Fits the Vollenweider (1965) regression model using original naming conventions from the publication.

Usage

```
vollenweider_generate_regression_ETR_II(
  data,
  pmax_start_value = vollengewider_default_start_value_pmax,
  a_start_value = vollengewider_default_start_value_a,
  alpha_start_value = vollengewider_default_start_value_alpha,
  n_start_value = vollengewider_default_start_value_n
)
```

Arguments

<code>data</code>	A data.table from <code>read_dual_pam_data</code> .
<code>pmax_start_value</code>	Numeric. Initial value for p_{max} . Default: <code>pmax_start_values_vollenweider_default</code> .
<code>a_start_value</code>	Numeric. Initial value for a . Default: <code>a_start_values_vollenweider_default</code> .
<code>alpha_start_value</code>	Numeric. Initial value for α . Default: <code>alpha_start_values_vollenweider_default</code> .
<code>n_start_value</code>	Numeric. Initial value for n . Default: <code>n_start_values_vollenweider_default</code> .

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#vollenweider_generate_regression_etr_i-and-vollenweider_generate_regression_etr_ii.

Value

A list containing:

- `etr_regression_data`: Predicted ETR values.
- `sdiff`: Deviation between actual and predicted ETR.
- `pmax`: Maximum electron transport rate (p_{max}).
- `a`: Parameter a .
- `alpha`: Parameter α .
- `n`: Parameter n .
- `popt`: Maximum electron transport rate with photoinhibition (p_{opt}).
- `ik`: Transition point from light limitation to light saturation without photoinhibition (I_k).
- `iik`: Transition point from light limitation to light saturation with photoinhibition (I'_k).
- `pmax_popt_and_ik_iik_ratio`: Ratio of p_{max} to p_{opt} and I_k to I'_k .

References

Vollenweider, R. A. (1965). *Calculation models of photosynthesis-depth curves and some implications regarding day rate estimates in primary production measurements*, p. 427-457. In C. R. Goldman [ed.], *Primary Productivity in Aquatic Environments*. Mem. Ist. Ital. Idrobiol., 18 Suppl., University of California Press, Berkeley.

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- vollenweider_generate_regression_ETR_II(data)
```

vollenweider_modified *Vollenweider Model Modification*

Description

This function adds parameters that were not originally included in the Vollenweider (1965) model, but were introduced by other models, and renames the parameters to a standardized one for all models.

Usage

```
vollenweider_modified(model_result)
```

Arguments

`model_result` A list containing the results of the model, including parameters such as `pmax`, `alpha`, and `ik`.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#vollenweider_modified

Value

A modified model result as a list containing the following elements:

- `etr_type`: ETR Type based on the model result.
- `etr_regression_data`: Regression data with ETR predictions based on the fitted model.
- `sdiff`: The difference between observed and predicted ETR values.
- `a`: Obtained parameter `a`, here equal to `etrmax_without_photoinhibition`.
- `b`: Obtained parameter `b`, transferred as `a`.
- `c`: Obtained parameter `c`, here transferred as `alpha`.
- `d`: Obtained parameter `d`, here transferred as `n`.
- `alpha`: The initial slope of the light curve.
- `beta`: Not available, here set to `NA_real_`.
- `etrmax_with_photoinhibition`: The maximum electron transport rate with photoinhibition, transferred as `popt`.
- `etrmax_without_photoinhibition`: The maximum electron transport rate without photoinhibition, transferred as `pmax`.
- `ik_with_photoinhibition`: PAR where the transition point from light limitation to light saturation is achieved taking photoinhibition into account, transferred as `iik`.
- `ik_without_photoinhibition`: PAR where the transition point from light limitation to light saturation is achieved not taking photoinhibition into account, transferred as `ik`.
- `im_with_photoinhibition`: The PAR at which the maximum electron transport rate is achieved by taking photoinhibition into account, determined using the regression data from the model.
- `w`: Not available, here set to `NA_real_`.
- `ib`: Transferred unchanged as `ib`.
- `etrmax_with_without_ratio`: Ratio of `etrmax_with_photoinhibition` to `etrmax_without_photoinhibition` and `ik_with_photoinhibition` to `ik_without_photoinhibition`.

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- vollenweider_generate_regression_ETR_II(data)
modified_result <- vollenweider_modified(result)
```

walsby_default_start_value_alpha
Default start value

Description

Default start value

Usage

walsby_default_start_value_alpha

Format

An object of class `numeric` of length 1.

walsby_default_start_value_beta
Default start value

Description

Default start value

Usage

walsby_default_start_value_beta

Format

An object of class `numeric` of length 1.

walsby_default_start_value_etr_max
Default start value

Description

Default start value

Usage

walsby_default_start_value_etr_max

Format

An object of class numeric of length 1.

walsby_generate_regression_ETR_I
Walsby Regression for ETR I

Description

Fits a modified Walsby (1997) regression model without the respiration term, using Romoth (2019) naming conventions. Calculates ETR_{max} without accounting for photoinhibition.

Usage

```
walsby_generate_regression_ETR_I(
  data,
  etr_max_start_value = walsby_default_start_value_etr_max,
  alpha_start_value = walsby_default_start_value_alpha,
  beta_start_value = walsby_default_start_value_alpha
)
```

Arguments

data A data.table from read_dual_pam_data.

etr_max_start_value Numeric. Initial value for ETR_{max} . Default: etr_max_start_value_walsby_default.

alpha_start_value Numeric. Initial value for α . Default: alpha_start_value_walsby_default.

beta_start_value Numeric. Initial value for β . Default: beta_start_value_walsby_default.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#walsby_generate_regression_etr_i-and-walsby_generate_regression_etr_ii.

Value

A list containing:

- `etr_regression_data`: Predicted ETR values.
- `sdiff`: Deviation between actual and predicted ETR.
- `etr_max`: Maximum ETR (ETR_{max}).
- `alpha`: Initial slope (α).
- `beta`: Photoinhibition factor (β).

References

Walsby, A. E. (1997). Numerical integration of phytoplankton photosynthesis through time and depth in a water column. *New Phytologist*, 136(2), 189-209. Available at: doi: [10.1046/j.1469-8137.1997.00736.x](https://doi.org/10.1046/j.1469-8137.1997.00736.x)

Romoth, K., Nowak, P., Kempke, D., Dietrich, A., Porsche, C., & Schubert, H. (2019). Acclimation limits of *Fucus evanescens* along the salinity gradient of the southwestern Baltic Sea. *Botanica Marina*, 62(1), 1-12. Available at: doi: [10.1515/bot20180098](https://doi.org/10.1515/bot20180098)

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- walsby_generate_regression_ETR_I(data)
```

walsby_generate_regression_ETR_II
Walsby Regression for ETR II

Description

Fits a modified Walsby (1997) regression model without the respiration term, using Romoth (2019) naming conventions. Calculates ETR_{max} without accounting for photoinhibition.

Usage

```
walsby_generate_regression_ETR_II(
  data,
  etr_max_start_value = walsby_default_start_value_etr_max,
  alpha_start_value = walsby_default_start_value_alpha,
  beta_start_value = walsby_default_start_value_beta
)
```

Arguments

`data` A `data.table` from `read_dual_pam_data`.

`etr_max_start_value` Numeric. Initial value for ETR_{max} . Default: `etr_max_start_value_walsby_default`.

`alpha_start_value` Numeric. Initial value for α . Default: `alpha_start_value_walsby_default`.

`beta_start_value` Numeric. Initial value for β . Default: `beta_start_value_walsby_default`.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#walsby_generate_regression_etr_i-and-walsby_generate_regression_etr_ii.

Value

A list containing:

- `etr_regression_data`: Predicted ETR values.
- `sdiff`: Deviation between actual and predicted ETR.
- `etr_max`: Maximum ETR (ETR_{max}).
- `alpha`: Initial slope (α).
- `beta`: Photoinhibition factor (β).

References

Walsby, A. E. (1997). Numerical integration of phytoplankton photosynthesis through time and depth in a water column. *New Phytologist*, 136(2), 189-209. Available at: doi: [10.1046/j.1469-8137.1997.00736.x](https://doi.org/10.1046/j.1469-8137.1997.00736.x)

Romoth, K., Nowak, P., Kempke, D., Dietrich, A., Porsche, C., & Schubert, H. (2019). Acclimation limits of *Fucus evanescens* along the salinity gradient of the southwestern Baltic Sea. *Botanica Marina*, 62(1), 1-12. Available at: doi: [10.1515/bot-20180098](https://doi.org/10.1515/bot-20180098)

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- walsby_generate_regression_ETR_II(data)
```

walsby_modified

Walsby Model Modification

Description

Enhances the Walsby (1997) model by adding parameters from other models and standardizing parameter names.

Usage

```
walsby_modified(model_result)
```

Arguments

`model_result` A list of model results including `etr_max`, `alpha`, and `beta`.

Details

A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#walsby_modified

Value

A list containing:

- `etr_type`: ETR Type based on the model result.
- `etr_regression_data`: Regression data with ETR predictions based on the fitted model.
- `sdiff`: The difference between observed and predicted ETR values.
- `a`: Obtained parameter `a`, equal to `etrmax_without_photoinhibition`.
- `b`: Obtained parameter `b`, equal to `alpha`.
- `c`: Obtained parameter `c`, equal to `beta`.
- `d`: Not available, set to `NA_real_`.
- `alpha`: The initial slope of the light curve, transferred unchanged as `alpha`.
- `beta`: The photoinhibition of the light curve, transferred unchanged as `beta`.
- `etrmax_with_photoinhibition`: The maximum electron transport rate with photoinhibition.
- `etrmax_without_photoinhibition`: The maximum electron transport rate without photoinhibition, transferred as `etr_max`.
- `ik_with_photoinhibition`: PAR where the transition point from light limitation to light saturation is achieved with photoinhibition.
- `ik_without_photoinhibition`: PAR where the transition point from light limitation to light saturation is achieved without photoinhibition.
- `im_with_photoinhibition`: PAR at the maximum ETR with photoinhibition.
- `w`: Not available, set to `NA_real_`.
- `ib`: Not available, set to `NA_real_`.
- `etrmax_with_without_ratio`: Ratio of `etrmax_with_photoinhibition` to `etrmax_without_photoinhibition`.

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- walsby_generate_regression_ETR_II(data)
modified_result <- walsby_modified(result)
```

```
write_model_result_csv
```

Write Model Result CSV

Description

This function exports the raw input data, regression data, and model parameters into separate CSV files for easy access and further analysis.

Usage

```
write_model_result_csv(dest_dir, name, data, model_result)
```

Arguments

<code>dest_dir</code>	A character string specifying the directory where the CSV files will be saved.
<code>name</code>	A character string specifying the base name for the output files.
<code>data</code>	A data frame containing the raw input data used in the model.
<code>model_result</code>	A list containing the model results, including parameter values and regression data.

Details

This function generates three CSV files:

1. **raw_data.csv:** Contains the original raw data used in the model.
2. **regression_data.csv:** Includes the regression data with predicted electron transport rate (ETR) values.
3. **model_result.csv:** Summarizes the parameter values derived from the model results (excluding regression data), such as alpha or beta.

The ‘name’ parameter serves as a prefix for each file, ensuring clarity and organization in the output directory. A detailed documentation can be found under https://github.com/biotoolbox/pam?tab=readme-ov-file#write_model_result_csv

Value

No return value, called for side effects

Examples

```
path <- file.path(system.file("extdata", package = "pam"), "20240925.csv")
data <- read_dual_pam_data(path)

result <- eilers_peeters_generate_regression_ETR_I(data)
write_model_result_csv(tempdir(), "20240925", data, result)
```

Index

* datasets

eilers_peeters_default_start_value_a, [6](#)
eilers_peeters_default_start_value_b, [7](#)
eilers_peeters_default_start_value_c, [7](#)
platt_default_start_value_alpha, [12](#)
platt_default_start_value_beta, [12](#)
platt_default_start_value_ps, [12](#)
vollenweider_default_start_value_a, [20](#)
vollenweider_default_start_value_alpha, [20](#)
vollenweider_default_start_value_n, [21](#)
vollenweider_default_start_value_pmax, [21](#)
walsby_default_start_value_alpha, [26](#)
walsby_default_start_value_beta, [26](#)
walsby_default_start_value_etr_max, [27](#)

combo_plot_control, [2](#)
compare_regression_models_ETR_I, [3](#)
compare_regression_models_ETR_II, [5](#)

eilers_peeters_default_start_value_a, [6](#)
eilers_peeters_default_start_value_b, [7](#)
eilers_peeters_default_start_value_c, [7](#)
eilers_peeters_generate_regression_ETR_I, [8](#)
eilers_peeters_generate_regression_ETR_II, [9](#)

eilers_peeters_modified, [10](#)
platt_default_start_value_alpha, [12](#)
platt_default_start_value_beta, [12](#)
platt_default_start_value_ps, [12](#)
platt_generate_regression_ETR_I, [13](#)
platt_generate_regression_ETR_II, [14](#)
platt_modified, [15](#)
plot_control, [17](#)
read_dual_pam_data, [18](#)
read_junior_pam_data, [19](#)
vollenweider_default_start_value_a, [20](#)
vollenweider_default_start_value_alpha, [20](#)
vollenweider_default_start_value_n, [21](#)
vollenweider_default_start_value_pmax, [21](#)
vollenweider_generate_regression_ETR_I, [22](#)
vollenweider_generate_regression_ETR_II, [23](#)
vollenweider_modified, [24](#)
walsby_default_start_value_alpha, [26](#)
walsby_default_start_value_beta, [26](#)
walsby_default_start_value_etr_max, [27](#)
walsby_generate_regression_ETR_I, [27](#)
walsby_generate_regression_ETR_II, [28](#)
walsby_modified, [30](#)
write_model_result_csv, [31](#)