

Package ‘auth0’

March 26, 2023

Type Package

Title Authentication in Shiny with Auth0

Version 0.2.3

Description Uses Auth0 API (see <<https://auth0.com>> for more information) to use a simple authentication system. It provides tools to log in and out a shiny application using social networks or a list of e-mails.

BugReports <https://github.com/curso-r/auth0/issues>

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.3

Imports httr, shiny, yaml, utils, shinyjs

Suggests knitr, rmarkdown

VignetteBuilder knitr

URL <https://curso-r.github.io/auth0/>

NeedsCompilation no

Author Julio Trecenti [cre],
Daniel Falbel [aut],
José Jesus [ctb],
Dean Attali [ctb],
C Lente [ctb]

Maintainer Julio Trecenti <julio.trecenti@gmail.com>

Repository CRAN

Date/Publication 2023-03-26 21:50:05 UTC

R topics documented:

auth0_config	2
auth0_find_config_file	2
auth0_info	3

auth0_logout_url	3
logout	4
logoutButton	5
logout_url	6
shinyAppAuth0	7
shinyAuth0App	7
ui-server	8
use_auth0	9

Index[10](#)

auth0_config *Parse _auth0.yml file.*

Description

Validates and creates a list of useful information from the _auth0.yml file.

Usage

```
auth0_config(config_file)
```

Arguments

config_file path to the _auth0.yml file. If not informed, will try to find the file using [auth0_find_config_file](#).

Value

List containing all the information from the _auth0.yml file.

auth0_find_config_file *Find the configuration file.*

Description

Tries to find the path to the _auth0.yml file. First, it tries to get this info from options(auth0_config_file =). If this option is NULL (the default) it tries to find the _auth0.yml within the working directory. If the file does not exist, it raises an error.

Usage

```
auth0_find_config_file()
```

Value

Character vector of length one containing the path of the `_auth0.yml` file.

See Also

[use_auth0](#).

auth0_info

Information used to connect to Auth0.

Description

Creates a list containing all the important information to connect to Auth0 service's API.

Usage

`auth0_info(config)`

Arguments

`config` path to the `_auth0.yml` file or the object returned by [auth0_config](#). If not informed, will try to find the file using [auth0_find_config_file](#).

Value

A list containing scope, state, keys, OAuth2.0 app, endpoints, audience and remote URL. For compatibility reasons, `remote_url` can be either a parameter in the root yaml or inside a `shiny_config` parameter.

See Also

[use_auth0](#) to create an `_auth0.yml` template.

auth0_logout_url

Generate logout URL

Description

`auth0_logout_url()` is defunct as of auth0 0.1.2 in order to simplify the user experience with the [logoutButton\(\)](#) function.

Usage

`auth0_logout_url(config_file = NULL, redirect_js = TRUE)`

Arguments

`config_file` Path to YAML configuration file.
`redirect_js` include javascript code to redirect page? Defaults to TRUE.

Examples

```
# simple UI with action button
# AFTER auth0 0.1.2

if (interactive()) {
  library(shiny)
  library(auth0)

  ui <- fluidPage(logoutButton())
  server <- function(input, output, session) {}
  config_file <- system.file("simple/_auth0.yml", package = "auth0")
  shinyAppAuth0(ui, server, config_file)

  # simple UI with action button
  # BEFORE auth0 0.1.2

  library(shiny)
  library(auth0)
  library(shinyjs)

  # note that you must include shinyjs::useShinyjs() for this to work
  ui <- fluidPage(shinyjs::useShinyjs(), actionButton("logout_auth0", "Logout"))

  # server with one observer that logouts
  server <- function(input, output, session) {
    observeEvent(input$logout_auth0, {
      # javascript code redirecting to correct url
      js <- auth0_logout_url()
      shinyjs::runjs(js)
    })
  }
  shinyAuth0App(ui, server, config_file)
}
```

Description

Log the current user out of an auth0 shiny app.

Usage

```
logout()
```

Details

You can also use a different configuration file by setting the auth0_config_file option with:
options(auth0_config_file = "path/to/file.yaml").

See Also

[logoutButton](#), [logout_url](#)

logoutButton

Create a button to log out

Description

A logoutButton is an [actionButton](#) that is meant to be used to log out of an auth0 Shiny app.

Usage

```
logoutButton(label = "Log out", ..., id = ".auth0logout_")
```

Arguments

label	The label on the button.
...	Named attributes to apply to the button.
id	An ID for the button. If you only have one logout button in your app, you do not need to explicitly provide an ID. If you have more than one logout button, you need to provide a unique ID to each button. When you create a button with a non-default ID, you must create an observer that listens to a click on this button and logs out of the app with a call to logout .

See Also

[logout](#), [logout_url](#)

Examples

```
if (interactive()) {
  ui <- fluidPage(
    logoutButton(),
    logoutButton(label = "Another logout button", id = "logout2")
  )
  server <- function(input, output, session) {
    observeEvent(input$logout2, {
      logout()
    })
  }
  shinyAuth0App(ui, server)
}
```

logout_url *Generate a logout URL*

Description

Generate a URL that will log the user out of the app if visited.

Usage

`logout_url()`

Details

You can also use a different configuration file by setting the `auth0_config_file` option with: `options(auth0_config_file = "path/to/file.yaml")`.

Value

URL string to log out.

See Also

[logoutButton](#), [logout](#)

shinyAppAuth0	<i>Create a Shiny app object with Auth0 Authentication</i>
---------------	--

Description

This function modifies ui and server objects to run using Auth0 authentication.

Usage

```
shinyAppAuth0(ui, server, config_file = NULL, ...)
```

Arguments

ui	an ordinary UI object to create shiny apps.
server	an ordinary server object to create shiny apps.
config_file	path to YAML configuration file.
...	Other arguments passed on to shiny::shinyApp() .

Details

You can also use a different configuration file by setting the auth0_config_file option with: `options(auth0_config_file = "path/to/file.yaml")`.

Disable auth0 while developing apps

Sometimes, using auth0 to develop and test apps can be frustrating, because every time the app is started, auth0 requires the user to log-in. To avoid this problem, one can run `options(auth0_disable = TRUE)` to disable auth0 temporarily.

shinyAuth0App	<i>Create a Shiny app object with Auth0 Authentication</i>
---------------	--

Description

As of auth0 0.1.2, shinAuth0App() has been renamed to [shinyAppAuth0\(\)](#) for consistency.

Usage

```
shinyAuth0App(ui, server, config_file = NULL)
```

Arguments

ui	an ordinary UI object to create shiny apps.
server	an ordinary server object to create shiny apps.
config_file	path to YAML configuration file.

ui-server*Modifies ui/server objects to authenticate using Auth0.***Description**

These functions can be used in a ui.R/server.R framework, modifying the shiny objects to authenticate using Auth0 service with no pain.

Usage

```
auth0_ui(ui, info)

auth0_server(server, info)
```

Arguments

<code>ui</code>	shiny.tag.list object to generate the user interface.
<code>info</code>	object returned from auth0_info . If not informed, will try to find the <code>_auth0.yml</code> and create it automatically.
<code>server</code>	the shiny server function.

See Also

[auth0_info](#).

Examples

```
# first, create the yml file using use_auth0() function

if (interactive()) {

  # ui.R file
  library(shiny)
  library(auth0)
  auth0_ui(fluidPage(logoutButton()))

  # server.R file
  library(auth0)
  auth0_server(function(input, output, session) {})

  # console
  options(shiny.port = 8080)
  shiny::runApp()
}
```

use_auth0	<i>Auth0 configuration file</i>
-----------	---------------------------------

Description

Create an YAML containing information to connect with Auth0.

Usage

```
use_auth0(path = ".", file = "_auth0.yml", overwrite = FALSE)
```

Arguments

path	Directory name. Should be the root of the shiny app you want to add this functionality
file	File name. Defaults to _auth0.yml.
overwrite	Will only overwrite existing path if TRUE.

Details

The YAML configuration file has required parameters and extra parameters.

The required parameters are:

- auth0_config is a list containing at least:
 - api_url: Your account at Auth0 (e.g. <https://jonhdoe.auth0.com>). It is the "Domain" in Auth0 application settings.
 - credentials: Your credentials to access Auth0 API, including
 - * key: the Client ID in Auth0 application settings.
 - * secret: the Client Secret in Auth0 application settings.

The extra parameters are:

- remote_url: If you are using Shiny-Server or ShinyApps IO service.
- scope: The information that Auth0 app will access. Defaults to "openid profile".
- request: Endpoit to request a token. Defaults to "oauth/token"
- access: Endpoit to access. Defaults to "oauth/token"

Index

actionButton, 5
auth0_config, 2, 3
auth0_find_config_file, 2, 2, 3
auth0_info, 3, 8
auth0_logout_url, 3
auth0_server (ui-server), 8
auth0_ui (ui-server), 8

logout, 4, 5, 6
logout_url, 5, 6
logoutButton, 5, 5, 6
logoutButton(), 3

shiny::shinyApp(), 7
shinyAppAuth0, 7
shinyAppAuth0(), 7
shinyAuth0App, 7

ui-server, 8
use_auth0, 3, 9