

# Package ‘autogam’

February 24, 2025

**Title** Automate the Creation of Generalized Additive Models (GAMs)

**Version** 0.1.0

**Language** en-US

**Description** This wrapper package for 'mgcv' makes it easier to create high-performing Generalized Additive Models (GAMs). With its central function autogam(), by entering just a dataset and the name of the outcome column as inputs, 'AutoGAM' tries to automate the procedure of configuring a highly accurate GAM which performs at reasonably high speed, even for large datasets.

**License** MIT + file LICENSE

**Config/testthat.edition** 3

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Depends** R (>= 4.2.0)

**Imports** cli, dplyr, methods, mgcv, purrr, rlang, staccuracy, stats, stringr, univariateML

**Suggests** testthat (>= 3.0.0)

**URL** <https://github.com/tripartio/autogam>,  
<https://tripartio.github.io/autogam/>

**BugReports** <https://github.com/tripartio/autogam/issues>

**NeedsCompilation** no

**Author** Chitu Okoli [aut, cre] (<<https://orcid.org/0000-0001-5574-7572>>)

**Maintainer** Chitu Okoli <Chitu.Okoli@skema.edu>

**Repository** CRAN

**Date/Publication** 2025-02-24 19:20:06 UTC

## Contents

autogam	2
autogam generic methods	3

plot.autogam . . . . .	4
print.autogam . . . . .	4
smooth_formula_string . . . . .	5
summary.autogam . . . . .	6

**autogam***Automate the creation of a Generalized Additive Model (GAM)***Description**

`autogam()` is a wrapper for `'mgcv::gam()'` that makes it easier to create high-performing Generalized Additive Models (GAMs). By entering just a dataset and the name of the outcome column as inputs, `autogam()` tries to automate the procedure of configuring a highly accurate GAM which performs at reasonably high speed, even for large datasets.

**Usage**

```
autogam(data, y_col, ..., bs = "cr")
```

**Arguments**

<code>data</code>	dataframe. All the variables in <code>data</code> will be used to predict <code>y_col</code> . To exclude any variables, assign as <code>data</code> only the subset of variables desired.
<code>y_col</code>	character(1). Name of the y outcome variable.
<code>...</code>	Arguments passed on to <code>mgcv::gam()</code> .
<code>bs</code>	character(1). The default basis function for GAM smooths. See <code>?mgcv::smooth.terms</code> for details. Whereas the default <code>bs</code> in <code>mgcv</code> is <code>'tp'</code> , <code>autogam</code> 's default is <code>'cr'</code> , which is much faster and comparably accurate.

**Value**

Returns an `mgcv::gam` object, the result of predicting `y_col` from all other variables in `data`.

**Examples**

```
autogam(mtcars, 'mpg')
```

---

**autogam generic methods**

*Generic autogam methods passed on to mgcv::gam methods*

---

**Description**

An autogam object contains a gam element that is simply an mgcv::gam object. So, it supports all mgcv::gam methods by, in most cases, simply passing the gam element on to their corresponding mgcv::gam methods. Only the following methods have special specifications for autogam (see their dedicated documentation files for details): [print.autogam\(\)](#).

**Usage**

```
## S3 method for class 'autogam'  
anova(object, ...)  
  
## S3 method for class 'autogam'  
coef(object, ...)  
  
## S3 method for class 'autogam'  
cooks.distance(model, ...)  
  
## S3 method for class 'autogam'  
formula(x, ...)  
  
## S3 method for class 'autogam'  
influence(model, ...)  
  
## S3 method for class 'autogam'  
logLik(object, ...)  
  
## S3 method for class 'autogam'  
model.matrix(object, ...)  
  
## S3 method for class 'autogam'  
predict(object, ...)  
  
## S3 method for class 'autogam'  
residuals(object, ...)  
  
## S3 method for class 'autogam'  
vcov(object, ...)
```

**Arguments**

object, model An object of class autogam.  
... other arguments

x formula

### Value

Returns the return object of the corresponding `mgcv:::gam` method.

`plot.autogam`

*Plot Method for autogam Objects*

### Description

This function plots an `autogam` object. It calls the `mgcv:::gam` object [`mgcv:::plot.gam\(\)`](#) method.

### Usage

```
## S3 method for class 'autogam'
plot(x, ...)
```

### Arguments

x	An object of class <code>autogam</code> .
...	Additional arguments passed to other methods.

### Value

Same return object as [`mgcv:::print.gam\(\)`](#).

`print.autogam`

*Print Method for autogam Objects*

### Description

This function prints an `autogam` object. It calls the `mgcv:::gam` object `print()` method and then adds basic performance metrics from the `autogam` object:

- For models that predict numeric outcomes, it prints "MAE", the mean absolute error, and "Std. accuracy", the standardized accuracy (staccuracy) of the winsorized MAE relative to the mean absolute deviation.
- For models that predict binary outcomes, it prints "AUC", the area under the ROC curve.

### Usage

```
## S3 method for class 'autogam'
print(x, ...)
```

**Arguments**

- x An object of class autogam.  
 ... Additional arguments passed to other methods.

**Value**

Invisibly returns the input object x.

`smooth_formula_string` *Create a character string for a mgcv::gam formula*

**Description**

Create a character string that wraps appropriate variables in a dataframe with `s()` smooth functions. Based on the datatype of each variable, it determines whether it is a numeric variable to be smoothed:

- Non-numeric: no smoothing.
- Numeric: determine knots based on the number of unique values for that variable:
  - $\leq 4$ : no smoothing
  - 5 to 19 (inclusive): smooth function with knots equal to the floored half of the number of unique values. E.g., 6 unique values receive 3 knots, 7 will receive 3 knots, and 8 will receive 4 knots.
  - $\geq 20$ : smooth function with no specified number of knots, allowing the `gam()` function to detect the appropriate number.

**Usage**

```
smooth_formula_string(
  data,
  y_col,
  smooth_fun = "s",
  bs = "cr",
  expand_parametric = TRUE
)
```

**Arguments**

- `data` dataframe. All the variables in `data` except `y_col` will be listed in the resulting formula string. To exclude any variables, assign as `data` only the subset of variables desired.
- `y_col` character(1). Name of the y outcome variable.
- `smooth_fun` character(1). Function to use for smooth wraps; default is 's' for the `s()` function.
- `bs` See documentation for [autogam\(\)](#)
- `expand_parametric` logical(1). If TRUE (default), explicitly list each non-smooth (parametric) term. If FALSE, use . to lump together all non-smooth terms.

**Value**

Returns a single character string that represents a formula with `y_col` on the left and all other variables in `data` on the right, each formatted with an appropriate `s()` function when applicable.

**Examples**

```
smooth_formula_string(mtcars, 'mpg')
```

---

`summary.autogam`*Summary Method for autogam Objects*

---

**Description**

This function returns a summary of an `autogam` object. It calls the `mgcv::gam` object [`mgcv::summary.gam\(\)`](#) method.

**Usage**

```
## S3 method for class 'autogam'  
summary(object, ...)
```

**Arguments**

- |                     |   |
|---------------------|---|
| <code>object</code> | An object of class <code>autogam</code> .     |
| <code>...</code>    | Additional arguments passed to other methods. |

**Value**

Same return object as [`mgcv::summary.gam\(\)`](#).

# Index

```
anova.autogam (autogam generic  
methods), 3  
autogam, 2  
autogam generic methods, 3  
autogam(), 5  
  
coef.autogam (autogam generic methods),  
3  
cooks.distance.autogam (autogam  
generic methods), 3  
  
formula.autogam (autogam generic  
methods), 3  
  
influence.autogam (autogam generic  
methods), 3  
  
logLik.autogam (autogam generic  
methods), 3  
  
mgcv::gam(), 2  
mgcv::plot.gam(), 4  
mgcv::print.gam(), 4  
mgcv::summary.gam(), 6  
model.matrix.autogam (autogam generic  
methods), 3  
  
plot.autogam, 4  
predict.autogam (autogam generic  
methods), 3  
print.autogam, 4  
print.autogam(), 3  
  
residuals.autogam (autogam generic  
methods), 3  
  
smooth_formula_string, 5  
summary.autogam, 6  
  
vcov.autogam (autogam generic methods),  
3
```