

Package ‘smd’

March 29, 2024

Type Package

Title Compute Standardized Mean Differences

Version 0.6.7

Description Computes standardized mean differences and confidence intervals for multiple data types based on Yang, D., & Dalton, J. E. (2012) <http://www.lerner.ccf.org/qhs/software/lib/stdiff.pdf>.

Imports MASS (>= 7.3-50), methods (>= 3.5.1)

Suggests testthat, stdiff, tableone, knitr, dplyr, purrr, markdown, rmarkdown

License MIT + file LICENSE

URL <https://bsaul.github.io/smd/>

BugReports <https://github.com/bsaul/smd/issues>

Encoding UTF-8

RoxygenNote 7.2.3

VignetteBuilder knitr

Repository CRAN

NeedsCompilation no

Author Bradley Saul [aut, cre],
Alex Breskin [ctb],
Catie Wiener [ctb],
Matt Phelan [ctb],
Daniel Sjoberg [ctb]

Maintainer Bradley Saul <bradleysaul@fastmail.com>

Date/Publication 2024-03-29 03:10:05 UTC

R topics documented:

smd	2
Index	4

smd

*Compute Standardized Mean Difference***Description**

Computes the standardized mean difference (SMD) between two groups.

$$d = \sqrt{D'S^{-1}D}$$

where D is a vector of differences between group 1 and 2 and S is the covariance matrix of these differences. If D is length 1, the result is multiplied by $sign(D)$.

In the case of a numeric or integer variable, this is equivalent to:

$$d = \frac{\bar{x}_1 - \bar{x}_2}{\sqrt{(s_1^2 + s_2^2)/2}}$$

where \bar{x}_g is the sample mean for group g and s_g^2 is the sample variance.

For a logical or factor with only two levels, the equation above is $\bar{x}_g = \hat{p}_g$, i.e. the sample proportion and $s_g^2 = \hat{p}_g(1 - \hat{p}_g)$.

Usage

```
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)
```

```
## S4 method for signature 'character,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)
```

```
## S4 method for signature 'character,ANY,numeric'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)
```

```
## S4 method for signature 'logical,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)
```

```
## S4 method for signature 'logical,ANY,numeric'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)
```

```
## S4 method for signature 'matrix,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)
```

```
## S4 method for signature 'matrix,ANY,numeric'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)
```

```
## S4 method for signature 'list,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)
```

```
## S4 method for signature 'list,ANY,numeric'
```

```
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)

## S4 method for signature 'data.frame,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)

## S4 method for signature 'data.frame,ANY,numeric'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L)
```

Arguments

x	a vector or matrix of values
g	a vector of at least 2 groups to compare. This should be coercible to a factor.
w	a vector of numeric weights (optional)
std.error	Logical indicator for computing standard errors using <code>compute_smd_var</code> . Defaults to FALSE.
na.rm	Remove NA values from x? Defaults to FALSE.
gref	an integer indicating which level of g to use as the reference group. Defaults to 1.

Value

a data.frame containing standardized mean differences between levels of g for values of x. The data.frame contains the columns:

- term: the level being compared to the reference level
- estimate: SMD estimates
- std.error: (if std.error = TRUE) SMD standard error estimates

Examples

```
x <- rnorm(100)
g <- rep(1:2, each = 50)
smd(x, g)
```

Index

`compute_smd_var`, 3

`smd`, 2

`smd, character, ANY, missing-method (smd)`,
2

`smd, character, ANY, numeric-method (smd)`,
2

`smd, data.frame, ANY, missing-method
(smd)`, 2

`smd, data.frame, ANY, numeric-method
(smd)`, 2

`smd, list, ANY, missing-method (smd)`, 2

`smd, list, ANY, numeric-method (smd)`, 2

`smd, logical, ANY, missing-method (smd)`, 2

`smd, logical, ANY, numeric-method (smd)`, 2

`smd, matrix, ANY, missing-method (smd)`, 2

`smd, matrix, ANY, numeric-method (smd)`, 2