

Package ‘tiledb’

May 9, 2024

Type Package

Version 0.27.0

Title Modern Database Engine for Complex Data Based on Multi-Dimensional Arrays

Description The modern database 'TileDB' introduces a powerful on-disk format for storing and accessing any complex data based on multi-dimensional arrays. It supports dense and sparse arrays, dataframes and key-values stores, cloud storage ('S3', 'GCS', 'Azure'), chunked arrays, multiple compression, encryption and checksum filters, uses a fully multi-threaded implementation, supports parallel I/O, data versioning ('time travel'), metadata and groups. It is implemented as an embeddable cross-platform C++ library with APIs from several languages, and integrations. This package provides the R support.

Copyright TileDB, Inc.

License MIT + file LICENSE

URL <https://github.com/TileDB-Inc/TileDB-R>,
<https://tiledb-inc.github.io/TileDB-R/>

BugReports <https://github.com/TileDB-Inc/TileDB-R/issues>

SystemRequirements A C++17 compiler is required; on macOS compilation version 11.0 or later is required. Optionally cmake (only when TileDB source build selected), curl (only when TileDB source build selected), and git (only when TileDB source build selected); on x86_64 and M1 platforms pre-built TileDB Embedded libraries are available at GitHub and are used if no TileDB installation is detected, and no other option to build or download was specified by the user.

Imports methods, Rcpp (>= 1.0.8), nanotime, spdlog, nanoarrow

LinkingTo Rcpp, RcppInt64, nanoarrow

Suggests tinytest, simplermardown, curl, bit64, Matrix,
palmerpenguins, nycflights13, data.table, tibble, arrow

VignetteBuilder simplermardown

RoxygenNote 7.3.1

Encoding UTF-8

NeedsCompilation yes

Author TileDB, Inc. [aut, cph],
Dirk Eddelbuettel [cre]

Maintainer Dirk Eddelbuettel <dirk@tiledb.com>

Repository CRAN

Date/Publication 2024-05-09 14:10:02 UTC

R topics documented:

allows_dups	9
allows_dups<-	10
array Consolidate	10
array Vacuum	11
as.data.frame.tiledb_config	12
as.vector.tiledb_config	12
attrs, tiledb_array, ANY-method	13
attrs, tiledb_array_schema, ANY-method	13
attrs, tiledb_array_schema, character-method	14
attrs, tiledb_array_schema, numeric-method	15
attrs<-, tiledb_array-method	16
capacity	16
capacity<-	17
cell_order, tiledb_array_schema-method	17
cell_val_num	18
cell_val_num, tiledb_dim-method	18
cell_val_num<-	19
completedBatched	19
config, tiledb_ctx-method	20
createBatched	21
datatype, tiledb_attr-method	21
datatype, tiledb_dim-method	22
datatype, tiledb_domain-method	22
datetimes_as_int64	23
datetimes_as_int64<-	24
describe	24
dim.tiledb_array_schema	25
dim.tiledb_dim	25
dim.tiledb_domain	26
dimensions, tiledb_array_schema-method	27
dimensions, tiledb_domain-method	27
domain, tiledb_array_schema-method	28
domain, tiledb_dim-method	29
extended	29
extended<-	30
fetchBatched	30

filter_list,tiledb_array_schema-method	31
filter_list,tiledb_attr-method	31
filter_list,tiledb_dim-method	32
filter_list<-,tiledb_attr-method	32
filter_list<-,tiledb_dim-method	33
fromDataFrame	33
fromMatrix	35
fromSparseMatrix	36
generics	37
has_attribute	38
is.anonymous	39
is.anonymous.tiledb_dim	40
is.integral,tiledb_domain-method	40
is.sparse,tiledb_array_schema-method	41
limitTileDBCores	41
max_chunk_size	42
name,tiledb_attr-method	43
name,tiledb_dim-method	44
nfilters,tiledb_filter_list-method	44
parse_query_condition	45
print.tiledb_metadata	46
query_condition	47
query_condition<-	47
query_layout	48
query_layout<-	48
query_statistics	49
query_statistics<-	49
raw_dump,tiledb_array_schema-method	50
raw_dump,tiledb_attr-method	50
raw_dump,tiledb_domain-method	51
return.array	51
return.array<-	52
return.data.frame,tiledb_array-method	52
return.data.frame<-,tiledb_array-method	53
return.matrix	53
return.matrix<-	54
return_as	54
return_as<-	55
r_to_tiledb_type	55
save_allocation_size_preference	56
save_return_as_preference	57
schema,character-method	58
schema,tiledb_array-method	58
schema_check	59
selected_points	59
selected_points<-	60
selected_ranges	60
selected_ranges<-	61

set_max_chunk_size	62
show,tiledb_array-method	62
show,tiledb_array_schema-method	63
show,tiledb_attr-method	63
show,tiledb_config-method	64
show,tiledb_dim-method	64
show,tiledb_domain-method	65
show,tiledb_filter-method	65
show,tiledb_filter_list-method	66
show,tiledb_group-method	66
statusBatched	67
strings_as_factors	67
strings_as_factors<-	68
tdb_collect,tiledb_array-method	68
tdb_filter,tiledb_array-method	69
tdb_select,tiledb_array-method	69
tile,tiledb_dim-method	70
tiledb_array	70
tiledb_array-class	73
tiledb_array_apply_aggregate	74
tiledb_array_close	74
tiledb_array_create	75
tiledb_array_delete_fragments	75
tiledb_array_get_non_empty_domain_from_index	76
tiledb_array_get_non_empty_domain_from_name	77
tiledb_array_has_enumeration	77
tiledb_array_is_heterogeneous	78
tiledb_array_is_homogeneous	78
tiledb_array_is_open	79
tiledb_array_open	79
tiledb_array_open_at	80
tiledb_array_schema	80
tiledb_array_schema-class	81
tiledb_array_schema_evolution	82
tiledb_array_schema_evolution-class	82
tiledb_array_schema_evolution_add_attribute	83
tiledb_array_schema_evolution_add_enumeration	83
tiledb_array_schema_evolution_add_enumeration_empty	84
tiledb_array_schema_evolution_array_evolve	84
tiledb_array_schema_evolution_drop_attribute	85
tiledb_array_schema_evolution_drop_enumeration	85
tiledb_array_schema_evolution_extend_enumeration	86
tiledb_array_schema_set_coords_filter_list	87
tiledb_array_schema_set_enumeration_empty	87
tiledb_array_schema_set_offsets_filter_list	88
tiledb_array_schema_set_validity_filter_list	89
tiledb_array_schema_version	89
tiledb_array_upgrade_version	90

<code>tiledb_arrow_array_ptr</code>	90
<code>tiledb_attr</code>	91
<code>tiledb_attr-class</code>	92
<code>tiledb_attribute_get_cell_size</code>	92
<code>tiledb_attribute_get_enumeration</code>	92
<code>tiledb_attribute_get_fill_value</code>	93
<code>tiledb_attribute_get_nullable</code>	93
<code>tiledb_attribute_has_enumeration</code>	94
<code>tiledb_attribute_is_ordered_enumeration_ptr</code>	94
<code>tiledb_attribute_is_variable_sized</code>	95
<code>tiledb_attribute_set_enumeration_name</code>	95
<code>tiledb_attribute_set_fill_value</code>	96
<code>tiledb_attribute_set_nullable</code>	96
<code>tiledb_config</code>	97
<code>tiledb_config-class</code>	97
<code>tiledb_config_as_built_json</code>	98
<code>tiledb_config_as_built_show</code>	98
<code>tiledb_config_load</code>	99
<code>tiledb_config_save</code>	99
<code>tiledb_config_unset</code>	100
<code>tiledb_ctx</code>	100
<code>tiledb_ctx-class</code>	101
<code>tiledb_ctx_set_default_tags</code>	101
<code>tiledb_ctx_set_tag</code>	102
<code>tiledb_ctx_stats</code>	102
<code>tiledb_datatype_R_type</code>	103
<code>tiledb_delete_metadata</code>	103
<code>tiledb_dim</code>	104
<code>tiledb_dim-class</code>	105
<code>tiledb_domain</code>	105
<code>tiledb_domain-class</code>	105
<code>tiledb_domain_get_dimension_from_index</code>	106
<code>tiledb_domain_get_dimension_from_name</code>	106
<code>tiledb_domain_has_dimension</code>	107
<code>tiledb_error_message</code>	107
<code>tiledb_filestore_buffer_export</code>	108
<code>tiledb_filestore_buffer_import</code>	108
<code>tiledb_filestore_schema_create</code>	109
<code>tiledb_filestore_size</code>	110
<code>tiledb_filestore_uri_export</code>	110
<code>tiledb_filestore_uri_import</code>	111
<code>tiledb_filter</code>	111
<code>tiledb_filter-class</code>	112
<code>tiledb_filter_get_option</code>	113
<code>tiledb_filter_list</code>	113
<code>tiledb_filter_list-class</code>	114
<code>tiledb_filter_set_option</code>	114
<code>tiledb_filter_type</code>	115

<code>tiledb_fragment_info</code>	115
<code>tiledb_fragment_info-class</code>	116
<code>tiledb_fragment_info_dense</code>	116
<code>tiledb_fragment_info_dump</code>	117
<code>tiledb_fragment_info_get_cell_num</code>	117
<code>tiledb_fragment_info_get_non_empty_domain_index</code>	118
<code>tiledb_fragment_info_get_non_empty_domain_name</code>	118
<code>tiledb_fragment_info_get_non_empty_domain_var_index</code>	119
<code>tiledb_fragment_info_get_non_empty_domain_var_name</code>	119
<code>tiledb_fragment_info_get_num</code>	120
<code>tiledb_fragment_info_get_size</code>	120
<code>tiledb_fragment_info_get_timestamp_range</code>	121
<code>tiledb_fragment_info_get_to_vacuum_num</code>	121
<code>tiledb_fragment_info_get_to_vacuum_uri</code>	122
<code>tiledb_fragment_info_get_unconsolidated_metadata_num</code>	122
<code>tiledb_fragment_info_get_version</code>	123
<code>tiledb_fragment_info_has_consolidated_metadata</code>	123
<code>tiledb_fragment_info_sparse</code>	124
<code>tiledb_fragment_info_uri</code>	124
<code>tiledb_get_all_metadata</code>	125
<code>tiledb_get_context</code>	125
<code>tiledb_get_metadata</code>	126
<code>tiledb_get_query_status</code>	126
<code>tiledb_get_vfs</code>	127
<code>tiledb_group</code>	127
<code>tiledb_group-class</code>	128
<code>tiledb_group_add_member</code>	128
<code>tiledb_group_close</code>	129
<code>tiledb_group_create</code>	129
<code>tiledb_group_delete</code>	130
<code>tiledb_group_delete_metadata</code>	130
<code>tiledb_group_get_all_metadata</code>	131
<code>tiledb_group_get_config</code>	131
<code>tiledb_group_get_metadata</code>	132
<code>tiledb_group_get_metadata_from_index</code>	132
<code>tiledb_group_has_metadata</code>	133
<code>tiledb_group_is_open</code>	133
<code>tiledb_group_is_relative</code>	134
<code>tiledb_group_member</code>	134
<code>tiledb_group_member_count</code>	135
<code>tiledb_group_member_dump</code>	135
<code>tiledb_group_metadata_num</code>	136
<code>tiledb_group_open</code>	136
<code>tiledb_group_put_metadata</code>	137
<code>tiledb_group_query_type</code>	137
<code>tiledb_group_remove_member</code>	138
<code>tiledb_group_set_config</code>	138
<code>tiledb_group_uri</code>	139

tiledb_has_metadata	139
tiledb_is_supported_fs	140
tiledb_ndim,tiledb_array_schema-method	140
tiledb_ndim,tiledb_dim-method	141
tiledb_ndim,tiledb_domain-method	142
tiledb_num_metadata	142
tiledb_object_ls	143
tiledb_object_mv	143
tiledb_object_rm	144
tiledb_object_type	144
tiledb_object_walk	145
tiledb_put_metadata	145
tiledb_query	146
tiledb_query-class	146
tiledb_query_add_range	147
tiledb_query_add_range_with_type	147
tiledb_query_alloc_buffer_ptr_char	148
tiledb_query_apply_aggregate	149
tiledb_query_buffer_alloc_ptr	149
tiledb_query_condition	150
tiledb_query_condition-class	150
tiledb_query_condition_combine	151
tiledb_query_condition_create	151
tiledb_query_condition_init	152
tiledb_query_condition_set_use_enumeration	153
tiledb_query_create_buffer_ptr	153
tiledb_query_create_buffer_ptr_char	154
tiledb_query_ctx	154
tiledb_query_export_buffer	155
tiledb_query_finalize	155
tiledb_query_get_buffer_char	156
tiledb_query_get_buffer_ptr	156
tiledb_query_get_est_result_size	157
tiledb_query_get_est_result_size_var	157
tiledb_query_get_fragment_num	158
tiledb_query_get_fragment_timestamp_range	158
tiledb_query_get_fragment_uri	159
tiledb_query_get_layout	159
tiledb_query_get_range	160
tiledb_query_get_range_num	160
tiledb_query_get_range_var	161
tiledb_query_import_buffer	161
tiledb_query_result_buffer_elements	162
tiledb_query_result_buffer_elements_vec	163
tiledb_query_set_buffer	163
tiledb_query_set_buffer_ptr	164
tiledb_query_set_buffer_ptr_char	164
tiledb_query_set_condition	165

<code>tiledb_query_set_layout</code>	165
<code>tiledb_query_set_subarray</code>	166
<code>tiledb_query_stats</code>	166
<code>tiledb_query_status</code>	167
<code>tiledb_query_submit</code>	167
<code>tiledb_query_submit_async</code>	168
<code>tiledb_query_type</code>	168
<code>tiledb_schema_get_dim_attr_status</code>	169
<code>tiledb_schema_get_enumeration_status</code>	169
<code>tiledb_schema_get_names</code>	170
<code>tiledb_schema_get_types</code>	170
<code>tiledb_schema_object</code>	171
<code>tiledb_set_context</code>	171
<code>tiledb_set_vfs</code>	172
<code>tiledb_stats_disable</code>	172
<code>tiledb_stats_dump</code>	172
<code>tiledb_stats_enable</code>	173
<code>tiledb_stats_print</code>	173
<code>tiledb_stats_raw_dump</code>	173
<code>tiledb_stats_raw_get</code>	174
<code>tiledb_stats_raw_print</code>	174
<code>tiledb_stats_reset</code>	174
<code>tiledb_subarray</code>	175
<code>tiledb_subarray-class</code>	175
<code>tiledb_subarray_to_query</code>	175
<code>tiledb_version</code>	176
<code>tiledb_vfs</code>	177
<code>tiledb_vfs-class</code>	177
<code>tiledb_vfs_close</code>	178
<code>tiledb_vfs_copy_file</code>	178
<code>tiledb_vfs_create_bucket</code>	179
<code>tiledb_vfs_create_dir</code>	179
<code>tiledb_vfs_dir_size</code>	180
<code>tiledb_vfs_empty_bucket</code>	180
<code>tiledb_vfs_file_size</code>	181
<code>tiledb_vfs_is_bucket</code>	181
<code>tiledb_vfs_is_dir</code>	182
<code>tiledb_vfs_is_empty_bucket</code>	182
<code>tiledb_vfs_is_file</code>	183
<code>tiledb_vfs_ls</code>	183
<code>tiledb_vfs_ls_recursive</code>	184
<code>tiledb_vfs_move_dir</code>	185
<code>tiledb_vfs_move_file</code>	185
<code>tiledb_vfs_open</code>	186
<code>tiledb_vfs_read</code>	186
<code>tiledb_vfs_remove_bucket</code>	187
<code>tiledb_vfs_remove_dir</code>	187
<code>tiledb_vfs_remove_file</code>	188

tiledb_vfs_serialize	188
tiledb_vfs_sync	189
tiledb_vfs_touch	189
tiledb_vfs_unserialize	190
tiledb_vfs_write	190
tile_order,tiledb_array_schema-method	191
[,tiledb_array,ANY-method	191
[,tiledb_config,ANY-method	192
[,tiledb_filter_list,ANY-method	193
[<-,tiledb_array,ANY,ANY,ANY-method	193
[<-,tiledb_config,ANY,ANY,ANY-method	194

Index**196**

allows_dups	<i>Returns logical value whether the array schema allows duplicate values or not. This is only valid for sparse arrays.</i>
-------------	---

Description

Returns logical value whether the array schema allows duplicate values or not. This is only valid for sparse arrays.

Usage

```
allows_dups(x)

## S4 method for signature 'tiledb_array_schema'
allows_dups(x)

tiledb_array_schema_get_allows_dups(x)
```

Arguments

x tiledb_array_schema

Value

the logical value

allows_dups<-	<i>Sets toggle whether the array schema allows duplicate values or not. This is only valid for sparse arrays.</i>
---------------	---

Description

Sets toggle whether the array schema allows duplicate values or not. This is only valid for sparse arrays.

Usage

```
allows_dups(x) <- value

## S4 replacement method for signature 'tiledb_array_schema'
allows_dups(x) <- value

tiledb_array_schema_set_allows_dups(x, value)
```

Arguments

x	tiledb_array_schema
value	logical value

Value

the tiledb_array_schema object

array_consolidate	<i>Consolidate fragments of a TileDB Array</i>
-------------------	--

Description

This function invokes a consolidation operation. Parameters affecting the operation can be set via an optional configuration object. Start and end timestamps can also be set directly.

Usage

```
array_consolidate(
  uri,
  cfg = NULL,
  start_time,
  end_time,
  ctx = tiledb_get_context()
)
```

Arguments

uri	A character value with the URI of a TileDB Array
cfg	An optional TileDB Configuration object
start_time	An optional timestamp value, if missing config default is used
end_time	An optional timestamp value, if missing config default is used
ctx	An option TileDB Context object

Value

NULL is returned invisibly

array_vacuum	<i>After consolidation, remove consolidated fragments of a TileDB Array</i>
--------------	---

Description

This function can remove fragments following a consolidation step. Note that vacuuming should *not* be run if one intends to use the TileDB *time-traveling* feature of opening arrays at particular timestamps.

Usage

```
array_vacuum(uri, cfg = NULL, start_time, end_time, ctx = tiledb_get_context())
```

Arguments

uri	A character value with the URI of a TileDB Array
cfg	An optional TileDB Configuration object
start_time	An optional timestamp value, if missing config default is used
end_time	An optional timestamp value, if missing config default is used
ctx	An option TileDB Context object

Details

Parameters affecting the operation can be set via an optional configuration object. Start and end timestamps can also be set directly.

Value

NULL is returned invisibly

```
as.data.frame.tiledb_config
```

Convert a tiledb_config object to a R data.frame

Description

Convert a tiledb_config object to a R data.frame

Usage

```
## S3 method for class 'tiledb_config'  
as.data.frame(x, ...)
```

Arguments

x	tiledb_config object
...	Extra parameter for method signature, currently unused.

Value

a data.frame with parameter, value columns

Examples

```
cfg <- tiledb_config()  
as.data.frame(cfg)
```

```
as.vector.tiledb_config
```

Convert a tiledb_config object to a R vector

Description

Convert a tiledb_config object to a R vector

Usage

```
## S3 method for class 'tiledb_config'  
as.vector(x, mode = "any")
```

Arguments

x	tiledb_config object
mode	Character value "any", currently unused

Value

a character vector of config parameter names, values

Examples

```
cfg <- tiledb_config()
as.vector(cfg)
```

attrs, tiledb_array, ANY-method

Retrieve attributes from tiledb_array object

Description

By default, all attributes will be selected. But if a subset of attribute names is assigned to the internal slot `attrs`, then only those attributes will be queried. This methods accesses the slot.

Usage

```
## S4 method for signature 'tiledb_array,ANY'
attrs(object)
```

Arguments

`object` A tiledb_array object

Value

An empty character vector if no attributes have been selected or else a vector with attributes; NA means no attributes will be returned.

attrs, tiledb_array_schema, ANY-method

Returns a list of all tiledb_attr objects associated with the tiledb_array_schema

Description

Returns a list of all tiledb_attr objects associated with the tiledb_array_schema

Usage

```
## S4 method for signature 'tiledb_array_schema,ANY'
attrs(object, idx, ...)
```

Arguments

object	tiledb_array_schema
idx	index argument, currently unused.
...	Extra parameter for method signature, currently unused.

Value

a list of tiledb_attr objects

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 10L), type = "INT32")))
sch <- tiledb_array_schema(dom, attrs = c(tiledb_attr("a1", type = "INT32"),
                                         tiledb_attr("a2", type = "FLOAT64")))
attrs(sch)

lapply(attrs(sch), datatype)
```

attrs, tiledb_array_schema, character-method

Returns a tiledb_attr object associated with the tiledb_array_schema with a given name.

Description

Returns a tiledb_attr object associated with the tiledb_array_schema with a given name.

Usage

```
## S4 method for signature 'tiledb_array_schema,character'
attrs(object, idx, ...)
```

Arguments

object	tiledb_array_schema
idx	attribute name string
...	Extra parameter for method signature, currently unused.

Value

a tiledb_attr object

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 10L), type = "INT32")))
sch <- tiledb_array_schema(dom, attrs = c(tiledb_attr("a1", type = "INT32"),
                                          tiledb_attr("a2", type = "FLOAT64")))
attrs(sch, "a2")
```

```
attrs, tiledb_array_schema, numeric-method
```

Returns a tiledb_attr object associated with the tiledb_array_schema with a given index

Description

The attribute index is defined by the order the attributes were defined in the schema

Usage

```
## S4 method for signature 'tiledb_array_schema,numeric'
attrs(object, idx, ...)
```

Arguments

object	tiledb_array_schema
idx	attribute index
...	Extra parameter for method signature, currently unused.

Value

a tiledb_attr object

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 10L), type = "INT32")))
sch <- tiledb_array_schema(dom, attrs = c(tiledb_attr("a1", type = "INT32"),
                                          tiledb_attr("a2", type = "FLOAT64")))
attrs(sch, 2)
```

```
attrs<-, tiledb_array-method
```

Selects attributes for the given TileDB array

Description

Selects attributes for the given TileDB array

Usage

```
## S4 replacement method for signature 'tiledb_array'
attrs(x) <- value
```

Arguments

x	A tiledb_array object
value	A character vector with attributes; the value NA_character_ signals no attributes should be returned; default is an empty character vector implying all columns are returned.

Value

The modified tiledb_array object

```
capacity
```

Retrieve schema capacity (for sparse fragments)

Description

Returns the tiledb_array schema tile capacity for sparse fragments.

Usage

```
capacity(object)

## S4 method for signature 'tiledb_array_schema'
capacity(object)

tiledb_array_schema_get_capacity(object)
```

Arguments

object	An array_schema object
--------	------------------------

Value

The tile capacity value

capacity<- *Sets the schema capacity (for sparse fragments)*

Description

Sets the tiledb_array schema tile capacity for sparse fragments.

Usage

```
capacity(x) <- value

## S4 replacement method for signature 'tiledb_array_schema'
capacity(x) <- value

tiledb_array_schema_set_capacity(x, value)
```

Arguments

x An array_schema object
value An integer or numeric value for the new tile capacity

Value

The modified array_schema object

cell_order,tiledb_array_schema-method
Returns the cell layout string associated with the tiledb_array_schema

Description

Returns the cell layout string associated with the tiledb_array_schema

Usage

```
## S4 method for signature 'tiledb_array_schema'
cell_order(object)
```

Arguments

object tiledb object

cell_val_num	<i>Return the number of scalar values per attribute cell</i>
--------------	--

Description

Return the number of scalar values per attribute cell

Usage

```
cell_val_num(object)

## S4 method for signature 'tiledb_attr'
cell_val_num(object)

tiledb_attribute_get_cell_val_num(object)
```

Arguments

object tiledb_attr object

Value

integer number of cells

Examples

```
a1 <- tiledb_attr("a1", type = "FLOAT64", ncells = 1)
cell_val_num(a1)
```

cell_val_num,tiledb_dim-method	<i>Return the number of scalar values per dimension cell</i>
--------------------------------	--

Description

Return the number of scalar values per dimension cell

Usage

```
## S4 method for signature 'tiledb_dim'
cell_val_num(object)

tiledb_dim_get_cell_val_num(object)
```

Arguments

object tiledb_dim object

Value

integer number of cells

cell_val_num<- *Set the number of scalar values per attribute cell*

Description

Set the number of scalar values per attribute cell

Usage

```
cell_val_num(x) <- value

## S4 replacement method for signature 'tiledb_attr'
cell_val_num(x) <- value

tiledb_attribute_set_cell_val_num(x, value)
```

Arguments

x A TileDB Attribute object
value An integer value of number of cells

Value

The modified attribute is returned

completedBatched *Check 'batched' query for completion*

Description

Batched queries return an initial result set even when it is incomplete. Where the normal retrieval process will loop in place to complete a (potentially large) result set, this function will return a result (which may be part of a larger result set) allowing the user to assemble all part.

Usage

```
completedBatched(obj)
```

Arguments

obj A list object as returned by createBatched

Value

A logical value to indicated if the query completed

config,tiledb_ctx-method

Retrieve the tiledb_config object from the tiledb_ctx

Description

Retrieve the tiledb_config object from the tiledb_ctx

Usage

```
## S4 method for signature 'tiledb_ctx'  
config(object = tiledb_get_context())
```

Arguments

object tiledb_ctx object

Value

tiledb_config object associated with the tiledb_ctx instance

Examples

```
ctx <- tiledb_ctx(c("sm.tile_cache_size" = "10"))  
cfg <- config(ctx)  
cfg["sm.tile_cache_size"]
```

createBatched	<i>Create a 'batched' query object</i>
---------------	--

Description

Batched queries return an initial result set even when it is incomplete. Where the normal retrieval process will loop in place to complete a (potentially large) result set, this function will return a result (which may be part of a larger result set) allowing the user to assemble all part.

Usage

```
createBatched(x)
```

Arguments

x	A tiledb_array object
---	-----------------------

Details

The tiledb_array object can be parameterised as usual.

Value

A batchedquery object, that is a list containing an external pointer to a TileDB Query object along with other support variables used by fetchBatched

datatype, tiledb_attr-method	<i>Return the tiledb_attr datatype</i>
------------------------------	--

Description

Return the tiledb_attr datatype

Usage

```
## S4 method for signature 'tiledb_attr'
datatype(object)
```

Arguments

object	tiledb_attr object
--------	--------------------

Value

tiledb datatype string

Examples

```
a1 <- tiledb_attr("a1", type = "INT32")
datatype(a1)

a2 <- tiledb_attr("a1", type = "FLOAT64")
datatype(a2)
```

datatype,tiledb_dim-method

Return the tiledb_dim datatype

Description

Return the tiledb_dim datatype

Usage

```
## S4 method for signature 'tiledb_dim'
datatype(object)
```

Arguments

object tiledb_dim object

Value

tiledb datatype string

Examples

```
d1 <- tiledb_dim("d1", domain = c(5L, 10L), tile = 2L, type = "INT32")
datatype(d1)
```

datatype,tiledb_domain-method

Returns the tiledb_domain TileDB type string

Description

Returns the tiledb_domain TileDB type string

Usage

```
## S4 method for signature 'tiledb_domain'  
datatype(object)
```

Arguments

```
object          tiledb_domain
```

Value

tiledb_domain type string

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 100L), type = "INT32"))  
datatype(dom)  
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(0.5, 100.0), type = "FLOAT64"))  
datatype(dom)
```

datetimes_as_int64 *Retrieve datetimes_as_int64 toggle*

Description

A tiledb_array object may contain date and datetime objects. While their internal representation is generally shielded from the user, it can be useful to access them as the ‘native’ format which is an integer64. This function retrieves the current value of the selection variable, which has a default of FALSE.

Usage

```
datetimes_as_int64(object)  
  
## S4 method for signature 'tiledb_array'  
datetimes_as_int64(object)
```

Arguments

```
object          A tiledb_array object
```

Value

A logical value indicating whether datetimes_as_int64 is selected

```
datetimes_as_int64<- Set datetimes_as_int64 toggle
```

Description

A tiledb_array object may contain date and datetime objects. While their internal representation is generally shielded from the user, it can be useful to access them as the 'native' format which is an integer64. This function sets the current value of the selection variable, which has a default of FALSE.

Usage

```
datetimes_as_int64(x) <- value

## S4 replacement method for signature 'tiledb_array'
datetimes_as_int64(x) <- value
```

Arguments

x	A tiledb_array object
value	A logical value with the selection

Value

The modified tiledb_array array object

```
describe Describe a TileDB array schema via code to create it
```

Description

Describe a TileDB array schema via code to create it

Usage

```
describe(arr)
```

Arguments

arr	A TileDB Array object
-----	-----------------------

Value

Nothing is returned as the function is invoked for the side effect of printing the schema via a sequence of R instructions to re-create it.

`dim.tiledb_array_schema`*Retrieve the dimension (domain extent) of the domain*

Description

Only valid for integral (integer) domains

Usage

```
## S3 method for class 'tiledb_array_schema'  
dim(x)
```

Arguments

x tiledb_array_schema

Value

a dimension vector

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 10L), type = "INT32"))  
sch <- tiledb_array_schema(dom, attrs = c(tiledb_attr("a1", type = "INT32"),  
                                          tiledb_attr("a2", type = "FLOAT64"))  
dim(sch)
```

`dim.tiledb_dim`*Retrieves the dimension of the tiledb_dim domain*

Description

Retrieves the dimension of the tiledb_dim domain

Usage

```
## S3 method for class 'tiledb_dim'  
dim(x)
```

Arguments

x tiledb_dim object

Value

a vector of the tile_dim domain type, of the dim domain dimension (extent)

Examples

```
d1 <- tiledb_dim("d1", c(1L, 10L), 5L)
dim(d1)
```

dim.tiledb_domain	<i>Retrieve the dimension (domain extent) of the domain</i>
-------------------	---

Description

Only valid for integral (integer) domains

Usage

```
## S3 method for class 'tiledb_domain'
dim(x)
```

Arguments

x tiledb_domain

Value

dimension vector

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 100L), type = "INT32"),
                             tiledb_dim("d2", c(1L, 100L), type = "INT32")))
dim(dom)
```

```
dimensions,tiledb_array_schema-method
```

```
Returns a list of tiledb_dim objects associated with the
tiledb_array_schema
```

Description

Returns a list of tiledb_dim objects associated with the tiledb_array_schema

Usage

```
## S4 method for signature 'tiledb_array_schema'
dimensions(object)
```

Arguments

```
object          tiledb_array_schema
```

Value

a list of tiledb_dim objects

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 100L), type = "INT32"),
                             tiledb_dim("d2", c(1L, 50L), type = "INT32")))
sch <- tiledb_array_schema(dom, attrs = c(tiledb_attr("a1", type = "INT32")))
dimensions(dom)

lapply(dimensions(dom), name)
```

```
dimensions,tiledb_domain-method
```

```
Returns a list of the tiledb_domain dimension objects
```

Description

Returns a list of the tiledb_domain dimension objects

Usage

```
## S4 method for signature 'tiledb_domain'
dimensions(object)
```

Arguments

object tiledb_domain

Value

a list of tiledb_dim

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 100L), type = "INT32"),
                             tiledb_dim("d2", c(1L, 50L), type = "INT32")))
dimensions(dom)

lapply(dimensions(dom), name)
```

domain,tiledb_array_schema-method

Returns the tiledb_domain object associated with a given tiledb_array_schema

Description

Returns the tiledb_domain object associated with a given tiledb_array_schema

Usage

```
## S4 method for signature 'tiledb_array_schema'
domain(object)
```

Arguments

object tiledb_array_schema

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 10L), type = "INT32")))
sch <- tiledb_array_schema(dom, attrs = c(tiledb_attr("a1", type = "INT32")))
domain(sch)
```

domain,tiledb_dim-method
Return the tiledb_dim domain

Description

Return the tiledb_dim domain

Usage

```
## S4 method for signature 'tiledb_dim'
domain(object)
```

Arguments

object tiledb_dim object

Value

a vector of (lb, ub) inclusive domain of the dimension

Examples

```
d1 <- tiledb_dim("d1", domain = c(5L, 10L))
domain(d1)
```

extended *Retrieve data.frame extended returns columns toggle*

Description

A tiledb_array object can be returned as data.frame. This methods returns the selection value for 'extended' format including row (and column, if present) indices.

Usage

```
extended(object)

## S4 method for signature 'tiledb_array'
extended(object)
```

Arguments

object A tiledb_array object

Value

A logical value indicating whether an extended return is selected

extended<-	<i>Set data.frame extended return columns toggle</i>
------------	--

Description

A tiledb_array object can be returned as data.frame. This methods set the selection value for 'extended' format including row (and column, if present) indices.

Usage

```
extended(x) <- value

## S4 replacement method for signature 'tiledb_array'
extended(x) <- value
```

Arguments

x	A tiledb_array object
value	A logical value with the selection

Value

The modified tiledb_array array object

fetchBatched	<i>Run a 'batched' query</i>
--------------	------------------------------

Description

Batched queries return an initial result set even when it is incomplete. Where the normal retrieval process will loop in place to complete a (potentially large) result set, this function will return a result (which may be part of a larger result set) allowing the user to assemble all part.

Usage

```
fetchBatched(x, obj)
```

Arguments

x	A tiledb_array object
obj	A batchedquery object as returned by createBatched

Details

The tiledb_array object can be parameterised as usual.

Value

A data.frame object with the (potentially partial) result of a batched query

filter_list,tiledb_array_schema-method
Returns the offsets and coordinate filter_lists associated with the tiledb_array_schema

Description

Returns the offsets and coordinate filter_lists associated with the tiledb_array_schema

Usage

```
## S4 method for signature 'tiledb_array_schema'
filter_list(object)
```

Arguments

object tiledb_array_schema

Value

a list of tiledb_filter_list objects

filter_list,tiledb_attr-method
Returns the TileDB Filter List object associated with the given TileDB Attribute

Description

Returns the TileDB Filter List object associated with the given TileDB Attribute

Usage

```
## S4 method for signature 'tiledb_attr'
filter_list(object)
```

Arguments

object TileDB Attribute

Value

a tiledb_filter_list object

Examples

```
attr <- tiledb_attr(type = "INT32", filter_list=tiledb_filter_list(list(tiledb_filter("ZSTD"))))
filter_list(attr)
```

`filter_list, tiledb_dim-method`

Returns the TileDB Filter List object associated with the given TileDB Dimension

Description

Returns the TileDB Filter List object associated with the given TileDB Dimension

Usage

```
## S4 method for signature 'tiledb_dim'
filter_list(object)
```

Arguments

object TileDB_Dimension

Value

A TileDB_filter_list object

`filter_list<-, tiledb_attr-method`

Sets the TileDB Filter List for the TileDB Attribute object

Description

Sets the TileDB Filter List for the TileDB Attribute object

Usage

```
## S4 replacement method for signature 'tiledb_attr'
filter_list(x) <- value
```


Arguments

x	TileDB Attribute
value	TileDB Filter List

Value

The modified TileDB Attribute object

```
filter_list<-, tiledb_dim-method
```

Sets the TileDB Filter List for the TileDB Dimension object

Description

Sets the TileDB Filter List for the TileDB Dimension object

Usage

```
## S4 replacement method for signature 'tiledb_dim'
filter_list(x) <- value
```

Arguments

x	TileDB Dimension
value	TileDB Filter List

Value

The modified TileDB Dimension object

```
fromDataFrame
```

Create a TileDB dense or sparse array from a given data.frame Object

Description

The supplied data.frame object is (currently) limited to integer, numeric, or character. In addition, three datetime columns are supported with the R representations of Date, POSIXct and nanotime.

Usage

```

fromDataFrame(
  obj,
  uri,
  col_index = NULL,
  sparse = TRUE,
  allows_dups = sparse,
  cell_order = "COL_MAJOR",
  tile_order = "COL_MAJOR",
  filter = "ZSTD",
  capacity = 10000L,
  tile_domain = NULL,
  tile_extent = NULL,
  mode = c("ingest", "schema_only", "append"),
  filter_list = NULL,
  coords_filters = "ZSTD",
  offsets_filters = "ZSTD",
  validity_filters = "RLE",
  debug = FALSE
)

```

Arguments

<code>obj</code>	A data.frame object.
<code>uri</code>	A character variable with an Array URI.
<code>col_index</code>	An optional column index, either numeric with a column index, or character with a column name, designating an index column; default is NULL implying an index column is added when the array is created
<code>sparse</code>	A logical switch to select sparse (the default) or dense
<code>allows_dups</code>	A logical switch to select if duplicate values are allowed or not, default is the same value as 'sparse'.
<code>cell_order</code>	A character variable with one of the TileDB cell order values, default is "COL_MAJOR".
<code>tile_order</code>	A character variable with one of the TileDB tile order values, default is "COL_MAJOR".
<code>filter</code>	A character variable vector, defaults to 'ZSTD', for one or more filters to be applied to each attribute;
<code>capacity</code>	A integer value with the schema capacity, default is 10000.
<code>tile_domain</code>	An integer vector or list or NULL. If an integer vector of size two it specifies the integer domain of the row dimension; if a list then a named element is used for the dimension of the same name; or if NULL the row dimension of the obj is used.
<code>tile_extent</code>	An integer value for the tile extent of the row dimensions; if NULL the row dimension of the obj is used. Note that the <code>tile_extent</code> cannot exceed the tile domain.

mode	A character variable with possible values ‘ingest’ (for schema creation and data ingestion, the default behavior), ‘schema_only’ (to create the array schema without writing to the newly-created array) and ‘append’ (to only append to an already existing array).
filter_list	A named list specifying filter choices per column, default is an empty list object. This argument applies for all named arguments and the matching dimensions or attributes. The filter argument still applies for all unnamed arguments.
coords_filters	A character vector with filters for coordinates, default is ZSTD.
offsets_filters	A character vector with filters for coordinates, default is ZSTD.
validity_filters	A character vector with filters for coordinates, default is RLE.
debug	Logical flag to select additional output.

Details

The created (dense or sparse) array will have as many attributes as there are columns in the `data.frame`. Each attribute will be a single column. For a sparse array, one or more columns have to be designated as dimensions.

At present, factor variables are converted to character.

Value

Null, invisibly.

Examples

```
uri <- tempfile()
fromDataFrame(iris, uri)
arr <- tiledb_array(uri, return_as="data.frame", extended=FALSE)
newdf <- arr[]
all.equal(iris, newdf, check.attributes=FALSE) # extra attribute on query in newdf
all.equal(as.matrix(iris), as.matrix(newdf)) # also strips attribute
```

fromMatrix

Create a TileDB array from an R matrix, or return an R matrix

Description

The functions `fromMatrix` and `toMatrix` help in storing (and retrieving) matrices using a TileDB backend. In particular they help for matrices with explicit rownames.

Usage

```
fromMatrix(obj, uri, filter = "ZSTD", capacity = 10000L)

toMatrix(uri)
```

Arguments

obj	A sparse matrix object.
uri	A character variable with an Array URI.
filter	A character variable vector, defaults to 'ZSTD', for one or more filters to be applied to each attribute;
capacity	A integer value with the schema capacity, default is 10000.

Value

Null, invisibly.

fromSparseMatrix	<i>Create (or return) a TileDB sparse array</i>
------------------	---

Description

The functions fromSparseMatrix and toSparseMatrix help in storing (and retrieving) sparse matrices using a TileDB backend.

Usage

```
fromSparseMatrix(
  obj,
  uri,
  cell_order = "ROW_MAJOR",
  tile_order = "ROW_MAJOR",
  filter = "ZSTD",
  capacity = 10000L
)

toSparseMatrix(uri)
```

Arguments

obj	A sparse matrix object.
uri	A character variable with an Array URI.
cell_order	A character variable with one of the TileDB cell order values, default is "COL_MAJOR".
tile_order	A character variable with one of the TileDB tile order values, default is "COL_MAJOR".
filter	A character variable vector, defaults to 'ZSTD', for one or more filters to be applied to each attribute;
capacity	A integer value with the schema capacity, default is 10000.

Value

Null, invisibly.

Examples

```
## Not run:
if (requireNamespace("Matrix", quietly=TRUE)) {
  library(Matrix)
  set.seed(123)      # just to fix it
  mat <- matrix(0, nrow=20, ncol=10)
  mat[sample(seq_len(200), 20)] <- seq(1, 20)
  spmat <- as(mat, "dgTMatrix") # sparse matrix in dgTMatrix format
  uri <- "sparse_matrix"
  fromSparseMatrix(spmat, uri) # now written
  chk <- toSparseMatrix(uri)   # and re-read
  print(chk)
  all.equal(spmat, chk)
}

## End(Not run)
```

generics

Generic Methods

Description

Definition of generic methods

Usage

```
schema(object, ...)

return.data.frame(object, ...)

return.data.frame(x) <- value

attrs(x) <- value

raw_dump(object, ...)

domain(object, ...)

dimensions(object, ...)

attrs(object, idx, ...)

cell_order(object, ...)

tile_order(object, ...)

filter_list(object, ...)
```

```

filter_list(x) <- value
is.sparse(object, ...)
tiledb_ndim(object, ...)
name(object)
datatype(object)
config(object, ...)
tile(object)
is.integral(object)
nfilters(object)
tdb_filter(x, ...)
tdb_select(x, ...)
tdb_collect(x, ...)

```

Arguments

object	A TileDB object
...	Currently unused
x	A TileDB Object
value	A value to be assigned
idx	An index argument

has_attribute	<i>Check a schema for a given attribute name</i>
---------------	--

Description

Check a schema for a given attribute name

Usage

```
has_attribute(schema, attr)
```

Arguments

schema A schema for a TileDB Array
 attr A character variable with an attribute name

Value

A boolean value indicating if the attribute exists in the schema

is.anonymous	<i>Returns TRUE if the tiledb_dim is anonymous</i>
--------------	--

Description

A TileDB attribute is anonymous if no name/label is defined

Usage

```
is.anonymous(object)

## S3 method for class 'tiledb_attr'
is.anonymous(object)
```

Arguments

object tiledb_attr object

Value

TRUE or FALSE

Examples

```
a1 <- tiledb_attr("a1", type = "FLOAT64")
is.anonymous(a1)

a2 <- tiledb_attr("", type = "FLOAT64")
is.anonymous(a2)
```

```
is.anonymous.tiledb_dim
```

Returns TRUE if the tiledb_dim is anonymous

Description

A TileDB dimension is anonymous if no name/label is defined

Usage

```
## S3 method for class 'tiledb_dim'  
is.anonymous(object)
```

Arguments

object tiledb_dim object

Value

TRUE or FALSE

Examples

```
d1 <- tiledb_dim("d1", c(1L, 10L), 10L)  
is.anonymous(d1)  
  
d2 <- tiledb_dim("", c(1L, 10L), 10L)  
is.anonymous(d2)
```

```
is.integral,tiledb_domain-method
```

Returns TRUE is tiledb_domain is an integral (integer) domain

Description

Returns TRUE is tiledb_domain is an integral (integer) domain

Usage

```
## S4 method for signature 'tiledb_domain'  
is.integral(object)
```

Arguments

object tiledb_domain

Value

TRUE if the domain is an integral domain, else FALSE

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 100L), type = "INT32")))
is.integral(dom)
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(0.5, 100.0), type = "FLOAT64")))
is.integral(dom)
```

is.sparse,tiledb_array_schema-method

Returns TRUE if the tiledb_array_schema is sparse, else FALSE

Description

Returns TRUE if the tiledb_array_schema is sparse, else FALSE

Usage

```
## S4 method for signature 'tiledb_array_schema'
is.sparse(object)
```

Arguments

object tiledb_array_schema

Value

TRUE if tiledb_array_schema is sparse

limitTileDBCores

Limit TileDB core use to a given number of cores

Description

By default, TileDB will use all available cores on a given machine. In multi-user or multi-process settings, one may want to reduce the number of core. This function will take a given number, or default to smaller of the 'Ncpus' options value or the "OMP_THREAD_LIMIT" environment variable (or two as hard fallback).

Usage

```
limitTileDBCores(ncores, verbose = FALSE)
```

Arguments

ncores	Value of CPUs used, if missing the smaller of a fallback of two, the value of 'Ncpus' (if set) and the value of environment variable "OMP_THREAD_LIMIT" is used.
verbose	Optional logical toggle; if set, a short message is displayed informing the user about the value set.

Details

As this function returns a config object, its intended use is as argument to the context creating functions: `ctx <- tiledb_ctx(limitTiledBCores())`. To check that the values are set (or at a later point, still set) the config object should be retrieved via the corresponding method and this ctx object: `cfg <- config(ctx)`.

Value

The modified configuration object is returned invisibly.

max_chunk_size	<i>Returns the filter_list's max_chunk_size</i>
----------------	---

Description

Returns the filter_list's max_chunk_size

Usage

```
max_chunk_size(object)

## S4 method for signature 'tiledb_filter_list'
max_chunk_size(object)

tiledb_filter_list_get_max_chunk_size(object)
```

Arguments

object	tiledb_filter_list
--------	--------------------

Value

integer max_chunk_size

Examples

```
flt <- tiledb_filter("ZSTD")
tiledb_filter_set_option(flt, "COMPRESSION_LEVEL", 5)
filter_list <- tiledb_filter_list(c(flt))
max_chunk_size(filter_list)
```

name,tiledb_attr-method

Return the tiledb_attr name

Description

Return the tiledb_attr name

Usage

```
## S4 method for signature 'tiledb_attr'
name(object)
```

Arguments

object tiledb_attr object

Value

string name, empty string if the attribute is anonymous

Examples

```
a1 <- tiledb_attr("a1", type = "INT32")
name(a1)

a2 <- tiledb_attr(type = "INT32")
name(a2)
```

name,tiledb_dim-method

Return the tiledb_dim name

Description

Return the tiledb_dim name

Usage

```
## S4 method for signature 'tiledb_dim'  
name(object)
```

Arguments

object tiledb_dim object

Value

string name, empty string if the dimension is anonymous

Examples

```
d1 <- tiledb_dim("d1", c(1L, 10L))  
name(d1)  
  
d2 <- tiledb_dim("", c(1L, 10L))  
name(d2)
```

nfilters,tiledb_filter_list-method

Returns the filter_list's number of filters

Description

Returns the filter_list's number of filters

Usage

```
## S4 method for signature 'tiledb_filter_list'  
nfilters(object)
```

Arguments

object tiledb_filter_list

Value

integer number of filters

Examples

```
flt <- tiledb_filter("ZSTD")
tiledb_filter_set_option(flt, "COMPRESSION_LEVEL", 5)
filter_list <- tiledb_filter_list(c(flt))
nfilters(filter_list)
```

parse_query_condition *Create a 'tiledb_query_condition' object from an expression*

Description

The grammar for query conditions is at present constraint to eight operators (" $>$ ", " $>=$ ", " $<$ ", " $<=$ ", " $=$ ", " $!=$ ", " $\%in\%$ ", " $\%nin\%$ "), and three boolean operators (" $\&\&$ ", also as " $\&$ ", (" $\|\|$ ", also as " $\|$ ", and " $!$ " for negation. Note that we locally define " $\%nin\%$ " as `Negate()` call around $\%in\%$) which extends R a little for this use case.

Usage

```
parse_query_condition(
  expr,
  ta = NULL,
  debug = FALSE,
  strict = TRUE,
  use_int64 = FALSE
)
```

Arguments

expr	An expression that is understood by the TileDB grammar for query conditions.
ta	A tiledb_array object that the query condition is applied to; this argument is optional in some cases but required in some others.
debug	A boolean toogle to enable more verbose operations, defaults to 'FALSE'.
strict	A boolean toogle to, if set, errors if a non-existing attribute is selected or filtered on, defaults to 'TRUE'; if 'FALSE' a warning is shown by execution proceeds.
use_int64	A boolean toggle to switch to integer64 if integer is seen, default is false to remain as a default four-byte int

Details

Expressions are parsed locally by this function. The `debug=TRUE` option may help if an issue has to be diagnosed. In most cases of an erroneous parse, it generally helps to supply the `tiledb_array` providing schema information. One example are numeric and integer columns where the data type is difficult to guess. Also, when using the `"%in%"` or `"%nin%"` operators, the argument is mandatory.

Value

A `tiledb_query_condition` object

Examples

```
## Not run:
uri <- "mem://airquality" # change to on-disk for persistence
fromDataFrame(airquality, uri, col_index=c("Month", "Day")) # dense array
## query condition on dense array requires extended=FALSE
tiledb_array(uri, return_as="data.frame", extended=FALSE,
             query_condition=parse_query_condition(Temp > 90))[]

## End(Not run)
```

`print.tiledb_metadata` *Print a TileDB Array Metadata object*

Description

Print a TileDB Array Metadata object

Usage

```
## S3 method for class 'tiledb_metadata'
print(x, width = NULL, ...)
```

Arguments

<code>x</code>	A TileDB array object
<code>width</code>	Optional display width, defaults to NULL
<code>...</code>	Optional method arguments, currently unused

Value

The array object, invisibly

query_condition	<i>Retrieve query_condition value for the array</i>
-----------------	---

Description

A tiledb_array object can have a corresponding query condition object. This methods returns it.

Usage

```
query_condition(object)

## S4 method for signature 'tiledb_array'
query_condition(object)
```

Arguments

object A tiledb_array object

Value

A tiledb_query_condition object

query_condition<-	<i>Set query_condition object for the array</i>
-------------------	---

Description

A tiledb_array object can have an associated query condition object to set conditions on the read queries. This methods sets the 'query_condition' object.

Usage

```
query_condition(x) <- value

## S4 replacement method for signature 'tiledb_array'
query_condition(x) <- value
```

Arguments

x A tiledb_array object
value A tiledb_query_conditon_object

Value

The modified tiledb_array array object

query_layout	<i>Retrieve query_layout values for the array</i>
--------------	---

Description

A tiledb_array object can have a corresponding query with a given layout given layout. This methods returns the selection value for 'query_layout' as a character value.

Usage

```
query_layout(object)

## S4 method for signature 'tiledb_array'
query_layout(object)
```

Arguments

object A tiledb_array object

Value

A character value describing the query layout

query_layout<-	<i>Set query_layout return values for the array</i>
----------------	---

Description

A tiledb_array object can have an associated query with a specific layout. This methods sets the selection value for 'query_layout' from a character value.

Usage

```
query_layout(x) <- value

## S4 replacement method for signature 'tiledb_array'
query_layout(x) <- value
```

Arguments

x A tiledb_array object
value A character variable for the query layout. Permitted values are "ROW_MAJOR", "COL_MAJOR", "GLOBAL_ORDER", or "UNORDERD".

Value

The modified tiledb_array array object

query_statistics	<i>Retrieve query_statistics toggle</i>
------------------	---

Description

A tiledb_array object can, if requested, return query statistics as a JSON string in an attribute 'query_statistics' attached to the return object. The default value of the logical switch is 'FALSE'. This method returns the current value.

Usage

```
query_statistics(object, ...)

## S4 method for signature 'tiledb_array'
query_statistics(object)
```

Arguments

object	A tiledb_array object
...	Currently unused

Value

A logical value indicating whether query statistics are returned.

query_statistics<-	<i>Set query_statistics toggle</i>
--------------------	------------------------------------

Description

A tiledb_array object can, if requested, return query statistics as a JSON string in an attribute 'query_statistics' attached to the return object. The default value of the logical switch is 'FALSE'. This method sets the value.

Usage

```
query_statistics(x) <- value

## S4 replacement method for signature 'tiledb_array'
query_statistics(x) <- value
```

Arguments

x	A tiledb_array object
value	A logical value with the selection

Value

The modified tiledb_array array object

raw_dump,tiledb_array_schema-method

Raw display of an array schema object

Description

This method used the display method provided by the underlying library.

Usage

```
## S4 method for signature 'tiledb_array_schema'
raw_dump(object)
```

Arguments

object An array_schema object

raw_dump,tiledb_attr-method

Raw display of an attribute object

Description

This method used the display method provided by the underlying library.

Usage

```
## S4 method for signature 'tiledb_attr'
raw_dump(object)
```

Arguments

object An attribute object

 raw_dump,tiledb_domain-method

Raw display of a domain object

Description

This method used the display method provided by the underlying library.

Usage

```
## S4 method for signature 'tiledb_domain'
raw_dump(object)
```

Arguments

object	A domain object
--------	-----------------

 return.array

Retrieve array return toggle

Description

A tiledb_array object can be returned as an array (or list of arrays), or, if select, as a data.frame or as a matrix. This methods returns the selection value for the array selection.

Usage

```
return.array(object, ...)

## S4 method for signature 'tiledb_array'
return.array(object)
```

Arguments

object	A tiledb_array object
...	Currently unused

Value

A logical value indicating whether array return is selected

```
return.array<-          Set array return toggle
```

Description

A tiledb_array object can be returned as an array (or list of arrays), or, if select, as a data.frame or a matrix. This methods sets the selection value for a array.

Usage

```
return.array(x) <- value

## S4 replacement method for signature 'tiledb_array'
return.array(x) <- value
```

Arguments

```
x                A tiledb_array object
value            A logical value with the selection
```

Value

The modified tiledb_array array object

```
return.data.frame,tiledb_array-method
          Retrieve data.frame return toggle
```

Description

A tiledb_array object can be returned as an array (or list of arrays), or, if select, as a data.frame. This methods returns the selection value.

Usage

```
## S4 method for signature 'tiledb_array'
return.data.frame(object)
```

Arguments

```
object          A tiledb_array object
```

Value

A logical value indicating whether data.frame return is selected

```
return.data.frame<-, tiledb_array-method
      Set data.frame return toggle
```

Description

A tiledb_array object can be returned as an array (or list of arrays), or, if select, as a data.frame. This methods sets the selection value.

Usage

```
## S4 replacement method for signature 'tiledb_array'
return.data.frame(x) <- value
```

Arguments

x	A tiledb_array object
value	A logical value with the selection

Value

The modified tiledb_array array object

```
return.matrix      Retrieve matrix return toggle
```

Description

A tiledb_array object can be returned as an array (or list of arrays), or, if select, as a data.frame or as a matrix. This methods returns the selection value for the matrix selection.

Usage

```
return.matrix(object, ...)

## S4 method for signature 'tiledb_array'
return.matrix(object)
```

Arguments

object	A tiledb_array object
...	Currently unused

Value

A logical value indicating whether matrix return is selected

return.matrix<-	<i>Set matrix return toggle</i>
-----------------	---------------------------------

Description

A tiledb_array object can be returned as an array (or list of arrays), or, if select, as a data.frame or a matrix. This methods sets the selection value for a matrix.

Usage

```
return.matrix(x) <- value

## S4 replacement method for signature 'tiledb_array'
return.matrix(x) <- value
```

Arguments

x	A tiledb_array object
value	A logical value with the selection

Value

The modified tiledb_array array object

return_as	<i>Retrieve return_as conversion preference</i>
-----------	---

Description

A tiledb_array object can be returned as a 'list' (default), 'array', 'matrix', 'data.frame', 'data.table' or 'tibble'. This method permits to select a preference for the returned object. The default value of 'asis' means that no conversion is performed.

Usage

```
return_as(object, ...)
```

```
## S4 method for signature 'tiledb_array'
return_as(object)
```

Arguments

object	A tiledb_array object
...	Currently unused

Value

A character value indicating the preferred conversion where the value is one of 'asis' (the default), 'array', 'matrix', 'data.frame', 'data.table', or 'tibble'.

return_as<-	<i>Retrieve return_as conversion preference</i>
-------------	---

Description

A tiledb_array object can be returned as a 'list' (default), 'array', 'matrix', 'data.frame', 'data.table' or 'tibble'. This method This methods permits to set a preference of returning a list, array, matrix, data.frame, a data.table, or a tibble. The default value of "asis" means that no conversion is performed and a list is returned.

Usage

```
return_as(x) <- value

## S4 replacement method for signature 'tiledb_array'
return_as(x) <- value
```

Arguments

x	A tiledb_array object
value	A character value with the selection

Value

The modified tiledb_array array object

r_to_tiledb_type	<i>Look up TileDB type corresponding to the type of an R object</i>
------------------	---

Description

Look up TileDB type corresponding to the type of an R object

Usage

```
r_to_tiledb_type(x)
```

Arguments

x	an R array or list
---	--------------------

Value

single character, e.g. INT32

save_allocation_size_preference
Store allocation size preference

Description

Save (or load) allocation size default preference in an optional config file

Usage

save_allocation_size_preference(value)

load_allocation_size_preference()

get_allocation_size_preference()

set_allocation_size_preference(value)

Arguments

value A numeric value with the desired allocation size (in bytes).

Details

When retrieving data from sparse arrays, allocation sizes cannot be determined *ex ante* as the degree of sparsity is unknown. A configuration value can aid in providing an allocation size value. These functions let the user store such a value for retrieval by their package or script code. The preference will be encoded in a configuration file as R (version 4.0.0 or later) allows a user- and package specific configuration files. These helper functions sets and retrieve the value, respectively, or retrieve the cached value from the package environment where is it set at package load.

The value will be stored as a character value and reparsed so ‘1e6’ and ‘1000000’ are equivalent, and the fixed (but adjustable) number of digits for numerical precision *use for formatting* will impact the writing. This should have no effect on standard allocation sizes.

The value is used as a limit *per column* so total memory use per query will a multiple of this value, and increasing in dimension and attribute count.

A fallback value of 10 mb is used if no user value is set.

Value

For the setter, TRUE is returned invisibly but the function is invoked for the side effect of storing the value. For the getters, the value as a numeric.

Note

This function requires R version 4.0.0 or later to utilise the per-user config directory accessor function. For older R versions, a fallback from the TileDB configuration object is used.

save_return_as_preference
Store object conversion preference

Description

Save (or load) 'return_as' conversion preference in an optional config file

Usage

```
save_return_as_preference(  
  value = c("asis", "array", "matrix", "data.frame", "data.table", "tibble")  
)  
  
load_return_as_preference()  
  
get_return_as_preference()  
  
set_return_as_preference(  
  value = c("asis", "array", "matrix", "data.frame", "data.table", "tibble")  
)
```

Arguments

value A character variable with one of the six permitted values

Details

The tiledb_array object can set a preference for conversion for each retrieved object. This preference can also be encoded in a configuration file as R (version 4.0.0 or later) allows a user- and package specific configuration files. These helper functions sets and retrieve the value, respectively, or retrieve the cached value from the package environment where is it set at package load.

Note that the value must be one of 'asis' (the default), 'array', 'matrix', 'data.frame', 'data.table' or 'tibble'. The latter two require the corresponding package to be installed.

Value

For the setter, TRUE is returned invisibly but the function is invoked for the side effect of storing the value. For either getter, the character value.

Note

This function requires R version 4.0.0 or later to utilise the per-user config directory accessor function. For older R versions, please set the attribute directly when creating the tiledb_array object, or via the return_as() method.

schema,character-method

Return a schema from a URI character value

Description

Return a schema from a URI character value

Usage

```
## S4 method for signature 'character'
schema(object, ...)
```

Arguments

object	A character variable with a URI
...	Extra parameters such as 'enckey', the encryption key

Value

The scheme for the object

schema,tiledb_array-method

Return a schema from a tiledb_array object

Description

Return a schema from a tiledb_array object

Usage

```
## S4 method for signature 'tiledb_array'
schema(object, ...)
```

Arguments

object	tiledb array object
...	Extra parameter for function signature, currently unused

Value

The scheme for the object

schema_check	<i>Check the schema for correctness</i>
--------------	---

Description

Returns the tiledb_array schema for correctness

Usage

```

schema_check(object)

## S4 method for signature 'tiledb_array_schema'
schema_check(object)

check(object)

## S4 method for signature 'tiledb_array_schema'
check(object)

tiledb_array_schema_check(object)

```

Arguments

object An array_schema object

Value

The boolean value TRUE is returned for a correct schema; for an incorrect schema an error condition is triggered.

selected_points	<i>Retrieve selected_points values for the array</i>
-----------------	--

Description

A tiledb_array object can have a range selection for each dimension attribute. This methods returns the selection value for 'selected_points' and returns a list (with one element per dimension) of vectors where each row describes one selected points. Alternatively, the list can be named with the names providing the match to the corresponding dimension.

Usage

```

selected_points(object)

## S4 method for signature 'tiledb_array'
selected_points(object)

```

Arguments

object A tiledb_array object

Value

A list which can contain a vector for each dimension

selected_points<- *Set selected_points return values for the array*

Description

A tiledb_array object can have a range selection for each dimension attribute. This methods sets the selection value for 'selected_points' which is a list (with one element per dimension) of two-column matrices where each row describes one pair of minimum and maximum values. Alternatively, the list can be named with the names providing the match to the corresponding dimension.

Usage

```
selected_points(x) <- value

## S4 replacement method for signature 'tiledb_array'
selected_points(x) <- value
```

Arguments

x A tiledb_array object

value A list of vectors where each list element 'i' corresponds to the dimension attribute 'i'.

Value

The modified tiledb_array array object

selected_ranges *Retrieve selected_ranges values for the array*

Description

A tiledb_array object can have a range selection for each dimension attribute. This methods returns the selection value for 'selected_ranges' and returns a list (with one element per dimension) of two-column matrices where each row describes one pair of minimum and maximum values. Alternatively, the list can be named with the names providing the match to the corresponding dimension.

Usage

```
selected_ranges(object)

## S4 method for signature 'tiledb_array'
selected_ranges(object)
```

Arguments

`object` A tiledb_array object

Value

A list which can contain a matrix for each dimension

`selected_ranges<-` *Set selected_ranges return values for the array*

Description

A tiledb_array object can have a range selection for each dimension attribute. This methods sets the selection value for 'selected_ranges' which is a list (with one element per dimension) of two-column matrices where each row describes one pair of minimum and maximum values. Alternatively, the list can be named with the names providing the match to the corresponding dimension.

Usage

```
selected_ranges(x) <- value

## S4 replacement method for signature 'tiledb_array'
selected_ranges(x) <- value
```

Arguments

`x` A tiledb_array object

`value` A list of two-column matrices where each list element 'i' corresponds to the dimension attribute 'i'. The matrices can contain rows where each row contains the minimum and maximum value of a range.

Value

The modified tiledb_array array object

set_max_chunk_size *Set the filter_list's max_chunk_size*

Description

Set the filter_list's max_chunk_size

Usage

```
set_max_chunk_size(object, value)

## S4 method for signature 'tiledb_filter_list,numeric'
set_max_chunk_size(object, value)

tiledb_filter_list_set_max_chunk_size(object, value)
```

Arguments

object	tiledb_filter_list
value	A numeric value

Examples

```
flt <- tiledb_filter("ZSTD")
tiledb_filter_set_option(flt, "COMPRESSION_LEVEL", 5)
filter_list <- tiledb_filter_list(c(flt))
set_max_chunk_size(filter_list, 10)
```

show,tiledb_array-method
Prints a tiledb_array object

Description

Prints a tiledb_array object

Usage

```
## S4 method for signature 'tiledb_array'
show(object)
```

Arguments

object	A tiledb array object
--------	-----------------------

show,tiledb_array_schema-method
Prints an array schema object

Description

Prints an array schema object

Usage

```
## S4 method for signature 'tiledb_array_schema'  
show(object)
```

Arguments

object An array_schema object

show,tiledb_attr-method
Prints an attribute object

Description

Prints an attribute object

Usage

```
## S4 method for signature 'tiledb_attr'  
show(object)
```

Arguments

object An attribute object

show,tiledb_config-method

Prints the config object to STDOUT

Description

Prints the config object to STDOUT

Usage

```
## S4 method for signature 'tiledb_config'  
show(object)
```

Arguments

object tiledb_config object

Examples

```
cfg <- tiledb_config()  
show(cfg)
```

show,tiledb_dim-method

Prints a dimension object

Description

Prints a dimension object

Usage

```
## S4 method for signature 'tiledb_dim'  
show(object)
```

Arguments

object A dimension object

show,tiledb_domain-method
Prints a domain object

Description

Prints a domain object

Usage

```
## S4 method for signature 'tiledb_domain'  
show(object)
```

Arguments

object A domain object

show,tiledb_filter-method
Prints a filter object

Description

Prints a filter object

Usage

```
## S4 method for signature 'tiledb_filter'  
show(object)
```

Arguments

object A filter object

show,tiledb_filter_list-method
Prints a filter_list object

Description

Prints a filter_list object

Usage

```
## S4 method for signature 'tiledb_filter_list'  
show(object)
```

Arguments

object A filter_list object

show,tiledb_group-method
Display the TileDB Group object to STDOUT

Description

Display the TileDB Group object to STDOUT

Usage

```
## S4 method for signature 'tiledb_group'  
show(object)
```

Arguments

object tiledb_group object

statusBatched	<i>Return 'batched' status</i>
---------------	--------------------------------

Description

Batched queries return an initial result set even when it is incomplete. Where the normal retrieval process will loop in place to complete a (potentially large) result set, this function will return a result (which may be part of a larger result set) allowing the user to assemble all part.

Usage

```
statusBatched(obj)
```

Arguments

obj	A list object as returned by createBatched
-----	--

Value

The Query status as a character variable

strings_as_factors	<i>Retrieve strings_as_factors conversion toggle</i>
--------------------	--

Description

A tiledb_array object containing character column can have those converted to factors variables. This methods returns the selection value for 'strings_as_factors'.

Usage

```
strings_as_factors(object)

## S4 method for signature 'tiledb_array'
strings_as_factors(object)
```

Arguments

object	A tiledb_array object
--------	-----------------------

Value

A logical value indicating whether an strings_as_factors return is selected

```
strings_as_factors<- Set strings_as_factors return toggle
```

Description

A tiledb_array object containing character column can have those converted to factors variables. This methods sets the selection value for 'strings_as_factors'.

Usage

```
strings_as_factors(x) <- value

## S4 replacement method for signature 'tiledb_array'
strings_as_factors(x) <- value
```

Arguments

x	A tiledb_array object
value	A logical value with the selection

Value

The modified tiledb_array array object

```
tdb_collect, tiledb_array-method
Collect the query results to finalize piped expression
```

Description

Collect the query results to finalize piped expression

Usage

```
## S4 method for signature 'tiledb_array'
tdb_collect(x, ...)
```

Arguments

x	A tiledb_array object as first argument, permitting piping
...	Ignored

Value

The object returning from a tiledb_array query (the type of which can be set via the return preference mechanism, see the help for "[" accessor)

 tdb_filter,tiledb_array-method

Filter from array for query via logical conditions

Description

Filter from array for query via logical conditions

Usage

```
## S4 method for signature 'tiledb_array'
tdb_filter(x, ..., strict = TRUE)
```

Arguments

x	A tiledb_array object as first argument, permitting piping
...	One or more expressions that are parsed as query_condition objects
strict	A boolean toggle to, if set, errors if a non-existing attribute is selected or filtered on, defaults to 'TRUE'; if 'FALSE' a warning is shown by execution proceeds.

Value

The tiledb_array object, permitting piping

tdb_select,tiledb_array-method

Select attributes from array for query

Description

Select attributes from array for query

Usage

```
## S4 method for signature 'tiledb_array'
tdb_select(x, ...)
```

Arguments

x	A tiledb_array object as first argument, permitting piping
...	One or more attributes of the query

Value

The tiledb_array object, permitting piping

```
tile, tiledb_dim-method
```

Return the tiledb_dim tile extent

Description

Return the tiledb_dim tile extent

Usage

```
## S4 method for signature 'tiledb_dim'  
tile(object)
```

Arguments

object tiledb_dim object

Value

a scalar tile extent

Examples

```
d1 <- tiledb_dim("d1", domain = c(5L, 10L), tile = 2L)  
tile(d1)
```

```
tiledb_array            Constructs a tiledb_array object backed by a persisted tiledb array uri
```

Description

tiledb_array returns a new object. This class is experimental.

Usage

```
tiledb_array(  
  uri,  
  query_type = c("READ", "WRITE"),  
  is.sparse = NA,  
  as.data.frame = FALSE,  
  attrs = character(),  
  extended = TRUE,  
  selected_ranges = list(),  
  selected_points = list(),
```

```

    query_layout = character(),
    datetimes_as_int64 = FALSE,
    encryption_key = character(),
    as.matrix = FALSE,
    as.array = FALSE,
    query_condition = new("tiledb_query_condition"),
    timestamp_start = as.POSIXct(double(), origin = "1970-01-01"),
    timestamp_end = as.POSIXct(double(), origin = "1970-01-01"),
    return_as = get_return_as_preference(),
    query_statistics = FALSE,
    strings_as_factors = getOption("stringsAsFactors", FALSE),
    keep_open = FALSE,
    sil = list(),
    dumpbuffers = character(),
    buffers = list(),
    ctx = tiledb_get_context()
)

tiledb_dense(...)

tiledb_sparse(...)

```

Arguments

uri	uri path to the tiledb dense array
query_type	optionally loads the array in "READ" or "WRITE" only modes.
is.sparse	optional logical switch, defaults to "NA" letting array determine it
as.data.frame	optional logical switch, defaults to "FALSE"
attrs	optional character vector to select attributes, default is empty implying all are selected, the special value NA_character_ has the opposite effect and implies no attributes are returned.
extended	optional logical switch selecting wide 'data.frame' format, defaults to TRUE
selected_ranges	optional A list with matrices where each matrix i describes the (min,max) pair of ranges selected for dimension i
selected_points	optional A list with vectors where each vector i describes the points selected in dimension i
query_layout	optional A value for the TileDB query layout, defaults to an empty character variable indicating no special layout is set
datetimes_as_int64	optional A logical value selecting date and datetime value representation as 'raw' integer64 and not as Date, POSIXct or nanotime objects.
encryption_key	optional A character value with an AES-256 encryption key in case the array was written with encryption.

<code>as.matrix</code>	optional logical switch, defaults to "FALSE"; currently limited to dense matrices; in the case of multiple attributes in query a list of matrices is returned
<code>as.array</code>	optional logical switch, defaults to "FALSE"; in the case of multiple attributes in query a list of arrays is returned
<code>query_condition</code>	optional <code>tiledb_query_condition</code> object, by default uninitialized without a condition; this functionality requires TileDB 2.3.0 or later
<code>timestamp_start</code>	optional A POSIXct Datetime value determining the inclusive time point at which the array is to be opened. No fragments written earlier will be considered.
<code>timestamp_end</code>	optional A POSIXct Datetime value determining the inclusive time point until which the array is to be opened. No fragments written earlier later be considered.
<code>return_as</code>	optional A character value with the desired <code>tiledb_array</code> conversion, permitted values are 'asis' (default, returning a list of columns), 'array', 'matrix', 'data.frame', 'data.table', 'tibble', 'arrow_table', or 'arrow' (as an alias for 'arrow_table'; here 'data.table', 'tibble' and 'arrow' require the respective packages to be installed. The existing <code>as.*</code> arguments take precedent over this.
<code>query_statistics</code>	optional A logical value, defaults to 'FALSE'; if 'TRUE' the query statistics are returned (as a JSON string) via the attribute 'query_statistics' of the return object.
<code>strings_as_factors</code>	An optional logical to convert character columns to factor type; defaults to the value of <code>getOption("stringsAsFactors", FALSE)</code> .
<code>keep_open</code>	An optional logical to not close after read or write
<code>sil</code>	optional A list, by default empty to store schema information when query objects are parsed.
<code>dumpbuffers</code>	An optional character variable with a directory name (relative to <code>/dev/shm</code>) for writing out results buffers (for internal use / testing)
<code>buffers</code>	An optional list with full pathnames of shared memory buffers to read data from
<code>ctx</code>	optional <code>tiledb_ctx</code>
<code>...</code>	Used as a pass-through for <code>tiledb_dense</code> and <code>tiledb_sparse</code> aliasing

Value

`tiledb_array` object

tiledb_array-class	<i>An S4 class for a TileDB Array</i>
--------------------	---------------------------------------

Description

This class replaces the earlier (and now removed) `tiledb_dense` and `tiledb_sparse` and provides equivalent functionality based on a refactored implementation utilising newer TileDB features.

Slots

`ctx` A TileDB context object

`uri` A character description with the array URI

`is.sparse` A logical value whether the array is sparse or not

`as.data.frame` A logical value

`attrs` A character vector to select particular column ‘attributes’; default is an empty character vector implying ‘all’ columns, the special value `NA_character_` has the opposite effect and selects ‘none’.

`extended` A logical value, defaults to TRUE, indicating whether index columns are returned as well.

`selected_ranges` An optional list with matrices where each matrix `i` describes the (min,max) pair of ranges for dimension `i`

`selected_points` An optional list with vectors where each vector `i` describes the selected points for dimension `i`

`query_layout` An optional character value

`datetimes_as_int64` A logical value

`encryption_key` A character value

`as.matrix` A logical value

`as.array` A logical value

`query_condition` A Query Condition object

`timestamp_start` A POSIXct datetime variable for the inclusive interval start

`timestamp_end` A POSIXct datetime variable for the inclusive interval start

`return_as` A character value with the desired `tiledb_array` conversion, permitted values are ‘asis’ (default, returning a list of columns), ‘array’, ‘matrix’, ‘data.frame’, ‘data.table’, ‘tibble’, ‘arrow_table’ or ‘arrow’ (where the last two are synonyms); note that ‘data.table’, ‘tibble’ and ‘arrow’ require the respective packages to be installed.

`query_statistics` A logical value, defaults to ‘FALSE’; if ‘TRUE’ the query statistics are returned (as a JSON string) via the attribute ‘query_statistics’ of the return object.

`sil` An optional and internal list object with schema information, used for parsing queries.

`dumpbuffers` An optional character variable with a directory name (relative to `/dev/shm`) for writing out results buffers (for internal use / testing)

`buffers` An optional list with full pathnames of shared memory buffers to read data from

`strings_as_factors` An optional logical to convert character columns to factor type

`keep_open` An optional logical to not close after read or write

`ptr` External pointer to the underlying implementation

tiledb_array_apply_aggregate

Run an aggregate query on the given (sparse) array and attribute

Description

For dense arrays, use tiledb_query_apply_aggregate after setting an appropriate subarray.

Usage

```
tiledb_array_apply_aggregate(
  array,
  attrname,
  operation = c("Count", "NullCount", "Min", "Max", "Mean", "Sum"),
  nullable = TRUE
)
```

Arguments

array	A TileDB Array object
attrname	The name of an attribute
operation	The name of aggregation operation
nullable	A boolean toggle whether the attribute is nullable

Value

The value of the aggregation

tiledb_array_close *Close a TileDB Array*

Description

Close a TileDB Array

Usage

```
tiledb_array_close(arr)
```

Arguments

arr	A TileDB Array object as for example returned by tiledb_array()
-----	---

Value

The TileDB Array object but closed

tiledb_array_create *Creates a new TileDB array given an input schema.*

Description

Creates a new TileDB array given an input schema.

Usage

```
tiledb_array_create(uri, schema, encryption_key)
```

Arguments

uri	URI specifying path to create the TileDB array object
schema	tiledb_array_schema object
encryption_key	optional A character value with an AES-256 encryption key in case the array should be encryption.

Examples

```
## Not run:
pth <- tempdir()
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 10L), type = "INT32")))
sch <- tiledb_array_schema(dom, attrs = c(tiledb_attr("a1", type = "INT32")))
tiledb_array_create(pth, sch)
tiledb_object_type(pth)

## End(Not run)
```

tiledb_array_delete_fragments *Delete fragments written between the start and end times given*

Description

Delete fragments written between the start and end times given

Usage

```
tiledb_array_delete_fragments(
  arr,
  ts_start,
  ts_end,
  ctx = tiledb_get_context()
)
```

Arguments

arr	A TileDB Array object as for example returned by tiledb_array()
ts_start	A Datetime object that will be converted to millisecond granularity
ts_end	A Datetime object that will be converted to millisecond granularity
ctx	A tiledb_ctx object (optional)

Value

A boolean indicating success

tiledb_array_get_non_empty_domain_from_index

Get the non-empty domain from a TileDB Array by index

Description

This functions works for both fixed- and variable-sized dimensions and switches internally.

Usage

```
tiledb_array_get_non_empty_domain_from_index(arr, idx)
```

Arguments

arr	A TileDB Array
idx	An integer index between one the number of dimensions

Value

A two-element object is returned describing the domain of selected dimension; it will either be a numeric vector in case of a fixed-size fixed-sized dimensions, or a character vector for a variable-sized one.

`tiledb_array_get_non_empty_domain_from_name`*Get the non-empty domain from a TileDB Array by name*

Description

This functions works for both fixed- and variable-sized dimensions and switches internally.

Usage

```
tiledb_array_get_non_empty_domain_from_name(arr, name)
```

Arguments

<code>arr</code>	A TileDB Array
<code>name</code>	An character variable with a dimension name

Value

A two-element object is returned describing the domain of selected dimension; it will either be a numeric vector in case of a fixed-size fixed-sized dimensions, or a character vector for a variable-sized one.

`tiledb_array_has_enumeration`*Check for Enumeration (aka Factor aka Dictionary)*

Description

Check for Enumeration (aka Factor aka Dictionary)

Usage

```
tiledb_array_has_enumeration(arr)
```

Arguments

<code>arr</code>	A TileDB Array object
------------------	-----------------------

Value

A boolean indicating if the array has homogeneous domains

tiledb_array_is_heterogeneous

Check for Heterogeneous Domain

Description

Check for Heterogeneous Domain

Usage

tiledb_array_is_heterogeneous(arr)

Arguments

arr A TileDB Array object

Value

A boolean indicating if the array has heterogenous domains

tiledb_array_is_homogeneous

Check for Homogeneous Domain

Description

Check for Homogeneous Domain

Usage

tiledb_array_is_homogeneous(arr)

Arguments

arr A TileDB Array object

Value

A boolean indicating if the array has homogeneous domains

tiledb_array_is_open *Test if TileDB Array is open*

Description

Test if TileDB Array is open

Usage

```
tiledb_array_is_open(arr)
```

Arguments

arr A TileDB Array object as for example returned by tiledb_array()

Value

A boolean indicating whether the TileDB Array object is open

tiledb_array_open *Open a TileDB Array*

Description

Open a TileDB Array

Usage

```
tiledb_array_open(
  arr,
  type = if (tiledb_version(TRUE) >= "2.12.0") c("READ", "WRITE", "DELETE",
    "MODIFY_EXCLUSIVE") else c("READ", "WRITE")
)
```

Arguments

arr A TileDB Array object as for example returned by tiledb_array()
 type A character value that must be either 'READ', 'WRITE' or (for TileDB 2.12.0 or later) 'DELETE' or 'MODIFY_EXCLUSIVE'

Value

The TileDB Array object but opened for reading or writing

tiledb_array_open_at *Open a TileDB Array at Timestamp*

Description

Open a TileDB Array at Timestamp

Usage

```
tiledb_array_open_at(arr, type = c("READ", "WRITE"), timestamp)
```

Arguments

arr	A TileDB Array object as for example returned by tiledb_array()
type	A character value that must be either 'READ' or 'WRITE'
timestamp	A Datetime object that will be converted to millisecond granularity

Value

The TileDB Array object but opened for reading or writing

tiledb_array_schema *Constructs a tiledb_array_schema object*

Description

Constructs a tiledb_array_schema object

Usage

```
tiledb_array_schema(
  domain,
  attrs,
  cell_order = "COL_MAJOR",
  tile_order = "COL_MAJOR",
  sparse = FALSE,
  coords_filter_list = NULL,
  offsets_filter_list = NULL,
  validity_filter_list = NULL,
  capacity = 10000L,
  allows_dups = FALSE,
  enumerations = NULL,
  ctx = tiledb_get_context()
)
```


Arguments

domain	tiledb_domain object
attrs	a list of one or more tiledb_attr objects
cell_order	(default "COL_MAJOR")
tile_order	(default "COL_MAJOR")
sparse	(default FALSE)
coords_filter_list	(optional)
offsets_filter_list	(optional)
validity_filter_list	(optional)
capacity	(optional)
allows_dups	(optional, requires 'sparse' to be TRUE)
enumerations	(optional) named list of enumerations
ctx	tiledb_ctx object (optional)

Examples

```

schema <- tiledb_array_schema(
  dom = tiledb_domain(
    dims = c(tiledb_dim("rows", c(1L, 4L), 4L, "INT32"),
             tiledb_dim("cols", c(1L, 4L), 4L, "INT32")),
    attrs = c(tiledb_attr("a", type = "INT32")),
    cell_order = "COL_MAJOR",
    tile_order = "COL_MAJOR",
    sparse = FALSE)
)
schema

```

tiledb_array_schema-class

An S4 class for the TileDB array schema

Description

An S4 class for the TileDB array schema

Slots

ptr An external pointer to the underlying implementation
 arrptr An optional external pointer to the underlying array, or NULL if missing

```
tiledb_array_schema_evolution
```

Creates a 'tiledb_array_schema_evolution' object

Description

Creates a 'tiledb_array_schema_evolution' object

Usage

```
tiledb_array_schema_evolution(ctx = tiledb_get_context())
```

Arguments

ctx (optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

A 'array_schema_evolution' object

```
tiledb_array_schema_evolution-class
```

An S4 class for a TileDB ArraySchemaEvolution object

Description

An S4 class for a TileDB ArraySchemaEvolution object

Slots

ptr An external pointer to the underlying implementation

 tiledb_array_schema_evolution_add_attribute

Add an Attribute to a TileDB Array Schema Evolution object

Description

Add an Attribute to a TileDB Array Schema Evolution object

Usage

```
tiledb_array_schema_evolution_add_attribute(object, attr)
```

Arguments

object	A TileDB 'array_schema_evolution' object
attr	A TileDB attribute

Value

The modified 'array_schema_evolution' object, invisibly

tiledb_array_schema_evolution_add_enumeration

Add an Enumeration to a TileDB Array Schema Evolution object

Description

Add an Enumeration to a TileDB Array Schema Evolution object

Usage

```
tiledb_array_schema_evolution_add_enumeration(
  object,
  name,
  enums,
  ordered = FALSE,
  ctx = tiledb_get_context()
)
```

Arguments

object	A TileDB 'array_schema_evolution' object
name	A character value with the name for the Enumeration
enums	A character vector
ordered	(optional) A boolean switch whether the enumeration is ordered
ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

The modified 'array_schema_evolution' object, invisibly

tiledb_array_schema_evolution_add_enumeration_empty
Evolve an Array Schema by adding an empty Enumeration

Description

Evolve an Array Schema by adding an empty Enumeration

Usage

```
tiledb_array_schema_evolution_add_enumeration_empty(
  ase,
  enum_name,
  type_str = "ASCII",
  cell_val_num = NA_integer_,
  ordered = FALSE,
  ctx = tiledb_get_context()
)
```

Arguments

ase	An ArraySchemaEvolution object
enum_name	A character value with the Enumeration name
type_str	A character value with the TileDB type, defaults to 'ASCII'
cell_val_num	An integer with number values per cell, defaults to NA_integer_ to flag the NA value use for character values
ordered	A logical value indicating standard factor (when FALSE, the default) or ordered (when TRUE)
ctx	Optional tiledb_ctx object

tiledb_array_schema_evolution_array_evolve
Evolve an Array Schema

Description

Evolve an Array Schema

Usage

```
tiledb_array_schema_evolution_array_evolve(object, uri)
```

Arguments

object A TileDB 'array_schema_evolution' object
 uri A character variable with an URI

Value

The modified 'array_schema_evolution' object, invisibly

tiledb_array_schema_evolution_drop_attribute

Drop an attribute given by name from a TileDB Array Schema Evolution object

Description

Drop an attribute given by name from a TileDB Array Schema Evolution object

Usage

tiledb_array_schema_evolution_drop_attribute(object, attrname)

Arguments

object A TileDB 'array_schema_evolution' object
 attrname A character variable with an attribute name

Value

The modified 'array_schema_evolution' object, invisibly

tiledb_array_schema_evolution_drop_enumeration

Drop an Enumeration given by name from a TileDB Array Schema Evolution object

Description

Drop an Enumeration given by name from a TileDB Array Schema Evolution object

Usage

tiledb_array_schema_evolution_drop_enumeration(object, attrname)

Arguments

object	A TileDB 'array_schema_evolution' object
attrname	A character variable with an attribute name

Value

The modified 'array_schema_evolution' object, invisibly

tiledb_array_schema_evolution_extend_enumeration
Extend an Evolution via Array Schema Evolution

Description

Extend an Evolution via Array Schema Evolution

Usage

```
tiledb_array_schema_evolution_extend_enumeration(
  ase,
  array,
  enum_name,
  new_values,
  nullable = FALSE,
  ordered = FALSE,
  ctx = tiledb_get_context()
)
```

Arguments

ase	An ArraySchemaEvolution object
array	A TileDB Array object
enum_name	A character value with the Enumeration name
new_values	A character vector with the new Enumeration values
nullable	A logical value indicating if the Enumeration can contain missing values (with a default of FALSE)
ordered	A logical value indicating standard factor (when FALSE, the default) or ordered (when TRUE)
ctx	Optional tiledb_ctx object

 tiledb_array_schema_set_coords_filter_list

Set a Filter List for Coordinate of a TileDB Schema

Description

Set a Filter List for Coordinate of a TileDB Schema

Usage

```
tiledb_array_schema_set_coords_filter_list(sch, fl)
```

Arguments

sch	A TileDB Array Schema object
fl	A TileDB Filter List object

Value

The modified Array Schema object

 tiledb_array_schema_set_enumeration_empty

Add an empty Enumeration to a Schema

Description

Add an empty Enumeration to a Schema

Usage

```
tiledb_array_schema_set_enumeration_empty(
  schema,
  attr,
  enum_name,
  type_str = "ASCII",
  cell_val_num = NA_integer_,
  ordered = FALSE,
  ctx = tiledb_get_context()
)
```

Arguments

schema	An Array Schema
attr	An Attribute for which an empty Enumeration will be added
enum_name	A character value with the Enumeration name
type_str	A character value with the TileDB type, defaults to 'ASCII'
cell_val_num	An integer with number values per cell, defaults to NA_integer_ to flag the NA value use for character values
ordered	A logical value indicated standard factor (when FALSE, the default) or ordered (when TRUE)
ctx	Optional tiledb_ctx object

tiledb_array_schema_set_offsets_filter_list

Set a Filter List for Variable-Sized Offsets of a TileDB Schema

Description

Set a Filter List for Variable-Sized Offsets of a TileDB Schema

Usage

```
tiledb_array_schema_set_offsets_filter_list(sch, fl)
```

Arguments

sch	A TileDB Array Schema object
fl	A TileDB Filter List object

Value

The modified Array Schema object

tiledb_array_schema_set_validity_filter_list
Set a Filter List for Validity of a TileDB Schema

Description

Set a Filter List for Validity of a TileDB Schema

Usage

```
tiledb_array_schema_set_validity_filter_list(sch, fl)
```

Arguments

sch	A TileDB Array Schema object
fl	A TileDB Filter List object

Value

The modified Array Schema object

tiledb_array_schema_version
Check the version of the array schema

Description

Returns the (internal) version of the tiledb_array schema

Usage

```
tiledb_array_schema_version(object)
```

Arguments

object	An array_schema object
--------	------------------------

Value

An integer value describing the internal schema format version

tiledb_array_upgrade_version

Upgrade an Array to the current TileDB Array Schema Format

Description

Upgrade an Array to the current TileDB Array Schema Format

Usage

```
tiledb_array_upgrade_version(array, config = NULL, ctx = tiledb_get_context())
```

Arguments

array	A TileDB Array object
config	A TileDB Configuration (optional, default NULL)
ctx	A tiledb_ctx object (optional)

Value

Nothing is returned as the function is invoked for its side effect

tiledb_arrow_array_ptr

(Deprecated) Allocate (or Release) Arrow Array and Schema Pointers

Description

These functions allocate (and free) appropriate pointer objects for, respectively, Arrow array and schema objects. These functions are deprecated and will be removed, it is recommended to rely directly on the nanoarrow replacements.

Usage

```
tiledb_arrow_array_ptr()
tiledb_arrow_schema_ptr()
tiledb_arrow_array_del(ptr)
tiledb_arrow_schema_del(ptr)
```

Arguments

ptr	A external pointer object previously allocated with these functions
-----	---

Value

The allocating functions return the requested pointer

tiledb_attr	<i>Constructs a tiledb_attr object</i>
-------------	--

Description

Constructs a tiledb_attr object

Usage

```
tiledb_attr(
  name,
  type,
  filter_list = tiledb_filter_list(),
  ncells = 1,
  nullable = FALSE,
  enumeration = NULL,
  ctx = tiledb_get_context()
)
```

Arguments

name	The dimension name / label string; if missing default "" is used.
type	The tiledb_attr TileDB datatype string; if missing the user is alerted that this is a <i>required</i> parameter.
filter_list	(default filter_list("NONE")) An optional tiledb_filter_list object
ncells	(default 1) The number of cells, use NA to signal variable length
nullable	(default FALSE) A logical switch whether the attribute can have missing values
enumeration	(default NULL) A character vector of dictionary values
ctx	tiledb_ctx object (optional)

Value

tiledb_dim object

Examples

```
flt <- tiledb_filter_list(list(tiledb_filter("GZIP")))
attr <- tiledb_attr(name = "a1", type = "INT32",
                  filter_list = flt)
attr
```

tiledb_attr-class *An S4 class for a TileDB attribute*

Description

An S4 class for a TileDB attribute

Slots

ptr External pointer to the underlying implementation

tiledb_attribute_get_cell_size
Get the TileDB Attribute cell size

Description

Get the TileDB Attribute cell size

Usage

tiledb_attribute_get_cell_size(attr)

Arguments

attr A TileDB Attribute object

Value

A numeric value with the cell size

tiledb_attribute_get_enumeration
Get the TileDB Attribute Enumeration

Description

Get the TileDB Attribute Enumeration

Usage

tiledb_attribute_get_enumeration(attr, arr, ctx = tiledb_get_context())

tiledb_attribute_get_enumeration_ptr(attr, arrptr, ctx = tiledb_get_context())

Arguments

<code>attr</code>	A TileDB Attribute object
<code>arr</code>	A Tiledb Array object
<code>ctx</code>	A Tiledb Context object (optional)
<code>arrptr</code>	A Tiledb Array object pointer

Value

A character vector with the enumeration (of length zero if none)

`tiledb_attribute_get_fill_value`
Get the fill value for a TileDB Attribute

Description

Get the fill value for a TileDB Attribute

Usage

`tiledb_attribute_get_fill_value(attr)`

Arguments

<code>attr</code>	A TileDB Attribute object
-------------------	---------------------------

Value

The fill value for the attribute

`tiledb_attribute_get_nullable`
Get the TileDB Attribute Nullable flag value

Description

Get the TileDB Attribute Nullable flag value

Usage

`tiledb_attribute_get_nullable(attr)`

Arguments

<code>attr</code>	A TileDB Attribute object
-------------------	---------------------------

Value

A boolean value with the 'Nullable' status

tiledb_attribute_has_enumeration

Test if TileDB Attribute has an Enumeration

Description

Test if TileDB Attribute has an Enumeration

Usage

```
tiledb_attribute_has_enumeration(attr, ctx = tiledb_get_context())
```

Arguments

attr	A TileDB Attribute object
ctx	A Tiledb Context object (optional)

Value

A logical value indicating if the attribute has an enumeration

tiledb_attribute_is_ordered_enumeration_ptr

Check if TileDB Attribute Enumeration is Ordered

Description

Check if TileDB Attribute Enumeration is Ordered

Usage

```
tiledb_attribute_is_ordered_enumeration_ptr(
  attr,
  arrptr,
  ctx = tiledb_get_context()
)
```

Arguments

attr	A Tiledb Array object
arrptr	A Tiledb Array object pointer
ctx	A Tiledb Context object (optional)

Value

A character vector with the enumeration (of length zero if none)

tiledb_attribute_is_variable_sized

Check whether TileDB Attribute is variable-sized

Description

Check whether TileDB Attribute is variable-sized

Usage

```
tiledb_attribute_is_variable_sized(attr)
```

Arguments

attr A TileDB Attribute object

Value

A boolean value indicating variable-size or not

tiledb_attribute_set_enumeration_name

Set a TileDB Attribute Enumeration Name

Description

Set a TileDB Attribute Enumeration Name

Usage

```
tiledb_attribute_set_enumeration_name(
  attr,
  enum_name,
  ctx = tiledb_get_context()
)
```

Arguments

attr A TileDB Attribute object
 enum_name A character value with the enumeration value
 ctx A Tiledb Context object (optional)

Value

The modified TileDB Attribute object

tiledb_attribute_set_fill_value

Set the fill value for a TileDB Attribute

Description

Set the fill value for a TileDB Attribute

Usage

```
tiledb_attribute_set_fill_value(attr, value)
```

Arguments

attr	A TileDB Attribute object
value	A fill value

Value

NULL is returned invisibly

tiledb_attribute_set_nullable

Set the TileDB Attribute Nullable flags

Description

Set the TileDB Attribute Nullable flags

Usage

```
tiledb_attribute_set_nullable(attr, flag)
```

Arguments

attr	A TileDB Attribute object
flag	A boolean flag to turn 'Nullable' on or off

Value

Nothing is returned

tiledb_config	<i>Creates a tiledb_config object</i>
---------------	---------------------------------------

Description

Note that for actually setting persistent values, the (altered) config object needs to be used to create (or update) the tiledb_ctx object. Similarly, to check whether values are set, one should use the config method of the tiledb_ctx object. Examples for this are `ctx <- tiledb_ctx(limitTileDBCores())` to use updated configuration values to create a context object, and `cfg <- config(ctx)` to retrieve it.

Usage

```
tiledb_config(config = NA_character_)
```

Arguments

config (optional) character vector of config parameter names, values

Value

tiledb_config object

Examples

```
cfg <- tiledb_config()
cfg["sm.tile_cache_size"]

# set tile cache size to custom value
cfg <- tiledb_config(c("sm.tile_cache_size" = "100"))
cfg["sm.tile_cache_size"]
```

tiledb_config-class	<i>An S4 class for a TileDB configuration</i>
---------------------	---

Description

An S4 class for a TileDB configuration

Slots

ptr An external pointer to the underlying implementation

tiledb_config_as_built_json

Return the 'AsBuilt' JSON string

Description

Return the 'AsBuilt' JSON string

Usage

```
tiledb_config_as_built_json()
```

Value

The JSON string containing 'AsBuilt' information

Examples

```
if (tiledb_version(TRUE) > "2.17")
  txt <- tiledb::tiledb_config_as_built_json()
## now eg either one of
##   sapply(jsonlite::fromJSON(txt)$as_built$parameters$storage_backends, \(x) x[[1]])
##   sapply(RcppSimdJson::fparse(txt)$as_built$parameters$storage_backends, \(x) x[[1]])
## will return a named vector such as
##   c(azure = FALSE, gcs = FALSE, hdfs = FALSE, s3 = TRUE)
```

tiledb_config_as_built_show

Display the 'AsBuilt' JSON string

Description

Display the 'AsBuilt' JSON string

Usage

```
tiledb_config_as_built_show()
```

Value

Nothing is returned but as a side-effect the 'AsBuilt' string is displayed

tiledb_config_load *Load a saved tiledb_config file from disk*

Description

Load a saved tiledb_config file from disk

Usage

```
tiledb_config_load(path)
```

Arguments

path path to the config file

Examples

```
tmp <- tempfile()
cfg <- tiledb_config(c("sm.tile_cache_size" = "10"))
pth <- tiledb_config_save(cfg, tmp)
cfg <- tiledb_config_load(pth)
cfg["sm.tile_cache_size"]
```

tiledb_config_save *Save a tiledb_config object to a local text file*

Description

Save a tiledb_config object to a local text file

Usage

```
tiledb_config_save(config, path)
```

Arguments

config The tiledb_config object
path The path to config file to be created

Value

path to created config file

Examples

```
tmp <- tempfile()
cfg <- tiledb_config(c("sm.tile_cache_size" = "10"))
pth <- tiledb_config_save(cfg, tmp)

cat(readLines(pth), sep = "\n")
```

tiledb_config_unset *Unset a TileDB Config parameter to its default value*

Description

Unset a TileDB Config parameter to its default value

Usage

```
tiledb_config_unset(config, param)
```

Arguments

config	A TileDB Config object
param	A character variable with the parameter name

Value

The modified TileDB Config object

tiledb_ctx *Creates a tiledb_ctx object*

Description

Creates a tiledb_ctx object

Usage

```
tiledb_ctx(config = NULL, cached = TRUE)
```

Arguments

config	(optional) character vector of config parameter names, values
cached	(optional) logical switch to force new creation

Value

tiledb_ctx object

Examples

```
# default configuration
ctx <- tiledb_ctx()

# optionally set config parameters
ctx <- tiledb_ctx(c("sm.tile_cache_size" = "100"))
```

tiledb_ctx-class	<i>An S4 class for a TileDB context</i>
------------------	---

Description

An S4 class for a TileDB context

Slots

ptr An external pointer to the underlying implementation

tiledb_ctx_set_default_tags	<i>Sets default context tags</i>
-----------------------------	----------------------------------

Description

Sets default context tags

Usage

```
tiledb_ctx_set_default_tags(object)
```

Arguments

object tiledb_ctx object

tiledb_ctx_set_tag *Sets a string:string "tag" on the Ctx*

Description

Sets a string:string "tag" on the Ctx

Usage

```
tiledb_ctx_set_tag(object, key, value)
```

Arguments

object	tiledb_ctx object
key	string
value	string

Examples

```
ctx <- tiledb_ctx(c("sm.tile_cache_size" = "10"))
cfg <- tiledb_ctx_set_tag(ctx, "tag", "value")
```

tiledb_ctx_stats *Return context statistics as a JSON string*

Description

Return context statistics as a JSON string

Usage

```
tiledb_ctx_stats(object = tiledb_get_context())
```

Arguments

object	A tiledb_ctx object
--------	---------------------

Value

A JSON-formatted string with context statistics

`tiledb_datatype_R_type`*Map from TileDB type to R datatype*

Description

This function maps from the TileDB types to the (fewer) key datatypes in R. This can be lossy as TileDB integers range from (signed and unsigned) 8 to 64 bit whereas R only has (signed) 32 bit values. Similarly, R only has 64 bit doubles whereas TileDB has 32 and 64 bit floating point types. TileDB also has more character encodings, and the full range of (NumPy) date and time types.

Usage

```
tiledb_datatype_R_type(datatype)
```

Arguments

`datatype` A string describing one TileDB datatype

Value

A string describing the closest match for an R datatype

`tiledb_delete_metadata`*Delete a TileDB Array Metadata object given by key*

Description

Delete a TileDB Array Metadata object given by key

Usage

```
tiledb_delete_metadata(arr, key)
```

Arguments

`arr` A TileDB Array object
`key` A character value describing a metadata key

Value

A boolean indicating success

tiledb_dim	<i>Constructs a tiledb_dim object</i>
------------	---------------------------------------

Description

Constructs a tiledb_dim object

Usage

```
tiledb_dim(
  name,
  domain,
  tile,
  type,
  filter_list = tiledb_filter_list(),
  ctx = tiledb_get_context()
)
```

Arguments

name	The dimension name / label string. This argument is required.
domain	The dimension (inclusive) domain. The domain of a dimension is defined by a (lower bound, upper bound) vector. For type ASCII, NULL is expected.
tile	The tile dimension tile extent. For type ASCII, NULL is expected.
type	The dimension TileDB datatype string.
filter_list	An optional tiledb_filter_list object, default is no filter
ctx	tiledb_ctx object (optional)

Value

tiledb_dim object

Examples

```
tiledb_dim(name = "d1", domain = c(1L, 10L), tile = 5L, type = "INT32")
```


tiledb_dim-class *An S4 class for a TileDB dimension object*

Description

An S4 class for a TileDB dimension object

Slots

ptr An external pointer to the underlying implementation

tiledb_domain *Constructs a tiledb_domain object*

Description

All tiledb_dim must be of the same TileDB type.

Usage

```
tiledb_domain(dims, ctx = tiledb_get_context())
```

Arguments

dims list() of tiledb_dim objects
 ctx tiledb_ctx (optional)

Value

tiledb_domain

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 100L), type = "INT32"),
                             tiledb_dim("d2", c(1L, 50L), type = "INT32")))
```

tiledb_domain-class *An S4 class for a TileDB domain*

Description

An S4 class for a TileDB domain

Slots

ptr External pointer to the underlying implementation

tiledb_domain_get_dimension_from_index

Returns a Dimension indicated by index for the given TileDB Domain

Description

Returns a Dimension indicated by index for the given TileDB Domain

Usage

```
tiledb_domain_get_dimension_from_index(domain, idx)
```

Arguments

domain	TileDB Domain object
idx	Integer index of the selected dimension

Value

TileDB Dimension object

tiledb_domain_get_dimension_from_name

Returns a Dimension indicated by name for the given TileDB Domain

Description

Returns a Dimension indicated by name for the given TileDB Domain

Usage

```
tiledb_domain_get_dimension_from_name(domain, name)
```

Arguments

domain	TileDB Domain object
name	A character variable with a dimension name

Value

TileDB Dimension object

tiledb_domain_has_dimension
Check a domain for a given dimension name

Description

Check a domain for a given dimension name

Usage

```
tiledb_domain_has_dimension(domain, name)
```

Arguments

domain	A domain of a TileDB Array schema
name	A character variable with a dimension name

Value

A boolean value indicating if the dimension exists in the domain

tiledb_error_message *Return the error message for a given context*

Description

Note that this function requires an actual error to have occurred.

Usage

```
tiledb_error_message(ctx = tiledb_get_context())
```

Arguments

ctx	A tiledb_ctx object
-----	---------------------

Value

A character variable with the error message

tiledb_filestore_buffer_export

Export from a TileDB Filestore to a character variable

Description

Export from a TileDB Filestore to a character variable

Usage

```
tiledb_filestore_buffer_export(  
    filestore_uri,  
    offset,  
    bytes,  
    ctx = tiledb_get_context()  
)
```

Arguments

filestore_uri	Character with an TileDB Array Schema URI
offset	(optional) Numeric variable with offset from beginning, default is zero
bytes	(optional) Numeric variable with number of bytes to read, default is zero
ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

A character variable containing the filestore content (subject to offset and bytes) is returned

tiledb_filestore_buffer_import

Import size bytes from a string into a TileDB Filestore

Description

Import size bytes from a string into a TileDB Filestore

Usage

```
tiledb_filestore_buffer_import(  
    filestore_uri,  
    buf,  
    bytes,  
    ctx = tiledb_get_context()  
)
```

Arguments

filestore_uri	Character with an TileDB Array Schema URI
buf	Character variable with content to be imported
bytes	Number of bytes to be import, defaults to length of buf
ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

A boolean is returned to indicate successful completion

tiledb_filestore_schema_create

Create an array schema from a given URI with schema

Description

Create an array schema from a given URI with schema

Usage

```
tiledb_filestore_schema_create(uri = NULL, ctx = tiledb_get_context())
```

Arguments

uri	Character with an TileDB Array Schema URI, if missing or NULL a default schema is returned
ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

An ArraySchema object corresponding to the supplied schema, or a default if missing

tiledb_filestore_size *Return (uncompressed) TileDB Filestore size*

Description

Return (uncompressed) TileDB Filestore size

Usage

```
tiledb_filestore_size(filestore_uri, ctx = tiledb_get_context())
```

Arguments

filestore_uri	Character with an TileDB Array Schema URI
ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

A numeric with the size is returned

tiledb_filestore_uri_export
Export a file from a TileDB Filestore

Description

Export a file from a TileDB Filestore

Usage

```
tiledb_filestore_uri_export(  
  file_uri,  
  filestore_uri,  
  ctx = tiledb_get_context()  
)
```

Arguments

file_uri	Character with a file URI
filestore_uri	Character with an TileDB Array Schema URI
ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

A boolean is returned to indicate successful completion

tiledb_filestore_uri_import
Import a file into a TileDB Filestore

Description

Import a file into a TileDB Filestore

Usage

```
tiledb_filestore_uri_import(  
    filestore_uri,  
    file_uri,  
    ctx = tiledb_get_context()  
)
```

Arguments

filestore_uri	Character with an TileDB Array Schema URI
file_uri	Character with a file URI
ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

A boolean is returned to indicate successful completion

tiledb_filter *Constructs a tiledb_filter object*

Description

Available filters:

- "NONE"
- "GZIP"
- "ZSTD"
- "LZ4"
- "RLE"
- "BZIP2"
- "DOUBLE_DELTA"
- "BIT_WIDTH_REDUCTION"
- "BITSHUFFLE"

- "BYTESHUFFLE"
- "POSITIVE_DELTA"
- "CHECKSUM_MD5"
- "CHECKSUM_SHA256"
- "DICTIONARY"
- "SCALE_FLOAT" (TileDB 2.11.0 or later)
- "FILTER_XOR" (TileDB 2.12.0 or later)

Usage

```
tiledb_filter(name = "NONE", ctx = tiledb_get_context())
```

Arguments

name	(default "NONE") TileDB filter name string
ctx	tiledb_ctx object (optional)

Details

Valid compression options vary depending on the filter used, consult the TileDB docs for more information.

Value

tiledb_filter object

Examples

```
tiledb_filter("ZSTD")
```

tiledb_filter-class *An S4 class for a TileDB filter*

Description

An S4 class for a TileDB filter

Slots

ptr External pointer to the underlying implementation

tiledb_filter_get_option
Returns the filter's option

Description

Returns the filter's option

Usage

```
tiledb_filter_get_option(object, option)
```

Arguments

object	tiledb_filter
option	string

Value

Integer value

Examples

```
c <- tiledb_filter("ZSTD")
tiledb_filter_set_option(c, "COMPRESSION_LEVEL", 5)
tiledb_filter_get_option(c, "COMPRESSION_LEVEL")
```

tiledb_filter_list *Constructs a tiledb_filter_list object*

Description

Constructs a tiledb_filter_list object

Usage

```
tiledb_filter_list(filters = c(), ctx = tiledb_get_context())
```

Arguments

filters	an optional list of one or more tiledb_filter_list objects
ctx	tiledb_ctx object (optional)

Value

tiledb_filter_list object

Examples

```
flt <- tiledb_filter("ZSTD")
tiledb_filter_set_option(flt, "COMPRESSION_LEVEL", 5)
filter_list <- tiledb_filter_list(c(flt))
filter_list
```

tiledb_filter_list-class

An S4 class for a TileDB filter list

Description

An S4 class for a TileDB filter list

Slots

ptr An external pointer to the underlying implementation

tiledb_filter_set_option

Set the option for a filter

Description

Set the option for a filter

Usage

```
tiledb_filter_set_option(object, option, value)
```

Arguments

object	tiledb_filter
option	string
value	int

Value

The modified filter object is returned.

Examples

```
c <- tiledb_filter("ZSTD")
tiledb_filter_set_option(c, "COMPRESSION_LEVEL", 5)
tiledb_filter_get_option(c, "COMPRESSION_LEVEL")
```

tiledb_filter_type *Returns the type of the filter used*

Description

Returns the type of the filter used

Usage

```
tiledb_filter_type(object)
```

Arguments

object tiledb_filter

Value

TileDB filter type string

Examples

```
c <- tiledb_filter("ZSTD")
tiledb_filter_type(c)
```

tiledb_fragment_info *Constructs a tiledb_fragment_info object*

Description

Constructs a tiledb_fragment_info object

Usage

```
tiledb_fragment_info(uri, ctx = tiledb_get_context())
```

Arguments

uri an character variable with the URI of the array for which fragment info is request
ctx tiledb_ctx object (optional)

Value

tiledb_fragment_info object

tiledb_fragment_info-class

An S4 class for a TileDB fragment info object

Description

An S4 class for a TileDB fragment info object

Slots

ptr An external pointer to the underlying implementation

tiledb_fragment_info_dense

Return if a fragment info index is dense

Description

Return if a fragment info index is dense

Usage

tiledb_fragment_info_dense(object, fid)

Arguments

object A TileDB fragment info object

fid A fragment object index

Value

A logical value indicating if the fragment is dense

`tiledb_fragment_info_dump`*Dump the fragment info to console*

Description

Dump the fragment info to console

Usage

```
tiledb_fragment_info_dump(object)
```

Arguments

object A TileDB fragment info object

Value

Nothing is returned, as a side effect the fragment info is displayed

`tiledb_fragment_info_get_cell_num`*Return a fragment info number of cells for a given fragment index*

Description

Return a fragment info number of cells for a given fragment index

Usage

```
tiledb_fragment_info_get_cell_num(object, fid)
```

Arguments

object A TileDB fragment info object

fid A fragment object index

Value

A numeric value with the number of cells

tiledb_fragment_info_get_non_empty_domain_index

Return a fragment info non-empty domain from index

Description

TODO: Rework with type information

Usage

tiledb_fragment_info_get_non_empty_domain_index(object, fid, did, typestr)

Arguments

object	A TileDB fragment info object
fid	A fragment object index
did	A domain index
typestr	An optional character variable describing the data type which will be accessed from the schema if missing

Value

A TileDB Domain object

tiledb_fragment_info_get_non_empty_domain_name

Return a fragment info non-empty domain from name

Description

TODO: Rework with type information

Usage

tiledb_fragment_info_get_non_empty_domain_name(object, fid, dim_name, typestr)

Arguments

object	A TileDB fragment info object
fid	A fragment object index
dim_name	A character variable with the dimension name
typestr	An optional character variable describing the data type which will be accessed from the schema if missing

Value

A TileDB Domain object

tiledb_fragment_info_get_non_empty_domain_var_index

Return a fragment info non-empty domain variable from index

Description

Return a fragment info non-empty domain variable from index

Usage

tiledb_fragment_info_get_non_empty_domain_var_index(object, fid, did)

Arguments

object	A TileDB fragment info object
fid	A fragment object index
did	A domain index

Value

A character vector with two elements

tiledb_fragment_info_get_non_empty_domain_var_name

Return a fragment info non-empty domain variable from name

Description

Return a fragment info non-empty domain variable from name

Usage

tiledb_fragment_info_get_non_empty_domain_var_name(object, fid, dim_name)

Arguments

object	A TileDB fragment info object
fid	A fragment object index
dim_name	A character variable with the dimension name

Value

A character vector with two elements

`tiledb_fragment_info_get_num`*Return a fragment info number of fragments*

Description

Return a fragment info number of fragments

Usage

```
tiledb_fragment_info_get_num(object)
```

Arguments

object A TileDB fragment info object

Value

A numeric variable with the number of fragments

`tiledb_fragment_info_get_size`*Return a fragment info fragment size for a given fragment index*

Description

Return a fragment info fragment size for a given fragment index

Usage

```
tiledb_fragment_info_get_size(object, fid)
```

Arguments

object A TileDB fragment info object

fid A fragment object index

Value

A numeric variable with the number of fragments

tiledb_fragment_info_get_timestamp_range

Return a fragment info timestamp range for a given fragment index

Description

Return a fragment info timestamp range for a given fragment index

Usage

tiledb_fragment_info_get_timestamp_range(object, fid)

Arguments

object	A TileDB fragment info object
fid	A fragment object index

Value

A Datetime vector with two elements for the range

tiledb_fragment_info_get_to_vacuum_num

Return the number of fragment info elements to be vacuumed

Description

Return the number of fragment info elements to be vacuumed

Usage

tiledb_fragment_info_get_to_vacuum_num(object)

Arguments

object	A TileDB fragment info object
--------	-------------------------------

Value

A numeric value with the number of to be vacuumed fragments

`tiledb_fragment_info_get_to_vacuum_uri`*Return fragment info URI of the to be vacuumed index*

Description

Return fragment info URI of the to be vacuumed index

Usage

```
tiledb_fragment_info_get_to_vacuum_uri(object, fid)
```

Arguments

object	A TileDB fragment info object
fid	A fragment object index

Value

A character variable with the URI of the be vacuumed index

`tiledb_fragment_info_get_unconsolidated_metadata_num`*Return fragment info number of unconsolidated metadata*

Description

Return fragment info number of unconsolidated metadata

Usage

```
tiledb_fragment_info_get_unconsolidated_metadata_num(object)
```

Arguments

object	A TileDB fragment info object
--------	-------------------------------

Value

A numeric value with the number of unconsolidated metadata

`tiledb_fragment_info_get_version`*Return a fragment info version for a given fragment index*

Description

Return a fragment info version for a given fragment index

Usage

```
tiledb_fragment_info_get_version(object, fid)
```

Arguments

<code>object</code>	A TileDB fragment info object
<code>fid</code>	A fragment object index

Value

A integer value value with the version

`tiledb_fragment_info_has_consolidated_metadata`*Return if a fragment info index has consolidated metadata*

Description

Return if a fragment info index has consolidated metadata

Usage

```
tiledb_fragment_info_has_consolidated_metadata(object, fid)
```

Arguments

<code>object</code>	A TileDB fragment info object
<code>fid</code>	A fragment object index

Value

A logical value indicating consolidated metadata

tiledb_fragment_info_sparse

Return if a fragment info index is sparse

Description

Return if a fragment info index is sparse

Usage

tiledb_fragment_info_sparse(object, fid)

Arguments

object	A TileDB fragment info object
fid	A fragment object index

Value

A logical value indicating if the fragment is sparse

tiledb_fragment_info_uri

Return a fragment info URI given its index

Description

Return a fragment info URI given its index

Usage

tiledb_fragment_info_uri(object, fid)

Arguments

object	A TileDB fragment info object
fid	A fragment object index

Value

A character variable with URI

`tiledb_get_all_metadata`*Return all TileDB Array Metadata objects as a named list*

Description

Return all TileDB Array Metadata objects as a named list

Usage

```
tiledb_get_all_metadata(arr)
```

Arguments

`arr` A TileDB Array object

Value

A named list with all Metadata objects indexed by the given key

`tiledb_get_context`*Retrieve a TileDB context object from the package cache*

Description

Retrieve a TileDB context object from the package cache

Usage

```
tiledb_get_context()
```

Value

A TileDB context object

tiledb_get_metadata *Return a TileDB Array Metadata object given by key*

Description

Return a TileDB Array Metadata object given by key

Usage

```
tiledb_get_metadata(arr, key)
```

Arguments

arr	A TileDB Array object
key	A character value describing a metadata key

Value

A object stored in the Metadata under the given key, or 'NULL' if none found.

tiledb_get_query_status
Retrieve the cached status of the last finalized query

Description

This function accesses the status of the last query without requiring the query object.

Usage

```
tiledb_get_query_status()
```

Value

The status of the last query

tiledb_get_vfs	<i>Retrieve a TileDB VFS object from the package environment and cache</i>
----------------	--

Description

Retrieve a TileDB VFS object from the package environment and cache

Usage

```
tiledb_get_vfs()
```

Value

A TileDB VFS object

tiledb_group	<i>Creates a 'tiledb_group' object</i>
--------------	--

Description

Creates a 'tiledb_group' object

Usage

```
tiledb_group(
  uri,
  type = c("READ", "WRITE"),
  ctx = tiledb_get_context(),
  cfg = NULL
)
```

Arguments

uri	Character variable with the URI of the new group object
type	Character variable with the query type value: one of "READ" or "WRITE"
ctx	(optional) A TileDB Context object; if not supplied the default context object is retrieved
cfg	(optional) A TileConfig object

Value

A 'group' object

tiledb_group-class	<i>An S4 class for a TileDB Group object</i>
--------------------	--

Description

An S4 class for a TileDB Group object

Slots

ptr An external pointer to the underlying implementation

tiledb_group_add_member	<i>Add Member to TileDB Group</i>
-------------------------	-----------------------------------

Description

Add Member to TileDB Group

Usage

```
tiledb_group_add_member(grp, uri, relative, name = NULL)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
uri	A character value with a new URI
relative	A logical value indicating whether URI is relative to the group
name	An optional character providing a name for the object, defaults to NULL

Value

The TileDB Group object, invisibly

tiledb_group_close *Close a TileDB Group*

Description

Close a TileDB Group

Usage

```
tiledb_group_close(grp)
```

Arguments

grp A TileDB Group object as for example returned by tiledb_group()

Value

The TileDB Group object but closed for reading or writing

tiledb_group_create *Create a TileDB Group at the given path*

Description

Create a TileDB Group at the given path

Usage

```
tiledb_group_create(uri, ctx = tiledb_get_context())
```

Arguments

uri Character variable with the URI of the new group

ctx (optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

The uri path, invisibly

Examples

```
## Not run:
pth <- tempdir()
tiledb_group_create(pth)
tiledb_object_type(pth)

## End(Not run)
```

tiledb_group_delete *Deletes all written data from a 'tiledb_group' object*

Description

The group must be opened in 'MODIFY_EXCLUSIVE' mode, otherwise the function will error out.

Usage

```
tiledb_group_delete(grp, uri, recursive = FALSE)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
uri	Character variable with the URI of the group item to be deleted
recursive	A logical value indicating whether all data inside the group is to be deleted

Value

Nothing is returned, the function is invoked for the side-effect of group data removal.

tiledb_group_delete_metadata
 Deletes Metadata from a TileDB Group

Description

Deletes Metadata from a TileDB Group

Usage

```
tiledb_group_delete_metadata(grp, key)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
key	A character value with they index under which the data will be written

Value

The TileDB Group object, invisibly

tiledb_group_get_all_metadata
Return all Metadata from a TileDB Group

Description

Return all Metadata from a TileDB Group

Usage

```
tiledb_group_get_all_metadata(grp)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
-----	---

Value

A named List with all Metadata objects index

tiledb_group_get_config
Get a TileDB Config from a TileDB Group

Description

Get a TileDB Config from a TileDB Group

Usage

```
tiledb_group_get_config(grp)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
-----	---

Value

The TileDB Config object of the TileDB Group object

`tiledb_group_get_metadata`*Accesses Metadata from a TileDB Group*

Description

Accesses Metadata from a TileDB Group

Usage

```
tiledb_group_get_metadata(grp, key)
```

Arguments

<code>grp</code>	A TileDB Group object as for example returned by <code>tiledb_group()</code>
<code>key</code>	A character value with the key of the metadata object to be retrieved

Value

The requested object, or NULL is not found

`tiledb_group_get_metadata_from_index`*Accesses Metadata by Index from a TileDB Group*

Description

Accesses Metadata by Index from a TileDB Group

Usage

```
tiledb_group_get_metadata_from_index(grp, idx)
```

Arguments

<code>grp</code>	A TileDB Group object as for example returned by <code>tiledb_group()</code>
<code>idx</code>	A numeric value with the index of the metadata object to be retrieved

Value

The requested object, or NULL is not found

`tiledb_group_has_metadata`*Checks for Metadata in a TileDB Group*

Description

Checks for Metadata in a TileDB Group

Usage

```
tiledb_group_has_metadata(grp, key)
```

Arguments

<code>grp</code>	A TileDB Group object as for example returned by <code>tiledb_group()</code>
<code>key</code>	A character value with they index under which the data will be written

Value

A boolean value indicating with the object is present

`tiledb_group_is_open` *Test if TileDB Group is open*

Description

Test if TileDB Group is open

Usage

```
tiledb_group_is_open(grp)
```

Arguments

<code>grp</code>	A TileDB Group object as for example returned by <code>tiledb_group()</code>
------------------	--

Value

A boolean indicating whether the TileDB Group object is open

tiledb_group_is_relative

Test if a Named Group is Using a Relative URI

Description

Test if a Named Group is Using a Relative URI

Usage

```
tiledb_group_is_relative(grp, name)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
name	A character value with a group name

Value

A boolean indicating whether the group uses a relative URI or not

tiledb_group_member *Get a Member (Description) by Index from TileDB Group*

Description

This function returns a three-element character vector with the member object translated to character, uri, and optional name.

Usage

```
tiledb_group_member(grp, idx)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
idx	A numeric value with the index of the metadata object to be retrieved

Value

A character vector with three elements: the member type, its uri, and name (or "" if the member is unnamed).

`tiledb_group_member_count`*Get Member Count from TileDB Group*

Description

Get Member Count from TileDB Group

Usage

```
tiledb_group_member_count(grp)
```

Arguments

`grp` A TileDB Group object as for example returned by `tiledb_group()`

Value

The Count of Members in the TileDB Group object

`tiledb_group_member_dump`*Dump the TileDB Group to String*

Description

Dump the TileDB Group to String

Usage

```
tiledb_group_member_dump(grp, recursive = FALSE)
```

Arguments

`grp` A TileDB Group object as for example returned by `tiledb_group()`
`recursive` A logical value indicating whether a recursive dump is desired, defaults to 'FALSE'. Note that recursive listings on remote object may be an expensive or slow operation.

Value

A character string

tiledb_group_metadata_num

Returns Number of Metadata Objects a TileDB Group

Description

Returns Number of Metadata Objects a TileDB Group

Usage

```
tiledb_group_metadata_num(grp)
```

Arguments

grp A TileDB Group object as for example returned by tiledb_group()

Value

A numeric value with the number of metadata objects

tiledb_group_open

Open a TileDB Group

Description

Open a TileDB Group

Usage

```
tiledb_group_open(grp, type = c("READ", "WRITE", "MODIFY_EXCLUSIVE"))
```

Arguments

grp A TileDB Group object as for example returned by tiledb_group()

type A character value that must be either 'READ', 'WRITE' or 'MODIFY_EXCLUSIVE'

Value

The TileDB Group object but opened for reading or writing

`tiledb_group_put_metadata`*Write Metadata to a TileDB Group*

Description

Write Metadata to a TileDB Group

Usage

```
tiledb_group_put_metadata(grp, key, val)
```

Arguments

<code>grp</code>	A TileDB Group object as for example returned by <code>tiledb_group()</code>
<code>key</code>	A character value with they index under which the data will be written
<code>val</code>	An R object (numeric, int, or char vector) that will be stored

Value

On success boolean ‘TRUE’ is returned

`tiledb_group_query_type`*Return a TileDB Group query type*

Description

Return a TileDB Group query type

Usage

```
tiledb_group_query_type(grp)
```

Arguments

<code>grp</code>	A TileDB Group object as for example returned by <code>tiledb_group()</code>
------------------	--

Value

A character value with the query type i.e. one of “READ” or “WRITE”.

tiledb_group_remove_member

Remove Member from TileDB Group

Description

Remove Member from TileDB Group

Usage

```
tiledb_group_remove_member(grp, uri)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
uri	A character value with a the URI of the member to be removed, or (if added with a name) the name of the member

Value

The TileDB Group object, invisibly

tiledb_group_set_config

Set a TileDB Config for a TileDB Group

Description

Set a TileDB Config for a TileDB Group

Usage

```
tiledb_group_set_config(grp, cfg)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
cfg	A TileDB Config object

Value

The TileDB Group object with added Config

tiledb_group_uri	<i>Return a TileDB Group URI</i>
------------------	----------------------------------

Description

Return a TileDB Group URI

Usage

```
tiledb_group_uri(grp)
```

Arguments

grp	A TileDB Group object as for example returned by tiledb_group()
-----	---

Value

A character value with the URI

tiledb_has_metadata	<i>Test if TileDB Array has Metadata</i>
---------------------	--

Description

Test if TileDB Array has Metadata

Usage

```
tiledb_has_metadata(arr, key)
```

Arguments

arr	A TileDB Array object
key	A character value describing a metadata key

Value

A logical value indicating if the given key exists in the metadata of the given array

tiledb_is_supported_fs

Query if a TileDB backend is supported

Description

The scheme corresponds to the URI scheme for TileDB resources.

Usage

```
tiledb_is_supported_fs(scheme, object = tiledb_get_context())
```

Arguments

scheme	URI string scheme ("file", "hdfs", "s3")
object	tiledb_ctx object

Details

Ex:

- {file}:///path/to/file
- {hdfs}:///path/to/file
- {s3}://hostname:port/path/to/file

Value

TRUE if tiledb backend is supported, FALSE otherwise

Examples

```
tiledb_is_supported_fs("file")
tiledb_is_supported_fs("s3")
```

tiledb_ndim,tiledb_array_schema-method

Return the number of dimensions associated with the tiledb_array_schema

Description

Return the number of dimensions associated with the tiledb_array_schema

Usage

```
## S4 method for signature 'tiledb_array_schema'
tiledb_ndim(object)
```

Arguments

```
object          tiledb_array_schema
```

Value

integer number of dimensions

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(1L, 10L), type = "INT32")))
sch <- tiledb_array_schema(dom, attrs = c(tiledb_attr("a1", type = "INT32"),
                                          tiledb_attr("a2", type = "FLOAT64")))
tiledb_ndim(sch)
```

tiledb_ndim,tiledb_dim-method

Returns the number of dimensions for a tiledb domain object

Description

Returns the number of dimensions for a tiledb domain object

Usage

```
## S4 method for signature 'tiledb_dim'
tiledb_ndim(object)
```

Arguments

```
object          tiledb_ndim object
```

Value

1L

Examples

```
d1 <- tiledb_dim("d1", c(1L, 10L), 10L)
tiledb_ndim(d1)
```

tiledb_ndim, tiledb_domain-method

Returns the number of dimensions of the tiledb_domain

Description

Returns the number of dimensions of the tiledb_domain

Usage

```
## S4 method for signature 'tiledb_domain'
tiledb_ndim(object)
```

Arguments

object tiledb_domain

Value

integer number of dimensions

Examples

```
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(0.5, 100.0), type = "FLOAT64")))
tiledb_ndim(dom)
dom <- tiledb_domain(dims = c(tiledb_dim("d1", c(0.5, 100.0), type = "FLOAT64"),
                             tiledb_dim("d2", c(0.5, 100.0), type = "FLOAT64")))
tiledb_ndim(dom)
```

tiledb_num_metadata *Return count of TileDB Array Metadata objects*

Description

Return count of TileDB Array Metadata objects

Usage

```
tiledb_num_metadata(arr)
```

Arguments

arr A TileDB Array object

Value

A integer variable with the number of Metadata objects

tiledb_object_ls	<i>List TileDB resources at a given root URI path</i>
------------------	---

Description

List TileDB resources at a given root URI path

Usage

```
tiledb_object_ls(uri, filter = NULL, ctx = tiledb_get_context())
```

Arguments

uri	uri path to walk
filter	optional filtering argument, default is "NULL", currently unused
ctx	tiledb_ctx object (optional)

Value

a dataframe with object type, object uri string columns

tiledb_object_mv	<i>Move a TileDB resource to new uri path</i>
------------------	---

Description

Raises an error if either uri is invalid, or the old uri resource is not a tiledb object

Usage

```
tiledb_object_mv(old_uri, new_uri, ctx = tiledb_get_context())
```

Arguments

old_uri	old uri of existing tiledb resource
new_uri	new uri to move tiledb resource
ctx	tiledb_ctx object (optional)

Value

new uri of moved tiledb resource

tiledb_object_rm	<i>Removes a TileDB resource</i>
------------------	----------------------------------

Description

Raises an error if the uri is invalid, or the uri resource is not a tiledb object

Usage

```
tiledb_object_rm(uri, ctx = tiledb_get_context())
```

Arguments

uri	path to TileDB resource
ctx	tiledb_ctx object (optional)

Value

uri of removed TileDB resource

tiledb_object_type	<i>Return the TileDB object type string of a TileDB resource</i>
--------------------	--

Description

Object types:

- "ARRAY", dense or sparse TileDB array
- "GROUP", TileDB group
- "INVALID", not a TileDB resource

Usage

```
tiledb_object_type(uri, ctx = tiledb_get_context())
```

Arguments

uri	path to TileDB resource
ctx	tiledb_ctx object (optional)

Value

TileDB object type string

tiledb_object_walk *Recursively discover TileDB resources at a given root URI path*

Description

Recursively discover TileDB resources at a given root URI path

Usage

```
tiledb_object_walk(
  uri,
  order = c("PREORDER", "POSTORDER"),
  ctx = tiledb_get_context()
)
```

Arguments

uri	root uri path to walk
order	traversal order, one of "PREORDER" and "POSTORDER" (default "PREORDER")
ctx	tiledb_ctx object (optional)

Value

a dataframe with object type, object uri string columns

tiledb_put_metadata *Store an object in TileDB Array Metadata under given key*

Description

Store an object in TileDB Array Metadata under given key

Usage

```
tiledb_put_metadata(arr, key, val)
```

Arguments

arr	A TileDB Array object
key	A character value describing a metadata key
val	An object to be stored

Value

A boolean value indicating success

tiledb_query	<i>Creates a 'tiledb_query' object</i>
--------------	--

Description

Creates a 'tiledb_query' object

Usage

```
tiledb_query(
  array,
  type = if (tiledb_version(TRUE) >= "2.12.0") c("READ", "WRITE", "DELETE",
    "MODIFY_EXCLUSIVE") else c("READ", "WRITE"),
  ctx = tiledb_get_context()
)
```

Arguments

array	A TileDB Array object
type	A character value that must be one of 'READ', 'WRITE', or 'DELETE' (for TileDB >= 2.12.0)
ctx	(optional) A TileDB Ctx object

Value

'tiledb_query' object

tiledb_query-class	<i>An S4 class for a TileDB Query object</i>
--------------------	--

Description

An S4 class for a TileDB Query object

Slots

ptr An external pointer to the underlying implementation

tiledb_query_add_range

Set a range for a given query

Description

Set a range for a given query

Usage

```
tiledb_query_add_range(query, schema, attr, lowval, highval, stride = NULL)
```

Arguments

query	A TileDB Query object
schema	A TileDB Schema object
attr	An character variable with a dimension name for which the range is set
lowval	The lower value of the range to be set
highval	The higher value of the range to be set
stride	An optional stride value for the range to be set

Value

The query object, invisibly

tiledb_query_add_range_with_type

Set a range for a given query, also supplying type

Description

Set a range for a given query, also supplying type

Usage

```
tiledb_query_add_range_with_type(
  query,
  idx,
  datatype,
  lowval,
  highval,
  stride = NULL
)
```

Arguments

query	A TileDB Query object
idx	An integer index, zero based, of the dimensions
datatype	A character value containing the data type
lowval	The lower value of the range to be set
highval	The highre value of the range to be set
stride	An optional stride value for the range to be set

Value

The query object, invisibly

tiledb_query_alloc_buffer_ptr_char

Allocate a Query buffer for reading a character attribute

Description

Allocate a Query buffer for reading a character attribute

Usage

```
tiledb_query_alloc_buffer_ptr_char(sizeoffsets, sizedata, nullable = FALSE)
```

Arguments

sizeoffsets	A numeric value with the size of the offsets vector
sizedata	A numeric value of the size of the data string
nullable	An optional boolean indicating whether the column can have NULLs

Value

An external pointer to the allocated buffer object

`tiledb_query_apply_aggregate`*Run an aggregate operation on the given query attribute*

Description

Run an aggregate operation on the given query attribute

Usage

```
tiledb_query_apply_aggregate(  
  query,  
  attrname,  
  operation = c("Count", "NullCount", "Min", "Max", "Mean", "Sum"),  
  nullable = TRUE  
)
```

Arguments

<code>query</code>	A TileDB Query object
<code>attrname</code>	The name of an attribute
<code>operation</code>	The name of aggregation operation
<code>nullable</code>	A boolean toggle whether the attribute is nullable

Value

The value of the aggregation

`tiledb_query_buffer_alloc_ptr`*Allocate a Query buffer for a given type*

Description

This function allocates a query buffer for the given data type.

Usage

```
tiledb_query_buffer_alloc_ptr(  
  query,  
  datatype,  
  ncells,  
  nullable = FALSE,  
  varnum = 1  
)
```

Arguments

query	A TileDB Query object
datatype	A character value containing the data type
ncells	A number of elements (not bytes)
nullable	Optional boolean parameter indicating whether missing values are allowed (for which another column is allocated), default is FALSE
varnum	Option integer parameter for the number of elements per variable, default is one

Value

An external pointer to the allocated buffer object

tiledb_query_condition

Creates a 'tiledb_query_condition' object

Description

Creates a 'tiledb_query_condition' object

Usage

```
tiledb_query_condition(ctx = tiledb_get_context())
```

Arguments

ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved
-----	---

Value

A 'tiledb_query_condition' object

tiledb_query_condition-class

An S4 class for a TileDB QueryCondition object

Description

An S4 class for a TileDB QueryCondition object

Slots

ptr An external pointer to the underlying implementation
 init A logical variable tracking if the query condition object has been initialized

`tiledb_query_condition_combine`*Combine two 'tiledb_query_condition' objects*

Description

Combines two query condition object using a relational operator. Support for operator 'AND' is generally available, the 'OR' operator is available if TileDB 2.10 or newer is used.

Usage

```
tiledb_query_condition_combine(lhs, rhs, op)
```

Arguments

lhs	A 'tiledb_query_condition' object on the left-hand side of the relation
rhs	A 'tiledb_query_condition' object on the left-hand side of the relation
op	A character value with then relation, this must be one of 'AND', 'OR' or 'NOT'.

Value

The combined 'tiledb_query_condition' object

`tiledb_query_condition_create`*Create a query condition for vector 'IN' and 'NOT_IN' operations*

Description

Uses 'IN' and 'NOT_IN' operators on given attribute

Usage

```
tiledb_query_condition_create(  
  name,  
  values,  
  op = "IN",  
  ctx = tiledb_get_context()  
)
```

Arguments

name	A character value with the scheme attribute name
values	A vector with the given values, supported types are integer, double, integer64 and character
op	(optional) A character value with the chosen set operation, this must be one of 'IN' or 'NOT_IN'; default to 'IN'
ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

A query condition object is returned

tiledb_query_condition_init
Initialize a 'tiledb_query_condition' object

Description

Initializes (and possibly allocates) a query condition object using a triplet of attribute name, comparison value, and operator. Six types of conditions are supported, they all take a single scalar comparison argument and attribute to compare against. At present only integer or numeric attribute comparisons are implemented.

Usage

```
tiledb_query_condition_init(
  attr,
  value,
  dtype,
  op,
  qc = tiledb_query_condition()
)
```

Arguments

attr	A character value with the scheme attribute name
value	A scalar value that the attribute is compared against
dtype	A character value with the TileDB data type of the attribute column, for example 'FLOAT64' or 'INT32'
op	A character value with then comparison operation, this must be one of 'LT', 'LE', 'GT', 'GE', 'EQ', 'NE'.
qc	(optional) A 'tiledb_query_condition' object to be initialized by this call, if none is given a new one is allocated.

Value

The initialized 'tiledb_query_condition' object

tiledb_query_condition_set_use_enumeration
Enable use of enumeration in query condition

Description

Set a boolean toggle to signal use of enumeration in query condition (TileDB 2.17 or later)

Usage

```
tiledb_query_condition_set_use_enumeration(
    qc,
    use_enum,
    ctx = tiledb_get_context()
)
```

Arguments

qc	A 'tiledb_query_condition' object
use_enum	A boolean to set (if TRUE) or unset (if FALSE) enumeration use
ctx	(optional) A TileDB Ctx object; if not supplied the default context object is retrieved

Value

Nothing is returned, the function is invoked for the side effect

tiledb_query_create_buffer_ptr
Allocate and populate a Query buffer for a given object of a given data type.

Description

This function allocates a query buffer for the given data object of the given type and assigns the object content to the buffer.

Usage

```
tiledb_query_create_buffer_ptr(query, datatype, object)
```

Arguments

query	A TileDB Query object
datatype	A character value containing the data type
object	A vector object of the given type

Value

An external pointer to the allocated buffer object

tiledb_query_create_buffer_ptr_char
Allocate and populate a Query buffer for writing the given char vector

Description

Allocate and populate a Query buffer for writing the given char vector

Usage

tiledb_query_create_buffer_ptr_char(query, varvec)

Arguments

query	A TileDB Query object
varvec	A vector of strings

Value

An external pointer to the allocated buffer object

tiledb_query_ctx *Return query context object*

Description

Return query context object

Usage

tiledb_query_ctx(query)

Arguments

query	A TileDB Query object
-------	-----------------------

Value

A TileDB Context object retrieved from the query

`tiledb_query_export_buffer`*Export Query Buffer to Pair of Arrow IO Pointers*

Description

This function exports the named buffer from a 'READ' query to two Arrow C pointers.

Usage

```
tiledb_query_export_buffer(query, name, ctx = tiledb_get_context())
```

Arguments

<code>query</code>	A TileDB Query object
<code>name</code>	A character variable identifying the buffer
<code>ctx</code>	tiledb_ctx object (optional)

Value

A nanoarrow object (which is an external pointer to an Arrow Array with the Arrow Schema stored as the external pointer tag) classed as an S3 object

`tiledb_query_finalize` *Finalize TileDB Query*

Description

Finalize TileDB Query

Usage

```
tiledb_query_finalize(query)
```

Arguments

<code>query</code>	A TileDB Query object
--------------------	-----------------------

Value

A character value, either 'READ' or 'WRITE'

`tiledb_query_get_buffer_char`*Retrieve content from a Query character buffer*

Description

This function uses a query buffer for a character attribute or dimension and returns its content.

Usage

```
tiledb_query_get_buffer_char(bufptr, sizeoffsets = 0, sizestring = 0)
```

Arguments

<code>bufptr</code>	An external pointer with a query buffer
<code>sizeoffsets</code>	An optional argument for the length of the internal offsets vector
<code>sizestring</code>	An optional argument for the length of the internal string

Value

An R object as resulting from the query

`tiledb_query_get_buffer_ptr`*Retrieve content from a Query buffer*

Description

This function uses a query buffer and returns its content.

Usage

```
tiledb_query_get_buffer_ptr(bufptr)
```

Arguments

<code>bufptr</code>	An external pointer with a query buffer
---------------------	---

Value

An R object as resulting from the query

`tiledb_query_get_est_result_size`*Retrieve the estimated result size for a query and attribute*

Description

When reading from sparse arrays, one cannot know beforehand how big the result will be (unless one actually executes the query). This function offers a way to get the estimated result size for the given attribute. As TileDB does not actually execute the query, getting the estimated result is very fast.

Usage

```
tiledb_query_get_est_result_size(query, name)
```

Arguments

query	A TileDB Query object
name	A variable with an attribute name

Value

An estimate of the query result size

`tiledb_query_get_est_result_size_var`*Retrieve the estimated result size for a query and variable-sized attribute*

Description

When reading variable-length attributes from either dense or sparse arrays, one cannot know beforehand how big the result will be (unless one actually executes the query). This function offers a way to get the estimated result size for the given attribute. As TileDB does not actually execute the query, getting the estimated result is very fast.

Usage

```
tiledb_query_get_est_result_size_var(query, name)
```

Arguments

query	A TileDB Query object
name	A variable with an attribute name

Value

An estimate of the query result size

tiledb_query_get_fragment_num

Retrieve the Number of Fragments for Query

Description

This function is only applicable to ‘WRITE’ queries.

Usage

tiledb_query_get_fragment_num(query)

Arguments

query A TileDB Query object

Value

An integer with the number of fragments for the given query

tiledb_query_get_fragment_timestamp_range

Retrieve the timestamp range for a given Query Fragment

Description

This function is only applicable to ‘WRITE’ queries. The time resolution in TileDB is milliseconds since the epoch so an R `Datetime` vector is returned.

Usage

tiledb_query_get_fragment_timestamp_range(query, idx)

Arguments

query A TileDB Query object

idx An integer (or numeric) index ranging from zero to the number of fragments minus 1

Value

A two-element datetime vector with the start and end time of the fragment write.

`tiledb_query_get_fragment_uri`*Retrieve the URI for a given Query Fragment*

Description

This function is only applicable to 'WRITE' queries.

Usage

```
tiledb_query_get_fragment_uri(query, idx)
```

Arguments

<code>query</code>	A TileDB Query object
<code>idx</code>	An integer (or numeric) index ranging from zero to the number of fragments minus 1

Value

An character value with the fragment URI

`tiledb_query_get_layout`*Get TileDB Query layout*

Description

Get TileDB Query layout

Usage

```
tiledb_query_get_layout(query)
```

Arguments

<code>query</code>	A TileDB Query object
--------------------	-----------------------

Value

The TileDB Query layout as a string

`tiledb_query_get_range`*Retrieve the query range for a query dimension and range index*

Description

Retrieve the query range for a query dimension and range index

Usage

```
tiledb_query_get_range(query, dimidx, rngidx)
```

Arguments

<code>query</code>	A TileDB Query object
<code>dimidx</code>	An integer or numeric index selecting the dimension
<code>rngidx</code>	An integer or numeric index selection the given range for the dimension

Value

An integer vector with elements start, end and stride for the query range for the given dimension and range index

`tiledb_query_get_range_num`*Retrieve the number of ranges for a query dimension*

Description

Retrieve the number of ranges for a query dimension

Usage

```
tiledb_query_get_range_num(query, idx)
```

Arguments

<code>query</code>	A TileDB Query object
<code>idx</code>	An integer or numeric index selecting the dimension

Value

An integer with the number of query range for the given dimensions

`tiledb_query_get_range_var`

Retrieve the query range for a variable-sized query dimension and range index

Description

Retrieve the query range for a variable-sized query dimension and range index

Usage

```
tiledb_query_get_range_var(query, dimidx, rngidx)
```

Arguments

<code>query</code>	A TileDB Query object
<code>dimidx</code>	An integer index selecting the variable-sized dimension
<code>rngidx</code>	An integer index selection the given range for the dimension

Value

An string vector with elements start and end for the query range for the given dimension and range index

`tiledb_query_import_buffer`

Import to Query Buffer from Pair of Arrow IO Pointers

Description

This function imports to the named buffer for a 'WRITE' query from two Arrow external pointers.

Usage

```
tiledb_query_import_buffer(  
  query,  
  name,  
  nanoarrowptr,  
  ctx = tiledb_get_context()  
)
```

Arguments

query	A TileDB Query object
name	A character variable identifying the buffer
nanoarrowptr	A nanoarrow object (which is an external pointer to an Arrow Array with the Arrow Schema stored as the external pointer tag) classed as an S3 object
ctx	tiledb_ctx object (optional)

Value

The update Query external pointer is returned

tiledb_query_result_buffer_elements

Get TileDB Query result buffer element size

Description

The underlying library functions returns a pair of values as a vector of length two. The first number is the number of element offsets for variable size attributes (and always zero for fixed-sized attributes and coordinates). The second is the number of elements in the data buffer. For variable-sized attributes the first number is the number of cells read (and hence the number of offsets), the second number is the number of elements in the data buffer.

Usage

```
tiledb_query_result_buffer_elements(query, attr)
```

Arguments

query	A TileDB Query object
attr	A character value containing the attribute

Details

As this function was first made available when only a scalar (corresponding to the second result) was returned, we still return that value.

Value

A integer with the number of elements in the results buffer for the given attribute

See Also

tiledb_query_result_buffer_elements_vec

tiledb_query_result_buffer_elements_vec

Get TileDB Query result buffer element size pair as vector

Description

The underlying library functions returns a pair of values as a vector of length two. The first number is the number of element offsets for variable size attributes (and always zero for fixed-sized attributes and coordinates). The second is the number of elements in the data buffer. For variable-sized attributes the first number is the number of cells read (and hence the number of offsets), the second number is the number of elements in the data buffer. In the case of a nullable attribute, a third element is returned with the size of the validity buffer.

Usage

```
tiledb_query_result_buffer_elements_vec(query, attr, nullable = FALSE)
```

Arguments

query	A TileDB Query object
attr	A character value containing the attribute
nullable	A logical variable that is 'TRUE' to signal that the attribute is nullable, and 'FALSE' otherwise

Value

A vector with the number of elements in the offsets buffer (and zero for fixed-size attribute or dimensions), the number elements in the results buffer for the given attribute, and (if nullable) a third element with the validity buffer size.

See Also

tiledb_query_result_buffer_elements

tiledb_query_set_buffer

Set TileDB Query buffer

Description

This function allocates query buffers directly from R vectors in case the types match: integer, double, logical. For more general types see tiledb_query_buffer_alloc_ptr and tiledb_query_buffer_assign_ptr

Usage

```
tiledb_query_set_buffer(query, attr, buffer)
```

Arguments

query	A TileDB Query object
attr	A character value containing the attribute
buffer	A vector providing the query buffer

Value

The modified query object, invisibly

tiledb_query_set_buffer_ptr

Assigns to a Query buffer for a given attribute

Description

This function assigns a given query buffer to a query.

Usage

```
tiledb_query_set_buffer_ptr(query, attr, bufptr)
```

Arguments

query	A TileDB Query object
attr	A character value containing the attribute
bufptr	An external pointer with a query buffer

Value

The modified query object, invisibly

tiledb_query_set_buffer_ptr_char

Assign a buffer to a Query attribute

Description

Assign a buffer to a Query attribute

Usage

```
tiledb_query_set_buffer_ptr_char(query, attr, bufptr)
```

Arguments

query	A TileDB Query object
attr	A character value containing the attribute
bufptr	An external pointer with a query buffer

Value

The modified query object, invisibly

tiledb_query_set_condition

Set a query combination object for a query

Description

Set a query combination object for a query

Usage

```
tiledb_query_set_condition(query, qc)
```

Arguments

query	A TileDB Query object
qc	A TileDB Query Combination object

Value

The modified query object, invisibly

tiledb_query_set_layout

Set TileDB Query layout

Description

Set TileDB Query layout

Usage

```
tiledb_query_set_layout(
  query,
  layout = c("COL_MAJOR", "ROW_MAJOR", "GLOBAL_ORDER", "UNORDERED")
)
```

Arguments

query	A TileDB Query object
layout	A character variable with the layout; must be one of "COL_MAJOR", "ROW_MAJOR", "GLOBAL_ORDER", "UNORDERED")

Value

The modified query object, invisibly

tiledb_query_set_subarray

Set subarray for TileDB Query object

Description

Set subarray for TileDB Query object

Usage

tiledb_query_set_subarray(query, subarray, type)

Arguments

query	A TileDB Query object
subarray	A subarray vector object
type	An optional type as a character, if missing type is inferred from the vector.

Value

The modified query object, invisibly

tiledb_query_stats

Return query statistics as a JSON string

Description

Return query statistics as a JSON string

Usage

tiledb_query_stats(query)

Arguments

query	A TileDB Query object
-------	-----------------------

Value

A JSON-formatted string with context statistics

tiledb_query_status *Get TileDB Query status*

Description

Get TileDB Query status

Usage

`tiledb_query_status(query)`

Arguments

`query` A TileDB Query object

Value

A character value describing the query status

tiledb_query_submit *Submit TileDB Query*

Description

Note that the query object may need to be finalized via `tiledb_query_finalize`.

Usage

`tiledb_query_submit(query)`

Arguments

`query` A TileDB Query object

Value

The modified query object, invisibly

tiledb_query_submit_async

Submit TileDB Query asynchronously without a callback returning immediately

Description

Note that the query object may need to be finalized via tiledb_query_finalize.

Usage

```
tiledb_query_submit_async(query)
```

Arguments

query A TileDB Query object

Value

The modified query object, invisibly

tiledb_query_type *Return TileDB Query type*

Description

Return TileDB Query type

Usage

```
tiledb_query_type(query)
```

Arguments

query A TileDB Query object

Value

A character value, either 'READ' or 'WRITE'

tiledb_schema_get_dim_attr_status
Get Dimension or Attribute Status

Description

Note that this function is an unexported internal function.

Usage

```
tiledb_schema_get_dim_attr_status(sch)
```

Arguments

sch A TileDB Schema object

Value

An integer vector where each element corresponds to a schema entry, and a value of one signals dimension and a value of two an attribute.

tiledb_schema_get_enumeration_status
Get Dimension or Attribute Status

Description

Note that this function is an unexported internal function.

Usage

```
tiledb_schema_get_enumeration_status(sch)
```

Arguments

sch A TileDB Schema object

Value

An integer vector where each element corresponds to a schema entry, and a value of one signals dimension and a value of two an attribute.

tiledb_schema_get_names

Get all Dimension and Attribute Names

Description

Get all Dimension and Attribute Names

Usage

tiledb_schema_get_names(sch)

Arguments

sch A TileDB Schema object

Value

A character vector of dimension and attribute names

tiledb_schema_get_types

Get all Dimension and Attribute Types

Description

Get all Dimension and Attribute Types

Usage

tiledb_schema_get_types(sch)

Arguments

sch A TileDB Schema object

Value

A character vector of dimension and attribute data types

tiledb_schema_object *Succinctly describe a TileDB array schema*

Description

This is an internal function that is not exported.

Usage

```
tiledb_schema_object(array)
```

Arguments

array A TileDB Array object

Value

A list containing two data frames, one describing the overall array as well as one with descriptions about dimensions and attributes in the schema

tiledb_set_context *Store a TileDB context object in the package cache*

Description

Store a TileDB context object in the package cache

Usage

```
tiledb_set_context(ctx)
```

Arguments

ctx A TileDB context object

Value

NULL, invisibly. The function is invoked for the side-effect of storing the VFS object.

tiledb_set_vfs	<i>Store a TileDB VFS object in the package environment</i>
----------------	---

Description

Store a TileDB VFS object in the package environment

Usage

```
tiledb_set_vfs(vfs)
```

Arguments

vfs	A TileDB VFS object
-----	---------------------

Value

NULL, invisibly. The function is invoked for the side-effect of storing the VFS object.

tiledb_stats_disable	<i>Disable internal TileDB statistics counters</i>
----------------------	--

Description

This function ends the collection of internal statistics.

Usage

```
tiledb_stats_disable()
```

tiledb_stats_dump	<i>Dumps internal TileDB statistics to file or stdout</i>
-------------------	---

Description

Dumps internal TileDB statistics to file or stdout

Usage

```
tiledb_stats_dump(path)
```

Arguments

path	Character variable with path to stats file; if the empty string is passed then the result is displayed on stdout.
------	---

Examples

```
pth <- tempfile()
tiledb_stats_dump(pth)
cat(readLines(pth)[1:10], sep = "\n")
```

tiledb_stats_enable *Enable internal TileDB statistics counters*

Description

This function starts the collection of internal statistics.

Usage

```
tiledb_stats_enable()
```

tiledb_stats_print *Print internal TileDB statistics*

Description

This function is a convenience wrapper for tiledb_stats_dump.

Usage

```
tiledb_stats_print()
```

tiledb_stats_raw_dump *Dumps internal TileDB statistics as JSON to a string*

Description

This function requires TileDB Embedded 2.0.3 or later.

Usage

```
tiledb_stats_raw_dump()
```

Examples

```
txt <- tiledb_stats_raw_dump()
cat(txt, "\n")
```

tiledb_stats_raw_get *Gets internal TileDB statistics as JSON string*

Description

This function is a (now deprecated) convenience wrapper for tiledb_stats_raw_dump and returns the result as a JSON string. It required TileDB Embedded 2.0.3 or later.

Usage

```
tiledb_stats_raw_get()
```

tiledb_stats_raw_print
 Print internal TileDB statistics as JSON

Description

This function is a convenience wrapper for tiledb_stats_raw_dump. It required TileDB Embedded 2.0.3 or later.

Usage

```
tiledb_stats_raw_print()
```

tiledb_stats_reset *Reset internal TileDB statistics counters*

Description

This function resets the counters for internal statistics.

Usage

```
tiledb_stats_reset()
```

tiledb_subarray	<i>Constructs a tiledb_subarray object from a TileDB Query</i>
-----------------	--

Description

Constructs a tiledb_subarray object from a TileDB Query

Usage

```
tiledb_subarray(query)
```

Arguments

query	A TileDB Query Object
-------	-----------------------

Value

tiledb_subarray object

tiledb_subarray-class	<i>An S4 class for a TileDB Subarray</i>
-----------------------	--

Description

An S4 class for a TileDB Subarray

Slots

ptr	External pointer to the underlying implementation
-----	---

tiledb_subarray_to_query	<i>Apply a Subarray to a Query</i>
--------------------------	------------------------------------

Description

Apply a Subarray to a Query

Usage

```
tiledb_subarray_to_query(query, subarray)
```

Arguments

query	A TileDB Query Object
subarray	A TileDB Subarray Object

Value

tiledb_query object

tiledb_version	<i>The version of the libtiledb library</i>
----------------	---

Description

The version of the libtiledb library

Usage

```
tiledb_version(compact = FALSE)
```

Arguments

compact	Logical value indicating wheter a compact package_version object should be returned
---------	---

Value

An named int vector c(major, minor, patch), or if select, a package_version object

Examples

```
tiledb_version()
tiledb_version(compact = TRUE)
```

tiledb_vfs	<i>Creates a tiledb_vfs object</i>
------------	------------------------------------

Description

Creates a tiledb_vfs object

Usage

```
tiledb_vfs(config = NULL, ctx = tiledb_get_context())
```

Arguments

config	(optional) character vector of config parameter names, values
ctx	(optional) A TileDB Ctx object

Value

The tiledb_vfs object

Examples

```
# default configuration  
vfs <- tiledb_vfs()
```

tiledb_vfs-class	<i>An S4 class for a TileDB VFS object</i>
------------------	--

Description

An S4 class for a TileDB VFS object

Slots

ptr An external pointer to the underlying implementation

tiledb_vfs_close	<i>Close a TileDB VFS Filehandle</i>
------------------	--------------------------------------

Description

Close a TileDB VFS Filehandle

Usage

```
tiledb_vfs_close(fh, ctx = tiledb_get_context())
```

Arguments

fh	A TileDB VFS Filehandle external pointer as returned from tiledb_vfs_open
ctx	(optional) A TileDB Ctx object

Value

The result of the close operation is returned.

tiledb_vfs_copy_file	<i>Copy a file to VFS</i>
----------------------	---------------------------

Description

Copy a file to VFS

Usage

```
tiledb_vfs_copy_file(file, uri, vfs = tiledb_get_vfs())
```

Arguments

file	Character variable with a local file path
uri	Character variable with a URI describing a file path
vfs	A TileDB VFS object; default is to use a cached value.

Value

The uri value of the removed file

tiledb_vfs_create_bucket
Create a VFS Bucket

Description

Create a VFS Bucket

Usage

```
tiledb_vfs_create_bucket(uri, vfs = tiledb_get_vfs())
```

Arguments

uri	Character variable with a URI describing a cloud bucket
vfs	A TileDB VFS object; default is to use a cached value.

Value

The uri value

tiledb_vfs_create_dir *Create a VFS Directory*

Description

Create a VFS Directory

Usage

```
tiledb_vfs_create_dir(uri, vfs = tiledb_get_vfs())
```

Arguments

uri	Character variable with a URI describing a directory path
vfs	A TileDB VFS object; default is to use a cached value.

Value

The uri value of the created directory

tiledb_vfs_dir_size *Return VFS Directory Size*

Description

Return VFS Directory Size

Usage

```
tiledb_vfs_dir_size(uri, vfs = tiledb_get_vfs())
```

Arguments

uri Character variable with a URI describing a file path
vfs A TileDB VFS object; default is to use a cached value.

Value

The size of the directory

tiledb_vfs_empty_bucket
 Empty a VFS Bucket

Description

Empty a VFS Bucket

Usage

```
tiledb_vfs_empty_bucket(uri, vfs = tiledb_get_vfs())
```

Arguments

uri Character variable with a URI describing a cloud bucket
vfs A TileDB VFS object; default is to use a cached value.

Value

The URI value that was emptied

tiledb_vfs_file_size *Return VFS File Size*

Description

Return VFS File Size

Usage

```
tiledb_vfs_file_size(uri, vfs = tiledb_get_vfs())
```

Arguments

uri Character variable with a URI describing a file path
vfs A TileDB VFS object; default is to use a cached value.

Value

The size of the file

tiledb_vfs_is_bucket *Check for VFS Bucket*

Description

Check for VFS Bucket

Usage

```
tiledb_vfs_is_bucket(uri, vfs = tiledb_get_vfs())
```

Arguments

uri Character variable with a URI describing a cloud bucket
vfs A TileDB VFS object; default is to use a cached value.

Value

A boolean value indicating if it is a valid bucket

Examples

```
## Not run:
cfg <- tiledb_config()
cfg["vfs.s3.region"] <- "us-west-1"
ctx <- tiledb_ctx(cfg)
vfs <- tiledb_vfs()
tiledb_vfs_is_bucket(vfs, "s3://tiledb-public-us-west-1/test-array-4x4")

## End(Not run)
```

tiledb_vfs_is_dir *Test for VFS Directory*

Description

Test for VFS Directory

Usage

```
tiledb_vfs_is_dir(uri, vfs = tiledb_get_vfs())
```

Arguments

uri Character variable with a URI describing a directory path
vfs A TileDB VFS object; default is to use a cached value.

Value

A boolean value indicating if it is a directory

tiledb_vfs_is_empty_bucket
Check for empty VFS Bucket

Description

Check for empty VFS Bucket

Usage

```
tiledb_vfs_is_empty_bucket(uri, vfs = tiledb_get_vfs())
```

Arguments

uri Character variable with a URI describing a cloud bucket
vfs A TileDB VFS object; default is to use a cached value.

Value

A boolean value indicating if it is an empty bucket

Examples

```
## Not run:
cfg <- tiledb_config()
cfg["vfs.s3.region"] <- "us-west-1"
ctx <- tiledb_ctx(cfg)
vfs <- tiledb_vfs()
tiledb_vfs_is_empty_bucket(vfs, "s3://tiledb-public-us-west-1/test-array-4x4")

## End(Not run)
```

tiledb_vfs_is_file *Test for VFS File*

Description

Test for VFS File

Usage

```
tiledb_vfs_is_file(uri, vfs = tiledb_get_vfs())
```

Arguments

- uri Character variable with a URI describing a file path
- vfs A TileDB VFS object; default is to use a cached value.

Value

A boolean value indicating if it is a file

tiledb_vfs_ls *Return VFS Directory Listing*

Description

Return VFS Directory Listing

Usage

```
tiledb_vfs_ls(uri, vfs = tiledb_get_vfs())
```

Arguments

uri	Character variable with a URI describing a file path
vfs	A TileDB VFS object; default is to use a cached value.

Value

The content of the directory, non-recursive

tiledb_vfs_ls_recursive

Recursively list objects from given URI

Description

This functionality is currently limited to S3 URIs.

Usage

```
tiledb_vfs_ls_recursive(
  uri,
  vfs = tiledb_get_vfs(),
  ctx = tiledb_get_context()
)
```

Arguments

uri	Character variable with a URI describing a file path
vfs	(optional) A TileDB VFS object; default is to use a cached value.
ctx	(optional) A TileDB Ctx object

Value

A data.frame object with two columns for the full path and the object size in bytes

tiledb_vfs_move_dir *Move (or rename) a VFS Directory*

Description

Move (or rename) a VFS Directory

Usage

```
tiledb_vfs_move_dir(olduri, newuri, vfs = tiledb_get_vfs())
```

Arguments

olduri	Character variable with an existing URI describing a directory path
newuri	Character variable with a new desired URI directory path
vfs	A TileDB VFS object; default is to use a cached value.

Value

The newuri value of the moved directory

tiledb_vfs_move_file *Move (or rename) a VFS File*

Description

Move (or rename) a VFS File

Usage

```
tiledb_vfs_move_file(olduri, newuri, vfs = tiledb_get_vfs())
```

Arguments

olduri	Character variable with an existing URI describing a file path
newuri	Character variable with a new desired URI file path
vfs	A TileDB VFS object; default is to use a cached value.

Value

The newuri value of the moved file

tiledb_vfs_open	<i>Open a TileDB VFS Filehandle for reading or writing</i>
-----------------	--

Description

Open a TileDB VFS Filehandle for reading or writing

Usage

```
tiledb_vfs_open(
  binfile,
  mode = c("READ", "WRITE", "APPEND"),
  vfs = tiledb_get_vfs(),
  ctx = tiledb_get_context()
)
```

Arguments

binfile	A character variable describing the (binary) file to be opened
mode	A character variable with value 'READ', 'WRITE' or 'APPEND'
vfs	A TileDB VFS object; default is to use a cached value.
ctx	(optional) A TileDB Ctx object

Value

A TileDB VFS Filehandle object (as an external pointer)

tiledb_vfs_read	<i>Read from a TileDB VFS Filehandle</i>
-----------------	--

Description

This interface currently defaults to reading an integer vector. This is suitable for R objects as a raw vector used for (de)serialization can be mapped easily to an integer vector. It is also possible to memcpy to the contiguous memory of an integer vector should other (non-R) data be transferred.

Usage

```
tiledb_vfs_read(fh, offset, nbytes, ctx = tiledb_get_context())
```

Arguments

fh	A TileDB VFS Filehandle external pointer as returned from tiledb_vfs_open
offset	A scalar value with the byte offset from the beginning of the file with a of zero.
nbytes	A scalar value with the number of bytes to be read.
ctx	(optional) A TileDB Ctx object

Value

The binary file content is returned as an integer vector.

tiledb_vfs_remove_bucket
Remove a VFS Bucket

Description

Remove a VFS Bucket

Usage

```
tiledb_vfs_remove_bucket(uri, vfs = tiledb_get_vfs())
```

Arguments

uri Character variable with a URI describing a cloud bucket
 vfs A TileDB VFS object; default is to use a cached value.

Value

The uri value

tiledb_vfs_remove_dir *Remove a VFS Directory*

Description

Remove a VFS Directory

Usage

```
tiledb_vfs_remove_dir(uri, vfs = tiledb_get_vfs())
```

Arguments

uri Character variable with a URI describing a diretory path
 vfs A TileDB VFS object; default is to use a cached value.

Value

The uri value of the removed directory

tiledb_vfs_remove_file

Remove a VFS File

Description

Remove a VFS File

Usage

```
tiledb_vfs_remove_file(uri, vfs = tiledb_get_vfs())
```

Arguments

`uri` Character variable with a URI describing a file path
`vfs` A TileDB VFS object; default is to use a cached value.

Value

The uri value of the removed file

tiledb_vfs_serialize *Serialize an R Object to a VFS-accessible URI*

Description

Serialize an R Object to a VFS-accessible URI

Usage

```
tiledb_vfs_serialize(obj, uri, vfs = tiledb_get_vfs())
```

Arguments

`obj` An R object which will be passed to `serialize()`
`uri` Character variable with a URI describing a file path to an RDS file
`vfs` A TileDB VFS object; default is to use a cached value.

Value

The uri is returned invisibly

tiledb_vfs_sync	<i>Sync a TileDB VFS Filehandle</i>
-----------------	-------------------------------------

Description

Sync a TileDB VFS Filehandle

Usage

```
tiledb_vfs_sync(fh, ctx = tiledb_get_context())
```

Arguments

fh	A TileDB VFS Filehandle external pointer as returned from tiledb_vfs_open
ctx	(optional) A TileDB Ctx object

Value

The result of the sync operation is returned.

tiledb_vfs_touch	<i>Touch a VFS URI Resource</i>
------------------	---------------------------------

Description

Touch a VFS URI Resource

Usage

```
tiledb_vfs_touch(uri, vfs = tiledb_get_vfs())
```

Arguments

uri	Character variable with a URI describing a bucket, file or directory
vfs	A TileDB VFS object; default is to use a cached value.

Value

The uri value

tiledb_vfs_unserialize

Unserialize an R Object from a VFS-accessible URI

Description

Unserialize an R Object from a VFS-accessible URI

Usage

```
tiledb_vfs_unserialize(uri, vfs = tiledb_get_vfs())
```

Arguments

uri	Character variable with a URI describing a file path to an RDS file
vfs	A TileDB VFS object; default is to use a cached value.

Value

The unserialized object

tiledb_vfs_write

Write to a TileDB VFS Filehandle

Description

This interface currently defaults to using an integer vector. This is suitable for R objects as the raw vector result from serialization can be mapped easily to an integer vector. It is also possible to memcpy to the contiguous memory of an integer vector should other (non-R) data be transferred.

Usage

```
tiledb_vfs_write(fh, vec, ctx = tiledb_get_context())
```

Arguments

fh	A TileDB VFS Filehandle external pointer as returned from tiledb_vfs_open
vec	An integer vector of content to be written
ctx	(optional) A TileDB Ctx object

Value

The result of the write operation is returned.

```
tile_order,tiledb_array_schema-method
    Returns the tile layout string associated with the
    tiledb_array_schema
```

Description

Returns the tile layout string associated with the tiledb_array_schema

Usage

```
## S4 method for signature 'tiledb_array_schema'
tile_order(object)
```

Arguments

object tiledb object

```
[,tiledb_array,ANY-method
    Returns a TileDB array, allowing for specific subset ranges.
```

Description

Heterogenous domains are supported, including timestamps and characters.

Usage

```
## S4 method for signature 'tiledb_array,ANY'
x[i, j, ..., drop = FALSE]
```

Arguments

x	tiledb_array object
i	optional row index expression which can be a list in which case minimum and maximum of each list element determine a range; multiple list elements can be used to supply multiple ranges.
j	optional column index expression which can be a list in which case minimum and maximum of each list element determine a range; multiple list elements can be used to supply multiple ranges.
...	Extra parameters for method signature, currently unused.
drop	Optional logical switch to drop dimensions, default FALSE, currently unused.

Details

This function may still change; the current implementation should be considered as an initial draft.

Value

The resulting elements in the selected format

```
[, tiledb_config, ANY-method
      Gets a config parameter value
```

Description

Gets a config parameter value

Usage

```
## S4 method for signature 'tiledb_config, ANY'
x[i, j, ..., drop = FALSE]
```

Arguments

x	tiledb_config object
i	parameter key string
j	parameter key string, currently unused.
...	Extra parameter for method signature, currently unused.
drop	Optional logical switch to drop dimensions, default FALSE, currently unused.

Value

a config string value if parameter exists, else NA

Examples

```
cfg <- tiledb_config()
cfg["sm.tile_cache_size"]
cfg["does_not_exist"]
```

```
[,tiledb_filter_list,ANY-method
```

Returns the filter at given index

Description

Returns the filter at given index

Usage

```
## S4 method for signature 'tiledb_filter_list,ANY'
x[i, j, ..., drop = FALSE]
```

Arguments

x	tiledb_config object
i	parameter key string
j	parameter key string, currently unused.
...	Extra parameter for method signature, currently unused.
drop	Optional logical switch to drop dimensions, default false.

Value

object tiledb_filter

Examples

```
flt <- tiledb_filter("ZSTD")
tiledb_filter_set_option(flt, "COMPRESSION_LEVEL", 5)
filter_list <- tiledb_filter_list(c(flt))
filter_list[0]
```

```
[<- ,tiledb_array,ANY,ANY,ANY-method
```

Sets a tiledb array value or value range

Description

This function assigns a right-hand side object, typically a data.frame or something that can be coerced to a data.frame, to a tiledb array.

Usage

```
## S4 replacement method for signature 'tiledb_array,ANY,ANY,ANY'
x[i, j, ...] <- value
```

Arguments

x	sparse or dense TileDB array object
i	parameter row index
j	parameter column index
...	Extra parameter for method signature, currently unused.
value	The value being assigned

Details

For sparse matrices, row and column indices can either be supplied as part of the left-hand side object, or as part of the data.frame provided appropriate column names.

This function may still change; the current implementation should be considered as an initial draft.

Value

The modified object

Examples

```
## Not run:
uri <- "quickstart_sparse"      ## as created by the other example
arr <- tiledb_array(uri)        ## open array
df <- arr[]                     ## read current content
## First approach: matching data.frame with appropriate row and column
newdf <- data.frame(rows=c(1,2,2), cols=c(1,3,4), a=df$a+100)
## Second approach: supply indices explicitly
arr[c(1,2), c(1,3)] <- c(42,43) ## two values
arr[2, 4] <- 88                 ## or just one

## End(Not run)
```

```
[<-, tiledb_config, ANY, ANY, ANY-method
```

Sets a config parameter value

Description

Sets a config parameter value

Usage

```
## S4 replacement method for signature 'tiledb_config, ANY, ANY, ANY'  
x[i, j] <- value
```

Arguments

x	tiledb_config object
i	parameter key string
j	parameter key string
value	value to set, will be converted into a string

Value

updated tiledb_config object

Examples

```
cfg <- tiledb_config()  
cfg["sm.tile_cache_size"]  
  
# set tile cache size to custom value  
cfg["sm.tile_cache_size"] <- 100  
cfg["sm.tile_cache_size"]
```

Index

[, tiledb_array
 ([, tiledb_array, ANY-method),
 191

[, tiledb_array, ANY, ANY, tiledb_array-method
 ([, tiledb_array, ANY-method),
 191

[, tiledb_array, ANY, tiledb_array-method
 ([, tiledb_array, ANY-method),
 191

[, tiledb_array, ANY-method, 191

[, tiledb_array-method
 ([, tiledb_array, ANY-method),
 191

[, tiledb_config
 ([, tiledb_config, ANY-method),
 192

[, tiledb_config, ANY, ANY, tiledb_config-method
 ([, tiledb_config, ANY-method),
 192

[, tiledb_config, ANY, tiledb_config-method
 ([, tiledb_config, ANY-method),
 192

[, tiledb_config, ANY-method, 192

[, tiledb_config-method
 ([, tiledb_config, ANY-method),
 192

[, tiledb_filter_list
 ([, tiledb_filter_list, ANY-method),
 193

[, tiledb_filter_list, ANY, ANY, tiledb_filter_list-method
 ([, tiledb_filter_list, ANY-method),
 193

[, tiledb_filter_list, ANY, tiledb_filter_list-method
 ([, tiledb_filter_list, ANY-method),
 193

[, tiledb_filter_list, ANY-method, 193

[, tiledb_filter_list-method
 ([, tiledb_filter_list, ANY-method),
 193

[<- , tiledb_array, ANY, ANY, ANY-method,
 193

[<- , tiledb_config, ANY, ANY, ANY-method,
 194

[<- , tiledb_array
 ([<- , tiledb_array, ANY, ANY, ANY-method),
 193

[<- , tiledb_array, ANY, ANY, tiledb_array-method
 ([<- , tiledb_array, ANY, ANY, ANY-method),
 193

[<- , tiledb_array, ANY, tiledb_array-method
 ([<- , tiledb_array, ANY, ANY, ANY-method),
 193

[<- , tiledb_array-method
 ([<- , tiledb_array, ANY, ANY, ANY-method),
 193

[<- , tiledb_config
 ([<- , tiledb_config, ANY, ANY, ANY-method),
 194

[<- , tiledb_config, ANY, ANY, tiledb_config-method
 ([<- , tiledb_config, ANY, ANY, ANY-method),
 194

[<- , tiledb_config, ANY, tiledb_config-method
 ([<- , tiledb_config, ANY, ANY, ANY-method),
 194

[<- , tiledb_config-method
 ([<- , tiledb_config, ANY, ANY, ANY-method),
 194

allows_dups, 9

allows_dups, tiledb_array_schema-method
 (allows_dups), 9

allows_dups<-, 10

allows_dups<-, tiledb_array_schema-method
 (allows_dups<-), 10

array_consolidate, 10

array_vacuum, 11

as.data.frame.tiledb_config, 12

as.vector.tiledb_config, 12

attrs(generics), 37

- attrs, tiledb_array, ANY-method, 13
- attrs, tiledb_array_schema, ANY-method, 13
- attrs, tiledb_array_schema, character-method, 14
- attrs, tiledb_array_schema, numeric-method, 15
- attrs<-, tiledb_array-method, 16
- attrs<- (generics), 37
- capacity, 16
- capacity, tiledb_array_schema-method (capacity), 16
- capacity<-, 17
- capacity<-, tiledb_array_schema-method (capacity<-), 17
- cell_order (generics), 37
- cell_order, tiledb_array_schema-method, 17
- cell_val_num, 18
- cell_val_num, tiledb_attr-method (cell_val_num), 18
- cell_val_num, tiledb_dim-method, 18
- cell_val_num<-, 19
- cell_val_num<-, tiledb_attr-method (cell_val_num<-), 19
- check (schema_check), 59
- check, tiledb_array_schema-method (schema_check), 59
- completedBatched, 19
- config (generics), 37
- config, tiledb_ctx-method, 20
- createBatched, 21
- datatype (generics), 37
- datatype, tiledb_attr-method, 21
- datatype, tiledb_dim-method, 22
- datatype, tiledb_domain-method, 22
- datetimes_as_int64, 23
- datetimes_as_int64, tiledb_array-method (datetimes_as_int64), 23
- datetimes_as_int64<-, 24
- datetimes_as_int64<-, tiledb_array-method (datetimes_as_int64<-), 24
- describe, 24
- dim.tiledb_array_schema, 25
- dim.tiledb_dim, 25
- dim.tiledb_domain, 26
- dimensions (generics), 37
- dimensions, tiledb_array_schema-method, 27
- dimensions, tiledb_domain-method, 27
- domain (generics), 37
- domain, tiledb_array_schema-method, 28
- domain, tiledb_dim-method, 29
- extended, 29
- extended, tiledb_array-method (extended), 29
- extended<-, 30
- extended<-, tiledb_array-method (extended<-), 30
- fetchBatched, 30
- filter_list (generics), 37
- filter_list, tiledb_array_schema-method, 31
- filter_list, tiledb_attr-method, 31
- filter_list, tiledb_dim-method, 32
- filter_list<-, tiledb_attr-method, 32
- filter_list<-, tiledb_dim-method, 33
- filter_list<- (generics), 37
- fromDataFrame, 33
- fromMatrix, 35
- fromSparseMatrix, 36
- generics, 37
- get_allocation_size_preference (save_allocation_size_preference), 56
- get_return_as_preference (save_return_as_preference), 57
- has_attribute, 38
- is.anonymous, 39
- is.anonymous.tiledb_dim, 40
- is.integral (generics), 37
- is.integral, tiledb_domain-method, 40
- is.sparse (generics), 37
- is.sparse, tiledb_array_schema-method, 41
- limitTileDBCores, 41
- load_allocation_size_preference (save_allocation_size_preference), 56
- load_return_as_preference (save_return_as_preference), 57

- max_chunk_size, 42
- max_chunk_size, tiledb_filter_list-method
(max_chunk_size), 42
- name (generics), 37
- name, tiledb_attr-method, 43
- name, tiledb_dim-method, 44
- nfilters (generics), 37
- nfilters, tiledb_filter_list-method, 44
- parse_query_condition, 45
- print.tiledb_metadata, 46
- query_condition, 47
- query_condition, tiledb_array-method
(query_condition), 47
- query_condition<-, 47
- query_condition<-, tiledb_array-method
(query_condition<-), 47
- query_layout, 48
- query_layout, tiledb_array-method
(query_layout), 48
- query_layout<-, 48
- query_layout<-, tiledb_array-method
(query_layout<-), 48
- query_statistics, 49
- query_statistics, tiledb_array-method
(query_statistics), 49
- query_statistics<-, 49
- query_statistics<-, tiledb_array-method
(query_statistics<-), 49
- r_to_tiledb_type, 55
- raw_dump (generics), 37
- raw_dump, tiledb_array_schema-method,
50
- raw_dump, tiledb_attr-method, 50
- raw_dump, tiledb_domain-method, 51
- return.array, 51
- return.array, tiledb_array-method
(return.array), 51
- return.array<-, 52
- return.array<-, tiledb_array-method
(return.array<-), 52
- return.data.frame (generics), 37
- return.data.frame, tiledb_array-method,
52
- return.data.frame<-, tiledb_array-method,
53
- return.data.frame<- (generics), 37
- return.matrix, 53
- return.matrix, tiledb_array-method
(return.matrix), 53
- return.matrix<-, 54
- return.matrix<-, tiledb_array-method
(return.matrix<-), 54
- return_as, 54
- return_as, tiledb_array-method
(return_as), 54
- return_as<-, 55
- return_as<-, tiledb_array-method
(return_as<-), 55
- save_allocation_size_preference, 56
- save_return_as_preference, 57
- schema (generics), 37
- schema, character-method, 58
- schema, tiledb_array-method, 58
- schema_check, 59
- schema_check, tiledb_array_schema-method
(schema_check), 59
- selected_points, 59
- selected_points, tiledb_array-method
(selected_points), 59
- selected_points<-, 60
- selected_points<-, tiledb_array-method
(selected_points<-), 60
- selected_ranges, 60
- selected_ranges, tiledb_array-method
(selected_ranges), 60
- selected_ranges<-, 61
- selected_ranges<-, tiledb_array-method
(selected_ranges<-), 61
- set_allocation_size_preference
(save_allocation_size_preference),
56
- set_max_chunk_size, 62
- set_max_chunk_size, tiledb_filter_list, numeric-method
(set_max_chunk_size), 62
- set_return_as_preference
(save_return_as_preference), 57
- show, tiledb_array-method, 62
- show, tiledb_array_schema-method, 63
- show, tiledb_attr-method, 63
- show, tiledb_config-method, 64
- show, tiledb_dim-method, 64
- show, tiledb_domain-method, 65
- show, tiledb_filter-method, 65

- show, tiledb_filter_list-method, 66
- show, tiledb_group-method, 66
- statusBatched, 67
- strings_as_factors, 67
- strings_as_factors, tiledb_array-method
(strings_as_factors), 67
- strings_as_factors<-, 68
- strings_as_factors<-, tiledb_array-method
(strings_as_factors<-), 68

- tdb_collect (generics), 37
- tdb_collect, tiledb_array-method, 68
- tdb_filter (generics), 37
- tdb_filter, tiledb_array-method, 69
- tdb_select (generics), 37
- tdb_select, tiledb_array-method, 69
- tile (generics), 37
- tile, tiledb_dim-method, 70
- tile_order (generics), 37
- tile_order, tiledb_array_schema-method,
191
- tiledb_array, 70
- tiledb_array-class, 73
- tiledb_array_apply_aggregate, 74
- tiledb_array_close, 74
- tiledb_array_create, 75
- tiledb_array_delete_fragments, 75
- tiledb_array_get_non_empty_domain_from_index,
76
- tiledb_array_get_non_empty_domain_from_name,
77
- tiledb_array_has_enumeration, 77
- tiledb_array_is_heterogeneous, 78
- tiledb_array_is_homogeneous, 78
- tiledb_array_is_open, 79
- tiledb_array_open, 79
- tiledb_array_open_at, 80
- tiledb_array_schema, 80
- tiledb_array_schema-class, 81
- tiledb_array_schema_check
(schema_check), 59
- tiledb_array_schema_evolution, 82
- tiledb_array_schema_evolution-class,
82
- tiledb_array_schema_evolution_add_attribute,
83
- tiledb_array_schema_evolution_add_enumeration,
83
- tiledb_array_schema_evolution_add_enumeration_empty,
84
- tiledb_array_schema_evolution_array_evolve,
84
- tiledb_array_schema_evolution_drop_attribute,
85
- tiledb_array_schema_evolution_drop_enumeration,
85
- tiledb_array_schema_evolution_extend_enumeration,
86
- tiledb_array_schema_get_allows_dups
(allows_dups), 9
- tiledb_array_schema_get_capacity
(capacity), 16
- tiledb_array_schema_set_allows_dups
(allows_dups<-), 10
- tiledb_array_schema_set_capacity
(capacity<-), 17
- tiledb_array_schema_set_coords_filter_list,
87
- tiledb_array_schema_set_enumeration_empty,
87
- tiledb_array_schema_set_offsets_filter_list,
88
- tiledb_array_schema_set_validity_filter_list,
89
- tiledb_array_schema_version, 89
- tiledb_array_upgrade_version, 90
- tiledb_arrow_array_del
(tiledb_arrow_array_ptr), 90
- tiledb_arrow_array_ptr, 90
- tiledb_arrow_schema_del
(tiledb_arrow_array_ptr), 90
- tiledb_arrow_schema_ptr
(tiledb_arrow_array_ptr), 90
- tiledb_attr, 91
- tiledb_attr-class, 92
- tiledb_attribute_get_cell_size, 92
- tiledb_attribute_get_cell_val_num
(cell_val_num), 18
- tiledb_attribute_get_enumeration, 92
- tiledb_attribute_get_enumeration_ptr
(tiledb_attribute_get_enumeration),
92
- tiledb_attribute_get_fill_value, 93
- tiledb_attribute_get_nullable, 93
- tiledb_attribute_has_enumeration, 94
- tiledb_attribute_is_ordered_enumeration_ptr,

- 94
- tiledb_attribute_is_variable_sized, 95
- tiledb_attribute_set_cell_val_num
(cell_val_num<-), 19
- tiledb_attribute_set_enumeration_name,
95
- tiledb_attribute_set_fill_value, 96
- tiledb_attribute_set_nullable, 96
- tiledb_config, 97
- tiledb_config-class, 97
- tiledb_config_as_built_json, 98
- tiledb_config_as_built_show, 98
- tiledb_config_load, 99
- tiledb_config_save, 99
- tiledb_config_unset, 100
- tiledb_ctx, 100
- tiledb_ctx-class, 101
- tiledb_ctx_set_default_tags, 101
- tiledb_ctx_set_tag, 102
- tiledb_ctx_stats, 102
- tiledb_datatype_R_type, 103
- tiledb_delete_metadata, 103
- tiledb_dense (tiledb_array), 70
- tiledb_dim, 104
- tiledb_dim-class, 105
- tiledb_dim_get_cell_val_num
(cell_val_num, tiledb_dim-method),
18
- tiledb_domain, 105
- tiledb_domain-class, 105
- tiledb_domain_get_dimension_from_index,
106
- tiledb_domain_get_dimension_from_name,
106
- tiledb_domain_has_dimension, 107
- tiledb_error_message, 107
- tiledb_filestore_buffer_export, 108
- tiledb_filestore_buffer_import, 108
- tiledb_filestore_schema_create, 109
- tiledb_filestore_size, 110
- tiledb_filestore_uri_export, 110
- tiledb_filestore_uri_import, 111
- tiledb_filter, 111
- tiledb_filter-class, 112
- tiledb_filter_get_option, 113
- tiledb_filter_list, 113
- tiledb_filter_list-class, 114
- tiledb_filter_list_get_max_chunk_size
(max_chunk_size), 42
- tiledb_filter_list_set_max_chunk_size
(set_max_chunk_size), 62
- tiledb_filter_set_option, 114
- tiledb_filter_type, 115
- tiledb_fragment_info, 115
- tiledb_fragment_info-class, 116
- tiledb_fragment_info_dense, 116
- tiledb_fragment_info_dump, 117
- tiledb_fragment_info_get_cell_num, 117
- tiledb_fragment_info_get_non_empty_domain_index,
118
- tiledb_fragment_info_get_non_empty_domain_name,
118
- tiledb_fragment_info_get_non_empty_domain_var_index,
119
- tiledb_fragment_info_get_non_empty_domain_var_name,
119
- tiledb_fragment_info_get_num, 120
- tiledb_fragment_info_get_size, 120
- tiledb_fragment_info_get_timestamp_range,
121
- tiledb_fragment_info_get_to_vacuum_num,
121
- tiledb_fragment_info_get_to_vacuum_uri,
122
- tiledb_fragment_info_get_unconsolidated_metadata_num,
122
- tiledb_fragment_info_get_version, 123
- tiledb_fragment_info_has_consolidated_metadata,
123
- tiledb_fragment_info_sparse, 124
- tiledb_fragment_info_uri, 124
- tiledb_get_all_metadata, 125
- tiledb_get_context, 125
- tiledb_get_metadata, 126
- tiledb_get_query_status, 126
- tiledb_get_vfs, 127
- tiledb_group, 127
- tiledb_group-class, 128
- tiledb_group_add_member, 128
- tiledb_group_close, 129
- tiledb_group_create, 129
- tiledb_group_delete, 130
- tiledb_group_delete_metadata, 130
- tiledb_group_get_all_metadata, 131
- tiledb_group_get_config, 131
- tiledb_group_get_metadata, 132

- tiledb_group_get_metadata_from_index, 132
- tiledb_group_has_metadata, 133
- tiledb_group_is_open, 133
- tiledb_group_is_relative, 134
- tiledb_group_member, 134
- tiledb_group_member_count, 135
- tiledb_group_member_dump, 135
- tiledb_group_metadata_num, 136
- tiledb_group_open, 136
- tiledb_group_put_metadata, 137
- tiledb_group_query_type, 137
- tiledb_group_remove_member, 138
- tiledb_group_set_config, 138
- tiledb_group_uri, 139
- tiledb_has_metadata, 139
- tiledb_is_supported_fs, 140
- tiledb_ndim (generics), 37
- tiledb_ndim, tiledb_array_schema-method, 140
- tiledb_ndim, tiledb_dim-method, 141
- tiledb_ndim, tiledb_domain-method, 142
- tiledb_num_metadata, 142
- tiledb_object_ls, 143
- tiledb_object_mv, 143
- tiledb_object_rm, 144
- tiledb_object_type, 144
- tiledb_object_walk, 145
- tiledb_put_metadata, 145
- tiledb_query, 146
- tiledb_query-class, 146
- tiledb_query_add_range, 147
- tiledb_query_add_range_with_type, 147
- tiledb_query_alloc_buffer_ptr_char, 148
- tiledb_query_apply_aggregate, 149
- tiledb_query_buffer_alloc_ptr, 149
- tiledb_query_condition, 150
- tiledb_query_condition-class, 150
- tiledb_query_condition_combine, 151
- tiledb_query_condition_create, 151
- tiledb_query_condition_init, 152
- tiledb_query_condition_set_use_enumeration, 153
- tiledb_query_create_buffer_ptr, 153
- tiledb_query_create_buffer_ptr_char, 154
- tiledb_query_ctx, 154
- tiledb_query_export_buffer, 155
- tiledb_query_finalize, 155
- tiledb_query_get_buffer_char, 156
- tiledb_query_get_buffer_ptr, 156
- tiledb_query_get_est_result_size, 157
- tiledb_query_get_est_result_size_var, 157
- tiledb_query_get_fragment_num, 158
- tiledb_query_get_fragment_timestamp_range, 158
- tiledb_query_get_fragment_uri, 159
- tiledb_query_get_layout, 159
- tiledb_query_get_range, 160
- tiledb_query_get_range_num, 160
- tiledb_query_get_range_var, 161
- tiledb_query_import_buffer, 161
- tiledb_query_result_buffer_elements, 162
- tiledb_query_result_buffer_elements_vec, 163
- tiledb_query_set_buffer, 163
- tiledb_query_set_buffer_ptr, 164
- tiledb_query_set_buffer_ptr_char, 164
- tiledb_query_set_condition, 165
- tiledb_query_set_layout, 165
- tiledb_query_set_subarray, 166
- tiledb_query_stats, 166
- tiledb_query_status, 167
- tiledb_query_submit, 167
- tiledb_query_submit_async, 168
- tiledb_query_type, 168
- tiledb_schema_get_dim_attr_status, 169
- tiledb_schema_get_enumeration_status, 169
- tiledb_schema_get_names, 170
- tiledb_schema_get_types, 170
- tiledb_schema_object, 171
- tiledb_set_context, 171
- tiledb_set_vfs, 172
- tiledb_sparse (tiledb_array), 70
- tiledb_stats_disable, 172
- tiledb_stats_dump, 172
- tiledb_stats_enable, 173
- tiledb_stats_print, 173
- tiledb_stats_raw_dump, 173
- tiledb_stats_raw_get, 174
- tiledb_stats_raw_print, 174
- tiledb_stats_reset, 174

tiledb_subarray, 175
tiledb_subarray-class, 175
tiledb_subarray_to_query, 175
tiledb_version, 176
tiledb_vfs, 177
tiledb_vfs-class, 177
tiledb_vfs_close, 178
tiledb_vfs_copy_file, 178
tiledb_vfs_create_bucket, 179
tiledb_vfs_create_dir, 179
tiledb_vfs_dir_size, 180
tiledb_vfs_empty_bucket, 180
tiledb_vfs_file_size, 181
tiledb_vfs_is_bucket, 181
tiledb_vfs_is_dir, 182
tiledb_vfs_is_empty_bucket, 182
tiledb_vfs_is_file, 183
tiledb_vfs_ls, 183
tiledb_vfs_ls_recursive, 184
tiledb_vfs_move_dir, 185
tiledb_vfs_move_file, 185
tiledb_vfs_open, 186
tiledb_vfs_read, 186
tiledb_vfs_remove_bucket, 187
tiledb_vfs_remove_dir, 187
tiledb_vfs_remove_file, 188
tiledb_vfs_serialize, 188
tiledb_vfs_sync, 189
tiledb_vfs_touch, 189
tiledb_vfs_unserialize, 190
tiledb_vfs_write, 190
toMatrix (fromMatrix), 35
toSparseMatrix (fromSparseMatrix), 36