

Package ‘fancycut’

July 22, 2025

Title A Fancy Version of 'base::cut'

Version 0.1.3

Description Provides the function fancycut() which is like cut() except you can mix left open and right open intervals with point values, intervals that are closed on both ends and intervals that are open on both ends.

License CC0

RoxygenNote 7.3.2

Encoding UTF-8

Suggests testthat

NeedsCompilation no

Author Adam Rich [aut, cre, cph] (ORCID:
<<https://orcid.org/0009-0007-0992-1956>>),
Richie Cotton [ctb]

Maintainer Adam Rich <adam@adamleerich.com>

Repository CRAN

Date/Publication 2024-09-27 16:00:02 UTC

Contents

| | |
|---------------------|----------|
| fancycut | 1 |
| wafflecut | 3 |
| Index | 5 |

| | |
|----------|---|
| fancycut | <i>Like cut, turn a vector of numbers into a factor</i> |
|----------|---|

Description

Like cut, turn a vector of numbers into a factor

Usage

```
fancycut(x, na.bucket = NA, unmatched.bucket = NA, out.as.factor = TRUE, ...)
```

Arguments

| | |
|-------------------------------|--|
| <code>x</code> | a numeric vector |
| <code>na.bucket</code> | what level should NA values be given? |
| <code>unmatched.bucket</code> | what level should numbers not covered by an interval be given? |
| <code>out.as.factor</code> | default is TRUE Should the resulting vector be a factor? If FALSE will return a character vector. |
| <code>...</code> | These take the form tag = value. Tags become the bucket names and values the interval definitions. |

Examples

```
fancycut(
  x = -10:10,
  Zero = 0,
  Small = '[0,2)',
  Medium = '[2,5]',
  Large = '(5,10]'
)

# The following examples are from Richie Cotton via
# https://www.rdocumentation.org/packages/fancycut/versions/0.1.1/topics/fancycut

# The tag = value syntax is useful.
x <- seq.int(0, 1, 0.25)
fancycut(x, low = '[0, 0.5]', high = '(0.5, 1]')

# Not all the values have to live in a bucket.
x <- seq.int(0, 1, 0.25)
fancycut(x, low = '(0.2, 0.3]', high = '(0.7, 0.8)')

# You can use unmatched.bucket to deal with these other intervals.
x <- seq.int(0, 1, 0.25)
fancycut(x, low = '(0.2, 0.3]', high = '(0.7, 0.8)', unmatched.bucket = 'other')

# To match a specific value, make the lower and upper bound the same number.
x <- seq.int(0, 1, 0.25)
fancycut(x, low = '[0, 0.5]', half = '[0.5,0.5]', high = '(0.5, 1]')

# To match NA values, use na.bucket.
x2 <- c(seq.int(0, 1, 0.25), NA)
fancycut(x2, low = '[0, 0.5]', high = '[0.5, 1]', na.bucket = 'missing')
```

| | |
|-----------|---|
| wafflecut | <i>Like cut, turn a vector of numbers into a factor</i> |
|-----------|---|

Description

Like cut, turn a vector of numbers into a factor

Usage

```
wafflecut(
  x,
  intervals,
  buckets = intervals,
  na.bucket = NA,
  unmatched.bucket = NA,
  out.as.factor = TRUE
)
```

Arguments

| | |
|------------------|---|
| x | a numeric vector |
| intervals | a character vector of intervals |
| buckets | a character vector of levels for the new factor these have a 1-1 correspondence with intervals |
| na.bucket | what level should NA values be given? |
| unmatched.bucket | what level should numbers not covered by an interval be given? |
| out.as.factor | default is TRUE Should the resulting vector be a factor? If FALSE will return a character vector. |

Examples

```
wafflecut(-10:10, c('[0,2)', '[2,5)', '[5,10]'), c('Small', 'Medium', 'Large'))
wafflecut(-10:10, c('[0,0]', '(0,2]', '(2,5)', '[5,10]'), c('Zero', 'Small', 'Medium', 'Large'))
wafflecut(-10:10, c('[0,2)', '[2,5)', '[5,10]'), c('Small', 'Medium', 'Large'))
wafflecut(-10:10, c('[0,0]', '[0,2]', '(2,5)', '[5,10]'), c('Zero', 'Small', 'Medium', 'Large'))

# The following examples are from Richie Cotton via
# https://www.rdocumentation.org/packages/fancycut/versions/0.1.1/topics/fancycut

# Not all the values have to live in a bucket.
x <- seq.int(0, 1, 0.25)
```

```
wafflecut(x, c('(0.2, 0.3)', '(0.7, 0.8)'), c('low', 'high'))

# You can use unmatched.bucket to deal with these other intervals.
x <- seq.int(0, 1, 0.25)
wafflecut(x, c('(0.2, 0.3)', '(0.7, 0.8)'), c('low', 'high'), unmatched.bucket = 'other')

# To match NA values, use na.bucket.
x2 <- c(seq.int(0, 1, 0.25), NA)
wafflecut(x2, c('[0, 0.5]', '[0.5, 1]'), c('low', 'high'), na.bucket = 'missing')
```

Index

fancy cut, 1

waffle cut, 3