

# Package ‘fishualize’

July 22, 2025

**Type** Package

**Title** Color Palettes Based on Fish Species

**Version** 0.2.3

**Maintainer** Nina M. D. Schiettekatte <nina.schiettekatte@gmail.com>

**Description** Implementation of color palettes based on fish species.

**License** GPL-2

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 2.10)

**Suggests** testthat, knitr, rmarkdown, rfishbase, rnaturalearth, pkgdown

**URL** <https://github.com/nschiett/fishualize>

**BugReports** <https://github.com/nschiett/fishualize/issues>

**Imports** ggplot2 (>= 1.0.1), gridExtra, grid, png, downloader, utils,  
httr, magrittr, stringr, dplyr, tidyr, scales, rlang, curl

**RoxygenNote** 7.1.2

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Nina M. D. Schiettekatte [cre, aut],  
Simon J. Brandl [aut],  
Jordan M. Casey [aut]

**Repository** CRAN

**Date/Publication** 2022-03-08 13:30:02 UTC

## Contents

add_fishape . . . . .	2
fish . . . . .	3
fishapes . . . . .	5
fishcolors . . . . .	5

fishualize . . . . .	6
fish_palettes . . . . .	6
scale_color_fish . . . . .	7

<b>Index</b>	<b>10</b>
--------------	-----------

---

add_fishape	<i>fish silhouette in ggplot2</i>
-------------	-----------------------------------

---

## Description

Adds a fish silhouette to your plot

## Usage

```
add_fishape(
  family = "Pomacanthidae",
  option = "Centropyge_loricula",
  xmin = -Inf,
  xmax = Inf,
  ymin = -Inf,
  ymax = Inf,
  scaled = FALSE,
  xlim = NULL,
  ylim = NULL,
  fill = "#000000",
  alpha = 1
)
```

## Arguments

family	character string indicating the fish family.
option	character string indicating the fish species. If NA, the first available option within a family will be selected
xmin	x location giving minimum horizontal location of silhouette
xmax	x location giving maximum horizontal location of silhouette
ymin	y location giving minimum vertical location of silhouette
ymax	y location giving maximum vertical location of silhouette
scaled	logical parameter. If TRUE, location parameters (xmin, xmax, ymin, ymax) should range between 0 and 1. If FALSE, location parameters should be provided according to the values on the plot axes.
xlim, ylim	vectors of length = 2, contains the data limits and must be provided if scaled is TRUE.
fill	color of fish shape
alpha	transparency of fish shape (value between 0 and 1)

**Value**

Adds a fish silhouette grob to a ggplot object.

**Examples**

```
## Not run:
library(ggplot2)

ggplot() + add_fishape(fill = fish(n = 5)[4])

ggplot(diamonds)+
  geom_bar(aes(cut, fill = cut)) +
  scale_fill_fish_d(option = "Naso_lituratus") +
  add_fishape(family = "Acanthuridae",
             option = "Naso_unicornis",
             xmin = 1, xmax = 3, ymin = 15000, ymax = 20000,
             fill = fish(option = "Naso_lituratus", n = 5)[3],
             alpha = 0.8) +
  theme_bw()

## example with relative coordinates
ggplot(diamonds)+
  geom_bar(aes(cut, fill = cut)) +
  scale_fill_fish_d(option = "Naso_lituratus") +
  add_fishape(family = "Acanthuridae",
             option = "Naso_unicornis",
             xmin = 0, xmax = 0.3, ymin = 0.8, ymax = 1,
             scaled = TRUE,
             xlim = c(0.5, 5.5), ylim = c(0, 21000) ,
             fill = fish(option = "Naso_lituratus", n = 5)[3],
             alpha = 1) +
  theme_bw()

## End(Not run)
```

---

fish

*fish Colour Map.*

---

**Description**

This function creates a vector of n equally spaced colors along the 'fish colour map' of your selection

**Usage**

```
fish(
  n,
  alpha = 1,
  begin = 0,
```

```

    end = 1,
    direction = 1,
    option = "Centropyge_loricula"
  )

fish_pal(
  alpha = 1,
  begin = 0,
  end = 1,
  direction = 1,
  option = "Centropyge_loricula"
)

```

### Arguments

<code>n</code>	The number of colors ( $\geq 1$ ) to be in the palette.
<code>alpha</code>	The alpha transparency, a number in $[0,1]$ , see argument <code>alpha</code> in <a href="#">hsv</a> .
<code>begin</code>	The (corrected) hue in $[0,1]$ at which the fish colormap begins.
<code>end</code>	The (corrected) hue in $[0,1]$ at which the fish colormap ends.
<code>direction</code>	Sets the order of colors in the scale. If 1, the default, colors are ordered from darkest to lightest. If -1, the order of colors is reversed.
<code>option</code>	A character string indicating the fish species to use.

### Value

`fish` returns a character vector, `cv`, of color hex codes. This can be used either to create a user-defined color palette for subsequent graphics by `palette(cv)`, a `col =` specification in graphics functions or in `par`.

Semi-transparent colors ( $0 < \alpha < 1$ ) are supported only on some devices: see [rgb](#).

### Examples

```

library(ggplot2)
library(fishualize)

dat <- data.frame(x = rnorm(1e4), y = rnorm(1e4))
ggplot(dat, aes(x = x, y = y)) +
  stat_density_2d(geom = "raster",
    aes(fill = after_stat(density)), contour = FALSE) +
  scale_fill_gradientn(colors = fish(128, option = 'Ostracion_cubicus'))

pal <- fish(256, option = "Thalassoma_hardwicke", direction = -1)
image(volcano, col = pal)

```

---

`fishapes`*Available fish silhouettes*

---

**Description**

This function returns a dataframe containing the all the available fish silhouettes accessible through the 'fishualize' package.

**Usage**

```
fishapes()
```

**Value**

fishapes returns a dataframe containing the all the available fish silhouettes available to use.

**Examples**

```
fishapes()
```

---

`fishcolors`*Original fish color database*

---

**Description**

A dataset containing some colour palettes inspired by fish species

**Usage**

```
fishcolors
```

**Format**

A data frame containing all the colours used in the palette:

- option: It is intended to be a general option for choosing the specific colour palette.
- hex: hex color code

---

fishualize	<i>Visualization of fish color palette</i>
------------	--

---

**Description**

This function creates an image of the specified fish color palette.

**Usage**

```
fishualize(option = "Centropyge_loricula", n = 5, ...)
```

**Arguments**

option	A character string indicating the fish species to use.
n	The number of colors ( $\geq 1$ ) to be in the palette.
...	Other arguments as can be specified in the function fish. See ?fishualize::fish for details.

**Value**

fishualize returns a visualisation of the specified color palette.

**Examples**

```
fishualize::fishualize()
fishualize::fishualize(option = "Zanclus_cornutus", n = 8)
```

---

fish_palettes	<i>Available Palettes.</i>
---------------	----------------------------

---

**Description**

This function returns a vector containing the names of all the available palettes in the 'fishualize' package.

**Usage**

```
fish_palettes()
```

**Value**

fish\_palettes returns a character vector with the names of the fish palettes available to use.

**Examples**

```
fish_palettes()
```

---

scale\_color\_fish      *fish colour scales*

---

**Description**

Uses the fish color scale.

**Usage**

```
scale_color_fish(  
  option = "Centropyge_loricula",  
  ...,  
  alpha = 1,  
  begin = 0,  
  end = 1,  
  direction = 1,  
  discrete = FALSE  
)
```

```
scale_colour_fish(  
  option = "Centropyge_loricula",  
  ...,  
  alpha = 1,  
  begin = 0,  
  end = 1,  
  direction = 1,  
  discrete = FALSE  
)
```

```
scale_colour_fish_d(  
  option = "Centropyge_loricula",  
  ...,  
  alpha = 1,  
  begin = 0,  
  end = 1,  
  direction = 1  
)
```

```
scale_color_fish_d(  
  option = "Centropyge_loricula",  
  ...,  
  alpha = 1,  
  begin = 0,  
  end = 1,  
  direction = 1  
)
```

```
scale_fill_fish_d(
  option = "Centropyge_loricula",
  ...,
  alpha = 1,
  begin = 0,
  end = 1,
  direction = 1
)
```

```
scale_fill_fish(
  option = "Centropyge_loricula",
  ...,
  alpha = 1,
  begin = 0,
  end = 1,
  direction = 1,
  discrete = FALSE
)
```

### Arguments

option	A character string indicating the fish species to use.
...	parameters to <code>discrete_scale</code> or <code>scale_fill_gradientn</code>
alpha	pass through parameter to fish
begin	The (corrected) hue in [0,1] at which the fish colormap begins.
end	The (corrected) hue in [0,1] at which the fish colormap ends.
direction	Sets the order of colors in the scale. If 1, the default, colors are as output by <code>fish_pal</code> . If -1, the order of colors is reversed.
discrete	generate a discrete palette? (default: FALSE - generate continuous palette)

### Details

For `discrete == FALSE` (the default) all other arguments are as to [scale\\_fill\\_gradientn](#) or [scale\\_color\\_gradientn](#). Otherwise the function will return a `discrete_scale` with the plot-computed number of colors.

### Value

Alias of `scale_color_fish` or `scale_fill_fish`

Alias of `scale_color_fish` or `scale_fill_fish`

Alias of `scale_color_fish` or `scale_fill_fish`

Alias of `scale_color_fish` or `scale_fill_fish`

Alias of `scale_color_fish` or `scale_fill_fish`



### Examples

```
library(ggplot2)
library(fishualize)

ggplot(diamonds, aes(factor(cut), fill=factor(cut))) +
  geom_bar() +
  scale_fill_fish(discrete = TRUE, option = "Centropyge_loricula")

ggplot(mtcars, aes(factor(gear), fill=factor(carb))) +
  geom_bar() +
  scale_fill_fish(discrete = TRUE, option = "Trimma_lantana")

ggplot(mtcars, aes(x = mpg, y = disp, colour = drat)) +
  geom_point(size = 4) +
  scale_colour_fish(option = "Ostracion_cubicus", direction = -1)
```

# Index

## \* datasets

fishcolors, 5

add\_fishape, 2

fish, 3

fish\_pal (fish), 3

fish\_palettes, 6

fishapes, 5

fishcolors, 5

fishualize, 6

hsv, 4

rgb, 4

scale\_color\_fish, 7

scale\_color\_fish\_d (scale\_color\_fish), 7

scale\_color\_gradientn, 8

scale\_colour\_fish (scale\_color\_fish), 7

scale\_colour\_fish\_d (scale\_color\_fish),  
7

scale\_fill\_fish (scale\_color\_fish), 7

scale\_fill\_fish\_d (scale\_color\_fish), 7

scale\_fill\_gradientn, 8